

Exam Questions 1z0-066

Oracle Database 12c: Data Guard Administration

<https://www.2passeasy.com/dumps/1z0-066/>



NEW QUESTION 1

Which two are prerequisites for configuring Transaction Guard in a Data Guard environment?

- A. Grant execute permission on the DBMS_APP_CONT package to relevant database schema owners
- B. Create a database service with COMMIT_OUTCOME set to TRUE, and ensure clients use that service to connect to the database instance.
- C. Ensure that connection descriptors for database clients use the failover clause with the COMMIT_OUTCOME parameter set to TRUE
- D. Set INSTANCE_NAME identically on all the Data Guard Configuration databases and modify the local service name on the client to include a CONNECTION_LIST containing all the standby hosts.
- E. Create a database service with COMMIT_OUTCOME set to TRUE and ensure that the service is statically registered with the default listener on the primary host

Answer: AB

NEW QUESTION 2

Which three are benefits of using the Data Guard Broker to manage standby databases?

- A. it simplifies physical standby database creation
- B. It provides an easy failover capability using a single command.
- C. it coordinates database state transitions and updates database properties dynamically.
- D. it automatically changes database properties after the protection mode for a configuration is changed
- E. It provides an easy switchover capability using a single command.
- F. It simplifies logical standby database creation.

Answer: BCE

NEW QUESTION 3

Examine the Data Guard configuration:

```
DGMGRL> show configuration;
```

Configuration –Animals

Protection Mode: MaxAvailability

Databases:

dogs- Primary database

cats- Physical standby database

sheep- Logical standby database

Fast-Start Failover: DISABLED

Configuration Status:

SUCCESS

Which three will be true after a switchover to Sheep?

- A. Dogs will be an enabled logical standby database.
- B. Sheep will be the primary database.
- C. Cats will be a disabled physical standby database.
- D. Dogs will be a disabled logical standby database
- E. Cats will be an enabled physical standby database.

Answer: ABE

NEW QUESTION 4

Which three statements are true about snapshot standby databases?

- A. Tablespaces can be dropped.
- B. Tables can be dropped
- C. The broker may be used to fail over to a snapshot standby database.
- D. A logical standby database can be converted into a snapshot standby database.
- E. Tablespaces can be created.

Answer: ABE

NEW QUESTION 5

Which three statements are true about standby redo logs in a Data Guard configuration with no Oracle Streams or Goldengate configured?

- A. They are required on a logical standby for real-time apply
- B. They are required only for synchronous redo transport.
- C. Only standby databases can write redo to them.
- D. It is recommended to have them on the primary database.
- E. They are required on a physical standby for real-time apply.
- F. The LGWR process writes to them on a standby database.

Answer: ACE

NEW QUESTION 6

Your Data Guard environment has two remote physical standby databases

Client applications use the local naming method to connect to the primary database instance.

You want applications to automatically connect to the new primary database instance in case of a switchover or a failover

Which will fulfill this requirement?

- A. Create a database service on each standby database that is started automatically by a trigger, when the database role is PRIMARY, modify the connection description used by client applications to include all the standby hosts and connect to the database instance using that service name.
- B. Create a database service on the primary database that is started automatically by a trigger, when the database role is PRIMARY, modify the connection descriptors used by client applications to include all the standby hosts and connect to the database instance using that service name.
- C. Set the INSTANCE_NAME parameter identically on all databases; modify the connection descriptor on client applications to include all the standby hosts and connect to the database instance using that service name.
- D. Set the DB_NAME and DB_UNIQUE_NAME identical on all databases, modify the connection descriptors on client applications to include all the standby hosts and connect to the database using that service name.

Answer: A

NEW QUESTION 7

A customer asks you to propose the most appropriate solution for this set of requirements:

1. We need a disaster recovery solution that enables us to fail over from our production database with zero data loss.
2. We want to generate reports from the proposed standby database at the same time that it is used for other purposes.
3. Developers may need to test occasionally on a copy of the live database.

You have to already confirmed that there are no unsupported data types on the primary database Which two solutions would you recommend?

- A. a remote physical standby database with RedoRoutes via a far sync instance
- B. a snapshot standby database with synchronous redo transport
- C. a physical standby database with real-time query enabled
- D. a logical standby database
- E. a read mostly implementation of a physical standby database

Answer: BC

NEW QUESTION 8

You must configure an Oracle Data Guard environment consisting of:

1. A primary database
- 2 Three Physical Standby Databases

You must meet these requirements:

? A designated physical standby database should become the primary database automatically whenever the primary database falls

? The chosen protection mode should provide the highest level of protection

possible without violating the other requirement

Which redo transport mode and protection mode would you configure to meet these requirements?

- A. SYNC NOAFFIRM and Maximum Protection
- B. SYNC NOAFFIRM and Maximum Availability
- C. ASYNC and Maximum Performance
- D. SYNC AFFIRM and Maximum Availability
- E. SYNC AFFIRM and Maximum Protection

Answer: D

NEW QUESTION 9

Examine the Data Guard configuration: DGMGRL> show configuration;

Configuration -Animals Protection Mode MaxAvailability Databases

dogs- Primary database

cats- Snapshot standby database

sheep- Snapshot standby database Fast-Start Failover DISABLED

Configuration Status: ORA-01034: ORACLE not available ORA-16625: cannot reach database "dogs"1 DGM-17017 unable to determine configuration status

You wish to perform a failover to Sheep

Which command, or sequence of commands, should you issue to the broker before executing "failover to sheep", using the broker?

- A. DGMGRL> convert database cats to physical standby,
- B. DGMGRL> convert database sheep to physical standby;
- C. DGMGRL> convert database sheep to physical standby; DGMGRL> convert database cats to physical standby;
- D. DGMGRL>edit configuration set protection mode as maxperformance; DGMGRL> convert database sheep to physical standby;
- E. None, because you can directly failover to a Snapshot Standby Database

Answer: C

NEW QUESTION 10

You are monitoring your Data Guard broker configuration and issue this set of DGMGRL commands:

DGMGRL> SHOW CONFIGURATION

Configuration – DRSolution

Protection Mode: MaxPerformance

Databases:

Close_by-Primary database

FS_inst- Far Sync

Far_away –Physical standby database

Fast-Start Failover: DISABLED

Configuration Status:

SUCCESS

What is true concerning this configuration?

- A. The Close_by primary database instance forwards redo to the FSjnst Far Sync instance, which forwards the redo in turn to the Far_away physical standby database instance.
- B. The far sync instance will not forward redo to the Far_away physical standby because the Protection mode is not MaxProtection.
- C. The close_by primary database forwards redo to the Far_away physical standby directly and also sends redo to the FSjnst Far Sync instance.
- D. The far sync instance will not forward redo to the Far_away physical standby because Fast-Start Failover is disabled
- E. The FSjnst Far Sync instance forwards redo to the Far_away physical standby only if the close_by primary database is not able to do so.

Answer: A

NEW QUESTION 10

You edit the DGConnectIdentifier database property using the edit database set property DGMGRL command Which two are effects of this change?

- A. The fal_client database initialization parameter on all standby databases is updated with the new value.
- B. The service attribute of the log_archive_dest_n initialization parameter for any database referring to the specified database is updated with the new value.
- C. The fal_client database initialization parameter for the specified database is updated with the new value
- D. The broker configuration must be disabled and then enabled to use the new connection property.
- E. The service attribute of the log_archive_dest_n initialization parameter referring to all standby databases is updated with the new value

Answer: AB

NEW QUESTION 13

Examine the Fast-start configuration

```
DGMGRL> show fast_start failover;
```

Fast-Start Failover: ENABLED

Threshold : 30 seconds

Target: sheep

Observer : 017.example.com

Lag Limit: 30 seconds (not in use)

Shutdown Primary: TRUE

Auto-reinstate: TRUE

Observer Reconnect: (none)

Observer Override: FALSE

Configurable Failover Conditions

Health Conditions:

Corrupted Controlfile YES

Corrupted Dictionary YES

Inaccessible Logfile NO

Stuck Archiver YES

Datafile Offline YES

Oracle Error Conditions: (none) Which three are true?

- A. The observer will initiate a failover when the primary database is unable to produce local archived redo log files.
- B. An automatic failover will be initiated even if the target standby database lags behind the primary
- C. The observer is running
- D. a failover may occur if the observer has lost connectivity to the primary database, even if the Fast-Start Failover target standby database has a good connection to the primary database
- E. The configuration operates in Maximum Availability mode
- F. The configuration operates in Maximum Performance mode

Answer: ACE

NEW QUESTION 14

Examine the Data Guard configuration;

```
DGMGRL> show configuration;
```

Configuration –Animals

Protection Mode: MaxPerformance

Databases:

dogs- Primary database

sheep- Physical standby database

cats- Snapshot standby database

Fast-Start Failover: DISABLED

Configuration Status:

SUCCESS

You receive an error while attempting to raise the protection mode to Maximum Protection:

```
DGMGRL> edit configuration set protection mode as maxprotection;
```

Error: ORA-16627: operation disallowed since no standby databases would remain to support protection mode
Failed.

What can you conclude based on this error?

- A. Cats is a snapshot standby database
- B. The redo transport mode is set to ASYNC for the standby database Sheep
- C. The redo transport mode is set to ASYNC for both standby databases
- D. The redo transport mode is set to ASYNC for the standby database Cats

Answer: B

NEW QUESTION 16

Which two are prerequisites for enabling Automatic Block Media Recovery in a Data Guard environment consisting of a primary database, one physical standby

database and one logical standby database?

- A. FLASHBACK DATABASE must be enabled on the physical standby database.
- B. There must be connectivity between the primary and the physical standby database.
- C. FLASHBACK DATABASE must be enabled on the primary database.
- D. The physical standby database must have Real-Time Apply enabled.
- E. The logical standby database must have Real-Time Query enabled

Answer: CD

NEW QUESTION 20

On your logical standby database, you specified these rules:

```
SQL> EXECUTE DBMS_LOGSTBY.SKIP (STMT=> 'DML', -  
SCHEMA_NAME => 'HR', -  
OBJECT_NAME=> 'EMP_NEW');
```

```
SQL> EXECUTE DBMS_LOGSTBY.SKIP (STMT=> 'DML', -  
SCHEMA_NAME => 'HR', -  
OBJECT_NAME=> 'EMP_OLD');
```

After completion of the weekend batch cycle you attempt to delete the SQL Apply filters:

```
SQL> EXECUTE DBMS_LOGSTBY.UNSKIP (STMT=> 'DML', -  
SCHEMA_NAME => 'HR', -  
OBJECT_NAME=> 'EMP%');
```

Which is true regarding the execution of the UNSKIP procedure?

- A. it succeeds only if SQL apply is stopped before deleting the SQL Apply filter
- B. it succeeds but the SQL Apply filters are not deleted.
- C. It deletes both the SQL Apply filters.
- D. it returns an error because the syntax to delete a SQL Apply filter must specify the same object names as specified when the filter was added
- E. it succeeds only if all DML statements executed on the primary have been applied on the logical standby

Answer: D

NEW QUESTION 22

Examine this list of possible steps:

- 1 Raise the compatibility level on both databases
- 2.Restart SQL Apply on the upgraded logical standby database
- 3 Start SQL Apply on the old primary database.
4. Perform a Switchover to the logical standby database
5. Upgrade the logical standby database.
6. Upgrade the old primary database.

Which is the minimum number of steps in the correct order, to perform a rolling release upgrade of a data guard environment using an existing logical standby database and to enable the new functionality?

- A. 5,2,4,3,6,1
- B. 1,5,2,4,6,3
- C. 5,2,4,6,3,1
- D. 4,6,5,2,3,1
- E. 5,2,4,1

Answer: A

NEW QUESTION 27

Examine the Data Guard configuration:

```
DGMGRL > show configuration;
```

Configuration-Animals

Protection Mode: MaxAvailability

Databases:

dogs- Primary database

dogsfsf –Far Sync

sheep- Physical standby database

Fast-Start Failover: DISABLED

Configuration Status:

SUCCESS

An attempt to enable fast-start failover raises an error:

```
DGMGRL> enable fast_start failover;
```

Error: ORA-16693: requirements not met for enabling fast-start failover
Failed.

Identify two possible reasons for this error.

- A. The FastStartFailoverTarget property is not set on Sheep.
- B. The FastStartFailoverTarget property is not set on Dogs.
- C. The FastStartFailoverTarget property is not set on DogsFSI.
- D. The LogXptMode property is set to ASYNC on Dogs.
- E. The RedoRoutes property is not set on Dogs
- F. The RedoRoutes property is not set on DogsFSI

Answer: AD

NEW QUESTION 30

Which three are true about using RMAN in a Data Guard environment?

- A. A recovery catalog is required when RMAN is used to take backups from a logical standby database in a Data Guard configuration if you plan to recover the primary using those backups.
- B. Backups of archived redo logs taken on a physical standby are interchangeable with a primary.
- C. A recovery catalog is required when RMAN is used to take backups from a physical standby database if you plan to recover the primary using those backups
- D. Backups of control files taken on a physical standby are not interchangeable with a primary.
- E. Backups of data files taken on a physical standby are interchangeable with a primary.

Answer: BCE

NEW QUESTION 34

Which three are among the various tasks performed by the data Guard Monitor (DMON) process?

- A. performing role transitions when switchover requests are made
- B. communicating with DMON processes in other database instances that are part of the broker configuration
- C. activating role-based services appropriately in the various database instances of the configuration, based on the database role
- D. communicating with the DMON process of the observer to monitor a primary database in case a fast start failover is required.
- E. maintaining information about all members of the broker configuration in binary configuration files

Answer: ABE

NEW QUESTION 36

A customer has these requirements for their potential Data Guard implementation:

1. Zero data loss must still be guaranteed through the loss of any one configuration component.
- 2 The primary database must be protected against a regional disaster
3. Performance overheads on the primary should be minimized as much as possible given these requirements.
4. Downtime on the primary database for any reason must be kept to a minimum. Components referred to in the broker commands are:

prima	the primary database
fs1	the Far Sync instance in the primary region
physt	a physical standby database in a remote region
physt1	a physical standby database in the primary
physt2	a physical standby database in a remote region

Which Data Guard broker commands are needed to implement these requirements?

- A. EDIT DATABASE prima SET PROPERTY REDOROUTES=' (LOCAL: physt1, FASTSYNC)'; EDIT DATABASE prima SET PROPERTY REDOROUTES=' (LOCAL: fs1 SYNC)'; EDIT FAR_SYNC fs1 SET PROPERTY REDORUOTES=' (pnma: physt2 SYNC)'; EDIT CONFIGURATION SET PROTECTION MODE AS MAXAVAILABILITY
- B. EDIT DATABASE prima SET PROPERTY REDOROUTES=' (LOCAL: fs1 ASYNC)'; EDIT FAR_SYNC fs1 SET PROPERTY REDORUOTES=' (prima physt FASTSYNC)'; EDIT CONFIGURATION SET PROTECTION MODE AS MAXPROTECTION
- C. EDIT DATABASE prima SET PROPERTY REDOROUTES^' (LOCAL: fs1 SYNC)'; EDIT FAR_SYNCfs1 SET PROPERTY REDORUOTES=' (prima physt ASYNC)'; EDIT CONFIGURATION SET PROTECTION MODE AS MAXAVAILABILITY;
- D. EDIT DATABASE prima SET PROPERTY REDOROUTES=' (LOCAL: physt1, FASTSYNC)'; EDIT DATABASE prima SET PROPERTY REDOROUTES= (LOCAL: fs1. FASTSYNC)'; EDIT FAR_SYNC fs1 SET PROPERTY REDORUOTES=' (prima: physt2 ASYNC)'; EDIT CONFIGURATION SET PROTECTION MODE AS MAXAVAILABILITY;

Answer: A

NEW QUESTION 41

Which two statements are true regarding Data Guard Broker?

- A. It automatically adds the primary database to an existing broker configuration when Enterprise Manager Cloud Control is used to create a standby
- B. It automatically starts the DMON process for the database instances that are part of a Data Guard configuration.
- C. it can be used to perform failovers and switchovers.
- D. It can be used to create and manage standby databases.
- E. It can be used to monitor redo transport and log apply services.

Answer: BC

NEW QUESTION 44

Which two are true about offloading backups to a physical standby database in a Data Guard environment?

- A. The standby database must be registered in an RMAN catalog after the primary database has been registered
- B. The standby database cannot be registered in an RMAN catalog if the primary database has not been registered
- C. Backups of the standby control file taken while connected to the catalog where the database is registered, may be used to restore the control file onthe primary database.
- D. The standby database must be registered in an RMAN catalog before the primary database has been registered

Answer: BC

NEW QUESTION 45

Which two are prerequisites for configuring flashback database for Oracle 12c databases, in a Data Guard environment?

- A. a flash recovery area must be configured
- B. The database must be in MOUNT state.
- C. The database must be in ARCHIVELOG mode.
- D. A far sync instance must be configured to flash back a standby when the primary has been flashed back.
- E. The Data Guard Broker must be used.

Answer: AC

NEW QUESTION 49

Examine the Data Guard configuration: DGMGRL> show configuration Configuration-Animals

Protection Mode: MaxAvailability Databases:

Sheep- Primary database

Warning: ORA-16817: unsynchronized fast-start failover configuration Dogs - (*) Physical standby database (disabled)

ORA-16661: the standby database needs to be reinstated

Fast-Start Failover: ENABLED Configuration Status: WARNING And the fast-start failover configuration:

DGMGRL> show fast_start failover; Fast-Start Failover: ENABLED Threshold: 30 seconds Target: dogs

Observer: 017.example.com Lag Limit: 30 seconds (not in use) Shutdown Primary: TRUE Auto-reinstate: TRUE Observer Reconnect 10 seconds Observer Override: FALSE

Configurable Failover Conditions Hearth Conditions: Corrupted Controlfile YES Inaccessible Logfile NO

Stuck Archiver NO Datafile Offline YES Oracle error Conditions

ORA-01578: ORACLE data block corrupted (file # %s, block # %s) And finally the reason for the fail over:

SQL> select last_failover_reason from v\$fs_failover_stats; LAST_FAILOVER_REASON

ORA-01578: ORACLE data block corrupted (file # %s, block # %s)

Identify the task, or sequence of tasks, to bring the configuration into the SUCCESS state.

- A. Bring Dogs to the NOMOUNT state and let the broker reinstate Dogs automatically.
- B. MOUNT DOGS and issue "reinstate database dogs;" at the DGMGRL prompt while connected to Dogs.

- C. MOUNT DOGS and issue "reinstat database dogs:" at the DGMGRL prompt while connected to Sheep
- D. Open Dogs and let the broker reinstat Dogs automatically.

Answer: C

NEW QUESTION 54

Which three are true concerning restoring of RMAN backups to primary and physical standby databases in a Data Guard environment?

- A. Backups of data files taken on the primary database may be restored on a physical standby database.
- B. Backups of control files taken on the primary database may not be restored and used on a physical standby database.
- C. Backups of SPFILEs taken on a physical standby database may not be restored on the primary database.
- D. Backups of control files taken on a physical standby database may be restored on the primary database.
- E. Backups of data files taken on a physical standby database may be restored on a primary database.
- F. Backups of SPFILEs taken on the primary database may not be restored and used on a physical standby database.

Answer: CEF

NEW QUESTION 58

Which three statements are true about snapshot standby databases?

- A. Snapshot standby databases may be used for rolling release upgrades.
- B. if datafiles grow while a database is a snapshot standby database, then they shrink when converted back to a physical standby database.
- C. Flashback logs are used to convert a snapshot standby database back into a physical standby database.
- D. a snapshot standby database can have Real-Time Query enabled
- E. A guaranteed restore point is created automatically when a physical standby database is converted into a snapshot standby database.

Answer: CE

NEW QUESTION 59

Which three statements are true about Data Guard configurations?

- A. All databases in one Data Guard environment must have the same database name.
- B. VALID_FOR is a LOG_ARCHIVE_DEST_N attribute that enables DB role change operations without having to modify LOG_ARCHIVE_DEST_n when performing switchovers or failovers.
- C. For Standard Edition, LOG_ARCHIVE_DUPLEX_DEST is used to configure redo transport, from the primary to the standby database.
- D. When using the Data Guard Broker, an spfile is not required.
- E. Up to 30 physical standby databases may exist within one configuration.
- F. The Oracle recommendation for the number of standby redo log groups per thread is one more than the number of online redo log groups per thread

Answer: AEF

NEW QUESTION 62

You are licensed to use Oracle Active Data Guard

Which two statements are true after enabling block change tracking on a physical standby database?

- A. it allows fast incremental backups to be offloaded to the physical standby database
- B. It starts the CTWR process on the physical standby database instance
- C. it allows fast incremental backups to be taken on the primary database.
- D. It starts the RVWR process on the physical standby database instance.
- E. It allows fast incremental backups to be offloaded to a snapshot standby database, when the physical standby database is converted.
- F. It starts the CTWR process on the primary database instance.

Answer: AB

NEW QUESTION 67

You must manually reinstate a database using DGMGRL

To which database should you connect with DGMGRL before issuing the REINSTATE command and in which state should the target database be?

- A. The target database should be in NOMOUNT state and DGMGRL should be connected to any database that is a member of the configuration
- B. The target database should be MOUNTED and DGMGRL should be connected to any database that is a member of the configuration
- C. The target database should be MOUNTED and DGMGRL should be connected to the primary database.
- D. The target database should be MOUNTED and DGMGRL should be connected to the target database
- E. The target database should be in NOMOUNT state and DGMGRL should be connected to the primary database

Answer: C

NEW QUESTION 69

You are monitoring your Data Guard broker configuration and issue this set of DGMGRL commands:

DGMGRL> SHOW CONFIGURATION

Configuration – DRSolution

Protection Mode: MaxPerformance

Databases:

Close_by-Primary database

FS_inst- Far Sync

Far_away –Physical standby database

Fast-Start Failover: DISABLED

Configuration Status:
SUCCESS

What is true concerning this configuration?

- A. The Close_by primary database instance forwards redo to the FSjnst Far Sync instance, which forwards the redo in turn to the Far_away physical standby database instance.
- B. The far sync instance will not forward redo to the Far_away physical standby because the Protection mode is not MaxProtection.
- C. The close_by primary database forwards redo to the Far_away physical standby directly and also sends redo to the FSjnst Far Sync instance.
- D. The far sync instance will not forward redo to the Far_away physical standby because Fast-Start Failover is disabled
- E. The FSjnst Far Sync instance forwards redo to the Far_away physical standby only if the close_by primary database is not able to do so.

Answer: A

NEW QUESTION 71

You must design an Oracle Data Guard configuration for an OLTP database that meets these permanent requirements:

1. Data loss is not permitted.
2. Read-only applications should not connect to the primary database instance. Additionally, there are these requirements, only one of which is ever done at any one time:
 1. It should be possible to apply designated patches with a minimum amount of downtime.
 2. Upgrading to a new database release should be performed with the least possible amount of downtime.
 3. New application software releases should be tested against an exact and up-to-date replica of the primary database.

Which configuration meets these requirements with the fewest databases?

- A. a primary database with three physical standby databases
- B. a primary database with one logical and two physical standby databases
- C. a primary database with one logical standby database
- D. a primary database with one logical and one physical standby database
- E. a primary database with two physical standby databases
- F. a primary database with one physical standby database

Answer: D

NEW QUESTION 74

Which three factors can influence the rate of redo apply on a physical standby database?

- A. the network latency between the primary and standby databases
- B. the number of archiver processes on the standby database
- C. the number and size of standby redo logs on the primary database
- D. the rate of redo generation on the primary database
- E. the number and size of standby redo logs on the standby database

Answer: ABE

NEW QUESTION 77

Examine the Data Guard configuration:

DGMGRL> show configuration:

Configuration –Animals

Protection Mode: MaxAvailability

Databases:

dogs- Primary database

cats- Snapshot standby database

sheep- Snapshot standby database

Fast-Start Failover: DISABLED

Configuration Status:

ORA-01034: ORACLE not available

ORA-16625: cannot reach database "dogs"

DGM-17017: unable to determine configuration status

Which three will be true after a successful failover to Cats?

- A. Sheep will be in the disabled state.
- B. Sheep will be in the enabled state.
- C. Dogs will be in the disabled state and has to be manually reinstated
- D. The configuration will be in Maximum Performance mode.
- E. The configuration will be in Maximum Availability mode.

Answer: BCD

NEW QUESTION 82

A Data Guard environment has this configuration and these attributes:

1. The primary database prima is in the local region.
2. A physical standby database physt1 is in the local region.
3. A physical standby database physt2 is in a remote region.
4. The primary ships redo to physt1.
5. physt1 ships redo physt2.
6. physt1 and physt2 have Real-Time Query enabled

A sequence has been created with this SQL statement in the primary database: CREATE SEQUENCE a NOCACHE SESSION: Which two statements are true?

- A. The sequence is usable on physt1 and physt2
- B. The sequence is usable on physt1 but not usable on physt2.
- C. The sequence is usable on physt2 if physt1 becomes unavailable, but only if an alternative redo destination has been configured on the primary database.
- D. physt2 will no longer receive redo if physt1 becomes unavailable, unless LOG_ARCHIVE_DEST_n has the ALTERNATE attribute specified on the primary database.
- E. physt2 will no longer receive redo if physt1 becomes unavailable, unless LOG_ARCHIVE_DEST_n has the ALTERNATE attribute specified on physt1.

Answer: CE

NEW QUESTION 85

Examine the Data Guard configuration:

DGMGRL > show configuration; Configuration-Animals

Protection Mode MaxPerformance Databases

dogs-Primary database sheep-Snapshot standby database cats-Snapshot standby database

Fast-Start Failover: DISABLED Configuration Status: SUCCESS

You receive an error while attempting to raise the protection mode to Maximum Availability: DGMGDRL> edit configuration set protection mode as max availability;

Error ORA-16627 operation disallowed since no standby databases would remain to support protection mode Failed.

Identify two statements that you can execute, either one of which will enable successful raising of the protection mode to Maximum Availability.

- A. DGMGRL> convert database sheep to physical standby;
- B. DGMGRL> convert database cats to physical standby;
- C. DGMGRL> edit database dogs set property LogXptMode= fastsync;
- D. DGMGRL> edit database sheep set property LogXptMode= fastsync;
- E. DGMGRL> edit database cats set property LogXptMode= sync;

Answer: BE

NEW QUESTION 90

Which three are prerequisites for enabling Fast-Start Failover?

- A. The Fast-Start Failover target standby database must receive REDO directly from the primary database
- B. Flashback Database must be enabled on both the primary database and the Fast-Start Failover target standby database.
- C. Flashback Database must be enabled only on the Fast-Start Failover target standby database.
- D. The configuration must be operating in either Maximum Performance or Maximum Availability mode

- E. The configuration must be operating in either Maximum Performance or Maximum Protection mode
- F. The Data Guard environment must be managed by the Data Guard Broker.

Answer: BDF

NEW QUESTION 91

A data file on one of your physical standby databases has been accidentally deleted and you must restore and recover it. All the archive logs required for recovery are still on disk in the directory pointed to by the log_archive_dest_1 parameter Which three steps must be performed to restore the missing file and recover the standby database while it is in the MOUNT state?

- A. Recover the datafile by using the RMAN RECOVER DATAFILE command
- B. Restart the redo apply.
- C. Restore the datafile by using the RMAN RESTORE DATAFILE command.
- D. Stop the redo apply.
- E. Recover the database by using the RMAN RECOVER DATABASE command.

Answer: CDE

NEW QUESTION 92

A query on the view DBA_LOGSTBY_UNSUPPORTED on your primary database returns no rows

As a result of this, you decide that an upgrade may use logical standby databases. Which two are true about upgrading Data Guard environments consisting of one logical standby database running on a separate host from the primary?

- A. The upgrade always requires downtime until the upgrade of the logical standby is completed
- B. Using manual upgrade, catctl.pl can be executed in some cases on the primary and standby database simultaneously.
- C. The upgrade always required downtime until the upgrade of the primary is completed
- D. Using manual upgrade, catupgr.sql needs to run on the primary database only.
- E. SQL Apply on the local standby database must be stopped while the primary database is upgraded.
- F. Fast-Start Failover can be used to protect the primary database during the upgrade.

Answer: BE

NEW QUESTION 95

Which two statements are true for Data Guard environments with multi-tenant databases?

- A. DB_UNIQUE_NAME must be specified differently for each pluggable database within a multi-tenant standby database.
- B. Each pluggable database within a multi-tenant physical standby database has a minimum of one associated Oracle Net service name.
- C. Each pluggable database within a multi-tenant physical standby has one MRP background process running during redo apply.
- D. A pluggable database within a multi-tenant standby database can have a different open mode than the container database
- E. A pluggable database within a multi-tenant standby database can have a different database role than the container database.

Answer: AD

NEW QUESTION 96

There are currently 6 APPLIER and 6 PREPARER processes running and no idle APPLIER processes on your logical standby database. The MAX_SERVERS SQL apply parameter and number of archiver processes are both set to 12. Identify two changes, each of which would allow you to increase the number of APPLIER processes.

- A. Increase the PROCESSES initialization parameter
- B. Increase the value for the MAX_SERVERS SQL apply parameter.
- C. Decrease the number of archiver processes on the standby databas
- D. increase the PARALLEL_MAX_SERVER initialization parameter
- E. Decrease the number of PREPARER processes
- F. Increase the RECOVERY_PARALLEUSM initialization parameter

Answer: BE

NEW QUESTION 99

Your Data Guard environment consists of these components and settings:

1. A primary database
2. A remote physical standby database
3. Real-time query is enabled
4. The redo transport mode is set to SYNC.
5. The protection mode is set to Maximum Availability.

You notice that queries executed on the physical standby database receive errors: ORA- 03172: STANDBY_MAX_DATA_DELAY of 15 seconds exceeded. Which two would you recommend to avoid this error?

- A. Change the protection mode to Maximum Performance.
- B. Increase the size of the buffer cache on the standby database instance.
- C. Reduce I/O latency for the storage used by the primary database.
- D. Change the protection mode to Maximum Protection.
- E. Increase the network bandwidth between the primary and standby databases
- F. Increase the number of standby redo log files on the primary database

Answer: AE

NEW QUESTION 100

A Data Guard environment has this configuration and these attributes:

1. A primary database
2. A Physical Standby Database named sbdb
3. The configuration is in maximum availability protection mode.

Then sbdb is converted to a snapshot standby database. When two statements are true?

- A. Sbdb can still apply redo
- B. The recovery point objective increases
- C. The protection mode is lowered to maximum performance
- D. The recovery time objective increases.
- E. Sbdb can still receive redo

Answer: DE

NEW QUESTION 101

Examine the Data Guard configuration:

```
DGMGRL> show configuration;
```

```
Configuration –Animals
Protection Mode: MaxPerformance
Databases:
dogs- Primary database
sheep- Physical standby database
cats- Snapshot standby database
```

```
Fast-Start Failover: DISABLED
```

```
Configuration Status:
SUCCESS
```

You receive an error while attempting to raise the protection mode to Maximum Protection:

```
DGMGRL> edit configuration set protection mode as maxprotection;
```

```
Error: ORA-16627: operation disallowed since no standby databases would remain to support protection mode
Failed.
```

What can you conclude based on this error?

- A. Cats is a snapshot standby database
- B. The redo transport mode is set to ASYNC for the standby database Sheep
- C. The redo transport mode is set to ASYNC for both standby databases
- D. The redo transport mode is set to ASYNC for the standby database Cats

Answer: B

NEW QUESTION 102

Which three are true regarding the Enterprise Manager Cloud Control Data Guard configuration verification wizard?

- A. it checks that supplemental logging is turned on if there is a logical standby database in the configuration.
- B. it verifies that parameter settings in the SPFILE or in memory or both, are consistent with the broker configuration properties for that database.
- C. It checks that the current data protection level is consistent with the broker's configured data protection mode.
- D. it modifies the database configurable parameters to match the values set for the broker configuration.
- E. It generates a workload on the primary database causing log switching, and monitors the arrival rate of redo on the standby database.

Answer: ABC

NEW QUESTION 104

Which three steps are prerequisites for the creation of a physical standby database on a separate server using the RMAN active database duplication method?

- A. Set the DB_UNIQUE_NAME parameter on the primary database to a different value than that of the DB_NAME parameter.
- B. Put the primary database into archivelog mode
- C. Startup nomount the standby database instance.
- D. Configure Oracle Net connectivity on the primary host to the standby database instance.
- E. Establish user equivalence for the database software owner between the primary host and standby host.

Answer: CDE

NEW QUESTION 109

Examine the Data Guard configuration:

```
DGMGRL> show configuration verbose;
```

Configuration –Animals

Protection Mode: MaxPerformance

Databases:

cats- Primary database

dogs-(*) Physical standby database

sheep- Physical standby database

(*) Fast-Start Failover target

Properties:

FastStartFailoverThreshold = '30'

OperationTimeout = '30'

TraceLevel = 'USER'

FastStartFailoverLagLimit = '30'

CommunicationTimeout= '180'

ObserverReconnect= '10'

FastStartFailoverAutoReinstate= 'FALSE'

FastStartFailoverPmyShutdown= 'TRUE'

BystanderFollowRoleChange= 'none'

ObserverOverride = 'FALSE'

Fast-Start Failover: ENABLED

Threshold: 30 seconds

Target: dogs

Observer: 015.example.com

Lag Limit: 30 seconds

Shutdown Primary: TRUE

Auto-reinstate: FALSE

Observer Reconnect: 10 seconds

Observer Override: TRUE

Configuration Status: SUCCESS Which two are true?

- A. The observer must run on host ol5.example.com and is currently not running.
- B. The observer will reinstate Sheep automatically after a failover, if required.
- C. The observer will mark another standby database as the failover target if the original failover target becomes unavailable.
- D. The observer will detect if the primary database is unable to accept new connections
- E. The former primary database will not be reinstated automatically after a failover.

Answer: BE

NEW QUESTION 111

Which three statements are true about snapshot standby databases?

- A. Tablespaces can be dropped.
- B. Tables can be dropped
- C. The broker may be used to fail over to a snapshot standby database.
- D. A logical standby database can be converted into a snapshot standby database.
- E. Tablespaces can be created.

Answer: ABE

NEW QUESTION 114

Which three are required in order to use Real-Time Query without lagging behind the primary?

- A. There must be standby redo logs on the standby database
- B. There must be standby redo logs on the primary database.

- C. The primary must ship redo asynchronously.
- D. COMPATIBLE must be set to 11.1.0 or higher.
- E. Real-Time apply must be enabled on the standby.

Answer: ADE

NEW QUESTION 118

Which two are prerequisites for creating a standby database using Enterprise Manager cloud control?

- A. The primary database must have FORCE LOGGING enabled.
- B. The primary database must be in archive log mode
- C. A backup of the primary database must exist.
- D. The primary host and the proposed standby database host must run the same operating system.
- E. The primary database instance must be started using an SPFILE.
- F. The primary database must have flashback enabled

Answer: AB

NEW QUESTION 121

Which four requirements can be met by deploying a logical standby database?

- A. Support for workloads requiring additional indexes.
- B. it can be used to create additional schemas.
- C. it can be used to create additional tables.
- D. It must have the same physical structure as the primary database.
- E. it must provide a disaster-recovery solution that protects all data with capability of performing switchovers and failovers.
- F. Support for workloads requiring additional materialized views.
- G. it can be used for Real Application Testing without affecting the disaster recovery capabilities.

Answer: ACEG

NEW QUESTION 123

Which three steps are prerequisites for the creation of a physical standby database on a separate server using the RMAN active database duplication method?

- A. Set the DB_UNIQUE_NAME parameter on the primary database to a different value than that of the DB_NAME parameter.
- B. Put the primary database into archivelog mode
- C. Startup nomount the standby database instance.
- D. Configure Oracle Net connectivity on the primary host to the standby database instance.
- E. Establish user equivalence for the database software owner between the primary host and standby host.

Answer: CDE

NEW QUESTION 126

A query on the view DBA_LOGSTBY_UNSUPPORTED on your primary database returns no rows

As a result of this, you decide that an upgrade may use logical standby databases. Which two are true about upgrading Data Guard environments consisting of one logical standby database running on a separate host from the primary?

- A. The upgrade always requires downtime until the upgrade of the logical standby is completed
- B. Using manual upgrade, catctl.pl can be executed in some cases on the primary and standby database simultaneously.
- C. The upgrade always required downtime until the upgrade of the primary is completed
- D. Using manual upgrade, catupgr.sql needs to run on the primary database only.
- E. SQL Apply on the local standby database must be stopped while the primary database is upgraded.
- F. Fast-Start Failover can be used to protect the primary database during the upgrade.

Answer: BE

NEW QUESTION 128

Which two are true about management of a far sync instance when using the Data Guard Broker?

- A. A far sync instance is in a disabled state in the broker configuration immediately after adding it
- B. A far sync instance that has its RedoRoutes property set may not be disabled in the broker configuration.
- C. Broker management of a far sync instance may only be disabled with the disable configuration DGMGRL command.
- D. A far sync instance need not exist before adding it to the broker configuration but may not be enabled until created

Answer: AB

NEW QUESTION 133

Which three are among the various tasks performed by the data Guard Monitor (DMON) process?

- A. performing role transitions when switchover requests are made
- B. communicating with DMON processes in other database instances that are part of the broker configuration
- C. activating role-based services appropriately in the various database instances of the configuration, based on the database role
- D. communicating with the DMON process of the observer to monitor a primary database in case a fast start failover is required.
- E. maintaining information about all members of the broker configuration in binary configuration files

Answer: ABE

NEW QUESTION 136

Which three are true concerning Automatic Block Media Recovery in a Data Guard environment when running an application as an ordinary Oracle user?

- A. Real Time Query must be enabled on the primary database
- B. Real Time Query must be enabled on the physical standby database.
- C. If a physically corrupt block is discovered on a physical standby database, then a valid block image from the primary database is retrieved.
- D. If a physically corrupt block is discovered on the primary database, then a valid block image from a physical standby database is retrieved
- E. if a physically corrupt block is discovered on a logical standby database, then a valid block image from the primary database is retrieved.
- F. If a physically corrupt block is discovered on a primary database, then a valid block image from the logically standby database is retrieved.

Answer: BCD

NEW QUESTION 141

Examine the Data Guard configuration after an accidental switchover to Sheep:

```
DGMGRL> show configuration;
```

Configuration –Animals

Protection Mode: MaxAvailability

Databases:

sheep- Primary database

dogs- Logical standby database

cats- Physical standby database (disabled)

ORA-16795: the standby database needs to be re-created

Fast-Start Failover: DISABLED

Configuration Status:

SUCCESS

Which three will be true after a switchover to Dogs?

- A. Sheep will be a disabled logical standby database.
- B. Sheep will be an enabled logical standby database.
- C. Cats will be a disabled physical standby database that can be manually enabled.
- D. Cats will be an enabled physical standby database.
- E. Dogs will be the primary database.

Answer: BCE

NEW QUESTION 146

You administer a Data Guard environment with a primary and two physical standby databases.

One of the physical standby databases is used for reporting and is on the same host as the primary database.

The other physical standby database is remote, used for disaster recovery and REDO is routed to it via a far sync instance.

Backups are offloaded to the remote physical standby.

Which three are true concerning the management of archive logs in this Data Guard configuration?

- A. Archive logs on the primary database may be deleted once they are applied on all standby databases.
- B. Archive logs on the primary database may be deleted once they are shipped on all standby databases.
- C. The deletion policy for archive logs on the remote physical standby should be set so that archived logs are deleted once they backed up at least once on the remote physical standby database.
- D. The deletion policy for archive logs on the remote physical standby should be set so that archived logs are deleted once they are applied on all standby databases.
- E. Archive logs on the primary database may be deleted once they are archived locally to disk.

Answer: ADE

NEW QUESTION 150

Which three statements are true about Global Sequences when connected to a physical standby database with Real-Time Query enabled?

- A. if the CACHE option is set then the size of the cache must be at least 100
- B. Their creation requires that a LOG_ARCHIVE_DEST_n parameter be defined in the standby that points back to their primary
- C. Their usage will always have a performance impact on the primary database.
- D. Their usage may have a performance impact on the physical standby database if the CACHE size is too small
- E. They must have the NOORDER and CACHE options set.

Answer: BDE

NEW QUESTION 153

You administer a Data Guard environment consisting of a primary and three physical standby databases.

One physical standby database is used for disaster recovery, one is used for reporting, and one is used as a replica for testing. The standby database used for testing is occasionally converted into a snapshot standby database and then converted back to a physical standby. The physical standby database is the only standby that is a mandatory destination. The broker configuration operates in MAXIMUM PERFORMANCE mode. Which ARCHIVELOG DELETION POLICY should be set, so that archive logs generated on the primary database are not deleted before they are consumed appropriately on each of the standby databases, but which allows them to be deleted from the primary as soon as it is safe to do so?

- A. CONFIGURE ARCHIVELOG DELETION POLICY TO APPLIED ON ALL STANDBY
- B. CONFIGURE ARCHIVELOG DELETION POLICY TO APPLIED ON STANDBY;
- C. CONFIGURE ARCHIVELOG DELETION POLICY TO SHIPPED TO ALL STANDBY;
- D. CONFIGURE ARCHIVELOG DELETION POLICY TO SHIPPED TO STANDBY,
- E. CONFIGURE ARCHIVELOG DELETION POLICY TO NONE;

Answer: B

NEW QUESTION 158

Which statement is true regarding Oracle Net connectivity for a Data Guard Broker configuration?

- A. To start SQL apply on a logical standby database, a TNS entry enabling connectivity to the primary database instance must be defined on the logical standby database host.
- B. the LOCALJJSTERNER initialization parameter must be set to the listener used to register the primary database instance.
- C. To enable Realtime Query on a physical standby database, a TNS entry enabling connectivity to the standby database instance must be defined on the primary database host.
- D. A TNS enabling connectivity to the primary database instance must be defined on each of the standby database hosts.
- E. A TNS entry or entries enabling connectivity to standby database instance(s) must be defined on the primary database host.

Answer: D

NEW QUESTION 160

A data file on one of your physical standby databases has been accidentally deleted and you must restore and recover it. All the archive logs required for recovery are still on disk in the directory pointed to by the log_archive_dest_1 parameter. Which three steps must be performed to restore the missing file and recover the standby database while it is in the MOUNT state?

- A. Recover the datafile by using the RMAN RECOVER DATAFILE command
- B. Restart the redo apply.
- C. Restore the datafile by using the RMAN RESTORE DATAFILE command.
- D. Stop the redo apply.
- E. Recover the database by using the RMAN RECOVER DATABASE command.

Answer: CDE

NEW QUESTION 163

Which statement is true regarding Oracle Net connectivity for a Data Guard Broker configuration?

- A. To start SQL apply on a logical standby database, a TNS entry enabling connectivity to the primary database instance must be defined on the logical standby database host.
- B. the LOCALJJSTERNER initialization parameter must be set to the listener used to register the primary database instance.
- C. To enable Realtime Query on a physical standby database, a TNS entry enabling connectivity to the standby database instance must be defined on the primary database host.
- D. A TNS enabling connectivity to the primary database instance must be defined on each of the standby database hosts.
- E. A TNS entry or entries enabling connectivity to standby database instance(s) must be defined on the primary database host.

Answer: D

NEW QUESTION 165

In which two cases is it possible to change the protection mode to maximum protection using Enterprise Manager Cloud Control?

- A. a snapshot standby database is the only standby database in the Data Guard configuration.
- B. A logical standby database is the only standby database in the data guard configuration.
- C. A far sync instance is the only Data Guard configuration member receiving redo in synchronous mode.
- D. Flashback is not enabled for either the primary database, the standby database, or both in the Data Guard configuration.
- E. The primary and standby databases are hosted on different operating systems.

Answer: BE

NEW QUESTION 170

Examine the Data Guard configuration: DGMGRL> show configuration;

Configuration - Animals Protection Mode MaxAvailability Databases

dogs- Primary database

cats- Snapshot standby database sheep- Snapshot standby database Fast-Start Failover DISABLED

Configuration Status: ORA-01034: ORACLE not available ORA-16625: cannot reach database "dogs"1 DGM-17017 unable to determine configuration status

You wish to perform a failover to Sheep

Which command, or sequence of commands, should you issue to the broker before executing "failover to sheep", using the broker?

- A. DGMGRL> convert database cats to physical standby,
- B. DGMGRL> convert database sheep to physical standby;
- C. DGMGRL> convert database sheep to physical standby; DGMGRL> convert database cats to physical standby;
- D. DGMGRL>edit configuration set protection mode as maxperformance; DGMGRL> convert database sheep to physical standby;
- E. None, because you can directly failover to a Snapshot Standby Database

Answer: C

NEW QUESTION 171

Which two statements are true about Real-Time Query?

- A. Setting STANDBY_MAX_DATA_DELAY =0 requires synchronous redo transport.
- B. Disabling Real-Time Query prevents the automatic start of redo apply when a physical standby database is opened READ ONLY.
- C. Real-Time Query sessions can be connected to a Far Sync instance.
- D. Real-Time Query has no limitations regarding the protection level of the Data Guard environment.
- E. A standby database enabled for Real-Time Query cannot be the Fast-Start Failover target of the Data Guard configuration.

Answer: BD

NEW QUESTION 172

Examine the Data Guard configuration:

```
DGMGRL> show configuration verbose;
```

Configuration –Animals

Protection Mode: MaxPerformance

Databases:

cats- Primary database
dogs-(*) Physical standby database
sheep- Physical standby database

(*) Fast-Start Failover target

Properties:

FastStartFailoverThreshold = '30'
OperationTimeout = '30'
TraceLevel = 'USER'
FastStartFailoverLagLimit = '30'
CommunicationTimeout= '180'
ObserverReconnect= '10'
FastStartFailoverAutoReinststate= 'FALSE'
FastStartFailoverPmyShutdown= 'TRUE'
BystanderFollowRoleChange= 'none'
ObserverOverride = 'FALSE'

Fast-Start Failover: ENABLED

Threshold: 30 seconds
Target: dogs
Observer: 015.example.com
Lag Limit: 30 seconds
Shutdown Primary: TRUE
Auto-reinststate: FALSE
Observer Reconnect: 10 seconds
Observer Override: TRUE

Configuration Status: SUCCESS Which two are true?

- A. The observer must run on host ol5.example com and is currently not running.

- B. The observer will reinstate Sheep automatically after a failover, if required.
- C. The observer will mark another standby database as the failover target if the original failover target becomes unavailable.
- D. The observer will detect if the primary database is unable to accept new connections
- E. The former primary database will not be reinstated automatically after a failover.

Answer: BE

NEW QUESTION 173

Attempting to start the observer raises an error: DGMGRL> start observer:

DGM-16954: Unable to open and lock the Observer configuration file Failed. Identify two possible reasons for this error

- A. Fast-Start Failover is not yet enabled for this Data Guard configuration
- B. The observer configuration file is marked read-only.
- C. There is already an observer running for this Data Guard configuration.
- D. There is another observer running for a Data Guard configuration which uses the same observer configuration file
- E. The broker configuration has not yet been created.

Answer: BD

NEW QUESTION 174

Examine the Data Guard configuration:

```
DGMGRL> show configuration;
```

```
Configuration –Animals
```

```
Protection Mode: MaxAvailability
```

```
Databases:
```

```
dogs- Primary database
```

```
sheep-Logical standby database
```

```
cats- Logical standby database
```

```
Fast-Start Failover: DISABLED
```

```
Configuration Status:
```

```
SUCCESS
```

Which three will be true after a switchover to Sheep?

- A. Cats will be an enabled logical standby database
- B. Cats will be a disabled logical standby database.
- C. Dogs will be a logical standby database.
- D. Dogs will be a physical standby database
- E. Sheep will be the primary database.

Answer: ACE

NEW QUESTION 179

Which two are prerequisites for configuring flashback database for Oracle 12c databases, in a Data Guard environment?

- A. a flash recovery area must be configured
- B. The database must be in MOUNT state.
- C. The database must be in ARCHIVELOG mode.
- D. A far sync instance must be configured to flash back a standby when the primary has been flashed back.
- E. The Data Guard Broker must be used.

Answer: AC

NEW QUESTION 184

Which three are required in order to use Real-Time Query without lagging behind the primary?

- A. There must be standby redo logs on the standby database
- B. There must be standby redo logs on the primary database.
- C. The primary must ship redo asynchronously.
- D. COMPATIBLE must be set to 11.1.0 or higher.
- E. Real-Time apply must be enabled on the standby.

Answer: ADE

NEW QUESTION 189

Your Data Guard environment consists of these components and settings:

1. A primary database
2. Two remote physical standby databases
3. The redo transport mode is set to SYNC.
4. Real-time query is enabled for both standby databases.
5. The DB_BLOCK_CHECKING parameter is set to TRUE on both standby databases.

You notice an increase in redo apply lag time on both standby databases.

Which two would you recommend to reduce the redo apply lag on the standby databases?

- A. Increase the size of the buffer cache on the physical standby database instances.
- B. Increase the number of standby redo log files on the standby databases.
- C. Decrease the redo log file size on the primary database.
- D. Lower DB_BLOCK_CHECKING to MEDIUM or LOW on the standby databases.
- E. Increase the size of standby redo log files on the standby databases.

Answer: AD

NEW QUESTION 193

Which three are true regarding the Enterprise Manager Cloud Control Data Guard configuration verification wizard?

- A. it checks that supplemental logging is turned on if there is a logical standby database in the configuration.
- B. it verifies that parameter settings in the SPFILE or in memory or both, are consistent with the broker configuration properties for that database.
- C. It checks that the current data protection level is consistent with the broker's configured data protection mode.
- D. it modifies the database configurable parameters to match the values set for the broker configuration.
- E. It generates a workload on the primary database causing log switching, and monitors the arrival rate of redo on the standby database.

Answer: ABC

NEW QUESTION 194

Which three are always benefits of using a logical standby database?

- A. it can be used for database rolling release upgrades
- B. it can be used to replicate a single pluggable database (PDB) in a multitenant container database.
- C. It can be used as an updatable database for Real Application testing and then converted back to a standby database without affecting the updates.
- D. It can be used for reporting workloads requiring additional indexes or materialized views or both.
- E. It provides a disaster-recovery solution with switchover and failover options that can recover any data updated on the primary database.
- F. it can be used for testing patches without affecting the primary database.

Answer: CDF

NEW QUESTION 196

Which three types of backups taken in which situations may be used to perform restore operations to a logical standby database in a Data Guard environment?

- A. backups of data files taken on the primary database if connected to the recovery catalog where the logical standby database is registered
- B. backups of data files taken on the standby database if connected to the recovery catalog where the logical standby database is registered
- C. backups of control files taken on the primary database if connected to the recovery catalog where the logical standby database is registered
- D. backups of data files taken on the logical standby database, if not connected to a recovery catalog
- E. backups of control files taken on the logical standby database if not connected to a recovery catalog

Answer: ADE

NEW QUESTION 198

Which three are true concerning Automatic Block Media Recovery in a Data Guard environment when running an application as an ordinary Oracle user?

- A. Real Time Query must be enabled on the primary database
- B. Real Time Query must be enabled on the physical standby database.
- C. If a physically corrupt block is discovered on a physical standby database, then a valid block image from the primary database is retrieved.
- D. If a physically corrupt block is discovered on the primary database, then a valid block image from a physical standby database is retrieved
- E. if a physically corrupt block is discovered on a logical standby database, then a valid block image from the primary database is retrieved.
- F. If a physically corrupt block is discovered on a primary database, then a valid block image from the logically standby database is retrieved.

Answer: BCD

NEW QUESTION 202

Examine this query and its output:

```
SQL> select fs_failover_status, fs_failover_current_target,  
2 fs_failover_observer_present, fs_failover_osever_host  
3 from v$database;  
FS_FAILOVER_STATUS FS_FAILOVER_CURRENT_TARGET  
FS_FAILOVER_OBSERVER_PRESENT FS_FAILOVER_OBSERVER_HOST
```

BYSTANDER cats NO
O17.example.com

Which are true?

- A. The observer is not connected to the database on which the query was executed.
- B. Cats is a bystander database.
- C. The observer is connected to the database on which the query was executed.
- D. The observer is currently running on o17.example.com
- E. The observer is not running, but should run on o17.example.com.

Answer: A

NEW QUESTION 207

Which two statements are true about Real-Time Query?

- A. Setting STANDBY_MAX_DATA_DELAY =0 requires synchronous redo transport.
- B. Disabling Real-Time Query prevents the automatic start of redo apply when a physical standby database is opened READ ONLY.
- C. Real-Time Query sessions can be connected to a Far Sync instance.
- D. Real-Time Query has no limitations regarding the protection level of the Data Guard environment.
- E. A standby database enabled for Real-Time Query cannot be the Fast-Start Failover target of the Data Guard configuration.

Answer: BD

NEW QUESTION 210

Which two are prerequisites for enabling Automatic Block Media Recovery in a Data Guard environment consisting of a primary database, one physical standby database and one logical standby database?

- A. FLASHBACK DATABASE must be enabled on the physical standby database.
- B. There must be connectivity between the primary and the physical standby database.
- C. FLASHBACK DATABASE must be enabled on the primary database.
- D. The physical standby database must have Real-Time Apply enabled.
- E. The logical standby database must have Real-Time Query enabled

Answer: CD

NEW QUESTION 213

Which two are true about management of a far sync instance when using the Data Guard Broker?

- A. A far sync instance is in a disabled state in the broker configuration immediately after adding it
- B. A far sync instance that has its RedoRoutes property set may not be disabled in the broker configuration.
- C. Broker management of a far sync instance may only be disabled with the disable configuration DGMGRL command.
- D. A far sync instance need not exist before adding it to the broker configuration but may not be enabled until created

Answer: AB

NEW QUESTION 217

After converting your physical standby database to a logical database, you get an error:

```
DGMGRL> show configuration
Configuration- proddg
Protection Mode: MaxPerformance
Databases:
prod-Primary datatabse
prodsby-Physical standby database
Error: ORA-16810 multiple errors or warnings detected for database
Fast-Start Failover: DISABLED
Configuration Status:
ERROR
```

How can you rectify the error?

- A. Add a logical standby database PRODSBY and enable it, thereby replacing the physical standby database metadata in the broker configuration.
- B. Remove the physical standby database PRODSBY from the broker configuration, add a logical standby database PRODSBY to the broker configuration and enable it.
- C. Reinstate the physical standby database PRODSBY as a logical standby, thereby replacing the physical standby database metadata in the broker configuration.
- D. Reinstate both the primary and physical standby databases The broker will automatically detect that PRODSBY is a logical standby update to the metadata.

Answer: D

NEW QUESTION 220

Which four requirements can be met by deploying a logical standby database?

- A. Support for workloads requiring additional indexes.
- B. it can be used to create additional schemas.
- C. it can be used to create additional tables.
- D. It must have the same physical structure as the primary database.
- E. it must provide a disaster-recovery solution that protects all data with capability of performing switchovers and failovers.
- F. Support for workloads requiring additional materialized views.
- G. it can be used for Real Application Testing without affecting the disaster recovery capabilities.

Answer: ACEG

NEW QUESTION 223

Examine the Data Guard configuration: DGMGRL> show configuration Configuration-Animals

Protection Mode: MaxAvailability Databases:

Sheep- Primary database

Warning: ORA-16817: unsynchronized fast-start failover configuration Dogs - (*) Physical standby database (disabled)

ORA-16661: the standby database needs to be reinstated

Fast-Start Failover: ENABLED Configuration Status: WARNING And the fast-start failover configuration:

DGMGRL> show fast_start failover; Fast-Start Failover: ENABLED Threshold: 30 seconds Target: dogs

Observer: 017.example.com Lag Limit: 30 seconds (not in use) Shutdown Primary: TRUE Auto-reinstate: TRUE Observer Reconnect 10 seconds Observer Override: FALSE

Configurable Failover Conditions Hearth Conditions: Corrupted Controlfile YES Inaccessible Logfile NO

Stuck Archiver NO Datafile Offline YES Oracle error Conditions

ORA-01578: ORACLE data block corrupted (file # %s, block # %s) And finally the reason for the fail over:

SQL> select last_failover_reason from v\$fs_failover_stats;

LAST_FAILOVER_REASON

ORA-01578: ORACLE data block corrupted (file # %s, block # %s)

Identify the task, or sequence of tasks, to bring the configuration into the SUCCESS state.

- A. Bring Dogs to the NOMOUNT state and let the broker reinstate Dogs automatically.
- B. MOUNT DOGS and issue "reinstate database dogs:" at the DGMGRL prompt while connected to Dogs.
- C. MOUNT DOGS and issue "reinstate database dogs:" at the DGMGRL prompt while connected to Sheep
- D. Open Dogs and let the broker reinstate Dogs automatically.

Answer: C

NEW QUESTION 227

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 1z0-066 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 1z0-066 Product From:

<https://www.2passeasy.com/dumps/1z0-066/>

Money Back Guarantee

1z0-066 Practice Exam Features:

- * 1z0-066 Questions and Answers Updated Frequently
- * 1z0-066 Practice Questions Verified by Expert Senior Certified Staff
- * 1z0-066 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1z0-066 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year