

CRT-450 Dumps

Salesforce Certified Platform Developer I (SU18)

<https://www.certleader.com/CRT-450-dumps.html>



NEW QUESTION 1

Which statement results in an Apex compiler error?

- A. `Map<Id,Leas> lmap = new Map<Id,Lead>([Select ID from Lead Limit 8]);`
- B. `Date d1 = Date.Today(), d2 = Date.ValueOf('2018-01-01');`
- C. `Integer a=5, b=6, c, d = 7;`
- D. `List<string> s = List<string>{'a','b','c'};`

Answer: D

NEW QUESTION 2

Which three tools can deploy metadata to production? (Choose three.)

- A. Change Set from Developer Org
- B. Force.com IDE
- C. Data Loader
- D. Change Set from Sandbox
- E. Metadata API

Answer: ADE

NEW QUESTION 3

How should a developer make sure that a child record on a custom object, with a lookup to the Account object, has the same sharing access as its associated account?

- A. Create a Sharing Rule comparing the custom object owner to the account owner.
- B. Create a validation rule on the custom object comparing the record owners on both records.
- C. Include the sharing related list on the custom object page layout.
- D. Ensure that the relationship between the objects is Master-Detail

Answer: D

NEW QUESTION 4

Which approach should be used to provide test data for a test class?

- A. Query for existing records in the database.
- B. Execute anonymous code blocks that create data.
- C. Use a test data factory class to create test data.
- D. Access data in `@TestVisible` class variable

Answer: C

NEW QUESTION 5

A developer created a Lightning component to display a short text summary for an object and wants to use it with multiple Apex classes. How should the developer design the Apex classes?

- A. Have each class define method `getObject()` that returns the `sObject` that is controlled by the Apex class.
- B. Extend each class from the same base class that has a method `getTextSummary()` that returns the summary.
- C. Have each class implement an interface that defines method `getTextSummary()` that returns the summary.
- D. Have each class define method `getTextSummary()` that returns the summary

Answer: C

NEW QUESTION 6

When is an Apex Trigger required instead of a Process Builder Process?

- A. When a record needs to be created
- B. When multiple records related to the triggering record need to be updated
- C. When a post to Chatter needs to be created
- D. When an action needs to be taken on a delete or undelete, or before a DML operation is executed.

Answer: D

NEW QUESTION 7

What is the requirement for a class to be used as a custom Visualforce controller?

- A. Any top-level Apex class that has a constructor that returns a `PageReference`
- B. Any top-level Apex class that extends a `PageReference`
- C. Any top-level Apex class that has a default, no-argument constructor
- D. Any top-level Apex class that implements the controller interface

Answer: D

NEW QUESTION 8

When an Account's custom picklist field called Customer Sentiment is changed to a value of "Confused", a new related Case should automatically be created. Which two methods should a developer use to create this case? (Choose two.)

- A. Process Builder
- B. Apex Trigger
- C. Custom Button
- D. Workflow Rule

Answer: AB

NEW QUESTION 9

When viewing a Quote, the sales representative wants to easily see how many discounted items are included in the Quote Line Items. What should a developer do to meet this requirement?

- A. Create a trigger on the Quote object that queries the Quantity field on discounted Quote Line Items.
- B. Create a Workflow Rule on the Quote Line Item object that updates a field on the parent Quote when the item is discounted.
- C. Create a roll-up summary field on the Quote object that performs a SUM on the quote Line Item Quantity field, filtered for only discounted Quote Line Items.
- D. Create a formula field on the Quote object that performs a SUM on the Quote Line Item Quantity field, filtered for only discounted Quote Line Items.

Answer: C

NEW QUESTION 10

An org has a single account named 'NoContacts' that has no related contacts. Given the query:
List<Account> accounts = [Select ID, (Select ID, Name from Contacts) from Account where Name='NoContacts']; What is the result of running this Apex?

- A. accounts[0].contacts is invalid Apex.
- B. accounts[0].contacts is an empty Apex.
- C. accounts[0].contacts is Null.
- D. A QueryException is throw

Answer: B

NEW QUESTION 10

A developer is asked to create a PDF quote document formatted using the company's branding guidelines, and automatically save it to the Opportunity record. Which two ways should a developer create this functionality? (Choose two.)

- A. Install an application from the AppExchange to generate documents.
- B. Create a Visualforce page with custom styling.
- C. Create an email template and use it in Process Builder.
- D. Create a visual flow that implements the company's formattin

Answer: AB

NEW QUESTION 13

Which two statements are true about using the @testSetup annotation in an Apex test class? (Choose two.)

- A. The @testSetup annotation cannot be used when the @isTest(SeeAllData=True) annotation is used.
- B. Test data is inserted once for all test methods in a class.
- C. Records created in the @testSetup method cannot be updates in individual test methods.
- D. The @testSetup method is automatically executed before each test method in the test class is execute

Answer: D

NEW QUESTION 14

Which three declarative fields are correctly mapped to variable types in Apex? (Choose three.)

- A. Number maps to Decimal.
- B. Number maps to Integer.
- C. TextArea maps to List of type String.
- D. Date/Time maps to Dateline.
- E. Checkbox maps to Boolea

Answer: ADE

NEW QUESTION 15

A method is passed a list of generic sObjects as a parameter. What should the developer do to determine which object type (Account, Lead, or Contact, for example) to cast each sObject?

- A. Use the first three characters of the sObject ID to determine the sObject type.
- B. Use the getSObjectType method on each generic sObject to retrieve the sObject token.
- C. Use the getSObjectName method on the sObject class to get the sObject name.
- D. Use a try-catch construct to cast the sObject into one of the three sObject type

Answer: B

NEW QUESTION 20

What are two valid options for iterating through each Account in the collection List<Account> named AccountList? (Choose two.)

- A. for (Account theAccount : AccountList) {...}
- B. for(AccountList) {...}
- C. for (List L : AccountList) {...}
- D. for (Integer i=0; i < AccountList.Size(); i++) {...}

Answer: AD

NEW QUESTION 25

A Visualforce page is required for displaying and editing Case records that includes both standard and custom functionality defined in an Apex class called myControllerExtension.

The Visualforce page should include which <apex:page> attribute(s) to correctly implement controller functionality?

- A. controller="Case" and extensions="myControllerExtension"
- B. extensions="myControllerExtension"
- C. controller="myControllerExtension"
- D. standardController="Case" and extensions="myControllerExtension"

Answer: D

NEW QUESTION 28

Which two strategies should a developer use to avoid hitting governor limits when developing in a multi-tenant environment? (Choose two.)

- A. Use collections to store all fields from a related object and not just minimally required fields.
- B. Use methods from the "Limits" class to monitor governor limits.
- C. Use SOQL for loops to iterate data retrieved from queries that return a high number of rows.
- D. Use variables within Apex classes to store large amounts of data

Answer: BC

NEW QUESTION 32

A developer writes the following code:

```
List<Account> acc = [SELECT Id FROM Account LIMIT 10];
Delete acc;
Database.emptyRecycleBin(acc);

System.Debug(Limits.getDMLStatements() + ', ' + Limits.getLimitDMLStatements());
```

What is the result of the debug statement? A. 1, 100

- A. 1, 150
- B. 2, 150
- C. 2, 200

Answer: C

NEW QUESTION 37

A developer created a Visualforce page and a custom controller with methods to handle different buttons and events that can occur on the page. What should the developer do to deploy to production?

- A. Create a test class that provides coverage of the Visualforce page.
- B. Create a test page that provides coverage of the Visualforce page.
- C. Create a test page that provides coverage of the custom controller.
- D. Create a test class that provides coverage of the custom controller

Answer: D

NEW QUESTION 39

Where can a developer identify the time taken by each process in a transaction using Developer Console log inspector?

- A. Performance Tree tab under Stack Tree panel
- B. Execution Tree tab under Stack Tree panel
- C. Timeline tab under Execution Overview panel
- D. Save Order tab under Execution Overview panel

Answer: C

NEW QUESTION 42

A developer is asked to set a picklist field to 'Monitor' on any new Leads owned by a subset of Users. How should the developer implement this request?

- A. Create an after insert Lead trigger.
- B. Create a before insert Lead trigger.
- C. Create a Lead Workflow Rule Field Update.
- D. Create a Lead formula field

Answer: C

NEW QUESTION 45

Which two number expressions evaluate correctly? (Choose two.)

- A. Double d = 3.14159;
- B. Integer l = 3.14159;
- C. Decimal d = 3.14159;
- D. Long l = 3.14159;

Answer: AC

NEW QUESTION 50

Which two Apex data types can be used to reference a Salesforce record ID dynamically? (Choose two.)

- A. ENUM
- B. sObject
- C. External ID
- D. String

Answer: AD

NEW QUESTION 53

How should a developer avoid hitting the governor limits in test methods?

- A. Use @TestVisible on methods that create records.
- B. Use Test.loadData() to load data from a static resource.
- C. Use @IsTest (SeeAllData=true) to use existing data.
- D. Use Test.startTest() to reset governor limit

Answer: D

NEW QUESTION 54

A developer executes the following code in the Developer Console:

```
List<Account> fList = new List<Account> ();For(integer i= 1; i <= 200; i++){fList.add(new Account ( Name = 'Universal Account ' + i));}Insert fList;List <Account> sList = new List<Account>();For (integer l = 201; l <= 20000; l ++){sList.add(new Account (Name = 'Universal Account ' + l));}Insert sList;How many accounts are created in the Salesforce organization ?
```

- A. 20000
- B. 200
- C. 1000

Answer: B

NEW QUESTION 56

A company has a custom object named Warehouse. Each Warehouse record has a distinct record owner, and is related to a parent Account in Salesforce. Which kind of relationship would a developer use to relate the Account to the Warehouse?

- A. One -to -Many
- B. Lookup
- C. Master -Detail
- D. Parent -Child

Answer: B

NEW QUESTION 57

Which data type or collection of data types can SOQL statements populate or evaluate to? (Choose 3)

- A. A single sObject
- B. An integer
- C. A string
- D. A list of sObjects
- E. A Boolean

Answer: ABD

NEW QUESTION 61

A developer in a Salesforce org with 100 Accounts executes the following code using the Developer console: Account myAccount = new Account(Name = 'MyAccount');Insert myAccount;For (Integer x = 0; x < 250; x++)

```
{Account newAccount = new Account (Name='MyAccount' + x);try {Insert newAccount;}catch (Exception ex) {System.debug (ex) ;}}insert new Account (Name='myAccount'); How many accounts are in the org after this code is run?
```

- A. 101
- B. 100
- C. 102

D. 252

Answer: B

NEW QUESTION 66

What is the return data type when `ApexPages.currentPage().getParameters()` is used to retrieve URL parameters from a visualforce controller?

- A. Map
- B. List
- C. Enum
- D. String[]

Answer: A

NEW QUESTION 71

Before putting an app into production, which step should be taken?

- A. Run the production check feature via the web interface
- B. Switch to a production database
- C. Insure that you have installed a performance introspection add-on
- D. Scale your dynos

Answer: A

NEW QUESTION 73

A developer created an Apex trigger using the Developer Console and now wants to debug code. How can the developer accomplish this in the Developer Console?

- A. Select the Override Log Triggers checkbox for the trigger
- B. Add the user name in the Log Inspector.
- C. Open the Progress tab in the Developer Console.
- D. Open the logs tab in the Developer Console

Answer: D

NEW QUESTION 74

What is an accurate constructor for a custom controller named "MyController"?

- A. `public MyController () { account = new Account (); }`
- B. `public MyController (sObject obj) { account = (Account) obj; }`
- C. `public MyController (List objects) { accounts = (List) objects; }`
- D. `public MyController (ApexPages.StandardController stdController) { account = (Account) stdController.getRecord(); }`

Answer: A

NEW QUESTION 75

What is true for a partial sandbox that is not true for a full sandbox? Choose 2 answers:

- A. More frequent refreshes.
- B. Only Includes necessary metadata.
- C. Use of change sets.
- D. Limited to 5 GB of data

Answer: AD

NEW QUESTION 77

A developer has the following code block:

```
public class PaymentTax {public static decimal SalesTax = 0.0875;} trigger OpportunityLineItemTrigger on OpportunityLineItem (before insert, before update)
{PaymentTax PayTax = new PaymentTax();decimal ProductTax = ProductCost * XXXXXXXXXXXX;} To calculate the productTax, which code segment would a
developer insert at the XXXXXXXXXXXX to make the value the class variable SalesTax accessible within the trigger?
```

- A. `SalesTax`
- B. `PayTax.SalesTax`
- C. `PaymentTax.SalesTax`
- D. `OpportunityLineItemTngger.SalesTax`

Answer: C

NEW QUESTION 78

Which code block returns the ListView of an Account object using the following debug statement? `system.debug(controller.getListViewOptions());`

- A. `ApexPages.StandardSetController controller = new ApexPages.StandardSetController(Database.getQueryLocator('SELECT Id FROM Account LIMIT 1'));`
- B. `ApexPages.StandardController controller = new ApexPages.StandardController([SELECT Id FROM Account LIMIT 1]);`
- C. `ApexPages.StandardController controller = new ApexPages.StandardController(Database.getQueryLocator('SELECT Id FROM Account LIMIT 1'));`
- D. `ApexPages.StandardController controller = new ApexPages.StandardController([SELECT Id FROM Account LIMIT 1]);`

Answer: A

NEW QUESTION 82

The Sales Management team hires a new intern. The intern is not allowed to view Opportunities, but needs to see the Most Recent Closed Date of all child Opportunities when viewing an Account record. What would a developer do to meet this requirement?

- A. Create a trigger on the Account object that queries the Close Date of the most recent Opportunities.
- B. Create a Workflow rule on the Opportunity object that updates a field on the parent Account.
- C. Create a formula field on the Account object that performs a MAX on the Opportunity Close Date field.
- D. Create a roll-up summary field on the Account object that performs a MAX on the Opportunity Close Date field.

Answer: D

NEW QUESTION 83

How would a developer determine if a CustomObject c record has been manually shared with the current user in Apex?

- A. By querying the role hierarchy.
- B. By calling the isShared() method for the record.
- C. By querying CustomObject Share.
- D. By calling the profile settings of the current user.

Answer: C

NEW QUESTION 84

A company wants a recruiting app that models candidates and interviews; displays the total number of interviews on each candidate record; and defines security on interview records that is independent from the security on candidate records. What would a developer do to accomplish this task? Choose 2 answers

- A. Create a roll-up summary field on the Candidate object that counts Interview records.
- B. Create a master-detail relationship between the Candidate and Interview objects.
- C. Create a lookup relationship between the Candidate and Interview objects.
- D. Create a trigger on the Interview object that updates a field on the Candidate object.

Answer: CD

NEW QUESTION 89

A developer writes a SOQL query to find child records for a specific parent. How many levels can be returned in a single query?

- A. 1
- B. 7
- C. 5
- D. 3

Answer: C

NEW QUESTION 94

In a single record, a user selects multiple values from a multi-select picklist. How are the selected values represented in Apex?

- A. As a String with each value separated by a comma
- B. As a Set with each value as an element in the set
- C. As a String with each value separated by a semicolon
- D. As a List with each value as an element in the list

Answer: C

NEW QUESTION 96

When loading data into an operation, what can a developer do to match records to update existing records? (Choose 2)

- A. Match an auto-generated Number field to a column in the imported file.
- B. Match an external Id Text field to a column in the imported file.
- C. Match the Name field to a column in the imported file.
- D. Match the Id field to a column in the imported file.

Answer: BD

NEW QUESTION 99

A developer needs to create records for the object Property c. The developer creates the following code block:
`List propertiesToCreate = helperClass.createProperties(); try { // line 3 } catch (Exception exp) { //exception handling }`
Which line of code would the developer insert at line 3 to ensure that at least some records are created, even if a few records have errors and fail to be created?

- A. Database.insert(propertiesToCreate, false);
- B. insert propertiesToCreate;
- C. Database.insert(propertiesToCreate, System.ALLOW_PARTIAL);
- D. Database.insert(propertiesToCreate);

Answer: A

NEW QUESTION 103

An org has different Apex Classes that provide Account -related functionality. After a new validation rule is added to the object, many of the test methods fail. What can be done to resolve the failures and reduce the number of code changes needed for future validation rules? Choose 2 answers:

- A. Create a method that creates valid Account records, and call this method from within test methods.
- B. Create a method that loads valid Account records from a Static Resource, and call this method within test methods.
- C. Create a method that performs a callout for a valid Account record, and call this method from within test methods.
- D. Create a method that queries for valid Account records, and call this method from within test method

Answer: AB

NEW QUESTION 107

On a Visualforce page with a custom controller, how should a developer retrieve a record by using an ID that is passed on the URL?

- A. Use the constructor method for the controller.
- B. Use the `$Action.View` method in the Visualforce page.
- C. Create a new PageReference object with the Id.
- D. Use the tag in the Visualforce pag

Answer: A

NEW QUESTION 108

In which two org types can a developer create new Apex Classes? Choose 2 answers

- A. Developer Edition
- B. Sandbox
- C. Enterprise Edition
- D. Unlimited

Answer: AB

NEW QUESTION 109

A developer needs to confirm that an Account trigger is working correctly without changing the organization's data. What would the developer do to test the Account trigger?

- A. Use the Test menu on the developer Console to run all test classes for the account trigger.
- B. Use the New button on the Salesforce Accounts Tab to create a new Account record.
- C. Use the Open Execute Anonymous feature on the Developer Console to run an 'insert Account' DML statement.
- D. Use Deploy from the Force.com IDE to deploy an 'insert Account' Apex clas

Answer: A

NEW QUESTION 113

What are two testing consideration when deploying code from a sandbox to production? Choose 2 answers

- A. 75% of test must execute without failure
- B. 100% of test must execute without failure
- C. Apex code requires 75% coverage
- D. Apex code requires 100% coverage

Answer: BC

NEW QUESTION 117

A Visualforce page has a standard controller for an object that has a lookup relationship to a parent object. How can a developer display data from the parent record on the page?

- A. By adding a second standard controller to the page for the parent record.
- B. By using a roll-up formula field on the child record to include data from the parent record.
- C. By using SOQL on the Visualforce page to query for data from the parent record.
- D. By using merge field syntax to retrieve data from the parent record.

Answer: D

NEW QUESTION 118

What is the value of x after the code segment executes?

```
String x = 'A'; Integer i = 10; if ( i < 15 ) { i = 15; x = 'B'; } else if ( i < 20 ) { x = 'C'; } else { x = 'D'; }
```

- A. D
- B. A
- C. B
- D. C

Answer: C

NEW QUESTION 120

A developer creates a Workflow Rule declaratively that updates a field on an object. An Apex update trigger exists for that object. What happens when a user updates a record?

- A. No changes are made to the data.
- B. Both the Apex Trigger and Workflow Rule are fired only once.
- C. The Workflow Rule is fired more than once.
- D. The Apex Trigger is fired more than once.

Answer: D

NEW QUESTION 122

Which two number expression evaluate correctly? Choose 2 answers

- A. Integer I = 3.14159;
- B. Decimal D = 3.14159;
- C. Long l = 3.14159;
- D. Double D = 3.14159;

Answer: BD

NEW QUESTION 124

Which type of code represents the Controller in MVC architecture on the Force.com platform? (Choose 2)

- A. JavaScript that is used to make a menu item display itself.
- B. A static resource that contains CSS and images.
- C. Custom Apex and JavaScript code that is used to manipulate data.
- D. StandardController system methods that are referenced by Visualforce

Answer: CD

NEW QUESTION 125

A developer is creating an application to track engines and their parts. An individual part can be used in different types of engines. What data model should be used to track the data and to prevent orphan records?

- A. Create a junction object to relate many engines to many parts through a master-detail relationship
- B. Create a lookup relationship to represent how each part relates to the parent engine object.
- C. Create a master-detail relationship to represent the one-to-many model of engines to parts.
- D. Create a junction object to relate many engines to many parts through a lookup relationship

Answer: A

NEW QUESTION 127

Which resource can be included in a Lightning Component bundle? Choose 2 answers

- A. Apex class
- B. Adobe Flash
- C. JavaScript
- D. Documentation

Answer: CD

NEW QUESTION 131

What is a benefit of the Lightning Component framework? Choose 3 answers

- A. It uses client-side Apex controllers for logic.
- B. It uses a traditional publish-subscribe model.
- C. It uses an event-driven architecture
- D. It uses an MVC architectural design pattern.
- E. It uses server-side JavaScript controller for logic.

Answer: BCD

NEW QUESTION 133

A developer wants to list all of the Tasks for each Account on the Account detail page. When a task is created for a Contact, what does the developer need to do to display the Task on the related Account record?

- A. Nothing
- B. The task is automatically displayed on the Account page.
- C. Nothing
- D. The Task cannot be related to an Account and a Contact.
- E. Create a Workflow rule to relate the Task to the Contact's Account.
- F. Create an Account formula field that displays the Task information

Answer: A

NEW QUESTION 136

Which type of information is provided by the Checkpoints tab in the Developer Console? (Choose 2)

- A. Namespace
- B. Time
- C. Exception
- D. Debug Statement

Answer: AB

NEW QUESTION 139

A developer creates an Apex Trigger with the following code block:
`List<Account> customers = new List<Account>();
For (Order c o: trigger.new){
Account a = [SELECT Id, Is_Customer c FROM Account WHERE Id = :o.Customer c];
a.Is_Customer c = true;
customers.add(a);
Database.update(customers, false);
}`
The developer tests the code using Apex Data Loader and successfully loads 10 Orders. Then, the developer loads 150 Orders. How many Orders are successfully loaded when the developer attempts to load the 150 Orders?

- A. 1
- B. 150
- C. 100

Answer: A

NEW QUESTION 144

What must the Controller for a Visualforce page utilize to override the Standard Opportunity view button?

- A. The StandardSetController to support related lists for pagination.
- B. The Opportunity StandardController for pre -built functionality.
- C. A callback constructor to reference the StandardController.
- D. A constructor that initializes a private Opportunity variable

Answer: B

NEW QUESTION 146

What is a correct pattern to follow when programming in Apex on a Multi-tenant platform?

- A. Apex code is created in a separate environment from schema to reduce deployment errors.
- B. DML is performed on one record at a time to avoid possible data concurrency issues.
- C. Queries select the fewest fields and records possible to avoid exceeding governor limits.
- D. Apex classes use the "with sharing" keyword to prevent access from other server tenant

Answer: C

NEW QUESTION 147

What should a developer working in a sandbox use to exercise a new test Class before the developer deploys that test production? Choose 2 answers

- A. The REST API and ApexTestRun method
- B. The Apex Test Execution page in Salesforce Setup.
- C. The Test menu in the Developer Console.
- D. The Run Tests page in Salesforce Setup

Answer: BC

NEW QUESTION 150

How can a developer refer to, or instantiate a PageReference in Apex? Choose 2 answers

- A. By using a PageReference with a partial or full URL.
- B. By using the Page object and a Visualforce page name.
- C. By using the ApexPages.Page() method with a Visualforce page name.
- D. By using the PageReference.Page() method with a partial or full UR

Answer: AB

NEW QUESTION 152

Which component is available to deploy using Metadata API? Choose 2 answers

- A. Case Layout
- B. Account Layout
- C. Case Feed Layout
- D. ConsoleLayout

Answer: AB

NEW QUESTION 157

What would a developer do to update a picklist field on related Opportunity records when a modification to the associated Account record is detected?

- A. Create a process with Process Builder.
- B. Create a workflow rule with a field update.
- C. Create a Lightning Component.
- D. Create a Visualforce page

Answer: A

NEW QUESTION 159

A developer wants to display all of the available record types for a Case object. The developer also wants to display the picklist values for the Case.Status field. The Case object and the Case Status field are on a custom visualforce page. Which action can the developer perform to get the record types and picklist values in the controller? Choose 2 answers

- A. Use Schema.PicklistEntry returned by Case Status getDescribe().getPicklistValues().
- B. Use Schema.RecordTypeInfo returned by Case.SObjectType getDescribe().getRecordTypeInfos()
- C. Use SOQL to query Case records in the org to get all the RecordType values available for Case.
- D. Use SOQL to query Case records in the org to get all value for the Status picklist field

Answer: AB

NEW QUESTION 162

A developer created a lightning component name accountList.cmp that display a list of Accounts. Client-side logic that is executed when a user hovers over an account in the list should be stored in which bundle member?

- A. AccountListHelper.js
- B. AccountListRenderer.js
- C. AccountList.renderer
- D. AccountList.helper

Answer: C

NEW QUESTION 164

To which primitive data type in Apex is a currency field atomically assigned?

- A. Integer
- B. Decimal
- C. Double
- D. Currency

Answer: B

NEW QUESTION 168

Which actions can a developer perform using the Schema Builder? Choose 2 answers

- A. Create a custom field and automatically add it to an existing page layout.
- B. Create a view containing only standard and system objects.
- C. Create a custom object and define a lookup relationship on that object
- D. Create a view of objects and relationships without fields

Answer: BC

NEW QUESTION 173

Developer needs to automatically populate the Reports To field in a Contact record based on the values of the related Account and Department fields in the Contact record. Which type of trigger would the developer create? Choose 2 answers

- A. Before update
- B. After insert
- C. Before insert
- D. After update

Answer: AC

NEW QUESTION 176

A reviewer is required to enter a reason in the comments field only when a candidate is recommended to be hired. Which action can a developer take to enforce this requirement?

- A. Create a required Visualforce component.
- B. Create a formula field.
- C. Create a required comments field.
- D. Create a validation rule

Answer: D

NEW QUESTION 179

The Review_c object has a lookup relationship to the job_Application_c object. The job_Application_c object has a master detail relationship up to the position_c object. The relationship is based on the auto populated defaults?

What is the recommended way to display field data from the related Review_c records a Visualforce page for a single Position_c record? Select one of the following:

- A. Utilize the Standard Controller for Position_c and cross-object Formula Fields on the Job_Application_c object to display Review_c data.
- B. Utilize the Standard Controller for Position_c and a Controller Extension to query for Review_c data.
- C. Utilize the Standard Controller for Position_c and expression syntax in the Page to display related Review_c through the Job_Application_c inject.
- D. Utilize the Standard Controller for Position_c and cross-object Formula Fields on the Review_c object to display Review_c data.

Answer: B

NEW QUESTION 180

A developer is creating a test coverage for a class and needs to insert records to validate functionality. Which method annotation should be used to create records for every method in the test class?

- A. @BeforeTest
- B. @isTest(SeeAllData=True)
- C. @TestSetup
- D. @PreTest

Answer: C

NEW QUESTION 185

How can a developer retrieve all Opportunity record type labels to populate a list collection? Choose 2 answers

- A. Obtain describe object results for the Opportunity object.
- B. Write a for loop that extracts values from the Opportunity.RecordType.Name field.
- C. Use the global variable \$RecordType and extract a list from the map.
- D. Write a SOQL for loop that iterates on the RecordType object.

Answer: AD

NEW QUESTION 186

Which resource can be included in a Lightning Component bundle? Choose 2 answers

- A. Apex class
- B. Adobe Flash
- C. JavaScript
- D. Documentation

Answer: CD

NEW QUESTION 191

A candidate may apply to multiple jobs at the company Universal Containers by submitting a single application per job posting. Once an application is submitted for a job posting, that application cannot be modified to be resubmitted to a different job posting. What can the administrator do to associate an application with each job posting in the schema for the organization?

- A. Create a master-detail relationship in the Job Postings custom object to the Applications custom object.
- B. Create a master-detail relationship in the Application custom object to the Job Postings custom object.
- C. Create a lookup relationship on both objects to a junction object called Job Posting Applications.
- D. Create a lookup relationship in the Applications custom object to the Job Postings custom object.

Answer: A

NEW QUESTION 196

A developer has the following query: Contact c = [SELECT id, firstname, lastname, email FROM Contact WHERE lastname = 'Smith']; What does the query return if there is no Contact with the last name 'Smith'?

- A. A contact initialized to null.
- B. An error that no rows are found.
- C. An empty List of Contacts.
- D. A Contact with empty value

Answer: B

NEW QUESTION 198

A Hierarchy Custom Setting stores a specific URL for each profile in Salesforce. Which statement can a developer use to retrieve the correct URL for the current user's profile and display this on a Visualforce Page?

- A. {!\$Setup.Url_Settings C.Instance[Profile.Id].URL c}
- B. {!\$Setup.Url_Settings C.URL c}
- C. {!\$Setup.Url_Settings C.[Profile.Id].URL c}
- D. {!\$Setup.Url_Settings C.[\$Profile.Id].URL c}

Answer: B

NEW QUESTION 202

How can a developer avoid exceeding governor limits when using Apex Triggers? (Choose 2)

- A. By using a helper class that can be invoked from multiple triggers
- B. By using Maps to hold data from query results
- C. By using the Database class to handle DML transactions
- D. By performing DML transactions on a list of sObject

Answer: BD

NEW QUESTION 205

Which statement about the Lookup Relationship between a Custom Object and a Standard Object is correct?

- A. The Lookup Relationship on the Custom Object can prevent the deletion of the Standard Object.
- B. The Lookup Relationship cannot be marked as required on the page layout for the Custom Object.
- C. The Custom Object will be deleted when the referenced Standard Object is deleted.
- D. The Custom Object inherits security from the referenced Standard Objects

Answer: C

NEW QUESTION 208

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your CRT-450 Exam with Our Prep Materials Via below:

<https://www.certleader.com/CRT-450-dumps.html>