



**Amazon**

## **Exam Questions AWS-Certified-Solutions-Architect-Professional**

Amazon AWS Certified Solutions Architect Professional

#### NEW QUESTION 1

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent notification to all devices associated with an identity to notify them that new data is available.

- A. get
- B. post
- C. pull
- D. push

**Answer:** D

#### Explanation:

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent push notification to all devices associated with an identity to notify them that new data is available.

Reference: <http://aws.amazon.com/cognito/faqs/>

#### NEW QUESTION 2

An organization is planning to host a Wordpress blog as well a Joomla CMS on a single instance launched with VPC. The organization wants to have separate domains for each application and assign them using Route 53. The organization may have about ten instances each with two applications as mentioned above. While launching the instance, the organization configured two separate network interfaces (primary + ENI) and wanted to have two elastic IPs for that instance. It was suggested to use a public IP from AWS instead of an elastic IP as the number of elastic IPs is restricted. What action will you recommend to the organization?

- A. I agree with the suggestion but will prefer that the organization should use separate subnets with each ENI for different public IPs.
- B. I do not agree as it is required to have only an elastic IP since an instance has more than one ENI and AWS does not assign a public IP to an instance with multiple ENIs.
- C. I do not agree as AWS VPC does not attach a public IP to an ENI; so the user has to use only an elastic IP only.
- D. I agree with the suggestion and it is recommended to use a public IP from AWS since the organization is going to use DNS with Route 53.

**Answer:** B

#### Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. An Elastic Network Interface (ENI) is a virtual network interface that the user can attach to an instance in a VPC.

The user can attach up to two ENIs with a single instance. However, AWS cannot assign a public IP when there are two ENIs attached to a single instance. It is recommended to assign an elastic IP in this scenario. If the organization wants more than 5 EIPs they can request AWS to increase the number.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

#### NEW QUESTION 3

While implementing the policy keys in AWS Direct Connect, if you use and the request comes from an Amazon EC2 instance, the instance's public IP address is evaluated to determine if access is allowed.

- A. aws:SecureTransport
- B. aws:EpochIP
- C. aws:SourceIp
- D. aws:CurrentTime

**Answer:** C

#### Explanation:

While implementing the policy keys in Amazon RDS, if you use aws:SourceIp and the request comes from an Amazon EC2 instance, the instance's public IP address is evaluated to determine if access is allowed. Reference: [http://docs.aws.amazon.com/directconnect/latest/UserGuide/using\\_iam.html](http://docs.aws.amazon.com/directconnect/latest/UserGuide/using_iam.html)

#### NEW QUESTION 4

A user has created a MySQL RDS instance with PIOPS. Which of the below mentioned statements will help user understand the advantage of PIOPS?

- A. The user can achieve additional dedicated capacity for the EBS I/O with an enhanced RDS option
- B. It uses a standard EBS volume with optimized configuration the stacks
- C. It uses optimized EBS volumes and optimized configuration stacks
- D. It provides a dedicated network bandwidth between EBS and RDS

**Answer:** C

#### Explanation:

RDS DB instance storage comes in two types: standard and provisioned IOPS. Standard storage is allocated on the Amazon EBS volumes and connected to the user's DB instance. Provisioned IOPS uses

optimized EBS volumes and an optimized configuration stack. It provides additional, dedicated capacity for the EBS I/O.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

#### NEW QUESTION 5

A user authenticating with Amazon Cognito will go through a multi-step process to bootstrap their credentials. Amazon Cognito has two different flows for authentication with public providers. Which of the following are the two flows?

- A. Authenticated and non-authenticated
- B. Public and private

- C. Enhanced and basic
- D. Single step and multistep

**Answer:** C

**Explanation:**

A user authenticating with Amazon Cognito will go through a multi-step process to bootstrap their credentials. Amazon Cognito has two different flows for authentication with public providers: enhanced and basic.

Reference: <http://docs.aws.amazon.com/cognito/devguide/identity/concepts/authentication-flow/>

**NEW QUESTION 6**

Which of the following is the Amazon Resource Name (ARN) condition operator that can be used within an Identity and Access Management (IAM) policy to check the case-insensitive matching of the ARN?

- A. ArnCheck
- B. ArnMatch
- C. ArnCase
- D. ArnLike

**Answer:** D

**Explanation:**

Amazon Resource Name (ARN) condition operators let you construct Condition elements that restrict access based on comparing a key to an ARN. ArnLike, for instance, is a case-insensitive matching of the ARN. Each of the six colon-delimited components of the ARN is checked separately and each can include a multi-character match wildcard (\*) or a single-character match wildcard (?).

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_ElementDescriptions.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html)

**NEW QUESTION 7**

IV|apMySite is setting up a web application in the AWS VPC. The organization has decided to use an AWS RDS instead of using its own DB instance for HA and DR requirements.

The organization also wants to secure RDS access. How should the web application be setup with RDS?

- A. Create a VPC with one public and one private subne
- B. Launch an application instance in the public subnet while RDS is launched in the private subnet.
- C. Setup a public and two private subnets in different AZs within a VPC and create a subnet grou
- D. Launch RDS with that subnet group.
- E. Create a network interface and attach two subnets to i
- F. Attach that network interface with RDS while launching a DB instance.
- G. Create two separate VPCs and launch a Web app in one VPC and RDS in a separate VPC and connect them with VPC peering.

**Answer:** B

**Explanation:**

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on the security and operational needs.

A DB subnet group is a collection of subnets (generally private) that a user can create in a VPC and assign to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating the DB instances. Each DB subnet group should have subnets in at least two Availability Zones in a given region.

Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_VPC.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html)

**NEW QUESTION 8**

An organization is hosting a scalable web application using AWS. The organization has configured ELB and Auto Scaling to make the application scalable. Which of the below mentioned statements is not required to be followed for ELB when the application is planning to host a web application on VPC?

- A. The ELB and all the instances should be in the same subnet.
- B. Configure the security group rules and network ACLs to allow traffic to be routed between the subnets in the VPC.
- C. The internet facing ELB should have a route table associated with the internet gateway.
- D. The internet facing ELB should be only in a public subne

**Answer:** A

**Explanation:**

Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances. There are two ELBs available with VPC: internet facing and internal (private) ELB. For the internet facing ELB it is required that the ELB should be in a public subnet. After the user creates the public subnet, he should ensure to associate the route table of the public subnet with the internet gateway to enable the load balancer in the subnet to connect with the internet. The ELB and instances can be in a separate subnet. However, to allow communication between the instance and the

ELB the user must configure the security group rules and network ACLs to allow traffic to be routed between the subnets in his VPC.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/CreateVPCForELB.html>

**NEW QUESTION 9**

Regarding Amazon SNS, you can send notification messages to mobile devices through any of the following supported push notification services, EXCEPT:

- A. Microsoft Windows Mobile Messaging (MWMM)
- B. Google Cloud Messaging for Android (GCM)
- C. Amazon Device Messaging (ADM)
- D. Apple Push Notification Service (APNS)

**Answer:** A

**Explanation:**

In Amazon SNS, you have the ability to send notification messages directly to apps on mobile devices. Notification messages sent to a mobile endpoint can appear in the mobile app as message alerts, badge updates, or even sound alerts. Microsoft Windows Mobile Messaging (MWMM) doesn't exist and is not supported by Amazon SNS.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

**NEW QUESTION 10**

Which of the following is NOT an advantage of using AWS Direct Connect?

- A. AWS Direct Connect provides users access to public and private resources by using two different connections while maintaining network separation between the public and private environments.
- B. AWS Direct Connect provides a more consistent network experience than Internet-based connections.
- C. AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS.
- D. AWS Direct Connect reduces your network cost

**Answer:** A

**Explanation:**

AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS. Using AWS Direct Connect, you can establish private connectMty between AWS and your datacenter, office, or colocation environment, which in many cases can reduce your network costs, increase bandwidth throughput, and provide a more consistent network experience than Internet-based connections.

By using industry standard 802.1q VLANs, this dedicated connection can be partitioned into multiple virtual interfaces. This allows you to use the same connection to access public resources such as objects stored in Amazon S3 using public IP address space, and private resources such as Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC) using private IP space, while maintaining network separation between the public and private environments.

Reference: <http://aws.amazon.com/directconnect/#details>

**NEW QUESTION 10**

Which of the following components of AWS Data Pipeline specifies the business logic of your data management?

- A. Task Runner
- B. Pipeline definition
- C. AWS Direct Connect
- D. Amazon Simple Storage Service (Amazon S3)

**Answer:** B

**Explanation:**

A pipeline definition specifies the business logic of your data management.

Reference: <http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/what-is-datapipeline.html>

**NEW QUESTION 15**

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create each user in a separate region so that they have their own URL to login
- B. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group
- E. The user can login with their own group ID

**Answer:** C

**Explanation:**

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/Using\\_SettingUpUser.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_SettingUpUser.html)

**NEW QUESTION 19**

An organization is planning to create a secure scalable application with AWS VPC and ELB. The organization has two instances already running and each instance has an ENI attached to it in addition to a primary network interface. The primary network interface and additional ENI both have an elastic IP attached to it.

If those instances are registered with ELB and the organization wants ELB to send data to a particular EIP of the instance, how can they achieve this?

- A. The organization should ensure that the IP which is required to receive the ELB traffic is attached to a primary network interface.
- B. It is not possible to attach an instance with two ENIs with ELB as it will give an IP conflict error.
- C. The organization should ensure that the IP which is required to receive the ELB traffic is attached to an additional ENI.
- D. It is not possible to send data to a particular IP as ELB will send to any one EI

**Answer:** A

**Explanation:**

Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances. There are two ELBs available with VPC: internet facing and internal (private) ELB. For the internet facing ELB it is required that the



ELB should be in a public subnet.

When the user registers a multi-homed instance (an instance that has an Elastic Network Interface (ENI) attached) with a load balancer, the load balancer will route the traffic to the IP address of the primary network interface (eth0).

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/gs-ec2VPC.html>

#### NEW QUESTION 22

Which of the following cache engines does Amazon ElastiCache support?

- A. Amazon ElastiCache supports Memcached and Redis.
- B. Amazon ElastiCache supports Redis and WinCache.
- C. Amazon ElastiCache supports Memcached and Hazelcast.
- D. Amazon ElastiCache supports Memcached onl

**Answer:** A

#### Explanation:

The cache engines supported by Amazon ElastiCache are Memcached and Redis.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/SelectEngine.html>

#### NEW QUESTION 27

A bucket owner has allowed another account's IAM users to upload or access objects in his bucket. The IAM user of Account A is trying to access an object created by the IAM user of account B. What will happen in this scenario?

- A. It is not possible to give permission to multiple IAM users
- B. AWS S3 will verify proper rights given by the owner of Account A, the bucket owner as well as by the IAM user B to the object
- C. The bucket policy may not be created as S3 will give error due to conflict of Access Rights
- D. It is not possible that the IAM user of one account accesses objects of the other IAM user

**Answer:** B

#### Explanation:

If a IAM user is trying to perform some action on an object belonging to another AWS user's bucket, S3 will verify whether the owner of the IAM user has given sufficient permission to him. It also verifies the policy for the bucket as well as the policy defined by the object owner.

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/access-control-auth-workflow-object-operation.html>

#### NEW QUESTION 29

An organization is setting up a multi-site solution where the application runs on premise as well as on AWS to achieve the minimum recovery time objective(RTO). Which of the below mentioned configurations will not meet the requirements of the multi-site solution scenario?

- A. Configure data replication based on RTO.
- B. Keep an application running on premise as well as in AWS with full capacity.
- C. Setup a single DB instance which will be accessed by both sites.
- D. Setup a weighted DNS service like Route 53 to route traffic across site

**Answer:** C

#### Explanation:

AWS has many solutions for DR(Disaster recovery) and HA(High Availability). When the organization wants to have HA and DR with multi-site solution, it should setup two sites: one on premise and the other on AWS with full capacity. The organization should setup a weighted DNS service which can route traffic to both sites based on the weightage. When one of the sites fails it can route the entire load to another site. The organization would have minimal RTO in this scenario. If the organization setups a single DB instance, it will not work well in failover.

Instead they should have two separate DBs in each site and setup data replication based on RTO(recovery time objective )of the organization.

Reference: [http://d36cz9buwru1tt.cloudfront.net/AWS\\_Disaster\\_Recovery.pdf](http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf)

#### NEW QUESTION 31

Which of the following is true of an instance profile when an IAM role is created using the console?

- A. The instance profile uses a different name.
- B. The console gives the instance profile the same name as the role it corresponds to.
- C. The instance profile should be created manually by a user.
- D. The console creates the role and instance profile as separate actions.

**Answer:** B

#### Explanation:

Amazon EC2 uses an instance profile as a container for an IAM role. When you create an IAM role using the console, the console creates an instance profile automatically and gives it the same name as the role it corresponds to. If you use the AWS CLI, API, or an AWS SDK to create a role, you create the role and instance profile as separate actions, and you might give them different names.

Reference:

[http://docs.aws.amazon.com/IAM/latest/UserGuide/id\\_roles\\_use\\_switch-role-ec2\\_instance-profiles.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_use_switch-role-ec2_instance-profiles.html)

#### NEW QUESTION 35

Regarding Identity and Access Management (IAM), Which type of special account belonging to your application allows your code to access Google services programmatically?

- A. Service account
- B. Simple Key

- C. OAuth
- D. Code account

**Answer:** A

**Explanation:**

A service account is a special Google account that can be used by applications to access Google services programmatically. This account belongs to your application or a virtual machine (VM), instead of to an individual end user. Your application uses the service account to call the Google API of a service, so that the users aren't directly involved. A service account can have zero or more pairs of service account keys, which are used to authenticate to Google. A service account key is a public/private keypair generated by Google. Google retains the public key, while the user is given the private key.  
Reference: <https://cloud.google.com/iam/docs/service-accounts>

**NEW QUESTION 37**

An organization is planning to use NoSQL DB for its scalable data needs. The organization wants to host an application securely in AWS VPC. What action can be recommended to the organization?

- A. The organization should setup their own NoSQL cluster on the AWS instance and configure route tables and subnets.
- B. The organization should only use a DynamoDB because by default it is always a part of the default subnet provided by AWS.
- C. The organization should use a DynamoDB while creating a table within the public subnet.
- D. The organization should use a DynamoDB while creating a table within a private subnet

**Answer:** A

**Explanation:**

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Currently VPC does not support DynamoDB. Thus, if the user wants to implement VPC, he has to setup his own NoSQL DB within the VPC. Reference:  
[http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Introduction.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Introduction.html)

**NEW QUESTION 39**

Can a Direct Connect link be connected directly to the Internet?

- A. Yes, this can be done if you pay for it.
- B. Yes, this can be done only for certain regions.
- C. Yes
- D. No

**Answer:** D

**Explanation:**

AWS Direct Connect is a network service that provides an alternative to using the Internet to utilize AWS cloud service. Hence, a Direct Connect link cannot be connected to the Internet directly.  
Reference: <http://aws.amazon.com/directconnect/faqs/>

**NEW QUESTION 43**

True or False: The Amazon ElastiCache clusters are not available for use in VPC at this time.

- A. TRUE
- B. True, but they are available only in the GovCloud.
- C. True, but they are available only on request.
- D. FALSE

**Answer:** D

**Explanation:**

Amazon ElastiCache clusters can be run in an Amazon VPC. With Amazon VPC, you can define a virtual network topology and customize the network configuration to closely resemble a traditional network that you might operate in your own datacenter. You can now take advantage of the manageability, availability and scalability benefits of Amazon ElastiCache Clusters in your own isolated network. The same functionality of Amazon ElastiCache, including automatic failure detection, recovery, scaling, auto discovery, Amazon CloudWatch metrics, and software patching, are now available in Amazon VPC. Reference:  
<http://aws.amazon.com/about-aws/whats-new/2012/12/20/amazon-elasticache-announces-support-for-a-mazon-vpc/>

**NEW QUESTION 47**

In Amazon Cognito what is a silent push notification?

- A. It is a push message that is received by your application on a user's device that will not be seen by the user.
- B. It is a push message that is received by your application on a user's device that will return the user's geolocation.
- C. It is a push message that is received by your application on a user's device that will not be heard by the user.
- D. It is a push message that is received by your application on a user's device that will return the user's authentication credentials.

**Answer:** A

**Explanation:**

Amazon Cognito uses the Amazon Simple Notification Service (SNS) to send silent push notifications to devices. A silent push notification is a push message that is received by your application on a user's device that will not be seen by the user.  
Reference: <http://aws.amazon.com/cognito/faqs/>

#### NEW QUESTION 49

When using Numeric Conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. Which of the following is the short version of the Numeric Condition "NumericLessThanEquals"?

- A. numlteq
- B. numlteql
- C. numltequals
- D. numeqql

**Answer:** A

#### Explanation:

When using Numeric Conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. For instance, numlteq is the short version of NumericLessThanEquals.

Reference: <http://awsdocs.s3.amazonaws.com/SQS/2011-10-01/sqs-dg-2011-10-01.pdf>

#### NEW QUESTION 51

Which of following IAM policy elements lets you specify an exception to a list of actions?

- A. NotException
- B. ExceptionAction
- C. Exception
- D. NotAction

**Answer:** D

#### Explanation:

The NotAction element lets you specify an exception to a list of actions. Reference:

[http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_ElementDescriptions.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html)

#### NEW QUESTION 55

An organization is setting up a web application with the JEE stack. The application uses the JBoss app server and |V|ySQL DB. The application has a logging module which logs all the actMties whenever a business function of the JEE application is called. The logging actMty takes some time due to the large size of the log file. If the application wants to setup a scalable infrastructure which of the below mentioned options will help achieve this setup?

- A. Host the log files on EBS with PIOPS which will have higher I/O.
- B. Host logging and the app server on separate sewers such that they are both in the same zone.
- C. Host logging and the app server on the same instance so that the network latency will be shorter.
- D. Create a separate module for logging and using SQS compartmentalize the module such that all calls to logging are asynchronous.

**Answer:** D

#### Explanation:

The organization can always launch multiple EC2 instances in the same region across multiple AZs for HA and DR. The AWS architecture practice recommends compartmentalizing the functionality such that

they can both run in parallel without affecting the performance of the main application. In this scenario logging takes a longer time due to the large size of the log file. Thus, it is recommended that the organization should separate them out and make separate modules and make asynchronous calls among them. This way the application can scale as per the requirement and the performance will not bear the impact of logging.

Reference: <http://www.awsarchitectureblog.com/2014/03/aws-and-compartmentalization.html>

#### NEW QUESTION 58

You're trying to delete an SSL certificate from the IAM certificate store, and you're getting the message "Certificate: <certificate-id> is being used by CloudFront." Which of the following statements is probably the reason why you are getting this error?

- A. Before you can delete an SSL certificate you need to set up https on your server.
- B. Before you can delete an SSL certificate, you need to set up the appropriate access level in IAM
- C. Before you can delete an SSL certificate, you need to either rotate SSL certificates or revert from using a custom SSL certificate to using the default CloudFront certificate.
- D. You can't delete SSL certificates . You need to request it from AW

**Answer:** C

#### Explanation:

CloudFront is a web service that speeds up distribution of your static and dynamic web content, for example, .html, .css, .php, and image files, to end users.

Every CloudFront web distribution must be associated either with the default CloudFront certificate or with a custom SSL certificate. Before you can delete an SSL certificate, you need to either rotate SSL certificates (replace the current custom SSL certificate with another custom SSL certificate) or revert from using a custom SSL certificate to using the default CloudFront certificate.

Reference: <http://docs.aws.amazon.com/AmazonC|oudFront/latest/DeveloperGuide/Troubleshooting.html>

#### NEW QUESTION 62

A user has set the IAM policy where it denies all requests if a request is not from IP 10.10.10.1/32. The other policy says allow all requests between 5 PM to 7 PM. What will happen when a user is requesting access from IP 55.109.10.12/32 at 6 PM?

- A. It will deny access
- B. It is not possible to set a policy based on the time or IP
- C. IAM will throw an error for policy conflict
- D. It will allow access

**Answer:**

A

**Explanation:**

When a request is made, the AWS IAM policy decides whether a given request should be allowed or denied. The evaluation logic follows these rules:  
By default, all requests are denied. (In general, requests made using the account credentials for resources in the account are always allowed.)  
An explicit allow policy overrides this default.  
An explicit deny policy overrides any allows.  
In this case since there are explicit deny and explicit allow statements. Thus, the request will be denied since deny overrides allow.  
Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_EvaluationLogic.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html)

**NEW QUESTION 65**

Do you need to use Amazon Cognito to use the Amazon Mobile Analytics service?

- A. N
- B. However, it is recommend by AWS to use Amazon Cognito for security best practices.
- C. Ye
- D. You need to use it only if you have IAM root access.
- E. N
- F. You cannot use it at all, and you need to use AWS IAM accounts.
- G. Ye
- H. It is recommended by AWS to use Amazon Cognito to use Amazon Mobile Analytics servic

**Answer:** A

**Explanation:**

You can initialize Amazon Mobile Analytics using AWS IAM accounts. AWS recommend using Amazon Cognito for security best practices.  
Reference: <http://aws.amazon.com/mobileanalytics/faqs/>

**NEW QUESTION 68**

You want to use Amazon Redshift and you are planning to deploy dw1.8xlarge nodes. What is the minimum amount of nodes that you need to deploy with this kind of configuration?

- A. 1
- B. 4
- C. 3
- D. 2

**Answer:** D

**Explanation:**

For a single-node configuration in Amazon Redshift, the only option available is the smallest of the two options. The 8XL extra-large nodes are only available in a multi-node configuration  
Reference: <http://docs.aws.amazon.com/redshift/latest/mgmt/working-with-clusters.html>

**NEW QUESTION 73**

Can Provisioned IOPS be used on RDS instances launched in a VPC?

- A. Yes, they can be used only with Oracle based instances.
- B. Yes, they can be used for all RDS instances.
- C. No
- D. Yes, they can be used only with MySQL based instance

**Answer:** B

**Explanation:**

The basic building block of Amazon RDS is the DB instance. DB instance storage comes in three types: Magnetic, General Purpose (SSD), and Provisioned IOPS (SSD). When you buy a server, you get CPU, memory, storage, and IOPS, all bundled together. With Amazon RDS, these are split apart so that you can scale them independently. So, for example, if you need more CPU, less IOPS, or more storage, you can easily allocate them.  
Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/RDSFAQ.PIOPS.html>

**NEW QUESTION 76**

To get started using AWS Direct Connect, in which of the following steps do you configure Border Gateway Protocol (BGP)?

- A. Complete the Cross Connect
- B. Configure Redundant Connections with AWS Direct Connect
- C. Create a Virtual Interface
- D. Download Router Configuration

**Answer:** C

**Explanation:**

In AWS Direct Connect, your network must support Border Gateway Protocol (BGP) and BGP MD5 authentication, and you need to provide a private Autonomous System Number (ASN) for that to connect to Amazon Virtual Private Cloud (VPC). To connect to public AWS products such as Amazon EC2 and Amazon S3, you will also need to provide a public ASN that you own (preferred) or a private ASN. You have to configure BGP in the Create a Virtual Interface step.  
Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/getstarted.html#createvirtualinterface>

**NEW QUESTION 78**



An organization is setting up their website on AWS. The organization is working on various security measures to be performed on the AWS EC2 instances. Which of the below mentioned security mechanisms will not help the organization to avoid future data leaks and identify security weaknesses?

- A. Run penetration testing on AWS with prior approval from Amazon.
- B. Perform SQL injection for application testing.
- C. Perform a Code Check for any memory leaks.
- D. Perform a hardening test on the AWS instanc

**Answer: C**

**Explanation:**

AWS security follows the shared security model where the user is as much responsible as Amazon. Since Amazon is a public cloud it is bound to be targeted by hackers. If an organization is planning to host their application on AWS EC2, they should perform the below mentioned security checks as a measure to find any security weakness/data leaks:

Perform penetration testing as performed by attackers to find any vulnerability. The organization must take an approval from AWS before performing penetration testing

Perform hardening testing to find if there are any unnecessary ports open Perform SQL injection to find any DB security issues

The code memory checks are generally useful when the organization wants to improve the application performance.

Reference: <http://aws.amazon.com/security/penetration-testing/>

**NEW QUESTION 80**

In Amazon ElastiCache, the default cache port is:

- A. for Memcached 11210 and for Redis 6380.
- B. for Memcached 11211 and for Redis 6380.
- C. for Memcached 11210 and for Redis 6379.
- D. for Memcached 11211 and for Redis 6379.

**Answer: D**

**Explanation:**

In Amazon ElastiCache, you can specify a new port number for your cache cluster, which by default is 11211 for Memcached and 6379 for Redis.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/GettingStarted.AuthorizeAccess.html>

**NEW QUESTION 84**

A user has created a VPC with public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The private subnet uses CIDR 20.0.0.0/24 . The NAT instance ID is i-a12345. Which of the below mentioned entries are required in the main route table attached with the private subnet to allow instances to connect with the internet?

- A. Destination: 20.0.0.0/0 and Target: 80
- B. Destination: 20.0.0.0/0 and Target: i-a12345
- C. Destination: 20.0.0.0/24 and Target: i-a12345
- D. Destination: 0.0.0.0/0 and Target: i-a12345

**Answer: D**

**Explanation:**

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create two route tables and attach to the subnets. The main route table will have the entry "Destination: 0.0.0.0/0 and Target: i-a12345", which allows all the instances in the private subnet to connect to the internet using NAT.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Scenario2.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario2.html)

**NEW QUESTION 86**

You're running an application on-premises due to its dependency on non-x86 hardware and want to use AWS for data backup. Your backup application is only able to write to POSIX-compatible block-based storage. You have 140TB of data and would like to mount it as a single folder on your file server Users must be able to access portions of this data while the backups are taking place. What backup solution would be most appropriate for this use case?

- A. Use Storage Gateway and configure it to use Gateway Cached volumes.
- B. Configure your backup software to use S3 as the target for your data backups.
- C. Configure your backup software to use Glacier as the target for your data backups.
- D. Use Storage Gateway and configure it to use Gateway Stored volume

**Answer: A**

**NEW QUESTION 87**

A read only news reporting site with a combined web and application tier and a database tier that receives large and unpredictable traffic demands must be able to respond to these traffic fluctuations automatically. What AWS services should be used meet these requirements?

- A. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaimg group monitored with CloudWatch and RDS with read replicas.
- B. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatch and RDS with read replicas.
- C. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWate
- D. And multi-AZ RDS.
- E. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaling group monitored with CloudWatch and multi-AZ RDS.

**Answer: A**

#### NEW QUESTION 88

You have been asked to design the storage layer for an application. The application requires disk performance of at least 100,000 IOPS. In addition, the storage layer must be able to survive the loss of an individual disk, EC2 instance, or Availability Zone without any data loss. The volume you provide must have a capacity of at least 3 TB. Which of the following designs will meet these objectives?

- A. Instantiate a c3.8xlarge instance in us-east-1. Provision 4x1TB EBS volumes, attach them to the instance, and configure them as a single RAID 5 volume
- B. Ensure that EBS snapshots are performed every 15 minutes.
- C. Instantiate a c3.8xlarge instance in us-east-1. Provision 3x1TB EBS volumes, attach them to the instance, and configure them as a single RAID 0 volume
- D. Ensure that EBS snapshots are performed every 15 minutes.
- E. Instantiate an i2.8xlarge instance in us-east-1
- F. Create a RAID 0 volume using the four 800GB SSD ephemeral disks provided with the instance
- G. Provision 3x1TB EBS volumes, attach them to the instance, and configure them as a second RAID 0 volume
- H. Configure synchronous, block-level replication from the ephemeral-backed volume to the EBS-backed volume.
- I. Instantiate a c3.8xlarge instance in us-east-1. Provision an AWS Storage Gateway and configure it for 3 TB of storage and 100,000 IOP
- J. Attach the volume to the instance.
- K. Instantiate an i2.8xlarge instance in us-east-1
- L. Create a RAID 0 volume using the four 800GB SSD ephemeral disks provided with the instance
- M. Configure synchronous, block-level replication to an identically configured instance in us-east-1b.

**Answer: C**

#### NEW QUESTION 90

An AWS customer is deploying an application that is composed of an AutoScaling group of EC2 instances.

The customer's security policy requires that every outbound connection from these instances to any other service within the customer's Virtual Private Cloud must be authenticated using a unique x.509 certificate that contains the specific instance-id.

In addition, x.509 certificates must be designed by the customer's Key management service in order to be trusted for authentication.

Which of the following configurations will support these requirements?

- A. Configure an IAM Role that grants access to an Amazon S3 object containing a signed certificate and configure the Auto Scaling group to launch instances with this role. Have the instances bootstrap get the certificate from Amazon S3 upon first boot.
- B. Embed a certificate into the Amazon Machine Image that is used by the Auto Scaling group. Have the launched instances generate a certificate signature request with the instance's assigned instance-id to the Key management service for signature.
- C. Configure the Auto Scaling group to send an SNS notification of the launch of a new instance to the trusted key management service.
- D. Have the Key management service generate a signed certificate and send it directly to the newly launched instance.
- E. Configure the launched instances to generate a new certificate upon first boot. Have the Key management service poll the Auto Scaling group for associated instances and send new instances a certificate signature (that contains the specific instance-id).

**Answer: A**

#### NEW QUESTION 95

Your customer wishes to deploy an enterprise application to AWS which will consist of several web servers, several application servers and a small (50GB) Oracle database. Information is stored, both in the database and the file systems of the various servers. The backup system must support database recovery, whole server and whole disk restores, and individual file restores with a recovery time of no more than two hours. They have chosen to use RDS Oracle as the database. Which backup architecture will meet these requirements?

- A. Backup RDS using automated daily DB backups. Backup the EC2 instances using AMIs and supplement with file-level backup to S3 using traditional enterprise backup software to provide file-level restore.
- B. Backup RDS using a Multi-AZ Deployment. Backup the EC2 instances using AMIs, and supplement by copying file system data to S3 to provide file-level restore.
- C. Backup RDS using automated daily DB backups. Backup the EC2 instances using EBS snapshots and supplement with file-level backups to Amazon Glacier using traditional enterprise backup software to provide file-level restore.
- D. Backup RDS database to S3 using Oracle RMAN. Backup the EC2 instances using AMIs, and supplement with EBS snapshots for individual volume restore.

**Answer: A**

#### NEW QUESTION 98

An AWS customer runs a public blogging website. The site users upload two million blog entries a month. The average blog entry size is 200 KB. The access rate to blog entries drops to negligible 6 months after publication and users rarely access a blog entry 1 year after publication. Additionally, blog entries have a high update rate during the first 3 months following publication, this drops to no updates after 6 months. The customer wants to use CloudFront to improve his user's load times. Which of the following recommendations would you make to the customer?

- A. Duplicate entries into two different buckets and create two separate CloudFront distributions where S3 access is restricted only to CloudFront identity.
- B. Create a CloudFront distribution with "US Europe" price class for US/Europe users and a different CloudFront distribution with "All Edge Locations" for the remaining users.
- C. Create a CloudFront distribution with S3 access restricted only to the CloudFront identity and partition the blog entry's location in S3 according to the month it was uploaded to be used with CloudFront behaviors.
- D. Create a CloudFront distribution with Restrict Viewer Access. Forward Query string set to true and minimum TTL of 0.

**Answer: C**

#### NEW QUESTION 101

You are designing an intrusion detection prevention (IDS/IPS) solution for a customer web application in a single VPC. You are considering the options for implementing IOS IPS protection for traffic coming from the Internet.

Which of the following options would you consider? (Choose 2 answers)

- A. Implement IDS/IPS agents on each instance running in VPC
- B. Configure an instance in each subnet to switch its network interface card to promiscuous mode and analyze network traffic.
- C. Implement Elastic Load Balancing with SSL listeners in front of the web applications
- D. Implement a reverse proxy layer in front of web servers and configure IDS/IPS agents on each reverse proxy server.

**Answer:** BD

#### NEW QUESTION 106

You are designing a social media site and are considering how to mitigate distributed denial-of-service (DDoS) attacks. Which of the below are viable mitigation techniques? (Choose 3 answers)

- A. Add multiple elastic network interfaces (ENIs) to each EC2 instance to increase the network bandwidth.
- B. Use dedicated instances to ensure that each instance has the maximum performance possible.
- C. Use an Amazon CloudFront distribution for both static and dynamic content.
- D. Use an Elastic Load Balancer with auto scaling groups at the we
- E. App and Amazon Relational Database Service (RDS) tiers
- F. Add alert Amazon CloudWatch to look for high Network in and CPU utilization.
- G. Create processes and capabilities to quickly add and remove rules to the instance OS firewall

**Answer:** CEF

#### NEW QUESTION 110

A corporate web application is deployed within an Amazon Virtual Private Cloud (VPC) and is connected to the corporate data center via an IPSec VPN. The application must authenticate against the on-premises LDAP server. After authentication, each logged-in user can only access an Amazon Simple Storage Space (S3) keyspace specific to that user. Which two approaches can satisfy these objectives? (Choose 2 answers)

- A. Develop an identity broker that authenticates against IAM security Token service to assume a IAM role in order to get temporary AWS security credentials The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.
- B. The application authenticates against LDAP and retrieves the name of an IAM role associated with the use
- C. The application then calls the IAM Security Token Service to assume that IAM rol
- D. The application can use the temporary credentials to access the appropriate S3 bucket.
- E. Develop an identity broker that authenticates against LDAP and then calls IAM Security Token Service to get IAM federated user credential
- F. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- G. The application authenticates against LDAP the application then calls the AWS identity and AccessManagement (IAM) Security service to log in to IAM using the LDAP credentials the application can use the IAM temporary credentials to access the appropriate S3 bucket.
- H. The application authenticates against IAM Security Token Service using the LDAP credentials the application uses those temporary AWS security credentials to access the appropriate S3 bucket.

**Answer:** BC

#### NEW QUESTION 111

You are designing an SSUTLS solution that requires HTTPS clients to be authenticated by the Webserver using client certificate authentication. The solution must be resilient.

Which of the following options would you consider for configuring the web server infrastructure? (Choose 2 answers)

- A. Configure ELB with TCP listeners on TCP/443. And place the Web servers behind it.
- B. Configure your Web servers with EIP
- C. Place the Web servers in a Route53 Record Set and configure health checks against all Web servers.
- D. Configure ELB with HTTPS listeners, and place the Web sewers behind it.
- E. Configure your web sewers as the origins for a CloudFront distributio
- F. Use custom SSL certificates on your CloudFront distribution.

**Answer:** AB

#### NEW QUESTION 116

You are migrating a legacy client-server application to AWS. The application responds to a specific DNS domain (e.g. www.example.com) and has a 2-tier architecture, with multiple application sewers and a database sewer. Remote clients use TCP to connect to the application servers. The application servers need to know the IP address of the clients in order to function properly and are currently taking that information from the TCP socket. A Multi-AZ RDS MySQL instance will be used for the database. During the migration you can change the application code, but you have to file a change request. How would you implement the architecture on AWS in order to maximize scalability and high availability?

- A. File a change request to implement Alias Resource support in the applicatio
- B. Use Route 53 Alias Resource Record to distribute load on two application servers in different Azs.
- C. File a change request to implement Latency Based Routing support in the applicatio
- D. Use Route 53 with Latency Based Routing enabled to distribute load on two application servers in different Azs.
- E. File a change request to implement Cross-Zone support in the applicatio
- F. Use an ELB with a TCP Listener and Cross-Zone Load Balancing enabled, two application servers in different AZs.
- G. File a change request to implement Proxy Protocol support in the applicatio
- H. Use an ELB with a TCP Listener and Proxy Protocol enabled to distribute load on two application servers in different Azs.

**Answer:** D

#### NEW QUESTION 120

You are responsible for a web application that consists of an Elastic Load Balancing (ELB) load balancer in front of an Auto Scaling group of Amazon Elastic Compute Cloud (EC2) instances. For a recent deployment of a new version of the application, a new Amazon Machine Image (AMI) was created, and the Auto Scaling group was updated with a new launch configuration that refers to this new AMI. During the deployment, you received complaints from users that the website was responding with errors. All instances passed the ELB health checks.

What should you do in order to avoid errors for future deployments? (Choose 2 answer)

- A. Add an Elastic Load Balancing health check to the Auto Scaling grou
- B. Set a short period for the health checks to operate as soon as possible in order to prevent premature registration of the instance to theload balancer.
- C. Enable EC2 instance CloudWatch alerts to change the launch configuration's AMI to the previous on



- D. Gradually terminate instances that are using the new AMI.
- E. Set the Elastic Load Balancing health check configuration to target a part of the application that fully tests application health and returns an error if the tests fail.
- F. Create a new launch configuration that refers to the new AMI, and associate it with the group.
- G. Double the size of the group, wait for the new instances to become healthy, and reduce back to the original size. If new instances do not become healthy, associate the previous launch configuration.
- H. Increase the Elastic Load Balancing Unhealthy Threshold to a higher value to prevent an unhealthy instance from going into service behind the load balancer.

**Answer:** CD

#### NEW QUESTION 124

Your fortune 500 company has undertaken a TCO analysis evaluating the use of Amazon S3 versus acquiring more hardware. The outcome was that all employees would be granted access to use Amazon S3 for storage of their personal documents.

Which of the following will you need to consider so you can set up a solution that incorporates single sign-on from your corporate AD or LDAP directory and restricts access for each user to a designated user folder in a bucket? (Choose 3 Answers)

- A. Setting up a federation proxy or identity provider
- B. Using AWS Security Token Service to generate temporary tokens
- C. Tagging each folder in the bucket
- D. Configuring IAM role
- E. Setting up a matching IAM user for every user in your corporate directory that needs access to a folder in the bucket

**Answer:** ABD

#### NEW QUESTION 127

Select the correct set of options. These are the initial settings for the default security group:

- A. Allow no inbound traffic, Allow all outbound traffic and Allow instances associated with this security group to talk to each other
- B. Allow all inbound traffic, Allow no outbound traffic and Allow instances associated with this security group to talk to each other
- C. Allow no inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other
- D. Allow all inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other

**Answer:** A

#### NEW QUESTION 131

Which of the following are characteristics of Amazon VPC subnets? Choose 2 answers

- A. Each subnet spans at least 2 Availability Zones to provide a high-availability environment.
- B. Each subnet maps to a single Availability Zone.
- C. CIDR block mask of /25 is the smallest range supported.
- D. By default, all subnets can route between each other, whether they are private or public.
- E. Instances in a private subnet can communicate with the Internet only if they have an Elastic IP

**Answer:** AE

#### NEW QUESTION 132

Your firm has uploaded a large amount of aerial image data to S3. In the past, in your on-premises environment, you used a dedicated group of servers to ingest and process this data and used Rabbit MQ - An open source messaging system to get job information to the servers. Once processed the data would go to tape and be shipped offsite. Your manager told you to stay with the current design, and leverage AWS archival storage and messaging services to minimize cost. Which is correct?

- A. Use SQS for passing job messages use Cloud Watch alarms to terminate EC2 worker instances when they become idle
- B. Once data is processed, change the storage class of the S3 objects to Reduced Redundancy Storage.
- C. Setup Auto-Scaled workers triggered by queue depth that use spot instances to process messages in SQS. Once data is processed,
- D. Change the storage class of the S3 objects to Reduced Redundancy Storage
- E. Setup Auto-Scaled workers triggered by queue depth that use spot instances to process messages in SQS. Once data is processed, change the storage class of the S3 objects to Glacier.
- F. Use SNS to pass job messages use Cloud Watch alarms to terminate spot worker instances when they become idle
- G. Once data is processed, change the storage class of the S3 object to Glacier.

**Answer:** D

#### NEW QUESTION 136

You are implementing AWS Direct Connect. You intend to use AWS public service endpoints such as Amazon S3, across the AWS Direct Connect link. You want other Internet traffic to use your existing link to an Internet Service Provider.

What is the correct way to configure AWS Direct Connect for access to services such as Amazon S3?

- A. Configure a public interface on your AWS Direct Connect link. Configure a static route via your AWS Direct Connect link that points to Amazon S3. Advertise a default route to AWS using BGP.
- B. Create a private interface on your AWS Direct Connect link
- C. Configure a static route via your AWS Direct Connect link that points to Amazon S3. Configure specific routes to your network in your VPC.
- D. Create a public interface on your AWS Direct Connect link. Redistribute BGP routes into your existing routing infrastructure; advertise specific routes for your network to AWS.
- E. Create a private interface on your AWS Direct Connect link
- F. Redistribute BGP routes into your existing routing infrastructure and advertise a default route to AWS.

**Answer:** C



#### NEW QUESTION 138

Your application is using an ELB in front of an Auto Scaling group of web/application servers deployed across two AZs and a Multi-AZ RDS Instance for data persistence.

The database CPU is often above 80% usage and 90% of I/O operations on the database are reads. To improve performance you recently added a single-node Memcached ElastiCache Cluster to cache frequent DB query results. In the next weeks the overall workload is expected to grow by 30%.

Do you need to change anything in the architecture to maintain the high availability of the application with the anticipated additional load? Why?

- A. Yes, you should deploy two Memcached ElastiCache Clusters in different AZs because the RDS instance will not be able to handle the load if the cache node fails.
- B. No, if the cache node fails you can always get the same data from the DB without having any availability impact.
- C. No, if the cache node fails the automated ElastiCache node recovery feature will prevent any availability impact.
- D. Yes, you should deploy the Memcached ElastiCache Cluster with two nodes in the same AZ as the RDS DB master instance to handle the load if one cache node fails.

**Answer:** A

#### NEW QUESTION 141

Auto Scaling requests are signed with a signature calculated from the request and the user's private key.

- A. SSL
- B. AES-256
- C. HMAC-SHA1
- D. X.509

**Answer:** C

#### NEW QUESTION 146

The following policy can be attached to an IAM group. It lets an IAM user in that group access a "home directory" in AWS S3 that matches their user name using the console.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Action": ["s3:*"], "Effect": "Allow",
      "Resource": ["arn:aws:s3:::bucket-name"], "Condition": {"StringLike": {"s3:prefix": ["home/${aws:username}/*"]}}
    },
    {
      "Action": ["s3:*"], "Effect": "Allow",
      "Resource": ["arn:aws:s3:::bucket-name/home/${aws:username}/*"]
    }
  ]
}
```

- A. True
- B. False

**Answer:** B

#### NEW QUESTION 148

How is AWS readily distinguished from other vendors in the traditional IT computing landscape?

- A. Experience
- B. Scalable and elastic
- C. Secure
- D. Cost-effective
- E. Reliable
- F. Secure
- G. Flexible
- H. Cost-effective
- I. Scalable and elastic
- J. Global
- K. Secure
- L. Flexible
- M. Cost-effective
- N. Scalable and elastic
- O. Experienced
- P. Flexible
- Q. Cost-effective
- R. Dynamic
- S. Secure
- T. Experience

**Answer:** C

#### NEW QUESTION 149

Your company is storing millions of sensitive transactions across thousands of 100-GB files that must be encrypted in transit and at rest. Analysts concurrently depend on subsets of files, which can consume up to 5 TB of space, to generate simulations that can be used to steer business decisions. You are required to design an AWS solution that can cost effectively accommodate the long-term storage and in-flight subsets of data.

- A. Use Amazon Simple Storage Service (S3) with server-side encryption, and run simulations on subsets in ephemeral drives on Amazon EC2.

- B. Use Amazon S3 with server-side encryption, and run simulations on subsets in-memory on Amazon EC2.
- C. Use HDFS on Amazon EMR, and run simulations on subsets in ephemeral drives on Amazon EC2.
- D. Use HDFS on Amazon Elastic MapReduce (EMR), and run simulations on subsets in-memory on Amazon Elastic Compute Cloud (EC2).
- E. Store the full data set in encrypted Amazon Elastic Block Store (EBS) volumes, and regularly capturesnapshots that can be cloned to EC2 workstation

**Answer:** D

#### NEW QUESTION 151

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### AWS-Certified-Solutions-Architect-Professional Practice Exam Features:

- \* AWS-Certified-Solutions-Architect-Professional Questions and Answers Updated Frequently
- \* AWS-Certified-Solutions-Architect-Professional Practice Questions Verified by Expert Senior Certified Staff
- \* AWS-Certified-Solutions-Architect-Professional Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* AWS-Certified-Solutions-Architect-Professional Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The AWS-Certified-Solutions-Architect-Professional Practice Test Here](#)**