

Exam Questions AWS-SysOps

Amazon AWS Certified SysOps Administrator - Associate

<https://www.2passeasy.com/dumps/AWS-SysOps/>



NEW QUESTION 1

- (Topic 1)

Your team is excited about the use of AWS because now they have access to programmable Infrastructure. You have been asked to manage your AWS infrastructure in a manner similar to the way you might manage application code. You want to be able to deploy exact copies of different versions of your infrastructure, stage changes into different environments, revert back to previous versions, and identify what versions are running at any particular time (development, test, QA, production).

Which approach addresses this requirement?

- A. Use cost allocation reports and AWS Opsworks to deploy and manage your infrastructure
- B. Use AWS CloudWatch metrics and alerts along with resource tagging to deploy and manage your infrastructure
- C. Use AWS Beanstalk and a version control system like GIT to deploy and manage your infrastructure
- D. Use AWS CloudFormation and a version control system like GIT to deploy and manage your infrastructure

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/opsworks/faqs/>

NEW QUESTION 2

- (Topic 1)

How can the domain's zone apex for example "myzoneapexdomain.com" be pointed towards an Elastic Load Balancer?

- A. By using an AAAA record
- B. By using an A record
- C. By using an Amazon Route 53 CNAME record
- D. By using an Amazon Route 53 Alias record

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/resource-record-sets-choosing-alias-non-alias.html>

NEW QUESTION 3

- (Topic 1)

You are tasked with setting up a cluster of EC2 Instances for a NoSQL database. The database requires random read IO disk performance up to a 100,000 IOPS at 4KB block size per node.

Which of the following EC2 instances will perform the best for this workload?

- A. A High-Memory Quadruple Extra Large (m2.4xlarge) with EBS-Optimized set to true and a Provisioned IOPS EBS volume
- B. A Cluster Compute Eight Extra Large (cc2.8xlarge) using instance storage
- C. High I/O Quadruple Extra Large (hi1.4xlarge) using instance storage
- D. A Cluster GPU Quadruple Extra Large (cg1.4xlarge) using four separate 4000 PIOPS EBS volumes in a RAID 0 configuration

Answer: C

Explanation:

Explanation: Reference:

<http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 4

- (Topic 1)

You have been asked to leverage Amazon VPC, EC2, and SQS to implement an application that submits and receives millions of messages per second to a message queue. You want to ensure your application has sufficient bandwidth between your EC2 instances and SQS. Which option will provide the most scalable solution for communicating between the application and SQS?

- A. Ensure the application instances are properly configured with an Elastic Load Balancer
- B. Ensure the application instances are launched in private subnets with the EBS-optimized option enabled
- C. Ensure the application instances are launched in public subnets with the `associate-public-ip-address=true` option enabled
- D. Launch application instances in private subnets with an Auto Scaling group and Auto Scaling triggers configured to watch the SQS queue size

Answer: B

Explanation:

Reference:

<http://www.cardinalpath.com/autoscaling-your-website-with-amazon-web-services-part-2/>

NEW QUESTION 5

- (Topic 1)

You have a server with a 500GB Amazon EBS data volume. The volume is 80% full. You need to back up the volume at regular intervals and be able to re-create the volume in a new Availability Zone in the shortest time possible. All applications using the volume can be paused for a period of a few minutes with no discernible user impact.

Which of the following backup methods will best fulfill your requirements?

- A. Take periodic snapshots of the EBS volume
- B. Use a third party incremental backup application to back up to Amazon Glacier

- C. Periodically back up all data to a single compressed archive and archive to Amazon S3 using a parallelized multi-part upload
- D. Create another EBS volume in the second Availability Zone attach it to the Amazon EC2 instance, and use a disk manager to mirror the two disks

Answer: D

Explanation:

Reference:
<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-creating-snapshot.html>

NEW QUESTION 6

- (Topic 1)

You have decided to change the Instance type for instances running in your application tier that are using Auto Scaling. In which area below would you change the instance type definition?

- A. Auto Scaling launch configuration
- B. Auto Scaling group
- C. Auto Scaling policy
- D. Auto Scaling tags

Answer: A

Explanation:

Reference:
<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/WhatIsAutoScaling.html>

NEW QUESTION 7

- (Topic 1)

You have set up Individual AWS accounts for each project. You have been asked to make sure your AWS Infrastructure costs do not exceed the budget set per project for each month.

Which of the following approaches can help ensure that you do not exceed the budget each month?

- A. Consolidate your accounts so you have a single bill for all accounts and projects
- B. Set up auto scaling with CloudWatch alarms using SNS to notify you when you are running too many Instances in a given account
- C. Set up CloudWatch billing alerts for all AWS resources used by each project, with a notification occurring when the amount for each resource tagged to a particular project matches the budget allocated to the project
- D. Set up CloudWatch billing alerts for all AWS resources used by each account, with email notifications when it hits 50%, 80% and 90% of its budgeted monthly spend

Answer: C

NEW QUESTION 8

- (Topic 1)

You are running a database on an EC2 instance, with the data stored on Elastic Block Store (EBS) for persistence. At times throughout the day, you are seeing large variance in the response times of the database queries. Looking into the instance with the `iotop` command you see a lot of wait time on the disk volume that the database's data is stored on.

What two ways can you improve the performance of the database's storage while maintaining the current persistence of the data?

Choose 2 answers

- A. Move to an SSD backed instance
- B. Move the database to an EBS-Optimized Instance
- C. Use Provisioned IOPS EBS
- D. Use the ephemeral storage on an m2.xlarge Instance Instead

Answer: AB

NEW QUESTION 9

- (Topic 1)

You are creating an Auto Scaling group whose Instances need to insert a custom metric into CloudWatch.

Which method would be the best way to authenticate your CloudWatch PUT request?

- A. Create an IAM role with the PutMetricData permission and modify the Auto Scaling launch configuration to launch instances in that role
- B. Create an IAM user with the PutMetricData permission and modify the Auto Scaling launch configuration to inject the user's credentials into the instance User Data
- C. Modify the appropriate CloudWatch metric policies to allow the PutMetricData permission to instances from the Auto Scaling group
- D. Create an IAM user with the PutMetricData permission and put the credentials in a private repository and have applications on the server pull the credentials as needed

Answer: A

NEW QUESTION 10

- (Topic 1)

When an EC2 instance that is backed by an S3-based AMI is terminated, what happens to the data on the root volume?

- A. Data is automatically saved as an EBS volume
- B. Data is automatically saved as an EBS snapshot
- C. Data is automatically deleted
- D. Data is unavailable until the instance is restarted

Answer: C

Explanation:

Reference:
<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ComponentsAMIs.html>

NEW QUESTION 10

- (Topic 1)

You have started a new job and are reviewing your company's infrastructure on AWS. You notice one web application where they have an Elastic Load Balancer (ELB) in front of web instances in an Auto Scaling Group. When you check the metrics for the ELB in CloudWatch, you see four healthy instances in Availability Zone (AZ) A and zero in AZ B. There are zero unhealthy instances. What do you need to fix to balance the instances across AZs?

- A. Set the ELB to only be attached to another AZ
- B. Make sure Auto Scaling is configured to launch in both AZs
- C. Make sure your AMI is available in both AZs
- D. Make sure the maximum size of the Auto Scaling Group is greater than 4

Answer: B

NEW QUESTION 14

- (Topic 1)

An organization's security policy requires multiple copies of all critical data to be replicated across at least a primary and backup data center. The organization has decided to store some critical data on Amazon S3. Which option should you implement to ensure this requirement is met?

- A. Use the S3 copy API to replicate data between two S3 buckets in different regions
- B. You do not need to implement anything since S3 data is automatically replicated between regions
- C. Use the S3 copy API to replicate data between two S3 buckets in different facilities within an AWS Region
- D. You do not need to implement anything since S3 data is automatically replicated between multiple facilities within an AWS Region

Answer: D

NEW QUESTION 19

- (Topic 1)

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW), the instance has an associated Elastic IP (EIP), and correct security group rules are in place. Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

Answer: B

Explanation:

Reference:
<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForVPC.html>

NEW QUESTION 24

- (Topic 1)

You have been asked to automate many routine systems administrator backup and recovery activities. Your current plan is to leverage AWS-managed solutions as much as possible and automate the rest with the AWS CLI and scripts. Which task would be best accomplished with a script?

- A. Creating daily EBS snapshots with a monthly rotation of snapshots
- B. Creating daily RDS snapshots with a monthly rotation of snapshots
- C. Automatically detect and stop unused or underutilized EC2 instances
- D. Automatically add Auto Scaled EC2 instances to an Amazon Elastic Load Balancer

Answer: A

NEW QUESTION 29

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 with only a private subnet and VPN connection using the VPC wizard. The user wants to connect to the instance in a private subnet over SSH. How should the user define the security rule for SSH?

- A. Allow Inbound traffic on port 22 from the user's network
- B. The user has to create an instance in EC2 Classic with an elastic IP and configure the security group of a private subnet to allow SSH from that elastic IP
- C. The user can connect to an instance in a private subnet using the NAT instance
- D. Allow Inbound traffic on port 80 and 22 to allow the user to connect to a private subnet over the Internet

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, the user can setup a case with a VPN only subnet (private. which uses VPN access to connect with his data centre. When the user has configured this setup with Wizard, all network connections to the instances in the subnet will come from his data centre. The user has to configure the security group of the private subnet which allows the inbound traffic on SSH (port 22. from the data centre's network range.

NEW QUESTION 31

- (Topic 2)

A user has setup an EBS backed instance and a CloudWatch alarm when the CPU utilization is more than 65%. The user has setup the alarm to watch it for 5 periods of 5 minutes each. The CPU utilization is 60% between 9 AM to 6 PM. The user has stopped the EC2 instance for 15 minutes between 11 AM to 11:15 AM. What will be the status of the alarm at 11:30 AM?

- A. Alarm
- B. OK
- C. Insufficient Data
- D. Error

Answer: B

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The state of the alarm will be OK for the whole day. When the user stops the instance for three periods the alarm may not receive the data

NEW QUESTION 34

- (Topic 2)

A user has launched an ELB which has 5 instances registered with it. The user deletes the ELB by mistake. What will happen to the instances?

- A. ELB will ask the user whether to delete the instances or not
- B. Instances will be terminated
- C. ELB cannot be deleted if it has running instances registered with it
- D. Instances will keep running

Answer: D

Explanation:

When the user deletes the Elastic Load Balancer, all the registered instances will be deregistered. However, they will continue to run. The user will incur charges if he does not take any action on those instances.

NEW QUESTION 36

- (Topic 2)

A user has setup connection draining with ELB to allow in-flight requests to continue while the instance is being deregistered through Auto Scaling. If the user has not specified the draining time, how long will ELB allow inflight requests traffic to continue?

- A. 600 seconds
- B. 3600 seconds
- C. 300 seconds
- D. 0 seconds

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can specify a maximum time (3600 seconds. for the load balancer to keep the connections alive before reporting the instance as deregistered. If the user does not specify the maximum timeout period, by default, the load balancer will close the connections to the deregistering instance after 300 seconds.

NEW QUESTION 41

- (Topic 2)

A user has configured ELB with three instances. The user wants to achieve High Availability as well as redundancy with ELB. Which of the below mentioned AWS services helps the user achieve this for ELB?

- A. Route 53
- B. AWS Mechanical Turk
- C. Auto Scaling
- D. AWS EMR

Answer: A

Explanation:

The user can provide high availability and redundancy for applications running behind Elastic Load Balancer by enabling the Amazon Route 53 Domain Name System (DNS. failover for the load balancers. Amazon Route 53 is a DNS service that provides reliable routing to the user's infrastructure.

NEW QUESTION 45

- (Topic 2)

A user has enabled the Multi AZ feature with the MS SQL RDS database server. Which of the below mentioned statements will help the user understand the Multi AZ feature better?

- A. In a Multi AZ, AWS runs two DBs in parallel and copies the data asynchronously to the replica copy
- B. In a Multi AZ, AWS runs two DBs in parallel and copies the data synchronously to the replica copy
- C. In a Multi AZ, AWS runs just one DB but copies the data synchronously to the standby replica
- D. AWS MS SQL does not support the Multi AZ feature

Answer: C

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. In a Multi-AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone. The primary DB instance is synchronously replicated across Availability Zones to a standby replica to provide data redundancy, eliminate I/O freezes, and minimize latency spikes during system backups. Running a DB instance with high availability can enhance availability during planned system maintenance, and help protect your databases against DB instance failure and Availability Zone disruption. Note that the high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a read replica.

NEW QUESTION 50

- (Topic 2)

An organization is setting up programmatic billing access for their AWS account. Which of the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

Answer: C

Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3) APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value) file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

NEW QUESTION 54

- (Topic 2)

A user has stored data on an encrypted EBS volume. The user wants to share the data with his friend's AWS account. How can user achieve this?

- A. Create an AMI from the volume and share the AMI
- B. Copy the data to an unencrypted volume and then share
- C. Take a snapshot and share the snapshot with a friend
- D. If both the accounts are using the same encryption key then the user can share the volume directly

Answer: B

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. If the user is having data on an encrypted volume and is trying to share it with others, he has to copy the data from the encrypted volume to a new unencrypted volume. Only then can the user share it as an encrypted volume data. Otherwise the snapshot cannot be shared.

NEW QUESTION 57

- (Topic 2)

A root account owner has created an S3 bucket testmycloud. The account owner wants to allow everyone to upload the objects as well as enforce that the person who uploaded the object should manage the permission of those objects. Which is the easiest way to achieve this?

- A. The root account owner should create a bucket policy which allows the IAM users to upload the object
- B. The root account owner should create the bucket policy which allows the other account owners to set the object policy of that bucket
- C. The root account should use ACL with the bucket to allow everyone to upload the object
- D. The root account should create the IAM users and provide them the permission to upload content to the bucket

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List) associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users in his account. ACLs are suitable for specific scenarios. For example, if a bucket owner allows other AWS accounts to upload objects, permissions to these objects can only be managed using the object ACL by the AWS account that owns the object.

NEW QUESTION 62

- (Topic 2)

A user has enabled detailed CloudWatch metric monitoring on an Auto Scaling group. Which of the below

mentioned metrics will help the user identify the total number of instances in an Auto Scaling group cluding pending, terminating and running instances?

- A. GroupTotalInstances
- B. GroupSumInstances
- C. It is not possible to get a count of all the three metrics togethe
- D. The user has to find the individual number of running, terminating and pending instances and sum it
- E. GroupInstancesCount

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For Auto Scaling, CloudWatch provides various metrics to get the group information, such as the Number of Pending, Running or Terminating instances at any moment. If the user wants to get the total number of Running, Pending and Terminating instances at any moment, he can use the GroupTotalInstances metric.

NEW QUESTION 67

- (Topic 2)

A user is trying to configure the CloudWatch billing alarm. Which of the below mentioned steps should be performed by the user for the first time alarm creation in the AWS Account Management section?

- A. Enable Receiving Billing Reports
- B. Enable Receiving Billing Alerts
- C. Enable AWS billing utility
- D. Enable CloudWatch Billing Threshold

Answer: B

Explanation:

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. Before the user can create an alarm on the estimated charges, he must enable monitoring of the estimated AWS charges, by selecting the option “Enable receiving billing alerts”. It takes about 15 minutes before the user can view the billing data. The user can then create the alarms.

NEW QUESTION 69

- (Topic 2)

An organization has configured the custom metric upload with CloudWatch. The organization has given permission to its employees to upload data using CLI as well SDK. How can the user track the calls made to CloudWatch?

- A. The user can enable logging with CloudWatch which logs all the activities
- B. Use CloudTrail to monitor the API calls
- C. Create an IAM user and allow each user to log the data using the S3 bucket
- D. Enable detailed monitoring with CloudWatch

Answer: B

Explanation:

AWS CloudTrail is a web service which will allow the user to monitor the calls made to the Amazon CloudWatch API for the organization’s account, including calls made by the AWS Management Console, Command Line Interface (CLI), and other services. When CloudTrail logging is turned on, CloudWatch will write log files into the Amazon S3 bucket, which is specified during the CloudTrail configuration.

NEW QUESTION 74

- (Topic 2)

A user is trying to delete an Auto Scaling group from CLI. Which of the below mentioned steps are to be performed by the user?

- A. Terminate the instances with the ec2-terminate-instance command
- B. Terminate the Auto Scaling instances with the as-terminate-instance command
- C. Set the minimum size and desired capacity to 0
- D. There is no need to change the capacit
- E. Run the as-delete-group command and it will reset all values to 0

Answer: C

Explanation:

If the user wants to delete the Auto Scaling group, the user should manually set the values of the minimum and desired capacity to 0. Otherwise Auto Scaling will not allow for the deletion of the group from CLI. While trying from the AWS console, the user need not set the values to 0 as the Auto Scaling console will automatically do so.

NEW QUESTION 76

- (Topic 2)

A user has a refrigerator plant. The user is measuring the temperature of the plant every 15 minutes. If the user wants to send the data to CloudWatch to view the data visually, which of the below mentioned statements is true with respect to the information given above?

- A. The user needs to use AWS CLI or API to upload the data
- B. The user can use the AWS Import Export facility to import data to CloudWatch
- C. The user will upload data from the AWS console
- D. The user cannot upload data to CloudWatch since it is not an AWS service metric

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. While sending the data the user has to include the metric name, namespace and timezone as part of the request.

NEW QUESTION 80

- (Topic 2)

An organization wants to move to Cloud. They are looking for a secure encrypted database storage option. Which of the below mentioned AWS functionalities helps them to achieve this?

- A. AWS MFA with EBS
- B. AWS EBS encryption
- C. Multi-tier encryption with Redshift
- D. AWS S3 server side storage

Answer: B

Explanation:

AWS EBS supports encryption of the volume while creating new volumes. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of EBS will be encrypted. The encryption occurs on the servers that host the EC2 instances, providing encryption of data as it moves between the EC2 instances and EBS storage. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard

NEW QUESTION 84

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25 and a private subnet with CIDR 20.0.0.128/25. The user has launched one instance each in the private and public subnets. Which of the below mentioned options cannot be the correct IP address (private IP) assigned to an instance in the public or private subnet?

- A. 20.0.0.255
- B. 20.0.0.132
- C. 20.0.0.122
- D. 20.0.0.55

Answer: A

Explanation:

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. In this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255.. The public subnet will have IP addresses between 20.0.0.0 - 20.0.0.127 and the private subnet will have IP addresses between 20.0.0.128 -20.0.0.255. AWS reserves the first four IP addresses and the last IP address in each subnet's CIDR block. These are not available for the user to use. Thus, the instance cannot have an IP address of 20.0.0.255

NEW QUESTION 86

- (Topic 3)

A user has created a VPC with a public subnet. The user has terminated all the instances which are part of the subnet. Which of the below mentioned statements is true with respect to this scenario?

- A. The user cannot delete the VPC since the subnet is not deleted
- B. All network interface attached with the instances will be deleted
- C. When the user launches a new instance it cannot use the same subnet
- D. The subnet to which the instances were launched with will be deleted

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface. When the user terminates the instance all the network interfaces attached with it are also deleted.

NEW QUESTION 87

- (Topic 3)

A sys admin has enabled logging on ELB. Which of the below mentioned fields will not be a part of the log file name?

- A. Load Balancer IP
- B. EC2 instance IP
- C. S3 bucket name
- D. Random string

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Elastic Load Balancing publishes a log file from

each load balancer node at the interval that the user has specified. The load balancer can deliver multiple logs for the same period. Elastic Load Balancing creates log file names in the following format: "{Bucket}/{Prefix}/AWSLogs/{AWS AccountID}/elasticloadbalancing/{Region}/{Year}/{Month}/{Day}/{AWS Account ID}_elasticloadbalancing_{Region}_{Load Balancer Name}_{End Time}_{Load Balancer IP}_{Random String}.log"

NEW QUESTION 90

- (Topic 3)

A user is trying to understand the detailed CloudWatch monitoring concept. Which of the below mentioned services does not provide detailed monitoring with CloudWatch?

- A. AWS EMR
- B. AWS RDS
- C. AWS ELB
- D. AWS Route53

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Services, such as RDS, EC2, Auto Scaling, ELB, and Route 53 can provide the monitoring data every minute.

NEW QUESTION 95

- (Topic 3)

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. Which of the below mentioned security policies is supported by ELB?

- A. Dynamic Security Policy
- B. All the other options
- C. Predefined Security Policy
- D. Default Security Policy

Answer: C

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. ELB supports two policies: Predefined Security Policy, which comes with predefined cipher and SSL protocols; Custom Security Policy, which allows the user to configure a policy.

NEW QUESTION 98

- (Topic 3)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        }
      },
      "NotIpAddress": {
        "aws:SourceIp": "192.168.100.188/32"
      }
    }
  ],
  "Principal": {
    "AWS": [
      "*"
    ]
  }
}
```

- A. Denies the server with the IP address 192.166 100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.166 100.188 full access to the "mybucket bucket
- C. Grants all the servers within the 192 168 100 0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192 168 100 188/32 subnet full access to the "mybucket" bucket

Answer: C

NEW QUESTION 103

- (Topic 3)

Which method can be used to prevent an IP address block from accessing public objects in an S3 bucket?

- A. Create a bucket policy and apply it to the bucket
- B. Create a NACL and attach it to the VPC of the bucket
- C. Create an ACL and apply it to all objects in the bucket
- D. Modify the IAM policies of any users that would access the bucket

Answer: A

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

NEW QUESTION 107

- (Topic 3)

A user is collecting 1000 records per second. The user wants to send the data to CloudWatch using the custom namespace. Which of the below mentioned options is recommended for this activity?

- A. Aggregate the data with statistics, such as Min, max, Average, Sum and Sample data and send the data to CloudWatch
- B. Send all the data values to CloudWatch in a single command by separating them with a comm
- C. CloudWatch will parse automatically
- D. Create one csv file of all the data and send a single file to CloudWatch
- E. It is not possible to send all the data in one cal
- F. Thus, it should be sent one by on
- G. CloudWatch will aggregate the data automatically

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. It is recommended that when the user is having multiple data points per minute, he should aggregate the data so that it will minimize the number of calls to put-metric-data. In this case it will be single call to CloudWatch instead of 1000 calls if the data is aggregated.

NEW QUESTION 108

- (Topic 3)

How can an EBS volume that is currently attached to an EC2 instance be migrated from one Availability Zone to another?

- A. Simply create a new volume in the other AZ and specify the original volume as the source
- B. Detach the volume, then use the ec2-migrate-volume command to move it to another AZ
- C. Create a snapshot of the volume, and create a new volume from the snapshot in the other AZ
- D. Detach the volume and attach it to another EC2 instance in the other AZ

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumes.html>

NEW QUESTION 110

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AlarmNotification (which notifies Auto Scaling for CloudWatch alarms. process for a while. What will Auto Scaling do during this period?

- A. AWS will not receive the alarms from CloudWatch
- B. AWS will receive the alarms but will not execute the Auto Scaling policy
- C. Auto Scaling will execute the policy but it will not launch the instances until the process is resumed
- D. It is not possible to suspend the AlarmNotification process

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate Alarm Notification etc. The user can also suspend individual process. The AlarmNotification process type accepts notifications from the Amazon CloudWatch alarms that are associated with the Auto Scaling group. If the user suspends this process type, Auto Scaling will not automatically execute the scaling policies that would be triggered by the alarms.

NEW QUESTION 115

- (Topic 3)

A user is observing the EC2 CPU utilization metric on CloudWatch. The user has observed some interesting patterns while filtering over the 1 week period for a particular hour. The user wants to zoom that data point to a more granular period. How can the user do that easily with CloudWatch?

- A. The user can zoom a particular period by selecting that period with the mouse and then releasing the mouse
- B. The user can zoom a particular period by double clicking on that period with the mouse
- C. The user can zoom a particular period by specifying the aggregation data for that period
- D. The user can zoom a particular period by specifying the period in the Time Range

Answer: A

NEW QUESTION 119

- (Topic 3)

A user is trying to setup a security policy for ELB. The user wants ELB to meet the cipher supported by the client by configuring the server order preference in ELB security policy. Which of the below mentioned preconfigured policies supports this feature?

- A. ELBSecurity Policy-2014-01
- B. ELBSecurity Policy-2011-08
- C. ELBDefault Negotiation Policy
- D. ELBSample- OpenSSLDefault Cipher Policy

Answer: A

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the load balancer is configured to support the Server Order Preference, then the load balancer gets to select the first cipher in its list that matches any one of the ciphers in the client's list. When the user verifies the preconfigured policies supported by ELB, the policy "ELBSecurity Policy-2014-01" supports server order preference.

NEW QUESTION 120

- (Topic 3)

You run a web application with the following components Elastic Load Balancer (ELB), 3 Web/Application servers, 1 MySQL RDS database with read replicas, and Amazon Simple Storage Service (Amazon S3) for static content. Average response time for users is increasing slowly. What three CloudWatch RDS metrics will allow you to identify if the database is the bottleneck? Choose 3 answers

- A. The number of outstanding IOs waiting to access the disk
- B. The amount of write latency
- C. The amount of disk space occupied by binary logs on the master
- D. The amount of time a Read Replica DB Instance lags behind the source DB Instance
- E. The average number of disk I/O operations per second

Answer: ABD

NEW QUESTION 123

- (Topic 3)

A sys admin has enabled a log on ELB. Which of the below mentioned activities are not captured by the log?

- A. Response processing time
- B. Front end processing time
- C. Backend processing time
- D. Request processing time

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Each request will have details, such as client IP, request path, ELB IP, time, and latencies. The time will have information, such as Request Processing time, Backend Processing time and Response Processing time.

NEW QUESTION 126

- (Topic 3)

A user is using CloudFormation to launch an EC2 instance and then configure an application after the instance is launched. The user wants the stack creation of ELB and AutoScaling to wait until the EC2 instance is launched and configured properly. How can the user configure this?

- A. It is not possible that the stack creation will wait until one service is created and launched
- B. The user can use the HoldCondition resource to wait for the creation of the other dependent resources
- C. The user can use the DependentCondition resource to hold the creation of the other dependent resources
- D. The user can use the WaitCondition resource to hold the creation of the other dependent resources

Answer: D

Explanation:

AWS CloudFormation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS CloudFormation provides a WaitCondition resource which acts as a barrier and blocks the creation of other resources until a completion signal is received from an external source, such as a user application or management system.

NEW QUESTION 130

- (Topic 3)

A user is creating a CloudFormation stack. Which of the below mentioned limitations does not hold true for CloudFormation?

- A. One account by default is limited to 100 templates
- B. The user can use 60 parameters and 60 outputs in a single template

- C. The template, parameter, output, and resource description fields are limited to 4096 characters
- D. One account by default is limited to 20 stacks

Answer: A

Explanation:

AWS CloudFormation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The limitations given below apply to the CloudFormation template and stack. There are no limits to the number of templates but each AWS CloudFormation account is limited to a maximum of 20 stacks by default. The Template, Parameter, Output, and Resource description fields are limited to 4096 characters. The user can include up to 60 parameters and 60 outputs in a template.

NEW QUESTION 135

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. If the user restarts the instance, what will happen to the ephemeral storage data?

- A. All the data will be erased but the ephemeral storage will stay connected
- B. All data will be erased and the ephemeral storage is released
- C. It is not possible to restart an instance launched from an instance store backed AMI
- D. The data is preserved

Answer: D

Explanation:

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. When an instance launched from an instance store backed AMI is rebooted all the ephemeral storage data is still preserved.

NEW QUESTION 137

- (Topic 3)

An organization has created 10 IAM users. The organization wants each of the IAM users to have access to a separate DynamoDB table. All the users are added to the same group and the organization wants to setup a group level policy for this. How can the organization achieve this?

- A. Define the group policy and add a condition which allows the access based on the IAM name
- B. Create a DynamoDB table with the same name as the IAM user name and define the policy rule which grants access based on the DynamoDB ARN using a variable
- C. Create a separate DynamoDB database for each user and configure a policy in the group based on the DB variable
- D. It is not possible to have a group level policy which allows different IAM users to different DynamoDB Tables

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. AWS DynamoDB has only tables and the organization cannot make separate databases. The organization should create a table with the same name as the IAM user name and use the ARN of DynamoDB as part of the group policy. The sample policy is shown below:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Action": ["dynamodb:*"],
    "Resource": "arn:aws:dynamodb:region:account-number-without-hyphens:table/${aws:username}"
  }]
}
```

NEW QUESTION 140

- (Topic 3)

A user has setup a custom application which generates a number in decimals. The user wants to track that number and setup the alarm whenever the number is above a certain limit. The application is sending the data to CloudWatch at regular intervals for this purpose. Which of the below mentioned statements is not true with respect to the above scenario?

- A. The user can get the aggregate data of the numbers generated over a minute and send it to CloudWatch
- B. The user has to supply the timezone with each data point
- C. CloudWatch will not truncate the number until it has an exponent larger than 126 (i.
- D. 1×10^{126} .
- E. The user can create a file in the JSON format with the metric name and value and supply it to CloudWatch

Answer: B

NEW QUESTION 145

- (Topic 3)

Amazon EBS snapshots have which of the following two characteristics? (Choose 2.) Choose 2 answers

- A. EBS snapshots only save incremental changes from snapshot to snapshot
- B. EBS snapshots can be created in real-time without stopping an EC2 instance
- C. EBS snapshots can only be restored to an EBS volume of the same size or smaller
- D. EBS snapshots can only be restored and mounted to an instance in the same Availability Zone as the original EBS volume

Answer: AD

NEW QUESTION 146

- (Topic 3)

A user has scheduled the maintenance window of an RDS DB on Monday at 3 AM. Which of the below mentioned events may force to take the DB instance offline during the maintenance window?

- A. Enabling Read Replica
- B. Making the DB Multi AZ
- C. DB password change
- D. Security patching

Answer: D

Explanation:

Amazon RDS performs maintenance on the DB instance during a user-definable maintenance window. The system may be offline or experience lower performance during that window. The only maintenance events that may require RDS to make the DB instance offline are: Scaling compute operations Software patching. Required software patching is automatically scheduled only for patches that are security and durability related. Such patching occurs infrequently (typically once every few months. and seldom requires more than a fraction of the maintenance window.

NEW QUESTION 149

- (Topic 3)

A user is trying to send custom metrics to CloudWatch using the PutMetricData APIs. Which of the below mentioned points should the user needs to take care while sending the data to CloudWatch?

- A. The size of a request is limited to 8KB for HTTP GET requests and 40KB for HTTP POST requests
- B. The size of a request is limited to 128KB for HTTP GET requests and 64KB for HTTP POST requests
- C. The size of a request is limited to 40KB for HTTP GET requests and 8KB for HTTP POST requests
- D. The size of a request is limited to 16KB for HTTP GET requests and 80KB for HTTP POST requests

Answer: A

Explanation:

With AWS CloudWatch, the user can publish data points for a metric that share not only the same time stamp, but also the same namespace and dimensions. CloudWatch can accept multiple data points in the same PutMetricData call with the same time stamp. The only thing that the user needs to take care of is that the size of a PutMetricData request is limited to 8KB for HTTP GET requests and 40KB for HTTP POST requests.

NEW QUESTION 151

- (Topic 3)

A sysadmin has created the below mentioned policy on an S3 bucket named cloudacademy. The bucket has both AWS.jpg and index.html objects. What does this policy define?

```
"Statement": [{  
  "Sid": "Stmt1388811069831",  
  "Effect": "Allow",  
  "Principal": { "AWS": "*" },  
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],  
  "Resource": [ "arn:aws:s3:::cloudacademy/*.*jpg" ]  
}]
```

- A. It will make all the objects as well as the bucket public
- B. It will throw an error for the wrong action and does not allow to save the policy
- C. It will make the AWS.jpg object as public
- D. It will make the AWS.jpg as well as the cloudacademy bucket as public

Answer: B

NEW QUESTION 156

- (Topic 3)

A user is planning to schedule a backup for an EBS volume. The user wants security of the snapshot data. How can the user achieve data encryption with a snapshot?

- A. Use encrypted EBS volumes so that the snapshot will be encrypted by AWS
- B. While creating a snapshot select the snapshot with encryption
- C. By default the snapshot is encrypted by AWS
- D. Enable server side encryption for the snapshot using S3

Answer: A

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of the encrypted EBS will also be encrypted. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard.

NEW QUESTION 159

- (Topic 3)

A user has launched an EC2 Windows instance from an instance store backed AMI. The user has also set the Instance initiated shutdown behavior to stop. What will happen when the user shuts down the OS?

- A. It will not allow the user to shutdown the OS when the shutdown behaviour is set to Stop
- B. It is not possible to set the termination behaviour to Stop for an Instance store backed AMI instance
- C. The instance will stay running but the OS will be shutdown
- D. The instance will be terminated

Answer: B

Explanation:

When the EC2 instance is launched from an instance store backed AMI, it will not allow the user to configure the shutdown behaviour to "Stop". It gives a warning that the instance does not have the EBS root volume.

NEW QUESTION 160

- (Topic 3)

A sys admin is trying to understand the sticky session algorithm. Please select the correct sequence of steps, both when the cookie is present and when it is not, to help the admin understand the implementation of the sticky session:

ELB inserts the cookie in the response ELB chooses the instance based on the load balancing algorithm Check the cookie in the service request The cookie is found in the request The cookie is not found in the request

- A. 3,1,4,2 [Cookie is not Present] & 3,1,5,2 [Cookie is Present]
- B. 3,4,1,2 [Cookie is not Present] & 3,5,1,2 [Cookie is Present]
- C. 3,5,2,1 [Cookie is not Present] & 3,4,2,1 [Cookie is Present]
- D. 3,2,5,4 [Cookie is not Present] & 3,2,4,5 [Cookie is Present]

Answer: C

Explanation:

Generally AWS ELB routes each request to a zone with the minimum load. The Elastic Load Balancer provides a feature called sticky session which binds the user's session with a specific EC2 instance. The load balancer uses a special load-balancer-generated cookie to track the application instance for each request. When the load balancer receives a request, it first checks to see if this cookie is present in the request. If so, the request is sent to the application instance specified in the cookie. If there is no cookie, the load balancer chooses an application instance based on the existing load balancing algorithm. A cookie is inserted into the response for binding subsequent requests from the same user to that application instance.

NEW QUESTION 165

- (Topic 3)

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. The ELB security policy supports various ciphers. Which of the below mentioned options helps identify the matching cipher at the client side to the ELB cipher list when client is requesting ELB DNS over SSL?

- A. Cipher Protocol
- B. Client Configuration Preference
- C. Server Order Preference
- D. Load Balancer Preference

Answer: C

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. When client is requesting ELB DNS over SSL and if the load balancer is configured to support the Server Order Preference, then the load balancer gets to select the first cipher in its list that matches any one of the ciphers in the client's list. Server Order Preference ensures that the load balancer determines which cipher is used for the SSL connection.

NEW QUESTION 169

- (Topic 3)

A user is running a batch process on EBS backed EC2 instances. The batch process starts a few instances to process hadoop Map reduce jobs which can run between 50 – 600 minutes or sometimes for more time. The user wants to configure that the instance gets terminated only when the process is completed. How can the user configure this with CloudWatch?

- A. Setup the CloudWatch action to terminate the instance when the CPU utilization is less than 5%
- B. Setup the CloudWatch with Auto Scaling to terminate all the instances
- C. Setup a job which terminates all instances after 600 minutes
- D. It is not possible to terminate instances automatically

Answer: D

Explanation:

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup an action which terminates the instances when their CPU utilization is below a certain threshold for a certain period of time. The EC2 action can either terminate or stop the instance as part of the EC2 action.

NEW QUESTION 171

- (Topic 3)

A user has created a VPC with two subnets: one public and one private. The user is planning to run the patch update for the instances in the private subnet. How

can the instances in the private subnet connect to the internet?

- A. Use the internet gateway with a private IP
- B. Allow outbound traffic in the security group for port 80 to allow internet updates
- C. The private subnet can never connect to the internet
- D. Use NAT with an elastic IP

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created two subnets (one private and one public), he would need a Network Address Translation (NAT) instance with the elastic IP address. This enables the instances in the private subnet to send requests to the internet (for example, to perform software updates..

NEW QUESTION 172

- (Topic 3)

Which of the below mentioned AWS RDS logs cannot be viewed from the console for MySQL?

- A. Error Log
- B. Slow Query Log
- C. Transaction Log
- D. General Log

Answer: C

Explanation:

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI), or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow querylog, and general logs. RDS does not support viewing the transaction logs.

NEW QUESTION 173

- (Topic 3)

An AWS account wants to be part of the consolidated billing of his organization's payee account. How can the owner of that account achieve this?

- A. The payee account has to request AWS support to link the other accounts with his account
- B. The owner of the linked account should add the payee account to his master account list from the billing console
- C. The payee account will send a request to the linked account to be a part of consolidated billing
- D. The owner of the linked account requests the payee account to add his account to consolidated billing

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. To add a particular account (linked to the master (payee) account, the payee account has to request the linked account to join consolidated billing. Once the linked account accepts the request henceforth all charges incurred by the linked account will be paid by the payee account.

NEW QUESTION 177

- (Topic 3)

A user has enabled session stickiness with ELB. The user does not want ELB to manage the cookie; instead he wants the application to manage the cookie. What will happen when the server instance, which is bound to a cookie, crashes?

- A. The response will have a cookie but stickiness will be deleted
- B. The session will not be sticky until a new cookie is inserted
- C. ELB will throw an error due to cookie unavailability
- D. The session will be sticky and ELB will route requests to another server as ELB keeps replicating the Cookie

Answer: B

Explanation:

With Elastic Load Balancer, if the admin has enabled a sticky session with application controlled stickiness, the load balancer uses a special cookie generated by the application to associate the session with the original server which handles the request. ELB follows the lifetime of the application-generated cookie corresponding to the cookie name specified in the ELB policy configuration. The load balancer only inserts a new stickiness cookie if the application response includes a new application cookie. The load balancer stickiness cookie does not update with each request. If the application cookie is explicitly removed or expires, the session stops being sticky until a new application cookie is issued.

NEW QUESTION 182

- (Topic 3)

A user has hosted an application on EC2 instances. The EC2 instances are configured with ELB and Auto Scaling. The application server session time out is 2 hours. The user wants to configure connection draining to ensure that all in-flight requests are supported by ELB even though the instance is being deregistered. What time out period should the user specify for connection draining?

- A. 5 minutes
- B. 1 hour
- C. 30 minutes
- D. 2 hours

Answer: B

NEW QUESTION 186

- (Topic 3)

A user has launched an EC2 instance. The instance got terminated as soon as it was launched. Which of the below mentioned options is not a possible reason for this?

- A. The user account has reached the maximum EC2 instance limit
- B. The snapshot is corrupt
- C. The AMI is missin
- D. It is the required part
- E. The user account has reached the maximum volume limit

Answer: A

Explanation:

When the user account has reached the maximum number of EC2 instances, it will not be allowed to launch an instance. AWS will throw an 'InstanceLimitExceeded' error. For all other reasons, such as "AMI is missing part", "Corrupt Snapshot" or "Volume limit has reached" it will launch an EC2 instance and then terminate it.

NEW QUESTION 187

- (Topic 3)

A user has created a launch configuration for Auto Scaling where CloudWatch detailed monitoring is disabled. The user wants to now enable detailed monitoring. How can the user achieve this?

- A. Update the Launch config with CLI to set InstanceMonitoringDisabled = false
- B. The user should change the Auto Scaling group from the AWS console to enable detailed monitoring
- C. Update the Launch config with CLI to set InstanceMonitoring.Enabled = true
- D. Create a new Launch Config with detail monitoring enabled and update the Auto Scaling group

Answer: D

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates the AutoScaling launch config as the first step for creating an Auto Scaling group, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. When the user has created a launch configuration with InstanceMonitoring.Enabled = false it will involve multiple steps to enable detail monitoring. The steps are: Create a new Launch config with detailed monitoring enabled Update the Auto Scaling group with a new launch config Enable detail monitoring on each EC2 instance

NEW QUESTION 188

- (Topic 3)

A user has enabled termination protection on an EC2 instance. The user has also set Instance initiated shutdown behaviour to terminate. When the user shuts down the instance from the OS, what will happen?

- A. The OS will shutdown but the instance will not be terminated due to protection
- B. It will terminate the instance
- C. It will not allow the user to shutdown the instance from the OS
- D. It is not possible to set the termination protection when an Instance initiated shutdown is set to Terminate

Answer: B

Explanation:

It is always possible that someone can terminate an EC2 instance using the Amazon EC2 console, command line interface or API by mistake. If the admin wants to prevent the instance from being accidentally terminated, he can enable termination protection for that instance. The user can also setup shutdown behaviour for an EBS backed instance to guide the instance on what should be done when he initiates shutdown from the OS using Instance initiated shutdown behaviour. If the instance initiated behaviour is set to terminate and the user shuts off the OS even though termination protection is enabled, it will still terminate the instance.

NEW QUESTION 192

- (Topic 3)

An organization is measuring the latency of an application every minute and storing data inside a file in the JSON format. The organization wants to send all latency data to AWS CloudWatch. How can the organization achieve this?

- A. The user has to parse the file before uploading data to CloudWatch
- B. It is not possible to upload the custom data to CloudWatch
- C. The user can supply the file as an input to the CloudWatch command
- D. The user can use the CloudWatch Import command to import data from the file to CloudWatch

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user has to always include the namespace as part of the request. If the user wants to upload the custom data from a Amazon AWS-SysOps : Practice Test file, he can supply file name along with the parameter -- metric-data to command put-metric-data.

NEW QUESTION 197

- (Topic 3)

A sys admin is using server side encryption with AWS S3. Which of the below mentioned statements helps the user understand the S3 encryption functionality?

- A. The server side encryption with the user supplied key works when versioning is enabled
- B. The user can use the AWS console, SDK and APIs to encrypt or decrypt the content for server side encryption with the user supplied key
- C. The user must send an AES-128 encrypted key
- D. The user can upload his own encryption key to the S3 console

Answer: A

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key. The encryption with the user supplied key (SSE-C) does not work with the AWS console. The S3 does not store the keys and the user has to send a key with each request. The SSE-C works when the user has enabled versioning.

NEW QUESTION 198

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created public and VPN only subnets along with hardware VPN access to connect to the user's data centre. The user has not yet launched any instance as well as modified or deleted any setup. He wants to delete this VPC from the console. Will the console allow the user to delete the VPC?

- A. Yes, the console will delete all the setups and also delete the virtual private gateway
- B. No, the console will ask the user to manually detach the virtual private gateway first and then allow deleting the VPC
- C. Yes, the console will delete all the setups and detach the virtual private gateway
- D. No, since the NAT instance is running

Answer: C

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. If the virtual private gateway is attached with VPC and the user deletes the VPC from the console it will first detach the gateway automatically and only then delete the VPC.

NEW QUESTION 200

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using VPC Wizard. The user has created a public CIDR (20.0.0.0/24) and a VPN only subnet CIDR (20.0.1.0/24) along with the hardware VPN access to connect to the user's data centre. Which of the below mentioned components is not present when the VPC is setup with the wizard?

- A. Main route table attached with a VPN only subnet
- B. A NAT instance configured to allow the VPN subnet instances to connect with the internet
- C. Custom route table attached with a public subnet
- D. An internet gateway for a public subnet

Answer: B

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. The wizard does not create a NAT instance by default. The user can create it manually and attach it with a VPN only subnet.

NEW QUESTION 201

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-SysOps Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-SysOps Product From:

<https://www.2passeasy.com/dumps/AWS-SysOps/>

Money Back Guarantee

AWS-SysOps Practice Exam Features:

- * AWS-SysOps Questions and Answers Updated Frequently
- * AWS-SysOps Practice Questions Verified by Expert Senior Certified Staff
- * AWS-SysOps Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-SysOps Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year