

Google

Exam Questions Professional-Cloud-Architect

Google Certified Professional - Cloud Architect (GCP)



NEW QUESTION 1

- (Exam Topic 1)

For this question, refer to the Mountkirk Games case study

Mountkirk Games needs to create a repeatable and configurable mechanism for deploying isolated application environments. Developers and testers can access each other's environments and resources, but they cannot access staging or production resources. The staging environment needs access to some services from production.

What should you do to isolate development environments from staging and production?

- A. Create a project for development and test and another for staging and production.
- B. Create a network for development and test and another for staging and production.
- C. Create one subnetwork for development and another for staging and production.
- D. Create one project for development, a second for staging and a third for production.

Answer: D

NEW QUESTION 2

- (Exam Topic 1)

For this question, refer to the Mountkirk Games case study.

Mountkirk Games wants you to design their new testing strategy. How should the test coverage differ from their existing backends on the other platforms?

- A. Tests should scale well beyond the prior approaches.
- B. Unit tests are no longer required, only end-to-end tests.
- C. Tests should be applied after the release is in the production environment.
- D. Tests should include directly testing the Google Cloud Platform (GCP) infrastructure.

Answer: A

Explanation:

From Scenario:

A few of their games were more popular than expected, and they had problems scaling their application servers, MySQL databases, and analytics tools.

Requirements for Game Analytics Platform include: Dynamically scale up or down based on game activity

NEW QUESTION 3

- (Exam Topic 1)

For this question, refer to the Mountkirk Games case study.

Mountkirk Games' gaming servers are not automatically scaling properly. Last month, they rolled out a new feature, which suddenly became very popular. A record number of users are trying to use the service, but many of them are getting 503 errors and very slow response times. What should they investigate first?

- A. Verify that the database is online.
- B. Verify that the project quota hasn't been exceeded.
- C. Verify that the new feature code did not introduce any performance bugs.
- D. Verify that the load-testing team is not running their tool against production.

Answer: B

Explanation:

503 is service unavailable error. If the database was online everyone would get the 503 error. https://cloud.google.com/docs/quota#capping_usage

NEW QUESTION 4

- (Exam Topic 2)

For this question, refer to the TerramEarth case study

Your development team has created a structured API to retrieve vehicle data. They want to allow third parties to develop tools for dealerships that use this vehicle event data. You want to support delegated authorization against this data. What should you do?

- A. Build or leverage an OAuth-compatible access control system.
- B. Build SAML 2.0 SSO compatibility into your authentication system.
- C. Restrict data access based on the source IP address of the partner systems.
- D. Create secondary credentials for each dealer that can be given to the trusted third party.

Answer: A

Explanation:

<https://cloud.google.com/appengine/docs/flexible/go/authorizing-apps> https://cloud.google.com/docs/enterprise/best-practices-for-enterprise-organizations#delegate_application_autho Delegate application authorization with OAuth2

Cloud Platform APIs support OAuth 2.0, and scopes provide granular authorization over the methods that are supported. Cloud Platform supports both service-account and user-account OAuth, also called three-legged OAuth.

References:

https://cloud.google.com/docs/enterprise/best-practices-for-enterprise-organizations#delegate_application_autho

<https://cloud.google.com/appengine/docs/flexible/go/authorizing-apps>

NEW QUESTION 5

- (Exam Topic 3)

For this question, refer to the JencoMart case study

A few days after JencoMart migrates the user credentials database to Google Cloud Platform and shuts down the old server, the new database server stops responding to SSH connections. It is still serving database requests to the application servers correctly. What three steps should you take to diagnose the problem? Choose 3 answers

- A. Delete the virtual machine (VM) and disks and create a new one.
- B. Delete the instance, attach the disk to a new VM, and investigate.
- C. Take a snapshot of the disk and connect to a new machine to investigate.
- D. Check inbound firewall rules for the network the machine is connected to.
- E. Connect the machine to another network with very simple firewall rules and investigate.
- F. Print the Serial Console output for the instance for troubleshooting, activate the interactive console, and investigate.

Answer: CDF

Explanation:

<https://cloud.google.com/compute/docs/troubleshooting/troubleshooting-ssh> D: Handling "Unable to connect on port 22" error message

Possible causes include:

There is no firewall rule allowing SSH access on the port. SSH access on port 22 is enabled on all Compute Engine instances by default. If you have disabled access, SSH from the Browser will not work. If you run sshd on a port other than 22, you need to enable the access to that port with a custom firewall rule.

The firewall rule allowing SSH access is enabled, but is not configured to allow connections from GCP Console services. Source IP addresses for browser-based SSH sessions are dynamically allocated by GCP Console and can vary from session to session.

References:

<https://cloud.google.com/compute/docs/ssh-in-browser> <https://cloud.google.com/compute/docs/ssh-in-browser>

NEW QUESTION 6

- (Exam Topic 4)

The current Dress4win system architecture has high latency to some customers because it is located in one data center.

As of a future evaluation and optimizing for performance in the cloud, Dress4win wants to distribute its system architecture to multiple locations when Google cloud platform. Which approach should they use?

- A. Use regional managed instance groups and a global load balancer to increase performance because the regional managed instance group can grow instances in each region separately based on traffic.
- B. Use a global load balancer with a set of virtual machines that forward the requests to a closer group of virtual machines managed by your operations team.
- C. Use regional managed instance groups and a global load balancer to increase reliability by providing automatic failover between zones in different regions.
- D. Use a global load balancer with a set of virtual machines that forward the requests to a closer group of virtual machines as part of a separate managed instance groups.

Answer: A

NEW QUESTION 7

- (Exam Topic 4)

For this question, refer to the Dress4Win case study.

You want to ensure Dress4Win's sales and tax records remain available for infrequent viewing by auditors for at least 10 years. Cost optimization is your top priority. Which cloud services should you choose?

- A. Google Cloud Storage Coldline to store the data, and gsutil to access the data.
- B. Google Cloud Storage Nearline to store the data, and gsutil to access the data.
- C. Google Bigtable with US or EU as location to store the data, and gcloud to access the data.
- D. BigQuery to store the data, and a web server cluster in a managed instance group to access the data. Google Cloud SQL mirrored across two distinct regions to store the data, and a Redis cluster in a managed instance group to access the data.

Answer: A

Explanation:

References: <https://cloud.google.com/storage/docs/storage-classes>

NEW QUESTION 8

- (Exam Topic 4)

Dress4win has end to end tests covering 100% of their endpoints.

They want to ensure that the move of cloud does not introduce any new bugs.

Which additional testing methods should the developers employ to prevent an outage?

- A. They should run the end to end tests in the cloud staging environment to determine if the code is working as intended.
- B. They should enable google stack driver debugger on the application code to show errors in the code
- C. They should add additional unit tests and production scale load tests on their cloud staging environment.
- D. They should add canary tests so developers can measure how much of an impact the new release causes to latency

Answer: B

NEW QUESTION 9

- (Exam Topic 5)

Your applications will be writing their logs to BigQuery for analysis. Each application should have its own table.

Any logs older than 45 days should be removed. You want to optimize storage and follow Google recommended practices. What should you do?

- A. Configure the expiration time for your tables at 45 days
- B. Make the tables time-partitioned, and configure the partition expiration at 45 days
- C. Rely on BigQuery's default behavior to prune application logs older than 45 days
- D. Create a script that uses the BigQuery command line tool (bq) to remove records older than 45 days

Answer: B

Explanation:

<https://cloud.google.com/bigquery/docs/managing-partitioned-tables>

NEW QUESTION 10

- (Exam Topic 5)

Your company has decided to build a backup replica of their on-premises user authentication PostgreSQL database on Google Cloud Platform. The database is 4 TB, and large updates are frequent. Replication requires private address space communication. Which networking approach should you use?

- A. Google Cloud Dedicated Interconnect
- B. Google Cloud VPN connected to the data center network
- C. A NAT and TLS translation gateway installed on-premises
- D. A Google Compute Engine instance with a VPN server installed connected to the data center network

Answer: A

Explanation:

<https://cloud.google.com/docs/enterprise/best-practices-for-enterprise-organizations>

Google Cloud Dedicated Interconnect provides direct physical connections and RFC 1918 communication between your on-premises network and Google's network. Dedicated Interconnect enables you to transfer large amounts of data between networks, which can be more cost effective than purchasing additional bandwidth over the public Internet or using VPN tunnels.

Benefits:

- Traffic between your on-premises network and your VPC network doesn't traverse the public Internet. Traffic traverses a dedicated connection with fewer hops, meaning there are less points of failure where traffic might get dropped or disrupted.
- Your VPC network's internal (RFC 1918) IP addresses are directly accessible from your on-premises network. You don't need to use a NAT device or VPN tunnel to reach internal IP addresses. Currently, you can only reach internal IP addresses over a dedicated connection. To reach Google external IP addresses, you must use a separate connection.
- You can scale your connection to Google based on your needs. Connection capacity is delivered over one or more 10 Gbps Ethernet connections, with a maximum of eight connections (80 Gbps total per interconnect).
- The cost of egress traffic from your VPC network to your on-premises network is reduced. A dedicated connection is generally the least expensive method if you have a high-volume of traffic to and from Google's network.

References: <https://cloud.google.com/interconnect/docs/details/dedicated>

NEW QUESTION 10

- (Exam Topic 5)

Your company has successfully migrated to the cloud and wants to analyze their data stream to optimize operations. They do not have any existing code for this analysis, so they are exploring all their options. These options include a mix of batch and stream processing, as they are running some hourly jobs and live-processing some data as it comes in. Which technology should they use for this?

- A. Google Cloud Dataproc
- B. Google Cloud Dataflow
- C. Google Container Engine with Bigtable
- D. Google Compute Engine with Google BigQuery

Answer: B

Explanation:

Dataflow is for processing both the Batch and Stream.

Cloud Dataflow is a fully-managed service for transforming and enriching data in stream (real time) and batch (historical) modes with equal reliability and expressiveness -- no more complex workarounds or compromises needed.

References: <https://cloud.google.com/dataflow/>

NEW QUESTION 15

- (Exam Topic 5)

You are using Cloud Shell and need to install a custom utility for use in a few weeks. Where can you store the file so it is in the default execution path and persists across sessions?

- A. ~/bin
- B. Cloud Storage
- C. /google/scripts
- D. /usr/local/bin

Answer: D

Explanation:

<https://medium.com/google-cloud/no-localhost-no-problem-using-google-cloud-shell-as-my-full-time-developm>

NEW QUESTION 20

- (Exam Topic 5)

Your company has decided to make a major revision of their API in order to create better experiences for their developers. They need to keep the old version of the API available and deployable, while allowing new customers and testers to try out the new API. They want to keep the same SSL and DNS records in place to serve both APIs. What should they do?

- A. Configure a new load balancer for the new version of the API.
- B. Reconfigure old clients to use a new endpoint for the new API.
- C. Have the old API forward traffic to the new API based on the path.
- D. Use separate backend pools for each API path behind the load balancer.

Answer: D

Explanation:

<https://cloud.google.com/endpoints/docs/openapi/lifecycle-management>

NEW QUESTION 21

- (Exam Topic 5)

You have developed an application using Cloud ML Engine that recognizes famous paintings from uploaded images. You want to test the application and allow specific people to upload images for the next 24 hours. Not all users have a Google Account. How should you have users upload images?

- A. Have users upload the images to Cloud Storage
- B. Protect the bucket with a password that expires after 24 hours.
- C. Have users upload the images to Cloud Storage using a signed URL that expires after 24 hours.
- D. Create an App Engine web application where users can upload image
- E. Configure App Engine to disable the application after 24 hour
- F. Authenticate users via Cloud Identity.
- G. Create an App Engine web application where users can upload images for the next 24 hours. Authenticate users via Cloud Identity.

Answer: A

Explanation:

<https://cloud.google.com/blog/products/storage-data-transfer/uploading-images-directly-to-cloud-storage-by-usi>

NEW QUESTION 22

- (Exam Topic 5)

Your customer wants to capture multiple GBs of aggregate real-time key performance indicators (KPIs) from their game servers running on Google Cloud Platform and monitor the KPIs with low latency. How should they capture the KPIs?

- A. Store time-series data from the game servers in Google Bigtable, and view it using Google Data Studio.
- B. Output custom metrics to Stackdriver from the game servers, and create a Dashboard in Stackdriver Monitoring Console to view them.
- C. Schedule BigQuery load jobs to ingest analytics files uploaded to Cloud Storage every ten minutes, and visualize the results in Google Data Studio.
- D. Insert the KPIs into Cloud Datastore entities, and run ad hoc analysis and visualizations of them in Cloud Datalab.

Answer: A

Explanation:

<https://cloud.google.com/monitoring/api/v3/metrics-details#metric-kinds>

NEW QUESTION 25

- (Exam Topic 5)

You need to deploy an application to Google Cloud. The application receives traffic via TCP and reads and writes data to the filesystem. The application does not support horizontal scaling. The application process requires full control over the data on the file system because concurrent access causes corruption. The business is willing to accept a downtime when an incident occurs, but the application must be available 24/7 to support their business operations. You need to design the architecture of this application on Google Cloud. What should you do?

- A. Use a managed instance group with instances in multiple zones, use Cloud Filestore, and use an HTTP load balancer in front of the instances.
- B. Use a managed instance group with instances in multiple zones, use Cloud Filestore, and use a network load balancer in front of the instances.
- C. Use an unmanaged instance group with an active and standby instance in different zones, use a regional persistent disk, and use an HTTP load balancer in front of the instances.
- D. Use an unmanaged instance group with an active and standby instance in different zones, use a regional persistent disk, and use a network load balancer in front of the instances.

Answer: D

Explanation:

Reference: <https://cloud.google.com/compute/docs/instance-groups>

NEW QUESTION 27

- (Exam Topic 5)

You deploy your custom java application to google app engine. It fails to deploy and gives you the following stack trace:


```
Java.lang.SecurityException : SHA1 digest

At com.google.appengine.runtime.Request.pr

At

Sun.security.util.manifestEntryVerifier.ver

At java . net . URLClassLoader . defineCla

At sun . reflect . GeneratedMethodAccessors

At

Sun.reflect . DelegatingMethodAccesorImpl.

At java . lang . reflect . MThod . invoke
```

- A. Recompile the CLoakedServlet class using and MD5 hash instead of SHA1
- B. Digitally sign all of your JAR files and redeploy your application.
- C. Upload missing JAR files and redeploy your application

Answer: B

NEW QUESTION 31

- (Exam Topic 5)

One of the developers on your team deployed their application in Google Container Engine with the Dockerfile below. They report that their application deployments are taking too long.

```
FROM ubuntu:16.04

COPY . /src

RUN apt-get update && apt-get install -y python python-pip

RUN pip install -r requirements.txt
```

You want to optimize this Dockerfile for faster deployment times without adversely affecting the app's functionality. Which two actions should you take? Choose 2 answers.

- A. Remove Python after running pip.
- B. Remove dependencies from requirements.txt.
- C. Use a slimmed-down base image like Alpine linux.
- D. Use larger machine types for your Google Container Engine node pools.
- E. Copy the source after the package dependencies (Python and pip) are installed.

Answer: CE

Explanation:

The speed of deployment can be changed by limiting the size of the uploaded app, limiting the complexity of the build necessary in the Dockerfile, if present, and by ensuring a fast and reliable internet connection.

Note: Alpine Linux is built around musl libc and busybox. This makes it smaller and more resource efficient than traditional GNU/Linux distributions. A container requires no more than 8 MB and a minimal installation to disk requires around 130 MB of storage. Not only do you get a fully-fledged Linux environment but a large selection of packages from the repository.

References: <https://groups.google.com/forum/#!topic/google-appengine/hZMEkmmObDU> <https://www.alpinelinux.org/about/>

NEW QUESTION 33

- (Exam Topic 5)

Your BigQuery project has several users. For audit purposes, you need to see how many queries each user ran in the last month.

- A. Connect Google Data Studio to BigQuer
- B. Create a dimension for the users and a metric for the amount of queries per user.
- C. In the BigQuery interface, execute a query on the JOBS table to get the required information.
- D. Use 'bq show' to list all job
- E. Per job, use 'bq ls' to list job information and get the required information.
- F. Use Cloud Audit Logging to view Cloud Audit Logs, and create a filter on the query operation to get the required information.

Answer: C

Explanation:

<https://cloud.google.com/bigquery/docs/managing-jobs>

NEW QUESTION 36

- (Exam Topic 5)

You team needs to create a Google Kubernetes Engine (GKE) cluster to host a newly built application that requires access to third-party services on the internet. Your company does not allow any Compute Engine instance to have a public IP address on Google Cloud. You need to create a deployment strategy that adheres to these guidelines. What should you do?

- A. Create a Compute Engine instance, and install a NAT Proxy on the instance
- B. Configure all workloads on GKE to pass through this proxy to access third-party services on the Internet
- C. Configure the GKE cluster as a private cluster, and configure Cloud NAT Gateway for the cluster subnet
- D. Configure the GKE cluster as a route-based cluster
- E. Configure Private Google Access on the Virtual Private Cloud (VPC)
- F. Configure the GKE cluster as a private cluster
- G. Configure Private Google Access on the Virtual Private Cloud (VPC)

Answer: B

Explanation:

A Cloud NAT gateway can perform NAT for nodes and Pods in a private cluster, which is a type of VPC-native cluster. The Cloud NAT gateway must be configured to apply to at least the following subnet IP address ranges for the subnet that your cluster uses:
Subnet primary IP address range (used by nodes)
Subnet secondary IP address range used for Pods in the cluster
Subnet secondary IP address range used for Services in the cluster
The simplest way to provide NAT for an entire private cluster is to configure a Cloud NAT gateway to apply to all of the cluster's subnet's IP address ranges.
<https://cloud.google.com/nat/docs/overview>

NEW QUESTION 37

- (Exam Topic 5)

Auditors visit your teams every 12 months and ask to review all the Google Cloud Identity and Access Management (Cloud IAM) policy changes in the previous 12 months. You want to streamline and expedite the analysis and audit process. What should you do?

- A. Create custom Google Stackdriver alerts and send them to the auditor.
- B. Enable Logging export to Google BigQuery and use ACLs and views to scope the data shared with the auditor.
- C. Use cloud functions to transfer log entries to Google Cloud SQL and use ACLs and views to limit an auditor's view.
- D. Enable Google Cloud Storage (GCS) log export to audit logs into a GCS bucket and delegate access to the bucket.

Answer: D

Explanation:

Export the logs to Google Cloud Storage bucket - Archive Storage, as it will not be used for 1 year, price for which is \$0.004 per GB per Month. The price for long term storage in BigQuery is \$0.01 per GB per Month (250% more). Also for analysis purpose, whenever Auditors are there (once per year), you can use BigQuery and use GCS bucket as external data source. BigQuery supports querying Cloud Storage data from these storage classes:
Standard Nearline Coldline Archive

NEW QUESTION 42

- (Exam Topic 5)

Your company wants to try out the cloud with low risk. They want to archive approximately 100 TB of their log data to the cloud and test the analytics features available to them there, while also retaining that data as a long-term disaster recovery backup. Which two steps should they take? Choose 2 answers

- A. Load logs into Google BigQuery.
- B. Load logs into Google Cloud SQL.
- C. Import logs into Google Stackdriver.
- D. Insert logs into Google Cloud Bigtable.
- E. Upload log files into Google Cloud Storage.

Answer: AE

NEW QUESTION 44

- (Exam Topic 5)

The database administration team has asked you to help them improve the performance of their new database server running on Google Compute Engine. The database is for importing and normalizing their performance statistics and is built with MySQL running on Debian Linux. They have an n1-standard-8 virtual machine with 80 GB of SSD persistent disk. What should they change to get better performance from this system?

- A. Increase the virtual machine's memory to 64 GB.
- B. Create a new virtual machine running PostgreSQL.
- C. Dynamically resize the SSD persistent disk to 500 GB.
- D. Migrate their performance metrics warehouse to BigQuery.
- E. Modify all of their batch jobs to use bulk inserts into the database.

Answer: C

NEW QUESTION 48

- (Exam Topic 5)

You are designing an application for use only during business hours. For the minimum viable product release, you'd like to use a managed product that automatically "scales to zero" so you don't incur costs when there is no activity. Which primary compute resource should you choose?

- A. Cloud Functions

- B. Compute Engine
- C. Kubernetes Engine
- D. AppEngine flexible environment

Answer: A

Explanation:

<https://cloud.google.com/serverless-options>

NEW QUESTION 50

- (Exam Topic 5)

You are implementing the infrastructure for a web service on Google Cloud. The web service needs to receive and store the data from 500,000 requests per second. The data will be queried later in real time, based on exact matches of a known set of attributes. There will be periods where the web service will not receive any requests. The business wants to keep costs low. Which web service platform and database should you use for the application?

- A. Cloud Run and BigQuery
- B. Cloud Run and Cloud Bigtable
- C. A Compute Engine autoscaling managed instance group and BigQuery
- D. A Compute Engine autoscaling managed instance group and Cloud Bigtable

Answer: B

Explanation:

<https://cloud.google.com/run/docs/about-instance-autoscaling> <https://cloud.google.com/blog/topics/developers-practitioners/bigtable-vs-bigquery-whats-difference>

NEW QUESTION 53

- (Exam Topic 5)

You need to develop procedures to test a disaster plan for a mission-critical application. You want to use Google-recommended practices and native capabilities within GCP.

What should you do?

- A. Use Deployment Manager to automate service provisionin
- B. Use Activity Logs to monitor and debug your tests.
- C. Use Deployment Manager to automate provisionin
- D. Use Stackdriver to monitor and debug your tests.
- E. Use gcloud scripts to automate service provisionin
- F. Use Activity Logs monitor and debug your tests.
- G. Use automated scripts to automate service provisionin
- H. Use Activity Logs monitor and debug your tests.

Answer: B

Explanation:

<https://cloud.google.com/solutions/dr-scenarios-planning-guide>

NEW QUESTION 58

- (Exam Topic 5)

You have an outage in your Compute Engine managed instance group: all instance keep restarting after 5 seconds. You have a health check configured, but autoscaling is disabled. Your colleague, who is a Linux expert, offered to look into the issue. You need to make sure that he can access the VMs. What should you do?

- A. Grant your colleague the IAM role of project Viewer
- B. Perform a rolling restart on the instance group
- C. Disable the health check for the instance grou
- D. Add his SSH key to the project-wide SSH keys
- E. Disable autoscaling for the instance grou
- F. Add his SSH key to the project-wide SSH Keys

Answer: C

Explanation:

<https://cloud.google.com/compute/docs/instance-groups/autohealing-instances-in-migs>

Health checks used for autohealing should be conservative so they don't preemptively delete and recreate your instances. When an autohealer health check is too aggressive, the autohealer might mistake busy instances for failed instances and unnecessarily restart them, reducing availability

NEW QUESTION 63

- (Exam Topic 5)

Your customer is moving their corporate applications to Google Cloud Platform. The security team wants detailed visibility of all projects in the organization. You provision the Google Cloud Resource Manager and set up yourself as the org admin. What Google Cloud Identity and Access Management (Cloud IAM) roles should you give to the security team'?

- A. Org viewer, project owner
- B. Org viewer, project viewer
- C. Org admin, project browser
- D. Project owner, network admin

Answer: B

Explanation:

<https://cloud.google.com/iam/docs/using-iam-securely>

NEW QUESTION 64

- (Exam Topic 5)

Your customer is moving an existing corporate application to Google Cloud Platform from an on-premises data center. The business owners require minimal user disruption. There are strict security team requirements for storing passwords. What authentication strategy should they use?

- A. Use G Suite Password Sync to replicate passwords into Google.
- B. Federate authentication via SAML 2.0 to the existing Identity Provider.
- C. Provision users in Google using the Google Cloud Directory Sync tool.
- D. Ask users to set their Google password to match their corporate password.

Answer: B

Explanation:

<https://cloud.google.com/solutions/authenticating-corporate-users-in-a-hybrid-environment>

NEW QUESTION 69

- (Exam Topic 5)

You are working in a highly secured environment where public Internet access from the Compute Engine VMs is not allowed. You do not yet have a VPN connection to access an on-premises file server. You need to install specific software on a Compute Engine instance. How should you install the software?

- A. Upload the required installation files to Cloud Storage
- B. Configure the VM on a subnet with a Private Google Access subne
- C. Assign only an internal IP address to the V
- D. Download the installation files to the VM using gsutil.
- E. Upload the required installation files to Cloud Storage and use firewall rules to block all traffic except the IP address range for Cloud Storag
- F. Download the files to the VM using gsutil.
- G. Upload the required installation files to Cloud Source Repositorie
- H. Configure the VM on a subnet with a Private Google Access subne
- I. Assign only an internal IP address to the V
- J. Download the installation files to the VM using gcloud.
- K. Upload the required installation files to Cloud Source Repositories and use firewall rules to block all traffic except the IP address range for Cloud Source Repositorie
- L. Download the files to the VM using gsutil.

Answer: A

Explanation:

<https://cloud.google.com/vpc/docs/private-access-options#pga-supported>

NEW QUESTION 70

- (Exam Topic 5)

Your company is running its application workloads on Compute Engine. The applications have been deployed in production, acceptance, and development environments. The production environment is business-critical and is used 24/7, while the acceptance and development environments are only critical during office hours. Your CFO has asked you to optimize these environments to achieve cost savings during idle times. What should you do?

- A. Create a shell script that uses the gcloud command to change the machine type of the development and acceptance instances to a smaller machine type outside of office hour
- B. Schedule the shell script on one of the production instances to automate the task.
- C. Use Cloud Scheduler to trigger a Cloud Function that will stop the development and acceptance environments after office hours and start them just before office hours.
- D. Deploy the development and acceptance applications on a managed instance group and enable autoscaling.
- E. Use regular Compute Engine instances for the production environment, and use preemptible VMs for the acceptance and development environments.

Answer: B

Explanation:

Reference: <https://cloud.google.com/blog/products/it-ops/best-practices-for-optimizing-your-cloud-costs>

NEW QUESTION 71

- (Exam Topic 5)

You need to reduce the number of unplanned rollbacks of erroneous production deployments in your company's web hosting platform. Improvement to the QA/Test processes accomplished an 80% reduction. Which additional two approaches can you take to further reduce the rollbacks? Choose 2 answers

- A. Introduce a green-blue deployment model.
- B. Replace the QA environment with canary releases.
- C. Fragment the monolithic platform into microservices.
- D. Reduce the platform's dependency on relational database systems.
- E. Replace the platform's relational database systems with a NoSQL database.

Answer: AC

NEW QUESTION 73

- (Exam Topic 5)

Your company places a high value on being responsive and meeting customer needs quickly. Their primary business objectives are release speed and agility. You want to reduce the chance of security errors being accidentally introduced. Which two actions can you take? Choose 2 answers

- A. Ensure every code check-in is peer reviewed by a security SME.
- B. Use source code security analyzers as part of the CI/CD pipeline.
- C. Ensure you have stubs to unit test all interfaces between components.
- D. Enable code signing and a trusted binary repository integrated with your CI/CD pipeline.
- E. Run a vulnerability security scanner as part of your continuous-integration /continuous-delivery (CI/CD) pipeline.

Answer: BE

Explanation:

<https://docs.microsoft.com/en-us/vsts/articles/security-validation-cicd-pipeline?view=vsts>

NEW QUESTION 76

- (Exam Topic 5)

You want to enable your running Google Container Engine cluster to scale as demand for your application changes.

What should you do?

- A. Add additional nodes to your Container Engine cluster using the following command: `gcloud container clusters resize CLUSTER_NAME --size 10`
- B. Add a tag to the instances in the cluster with the following command: `gcloud compute instances add-tags INSTANCE --tags enable --autoscaling max-nodes=10`
- C. Update the existing Container Engine cluster with the following command: `gcloud alpha container clusters update mycluster --enable-autoscaling --min-nodes=1 --max-nodes=10`
- D. Create a new Container Engine cluster with the following command: `gcloud alpha container clusters create mycluster --enable-autocaling --min-nodes=1 --max-nodes=10` and redeploy your application.

Answer: B

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/concepts/cluster-autoscaler> Cluster autoscaling

--enable-autoscaling

Enables autoscaling for a node pool.

Enables autoscaling in the node pool specified by --node-pool or the default node pool if --node-pool is not provided.

Where:

--max-nodes=MAX_NODES

Maximum number of nodes in the node pool.

Maximum number of nodes to which the node pool specified by --node-pool (or default node pool if unspecified) can scale.

NEW QUESTION 79

- (Exam Topic 5)

You are designing a large distributed application with 30 microservices. Each of your distributed microservices needs to connect to a database back-end. You want to store the credentials securely. Where should you store the credentials?

- A. In the source code
- B. In an environment variable
- C. In a secret management system
- D. In a config file that has restricted access through ACLs

Answer: C

Explanation:

https://cloud.google.com/docs/authentication/production#providing_credentials_to_your_application

NEW QUESTION 80

- (Exam Topic 5)

Your customer runs a web service used by e-commerce sites to offer product recommendations to users. The company has begun experimenting with a machine learning model on Google Cloud Platform to improve the quality of results.

What should the customer do to improve their model's results over time?

- A. Export Cloud Machine Learning Engine performance metrics from Stackdriver to BigQuery, to be used to analyze the efficiency of the model.
- B. Build a roadmap to move the machine learning model training from Cloud GPUs to Cloud TPUs, which offer better results.
- C. Monitor Compute Engine announcements for availability of newer CPU architectures, and deploy the model to them as soon as they are available for additional performance.
- D. Save a history of recommendations and results of the recommendations in BigQuery, to be used as training data.

Answer: D

Explanation:

<https://cloud.google.com/solutions/building-a-serverless-ml-model>

NEW QUESTION 82

- (Exam Topic 5)

During a high traffic portion of the day, one of your relational databases crashes, but the replica is never promoted to a master. You want to avoid this in the future. What should you do?

- A. Use a different database.
- B. Choose larger instances for your database.
- C. Create snapshots of your database more regularly.
- D. Implement routinely scheduled failovers of your databases.

Answer: D

Explanation:

<https://cloud.google.com/solutions/dr-scenarios-planning-guide>

NEW QUESTION 85

- (Exam Topic 5)

You have deployed an application on Anthos clusters (formerly Anthos GKE). According to the SRE practices at your company you need to be alerted if the request latency is above a certain threshold for a specified amount of time. What should you do?

- A. Enable the Cloud Trace API on your project and use Cloud Monitoring Alerts to send an alert based on the Cloud Trace metrics
- B. Configure Anthos Config Management on your cluster and create a yaml file that defines the SLO and alerting policy you want to deploy in your cluster
- C. Use Cloud Profiler to follow up the request latency
- D. Create a custom metric in Cloud Monitoring based on the results of Cloud Profiler, and create an Alerting Policy in case this metric exceeds the threshold
- E. Install Anthos Service Mesh on your cluster
- F. Use the Google Cloud Console to define a Service Level Objective (SLO)

Answer: D

Explanation:

<https://cloud.google.com/service-mesh/docs/overview> <https://cloud.google.com/service-mesh/docs/observability/slo-overview>

NEW QUESTION 90

- (Exam Topic 5)

Your company has just acquired another company, and you have been asked to integrate their existing Google Cloud environment into your company's data center. Upon investigation, you discover that some of the RFC 1918 IP ranges being used in the new company's Virtual Private Cloud (VPC) overlap with your data center IP space. What should you do to enable connectivity and make sure that there are no routing conflicts when connectivity is established?

- A. Create a Cloud VPN connection from the new VPC to the data center, create a Cloud Router, and apply new IP addresses so there is no overlapping IP space.
- B. Create a Cloud VPN connection from the new VPC to the data center, and create a Cloud NAT instance to perform NAT on the overlapping IP space.
- C. Create a Cloud VPN connection from the new VPC to the data center, create a Cloud Router, and apply a custom route advertisement to block the overlapping IP space.
- D. Create a Cloud VPN connection from the new VPC to the data center, and apply a firewall rule that blocks the overlapping IP space.

Answer: A

Explanation:

To connect two networks together we need (1) either VPN or interconnect and (2) peering. When there is peering, you cannot have conflicting IP addresses. You can use either Cloud VPN or Cloud Interconnect to securely connect your on-premises network to your VPC network. (<https://cloud.google.com/vpc/docs/vpc-peering#transit-network>) At the time of peering, Google Cloud checks to see if there are any subnet IP ranges that overlap subnet IP ranges in the other network. If there is any overlap, peering is not established. (<https://cloud.google.com/vpc/docs/vpc-peering#considerations>) NAT is used to translate private to public IP and vice versa, however because we are connecting 2 networks together, they become private IPs. So it is not applicable.

NEW QUESTION 95

- (Exam Topic 5)

You want to make a copy of a production Linux virtual machine in the US-Central region. You want to manage and replace the copy easily if there are changes on the production virtual machine. You will deploy the copy as a new instances in a different project in the US-East region. What steps must you take?

- A. Use the Linux dd and netcat command to copy and stream the root disk contents to a new virtual machine instance in the US-East region.
- B. Create a snapshot of the root disk and select the snapshot as the root disk when you create a new virtual machine instance in the US-East region.
- C. Create an image file from the root disk with Linux dd command, create a new disk from the image file, and use it to create a new virtual machine instance in the US-East region
- D. Create a snapshot of the root disk, create an image file in Google Cloud Storage from the snapshot, and create a new virtual machine instance in the US-East region using the image file for the root disk.

Answer: D

Explanation:

<https://stackoverflow.com/questions/36441423/migrate-google-compute-engine-instance-to-a-different-region>

NEW QUESTION 96

- (Exam Topic 5)

Your company is running a stateless application on a Compute Engine instance. The application is used heavily during regular business hours and lightly outside of business hours. Users are reporting that the application is slow during peak hours. You need to optimize the application's performance. What should you do?

- A. Create a snapshot of the existing disk
- B. Create an instance template from the snapshot
- C. Create an autoscaled managed instance group from the instance template.
- D. Create a snapshot of the existing disk
- E. Create a custom image from the snapshot
- F. Create an autoscaled managed instance group from the custom image.
- G. Create a custom image from the existing disk
- H. Create an instance template from the custom image. Create an autoscaled managed instance group from the instance template.
- I. Create an instance template from the existing disk
- J. Create a custom image from the instance template. Create an autoscaled managed instance group from the custom image.

Answer: B

Explanation:

<https://cloud.google.com/compute/docs/instance-templates/create-instance-templates>

NEW QUESTION 100

- (Exam Topic 5)

You are building a continuous deployment pipeline for a project stored in a Git source repository and want to ensure that code changes can be verified deploying to production. What should you do?

- A. Use Spinnaker to deploy builds to production using the red/black deployment strategy so that changes can easily be rolled back.
- B. Use Spinnaker to deploy builds to production and run tests on production deployments.
- C. Use Jenkins to build the staging branches and the master branch
- D. Build and deploy changes to production for 10% of users before doing a complete rollout.
- E. Use Jenkins to monitor tags in the repository
- F. Deploy staging tags to a staging environment for testing. After testing, tag the repository for production and deploy that to the production environment.

Answer: D

Explanation:

Reference: <https://github.com/GoogleCloudPlatform/continuous-deployment-on-kubernetes/blob/master/README.md>

NEW QUESTION 105

- (Exam Topic 5)

Your company has just recently activated Cloud Identity to manage users. The Google Cloud Organization has been configured as well. The security team needs to secure protects that will be part of the Organization. They want to prohibit IAM users outside the domain from gaining permissions from now on. What should they do?

- A. Configure an organization policy to restrict identities by domain
- B. Configure an organization policy to block creation of service accounts
- C. Configure Cloud Scheduler to trigger a Cloud Function every hour that removes all users that don't belong to the Cloud identity domain from all projects.

Answer: A

NEW QUESTION 110

- (Exam Topic 5)

A development team at your company has created a dockerized HTTPS web application. You need to deploy the application on Google Kubernetes Engine (GKE) and make sure that the application scales automatically. How should you deploy to GKE?

- A. Use the Horizontal Pod Autoscaler and enable cluster autoscaling
- B. Use an Ingress resource to loadbalance the HTTPS traffic.
- C. Use the Horizontal Pod Autoscaler and enable cluster autoscaling on the Kubernetes cluster
- D. Use a Service resource of type LoadBalancer to load-balance the HTTPS traffic.
- E. Enable autoscaling on the Compute Engine instance group
- F. Use an Ingress resource to load balance the HTTPS traffic.
- G. Enable autoscaling on the Compute Engine instance group
- H. Use a Service resource of type LoadBalancer to load-balance the HTTPS traffic.

Answer: B

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/tutorials/http-balancer> <https://cloud.google.com/kubernetes-engine/docs/concepts/network-overview#ext-lb>

NEW QUESTION 115

- (Exam Topic 5)

Your solution is producing performance bugs in production that you did not see in staging and test environments. You want to adjust your test and deployment procedures to avoid this problem in the future. What should you do?

- A. Deploy fewer changes to production.
- B. Deploy smaller changes to production.
- C. Increase the load on your test and staging environments.
- D. Deploy changes to a small subset of users before rolling out to production.

Answer: C

NEW QUESTION 117

- (Exam Topic 5)

Your organization wants to control IAM policies for different departments independently, but centrally. Which approach should you take?

- A. Multiple Organizations with multiple Folders
- B. Multiple Organizations, one for each department
- C. A single Organization with Folder for each department
- D. A single Organization with multiple projects, each with a central owner

Answer: C

Explanation:

Folders are nodes in the Cloud Platform Resource Hierarchy. A folder can contain projects, other folders, or a combination of both. You can use folders to group projects under an organization in a hierarchy. For example, your organization might contain multiple departments, each with its own set of GCP resources. Folders allow you to group these resources on a per-department basis. Folders are used to group resources that share common IAM policies. While a folder can contain multiple folders or resources, a given folder or resource can have exactly one parent.

References: <https://cloud.google.com/resource-manager/docs/creating-managing-folders>

NEW QUESTION 121

- (Exam Topic 5)

Your marketing department wants to send out a promotional email campaign. The development team wants to minimize direct operation management. They project a wide range of possible customer responses, from 100 to 500,000 click-throughs per day. The link leads to a simple website that explains the promotion and collects user information and preferences. Which infrastructure should you recommend? (CHOOSE TWO)

- A. Use Google App Engine to serve the website and Google Cloud Datastore to store user data.
- B. Use a Google Container Engine cluster to serve the website and store data to persistent disk.
- C. Use a managed instance group to serve the website and Google Cloud Bigtable to store user data.
- D. Use a single compute Engine virtual machine (VM) to host a web server, backed by Google Cloud SQL.

Answer: AC

Explanation:

Reference: <https://cloud.google.com/storage-options/> References: <https://cloud.google.com/storage-options/>

NEW QUESTION 123

- (Exam Topic 5)

An application development team has come to you for advice. They are planning to write and deploy an HTTP(S) API using Go 1.12. The API will have a very unpredictable workload and must remain reliable during peaks in traffic. They want to minimize operational overhead for this application. What approach should you recommend?

- A. Use a Managed Instance Group when deploying to Compute Engine
- B. Develop an application with containers, and deploy to Google Kubernetes Engine (GKE)
- C. Develop the application for App Engine standard environment
- D. Develop the application for App Engine Flexible environment using a custom runtime

Answer: C

Explanation:

<https://cloud.google.com/appengine/docs/the-appengine-environments>

NEW QUESTION 124

- (Exam Topic 5)

Your company is developing a new application that will allow globally distributed users to upload pictures and share them with other selected users. The application will support millions of concurrent users. You want to allow developers to focus on just building code without having to create and maintain the underlying infrastructure. Which service should you use to deploy the application?

- A. App Engine
- B. Cloud Endpoints
- C. Compute Engine
- D. Google Kubernetes Engine

Answer: A

Explanation:

Reference: <https://cloud.google.com/terms/services> <https://cloud.google.com/appengine/docs/standard/go/how-requests-are-handled>

NEW QUESTION 126

- (Exam Topic 5)

The operations manager asks you for a list of recommended practices that she should consider when migrating a J2EE application to the cloud. Which three practices should you recommend? Choose 3 answers

- A. Port the application code to run on Google App Engine.
- B. Integrate Cloud Dataflow into the application to capture real-time metrics.
- C. Instrument the application with a monitoring tool like Stackdriver Debugger.
- D. Select an automation framework to reliably provision the cloud infrastructure.
- E. Deploy a continuous integration tool with automated testing in a staging environment.
- F. Migrate from MySQL to a managed NoSQL database like Google Cloud Datastore or Bigtable.

Answer: AEF

Explanation:

References: <https://cloud.google.com/appengine/docs/standard/java/tools/uploadinganapp> <https://cloud.google.com/appengine/docs/standard/java/building-app/cloud-sql>

NEW QUESTION 131

- (Exam Topic 5)

You are working at a sports association whose members range in age from 8 to 30. The association collects a large amount of health data, such as sustained injuries. You are storing this data in BigQuery. Current legislation requires you to delete such information upon request of the subject. You want to design a solution that can accommodate such a request. What should you do?

- A. Use a unique identifier for each individual
- B. Upon a deletion request, delete all rows from BigQuery with this identifier.
- C. When ingesting new data in BigQuery, run the data through the Data Loss Prevention (DLP) API to identify any personal information
- D. As part of the DLP scan, save the result to Data Catalog
- E. Upon a deletion request, query Data Catalog to find the column with personal information.
- F. Create a BigQuery view over the table that contains all data

- G. Upon a deletion request, exclude the rows that affect the subject's data from this view
- H. Use this view instead of the source table for all analysis tasks.
- I. Use a unique identifier for each individual
- J. Upon a deletion request, overwrite the column with the unique identifier with a salted SHA256 of its value.

Answer: B

Explanation:

Current legislation requires you to delete "SUCH" information upon request of the subject. " So from that point of view the question is not to delete the entire user records but specific data related to personal health data. With DLP you can use InfoTypes and InfoType detectors to specifically scan for those entries and how to act upon them (link <https://cloud.google.com/dlp/docs/concepts-infotypes>)
<https://cloud.google.com/dlp#section-6>

NEW QUESTION 132

- (Exam Topic 5)

Your company has an application running on a deployment in a GKE cluster. You have a separate cluster for development, staging and production. You have discovered that the team is able to deploy a Docker image to the production cluster without first testing the deployment in development and then staging. You want to allow the team to have autonomy but want to prevent this from happening. You want a Google Cloud solution that can be implemented quickly with minimal effort. What should you do?

- A. Create a Kubernetes admission controller to prevent the container from starting if it is not approved for usage in the given environment
- B. Configure a Kubernetes lifecycle hook to prevent the container from starting if it is not approved for usage in the given environment
- C. Implement a corporate policy to prevent teams from deploying Docker image to an environment unless the Docker image was tested in an earlier environment
- D. Configure the binary authorization policies for the development, staging and production cluster
- E. Create attestations as part of the continuous integration pipeline"

Answer: D

Explanation:

<https://cloud.google.com/architecture/prep-kubernetes-engine-for-prod#binary-authorization>

The most common Binary Authorization use cases involve attestations. An attestation certifies that a specific image has completed a previous stage, as described previously. You configure the Binary Authorization policy to verify the attestation before allowing the image to be deployed. At deploy time, instead of redoing activities that were completed in earlier stages, Binary Authorization only needs to verify the attestation. <https://cloud.google.com/binary-authorization/docs/overview>

NEW QUESTION 133

- (Exam Topic 5)

You need to develop procedures to verify resilience of disaster recovery for remote recovery using GCP. Your production environment is hosted on-premises. You need to establish a secure, redundant connection between your on premises network and the GCP network. What should you do?

- A. Verify that Dedicated Interconnect can replicate files to GC
- B. Verify that direct peering can establish a secure connection between your networks if Dedicated Interconnect fails.
- C. Verify that Dedicated Interconnect can replicate files to GC
- D. Verify that Cloud VPN can establish a secure connection between your networks if Dedicated Interconnect fails.
- E. Verify that the Transfer Appliance can replicate files to GC
- F. Verify that direct peering can establish a secure connection between your networks if the Transfer Appliance fails.
- G. Verify that the Transfer Appliance can replicate files to GC
- H. Verify that Cloud VPN can establish a secure connection between your networks if the Transfer Appliance fails.

Answer: B

Explanation:

<https://cloud.google.com/interconnect/docs/how-to/direct-peering>

NEW QUESTION 135

- (Exam Topic 5)

Your company captures all web traffic data in Google Analytics 260 and stores it in BigQuery. Each country has its own dataset. Each dataset has multiple tables. You want analysts from each country to be able to see and query only the data for their respective countries. How should you configure the access rights?

- A. Create a group per country
- B. Add analysts to their respective country-group
- C. Create a single group 'all_analysts', and add all country-groups as member
- D. Grant the 'all-analysis' group the IAM role of BigQuery jobUser
- E. Share the appropriate dataset with view access with each respective analyst country-group.
- F. Create a group per country
- G. Add analysts to their respective country-group
- H. Create a single group 'all_analysts', and add all country-groups as member
- I. Grant the 'all-analysis' group the IAM role of BigQuery jobUser
- J. Share the appropriate tables with view access with each respective analyst countrygroup.
- K. Create a group per country
- L. Add analysts to their respective country-group
- M. Create a single group 'all_analysts', and add all country-groups as member
- N. Grant the 'all-analysis' group the IAM role of BigQuery dataViewer
- O. Share the appropriate dataset with view access with each respective analyst country-group.
- P. Create a group per country
- Q. Add analysts to their respective country-group
- R. Create a single group 'all_analysts', and add all country-groups as member
- S. Grant the 'all-analysis' group the IAM role of BigQuery dataViewer

T. Share the appropriate table with view access with each respective analyst countrygroup.

Answer: A

NEW QUESTION 136

- (Exam Topic 5)

You are moving an application that uses MySQL from on-premises to Google Cloud. The application will run on Compute Engine and will use Cloud SQL. You want to cut over to the Compute Engine deployment of the application with minimal downtime and no data loss to your customers. You want to migrate the application with minimal modification. You also need to determine the cutover strategy. What should you do?

- A. * 1. Set up Cloud VPN to provide private network connectivity between the Compute Engine application and the on-premises MySQL server.* 2. Stop the on-premises application.* 3. Create a mysqldump of the on-premises MySQL serve
- B. * 4.Upload the dump to a Cloud Storage bucket.* 5. Import the dump into Cloud SQL.* 6. Modify the source code of the application to write queries to both databases and read from its local database.* 7. Start the Compute Engine applicatio
- C. 8.Stop the on-premises application.
- D. * 1. Set up Cloud SQL proxy and MySQL proxy.* 2. Create a mysqldump of the on-premises MySQL serve
- E. * 3. Upload the dump to a Cloud Storage bucket.* 4. Import the dump into Cloud SQ
- F. * 5. Stop the on-premises applicatio
- G. * 6. Start the Compute Engine application.
- H. * 1. Set up Cloud VPN to provide private network connectivity between the Compute Engine applicationand the on-premises MySQL serve
- I. * 2. Stop the on-premises application.* 3. Start the Compute Engine application, configured to read and write to the on-premises MySQL serve
- J. * 4. Create the replication configuration in Cloud SQL.* 5. Configure the source database server to accept connections from the Cloud SQL replic
- K. * 6. Finalize the Cloud SQL replica configuration.* 7. When replication has been completed, stop the Compute Engine applicatio
- L. * 8. Promote the Cloud SQL replica to a standalone instance.* 9. Restart the Compute Engine application, configured to read and write to the Cloud SQL standalone instance.
- M. * 1. Stop the on-premises application.* 2. Create a mysqldump of the on-premises MySQL serve
- N. * 3. Upload the dump to a Cloud Storage bucket.* 4. Import the dump into Cloud SQL.* 5. Start the application on Compute Engine.

Answer: C

Explanation:

External replica promotion migration In the migration strategy of external replica promotion, you create an external database replica and synchronize the existing data to that replica. This can happen with minimal downtime to the existing database. When you have a replica database, the two databases have different roles that are referred to in this document as primary and replica. After the data is synchronized, you promote the replica to be the primary in order to move the management layer with minimal impact to database uptime. In Cloud SQL, an easy way to accomplish the external replica promotion is to use the automated migration workflow. This process automates many of the steps that are needed for this type of migration.

<https://cloud.google.com/architecture/migrating-mysql-to-cloudsql-concept>

- The best option for migrating your MySQL database is to use an external replica promotion. In this strategy, you create a replica database and set your existing database as the primary. You wait until the two databases are in sync, and you then promote your MySQL replica database to be the primary. This process minimizes database downtime related to the database migration. https://cloud.google.com/architecture/migrating-mysql-to-cloudsql-concept#external_replica_promotion_migrat

NEW QUESTION 139

- (Exam Topic 5)

An application development team believes their current logging tool will not meet their needs for their new cloud-based product. They want a better tool to capture errors and help them analyze their historical log data. You want to help them find a solution that meets their needs, what should you do?

- A. Direct them to download and install the Google StackDriver logging agent.
- B. Send them a list of online resources about logging best practices.
- C. Help them define their requirements and assess viable logging tools.
- D. Help them upgrade their current tool to take advantage of any new features.

Answer: C

Explanation:

Help them define their requirements and assess viable logging tools. They know the requirements and the existing tools' problems. While it's true StackDriver Logging and Error Reporting possibly meet all their requirements, there might be other tools also meet their need. They need you to provide expertise to make assessment for new tools, specifically, logging tools that can "capture errors and help them analyze their historical log data".

References: <https://cloud.google.com/logging/docs/agent/installation>

NEW QUESTION 143

- (Exam Topic 5)

You want to establish a Compute Engine application in a single VPC across two regions. The application must communicate over VPN to an on-premises network. How should you deploy the VPN?

- A. Use VPC Network Peering between the VPC and the on-premises network.
- B. Expose the VPC to the on-premises network using IAM and VPC Sharing.
- C. Create a global Cloud VPN Gateway with VPN tunnels from each region to the on-premises peer gateway.
- D. Deploy Cloud VPN Gateway in each regio
- E. Ensure that each region has at least one VPN tunnel to the on-premises peer gateway.

Answer: C

Explanation:

<https://cloud.google.com/vpn/docs/how-to/creating-static-vpns>

NEW QUESTION 147

- (Exam Topic 5)

Your company recently acquired a company that has infrastructure in Google Cloud. Each company has its own Google Cloud organization Each company is using

a Shared Virtual Private Cloud (VPC) to provide network connectivity for its applications. Some of the subnets used by both companies overlap. In order for both businesses to integrate, the applications need to have private network connectivity. These applications are not on overlapping subnets. You want to provide connectivity with minimal re-engineering. What should you do?

- A. Set up VPC peering and peer each Shared VPC together
- B. Configure SSH port forwarding on each application to provide connectivity between applications in the different Shared VPCs
- C. Migrate the protects from the acquired company into your company's Google Cloud organization. Re-launch the instances in your company's Shared VPC
- D. Set up a Cloud VPN gateway in each Shared VPC and peer Cloud VPNs

Answer: B

NEW QUESTION 152

- (Exam Topic 5)

Your company provides a recommendation engine for retail customers. You are providing retail customers with an API where they can submit a user ID and the API returns a list of recommendations for that user. You are responsible for the API lifecycle and want to ensure stability for your customers in case the API makes backward-incompatible changes. You want to follow Google-recommended practices. What should you do?

- A. Create a distribution list of all customers to inform them of an upcoming backward-incompatible change at least one month before replacing the old API with the new API.
- B. Create an automated process to generate API documentation, and update the public API documentation as part of the CI/CD process when deploying an update to the API.
- C. Use a versioning strategy for the APIs that increases the version number on every backward-incompatible change.
- D. Use a versioning strategy for the APIs that adds the suffix "DEPRECATED" to the current API version number on every backward-incompatible change.
- E. Use the current version number for the new API.

Answer: C

Explanation:

<https://cloud.google.com/apis/design/versioning>

All Google API interfaces must provide a major version number, which is encoded at the end of the protobuf package, and included as the first part of the URI path for REST APIs. If an API introduces a breaking change, such as removing or renaming a field, it must increment its API version number to ensure that existing user code does not suddenly break.

NEW QUESTION 155

- (Exam Topic 5)

You want to optimize the performance of an accurate, real-time, weather-charting application. The data comes from 50,000 sensors sending 10 readings a second, in the format of a timestamp and sensor reading. Where should you store the data?

- A. Google BigQuery
- B. Google Cloud SQL
- C. Google Cloud Bigtable
- D. Google Cloud Storage

Answer: C

Explanation:

It is time-series data, So Big Table. <https://cloud.google.com/bigtable/docs/schema-design-time-series>

Google Cloud Bigtable is a scalable, fully-managed NoSQL wide-column database that is suitable for both real-time access and analytics workloads. Good for:

- Low-latency read/write access
- High-throughput analytics
- Native time series support
- Common workloads:
- IoT, finance, adtech
- Personalization, recommendations
- Monitoring
- Geospatial datasets
- Graphs

References: <https://cloud.google.com/storage-options/>

NEW QUESTION 159

- (Exam Topic 5)

You have developed a non-critical update to your application that is running in a managed instance group, and have created a new instance template with the update that you want to release. To prevent any possible impact to the application, you don't want to update any running instances. You want any new instances that are created by the managed instance group to contain the new update. What should you do?

- A. Start a new rolling restart operation.
- B. Start a new rolling replace operation.
- C. Start a new rolling update.
- D. Select the Proactive update mode.
- E. Start a new rolling update.
- F. Select the Opportunistic update mode.

Answer: D

Explanation:

In certain scenarios, an opportunistic update is useful because you don't want to cause instability to the system if it can be avoided. For example, if you have a non-

critical update that can be applied as necessary without any urgency and you have a MIG that is actively being autoscaled, perform an opportunistic update so that Compute Engine does not actively tear down your existing instances to apply the update. When resizing down, the autoscaler preferentially terminates instances with the old template as well as instances that are not yet in a RUNNING state.

NEW QUESTION 162

- (Exam Topic 5)

You are migrating your on-premises solution to Google Cloud in several phases. You will use Cloud VPN to maintain a connection between your on-premises systems and Google Cloud until the migration is completed.

You want to make sure all your on-premises systems remain reachable during this period. How should you organize your networking in Google Cloud?

- A. Use the same IP range on Google Cloud as you use on-premises
- B. Use the same IP range on Google Cloud as you use on-premises for your primary IP range and use a secondary range that does not overlap with the range you use on-premises
- C. Use an IP range on Google Cloud that does not overlap with the range you use on-premises
- D. Use an IP range on Google Cloud that does not overlap with the range you use on-premises for your primary IP range and use a secondary range with the same IP range as you use on-premises

Answer: C

NEW QUESTION 167

- (Exam Topic 6)

For this question, refer to the Dress4Win case study. Which of the compute services should be migrated as –is and would still be an optimized architecture for performance in the cloud?

- A. Web applications deployed using App Engine standard environment
- B. RabbitMQ deployed using an unmanaged instance group
- C. Hadoop/Spark deployed using Cloud Dataproc Regional in High Availability mode
- D. Jenkins, monitoring, bastion hosts, security scanners services deployed on custom machine types

Answer: C

NEW QUESTION 169

- (Exam Topic 7)

For this question, refer to the TerramEarth case study. Considering the technical requirements, how should you reduce the unplanned vehicle downtime in GCP?

- A. Use BigQuery as the data warehouse
- B. Connect all vehicles to the network and stream data into BigQuery using Cloud Pub/Sub and Cloud Dataflow
- C. Use Google Data Studio for analysis and reporting.
- D. Use BigQuery as the data warehouse
- E. Connect all vehicles to the network and upload gzip files to a Multi-Regional Cloud Storage bucket using gcloud
- F. Use Google Data Studio for analysis and reporting.
- G. Use Cloud Dataproc Hive as the data warehouse
- H. Upload gzip files to a MultiRegional Cloud Storage bucket
- I. Upload this data into BigQuery using gcloud
- J. Use Google data Studio for analysis and reporting.
- K. Use Cloud Dataproc Hive as the data warehouse
- L. Directly stream data into partitioned Hive table
- M. Use Pig scripts to analyze data.

Answer: A

NEW QUESTION 171

- (Exam Topic 7)

TerramEarth has a legacy web application that you cannot migrate to cloud. However, you still want to build a cloud-native way to monitor the application. If the application goes down, you want the URL to point to a "Site is unavailable" page as soon as possible. You also want your Ops team to receive a notification for the issue. You need to build a reliable solution for minimum cost

What should you do?

- A. Create a scheduled job in Cloud Run to invoke a container every minute
- B. The container will check the application URL. If the application is down, switch the URL to the "Site is unavailable" page, and notify the Ops team.
- C. Create a cron job on a Compute Engine VM that runs every minute
- D. The cron job invokes a Python program to check the application URL. If the application is down, switch the URL to the "Site is unavailable" page, and notify the Ops team.
- E. Create a Cloud Monitoring uptime check to validate the application URL. If it fails, put a message in a Pub/Sub queue that triggers a Cloud Function to switch the URL to the "Site is unavailable" page, and notify the Ops team.
- F. Use Cloud Error Reporting to check the application URL. If the application is down, switch the URL to the "Site is unavailable" page, and notify the Ops team.

Answer: C

Explanation:

<https://cloud.google.com/blog/products/management-tools/how-to-use-pubsub-as-a-cloud-monitoring-notification>

NEW QUESTION 172

- (Exam Topic 7)

For this question, refer to the TerramEarth case study. A new architecture that writes all incoming data to BigQuery has been introduced. You notice that the data is dirty, and want to ensure data quality on an automated daily basis while managing cost.

What should you do?

- A. Set up a streaming Cloud Dataflow job, receiving data by the ingestion proces
- B. Clean the data in a Cloud Dataflow pipeline.
- C. Create a Cloud Function that reads data from BigQuery and cleans i
- D. Trigger i
- E. Trigger the Cloud Function from a Compute Engine instance.
- F. Create a SQL statement on the data in BigQuery, and save it as a vie
- G. Run the view daily, and save the result to a new table.
- H. Use Cloud Dataprep and configure the BigQuery tables as the sourc
- I. Schedule a daily job to clean the data.

Answer: A

NEW QUESTION 173

- (Exam Topic 7)

You have broken down a legacy monolithic application into a few containerized RESTful microservices. You want to run those microservices on Cloud Run. You also want to make sure the services are highly available with low latency to your customers. What should you do?

- A. Deploy Cloud Run services to multiple availability zone
- B. Create Cloud Endpoints that point to the service
- C. Create a global HTIP(S) Load Balancing instance and attach the Cloud Endpoints to its backend.
- D. Deploy Cloud Run services to multiple regions Create serverless network endpoint groups pointing to the service
- E. Add the serverless NE Gs to a backend service that is used by a global HTIP(S) Load Balancing instance.
- F. Cloud Run services to multiple region
- G. In Cloud DNS, create a latency-based DNS name that points to the services.
- H. Deploy Cloud Run services to multiple availability zone
- I. Create a TCP/IP global load balance
- J. Add the Cloud Run Endpoints to its backend service.

Answer: B

Explanation:

<https://cloud.google.com/run/docs/multiple-regions>

NEW QUESTION 176

- (Exam Topic 7)

For this question, refer to the TerramEarth case study. To be compliant with European GDPR regulation, TerramEarth is required to delete data generated from its European customers after a period of 36 months when it contains personal data. In the new architecture, this data will be stored in both Cloud Storage and BigQuery. What should you do?

- A. Create a BigQuery table for the European data, and set the table retention period to 36 month
- B. For Cloud Storage, use gsutil to enable lifecycle management using a DELETE action with an Age condition of 36 months.
- C. Create a BigQuery table for the European data, and set the table retention period to 36 month
- D. For Cloud Storage, use gsutil to create a SetStorageClass to NONE action when with an Age condition of 36 months.
- E. Create a BigQuery time-partitioned table for the European data, and set the partition expiration period to 36 month
- F. For Cloud Storage, use gsutil to enable lifecycle management using a DELETE action with an Age condition of 36 months.
- G. Create a BigQuery time-partitioned table for the European data, and set the partition period to 36 month
- H. For Cloud Storage, use gsutil to create a SetStorageClass to NONE action with an Age condition of 36 months.

Answer: C

Explanation:

<https://cloud.google.com/bigquery/docs/managing-partitioned-tables#partition-expiration> <https://cloud.google.com/storage/docs/lifecycle>

NEW QUESTION 181

- (Exam Topic 8)

For this question, refer to the Mountkirk Games case study. You are in charge of the new Game Backend Platform architecture. The game communicates with the backend over a REST API.

You want to follow Google-recommended practices. How should you design the backend?

- A. Create an instance template for the backen
- B. For every region, deploy it on a multi-zone managed instance grou
- C. Use an L4 load balancer.
- D. Create an instance template for the backen
- E. For every region, deploy it on a single-zone managed instance grou
- F. Use an L4 load balancer.
- G. Create an instance template for the backen
- H. For every region, deploy it on a multi-zone managed instance grou
- I. Use an L7 load balancer.
- J. Create an instance template for the backen
- K. For every region, deploy it on a single-zone managed instance grou
- L. Use an L7 load balancer.

Answer: C

Explanation:

https://cloud.google.com/solutions/gaming/cloud-game-infrastructure#dedicated_game_server

NEW QUESTION 184

- (Exam Topic 8)

For this question, refer to the Mountkirk Games case study. Mountkirk Games wants you to design a way to test the analytics platform's resilience to changes in mobile network latency. What should you do?

- A. Deploy failure injection software to the game analytics platform that can inject additional latency to mobile client analytics traffic.
- B. Build a test client that can be run from a mobile phone emulator on a Compute Engine virtual machine, and run multiple copies in Google Cloud Platform regions all over the world to generate realistic traffic.
- C. Add the ability to introduce a random amount of delay before beginning to process analytics files uploaded from mobile devices.
- D. Create an opt-in beta of the game that runs on players' mobile devices and collects response times from analytics endpoints running in Google Cloud Platform regions all over the world.

Answer: D

NEW QUESTION 185

- (Exam Topic 8)

For this question, refer to the Mountkirk Games case study. Mountkirk Games wants to migrate from their current analytics and statistics reporting model to one that meets their technical requirements on Google Cloud Platform.

Which two steps should be part of their migration plan? (Choose two.)

- A. Evaluate the impact of migrating their current batch ETL code to Cloud Dataflow.
- B. Write a schema migration plan to denormalize data for better performance in BigQuery.
- C. Draw an architecture diagram that shows how to move from a single MySQL database to a MySQL cluster.
- D. Load 10 TB of analytics data from a previous game into a Cloud SQL instance, and run test queries against the full dataset to confirm that they complete successfully.
- E. Integrate Cloud Armor to defend against possible SQL injection attacks in analytics files uploaded to Cloud Storage.

Answer: AB

Explanation:

https://cloud.google.com/bigquery/docs/loading-data#loading_denormalized_nested_and_repeated_data

NEW QUESTION 188

- (Exam Topic 8)

Your development teams release new versions of games running on Google Kubernetes Engine (GKE) daily. You want to create service level indicators (SLIs) to evaluate the quality of the new versions from the user's perspective. What should you do?

- A. Create CPU Utilization and Request Latency as service level indicators.
- B. Create GKE CPU Utilization and Memory Utilization as service level indicators.
- C. Create Request Latency and Error Rate as service level indicators.
- D. Create Server Uptime and Error Rate as service level indicators.

Answer: C

NEW QUESTION 189

- (Exam Topic 8)

For this question, refer to the Mountkirk Games case study. Mountkirk Games wants to design their solution for the future in order to take advantage of cloud and technology improvements as they become available. Which two steps should they take? (Choose two.)

- A. Store as much analytics and game activity data as financially feasible today so it can be used to train machine learning models to predict user behavior in the future.
- B. Begin packaging their game backend artifacts in container images and running them on Kubernetes Engine to improve the availability to scale up or down based on game activity.
- C. Set up a CI/CD pipeline using Jenkins and Spinnaker to automate canary deployments and improve development velocity.
- D. Adopt a schema versioning tool to reduce downtime when adding new game features that require storing additional player data in the database.
- E. Implement a weekly rolling maintenance process for the Linux virtual machines so they can apply critical kernel patches and package updates and reduce the risk of 0-day vulnerabilities.

Answer: BC

NEW QUESTION 190

- (Exam Topic 8)

Mountkirk Games wants to limit the physical location of resources to their operating Google Cloud regions. What should you do?

- A. Configure an organizational policy which constrains where resources can be deployed.
- B. Configure IAM conditions to limit what resources can be configured.
- C. Configure the quotas for resources in the regions not being used to 0.
- D. Configure a custom alert in Cloud Monitoring so you can disable resources as they are created in other regions.

Answer: A

NEW QUESTION 194

- (Exam Topic 8)

Mountkirk Games wants you to secure the connectivity from the new gaming application platform to Google Cloud. You want to streamline the process and follow Google-recommended practices. What should you do?

- A. Configure Workload Identity and service accounts to be used by the application platform.
- B. Use Kubernetes Secrets, which are obfuscated by default
- C. Configure these Secrets to be used by the application platform.
- D. Configure Kubernetes Secrets to store the secret, enable Application-Layer Secrets Encryption, and use Cloud Key Management Service (Cloud KMS) to

manage the encryption key

E. Configure these Secrets to be used by the application platform.

F. Configure HashiCorp Vault on Compute Engine, and use customer managed encryption keys and Cloud Key Management Service (Cloud KMS) to manage the encryption key

G. Configure these Secrets to be used by the application platform.

Answer: A

NEW QUESTION 197

- (Exam Topic 10)

For this question, refer to the EHR Healthcare case study. You are responsible for ensuring that EHR's use of Google Cloud will pass an upcoming privacy compliance audit. What should you do? (Choose two.)

A. Verify EHR's product usage against the list of compliant products on the Google Cloud compliance page.

B. Advise EHR to execute a Business Associate Agreement (BAA) with Google Cloud.

C. Use Firebase Authentication for EHR's user facing applications.

D. Implement Prometheus to detect and prevent security breaches on EHR's web-based applications.

E. Use GKE private clusters for all Kubernetes workloads.

Answer: AB

Explanation:

<https://cloud.google.com/security/compliance/hipaa>

NEW QUESTION 201

- (Exam Topic 10)

For this question, refer to the EHR Healthcare case study. You need to define the technical architecture for securely deploying workloads to Google Cloud. You also need to ensure that only verified containers are deployed using Google Cloud services. What should you do? (Choose two.)

A. Enable Binary Authorization on GKE, and sign containers as part of a CI/CD pipeline.

B. Configure Jenkins to utilize Kritis to cryptographically sign a container as part of a CI/CD pipeline.

C. Configure Container Registry to only allow trusted service accounts to create and deploy containers from the registry.

D. Configure Container Registry to use vulnerability scanning to confirm that there are no vulnerabilities before deploying the workload.

Answer: A

Explanation:

Binary Authorization to ensure only verified containers are deployed To ensure deployment are secure and and consistent, automatically scan images for vulnerabilities with container analysis (https://cloud.google.com/docs/ci-cd/overview?hl=en&skip_cache=true)

NEW QUESTION 202

- (Exam Topic 10)

For this question, refer to the EHR Healthcare case study. You are responsible for designing the Google Cloud network architecture for Google Kubernetes Engine. You want to follow Google best practices. Considering the EHR Healthcare business and technical requirements, what should you do to reduce the attack surface?

A. Use a private cluster with a private endpoint with master authorized networks configured.

B. Use a public cluster with firewall rules and Virtual Private Cloud (VPC) routes.

C. Use a private cluster with a public endpoint with master authorized networks configured.

D. Use a public cluster with master authorized networks enabled and firewall rules.

Answer: A

Explanation:

<https://cloud.google.com/kubernetes-engine/docs/concepts/private-cluster-concept#overview>

NEW QUESTION 204

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

Professional-Cloud-Architect Practice Exam Features:

- * Professional-Cloud-Architect Questions and Answers Updated Frequently
- * Professional-Cloud-Architect Practice Questions Verified by Expert Senior Certified Staff
- * Professional-Cloud-Architect Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * Professional-Cloud-Architect Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The Professional-Cloud-Architect Practice Test Here](#)