



Amazon

Exam Questions AWS-SysOps

Amazon AWS Certified SysOps Administrator - Associate

NEW QUESTION 1

- (Topic 1)

Your team is excited about the use of AWS because now they have access to programmable Infrastructure. You have been asked to manage your AWS infrastructure in a manner similar to the way you might manage application code. You want to be able to deploy exact copies of different versions of your infrastructure, stage changes into different environments, revert back to previous versions, and identify what versions are running at any particular time (development, test, QA, production).

Which approach addresses this requirement?

- A. Use cost allocation reports and AWS OpsWorks to deploy and manage your infrastructure
- B. Use AWS CloudWatch metrics and alerts along with resource tagging to deploy and manage your infrastructure
- C. Use AWS Beanstalk and a version control system like GIT to deploy and manage your infrastructure
- D. Use AWS CloudFormation and a version control system like GIT to deploy and manage your infrastructure

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/opsworks/faqs/>

NEW QUESTION 2

- (Topic 1)

A media company produces new video files on-premises every day with a total size of around 100GBs after compression. All files have a size of 1-2 GB and need to be uploaded to Amazon S3 every night in a fixed time window between 3am and 5am. Current upload takes almost 3 hours, although less than half of the available bandwidth is used.

What step(s) would ensure that the file uploads are able to complete in the allotted time window?

- A. Increase your network bandwidth to provide faster throughput to S3
- B. Upload the files in parallel to S3
- C. Pack all files into a single archive, upload it to S3, then extract the files in AWS
- D. Use AWS Import/Export to transfer the video files

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/importexport/faqs/>

NEW QUESTION 3

- (Topic 1)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB instance is switched to the standby DB instance
- B. The RDS (Relational Database Service) DB instance reboots
- C. A new DB instance is created in the standby availability zone
- D. The canonical name record (CNAME) is changed from primary to standby

Answer: D

NEW QUESTION 4

- (Topic 1)

How can the domain's zone apex for example "myzoneapexdomain.com" be pointed towards an Elastic Load Balancer?

- A. By using an AAAA record
- B. By using an A record
- C. By using an Amazon Route 53 CNAME record
- D. By using an Amazon Route 53 Alias record

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/resource-record-sets-choosing-alias-non-alias.html>

NEW QUESTION 5

- (Topic 1)

You are tasked with setting up a cluster of EC2 Instances for a NoSQL database. The database requires random read IO disk performance up to a 100,000 IOPS at 4KB block size per node.

Which of the following EC2 instances will perform the best for this workload?

- A. A High-Memory Quadruple Extra Large (m2.4xlarge) with EBS-Optimized set to true and a Provisioned IOPS EBS volume
- B. A Cluster Compute Eight Extra Large (cc2.8xlarge) using instance storage
- C. High I/O Quadruple Extra Large (hi1.4xlarge) using instance storage
- D. A Cluster GPU Quadruple Extra Large (cg1.4xlarge) using four separate 4000 PIOPS EBS volumes in a RAID 0 configuration

Answer: C

Explanation:

Explanation: Reference:
<http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 6

- (Topic 1)

You use S3 to store critical data for your company. Several users within your group currently have full permissions to your S3 buckets. You need to come up with a solution that does not impact your users and also protect against the accidental deletion of objects.

Which two options will address this issue? Choose 2 answers

- A. Enable versioning on your S3 Buckets
- B. Configure your S3 Buckets with MFA delete
- C. Create a Bucket policy and only allow read only permissions to all users at the bucket level
- D. Enable object life cycle policies and configure the data older than 3 months to be archived in Glacier

Answer: AB

NEW QUESTION 7

- (Topic 1)

You have been asked to leverage Amazon VPC, EC2, and SQS to implement an application that submits and receives millions of messages per second to a message queue. You want to ensure your application has sufficient bandwidth between your EC2 instances and SQS. Which option will provide the most scalable solution for communicating between the application and SQS?

- A. Ensure the application instances are properly configured with an Elastic Load Balancer
- B. Ensure the application instances are launched in private subnets with the EBS-optimized option enabled
- C. Ensure the application instances are launched in public subnets with the `associate-public-IP-address=true` option enabled
- D. Launch application instances in private subnets with an Auto Scaling group and Auto Scaling triggers configured to watch the SQS queue size

Answer: B

Explanation:

Reference:
<http://www.cardinalpath.com/autoscaling-your-website-with-amazon-web-services-part-2/>

NEW QUESTION 8

- (Topic 1)

You have a web-style application with a stateless but CPU and memory-intensive web tier running on a `cc2.8xlarge` EC2 instance inside of a VPC. The instance when under load is having problems returning requests within the SLA as defined by your business. The application maintains its state in a DynamoDB table, but the data tier is properly provisioned and responses are consistently fast.

How can you best resolve the issue of the application responses not meeting your SLA?

- A. Add another `cc2.8xlarge` application instance, and put both behind an Elastic Load Balancer
- B. Move the `cc2.8xlarge` to the same Availability Zone as the DynamoDB table
- C. Cache the database responses in ElastiCache for more rapid access
- D. Move the database from DynamoDB to RDS MySQL in scale-out read-replica configuration

Answer: B

Explanation:

Reference:
<http://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 9

- (Topic 1)

You have set up Individual AWS accounts for each project. You have been asked to make sure your AWS Infrastructure costs do not exceed the budget set per project for each month.

Which of the following approaches can help ensure that you do not exceed the budget each month?

- A. Consolidate your accounts so you have a single bill for all accounts and projects
- B. Set up auto scaling with CloudWatch alarms using SNS to notify you when you are running too many Instances in a given account
- C. Set up CloudWatch billing alerts for all AWS resources used by each project, with a notification occurring when the amount for each resource tagged to a particular project matches the budget allocated to the project
- D. Set up CloudWatch billing alerts for all AWS resources used by each account, with email notifications when it hits 50%, 80% and 90% of its budgeted monthly spend

Answer: C

NEW QUESTION 10

- (Topic 1)

You run a web application where web servers on EC2 Instances are in an Auto Scaling group. Monitoring over the last 6 months shows that 6 web servers are necessary to handle the minimum load. During the day up to 12 servers are needed. Five to six days per year, the number of web servers required might go up to 15.

What would you recommend to minimize costs while being able to provide high availability?

- A. 6 Reserved instances (heavy utilization), 6 Reserved instances (medium utilization), rest covered by On-Demand instances
- B. 6 Reserved instances (heavy utilization), 6 On-Demand instances, rest covered by Spot Instances
- C. 6 Reserved instances (heavy utilization), 6 Spot instances, rest covered by On-Demand instances
- D. 6 Reserved instances (heavy utilization), 6 Reserved instances (medium utilization), rest covered by Spot instances

Answer: B

NEW QUESTION 10

- (Topic 1)

You have a web application leveraging an Elastic Load Balancer (ELB) In front of the web servers deployed using an Auto Scaling Group Your database is running on Relational

Database Service (RDS) The application serves out technical articles and responses to them in general there are more views of an article than there are responses to the article. On occasion, an article on the site becomes extremely popular resulting in significant traffic Increases that causes the site to go down.

What could you do to help alleviate the pressure on the infrastructure while maintaining availability during these events?

Choose 3 answers

- A. Leverage CloudFront for the delivery of the article
- B. Add RDS read-replicas for the read traffic going to your relational database
- C. Leverage ElastiCache for caching the most frequently used dat
- D. Use SOS to queue up the requests for the technical posts and deliver them out of the queu
- E. Use Route53 health checks to fail over to an S3 bucket for an error pag

Answer: ACE

NEW QUESTION 14

- (Topic 1)

You are tasked with the migration of a highly trafficked Node JS application to AWS In order to comply with organizational standards Chef recipes must be used to configure the application servers that host this application and to support application lifecycle events.

Which deployment option meets these requirements while minimizing administrative burden?

- A. Create a new stack within Opsworks add the appropriate layers to the stack and deploy the application
- B. Create a new application within Elastic Beanstalk and deploy this application to a new environment
- C. Launch a Mode JS server from a community AMI and manually deploy the application to the launched EC2 instance
- D. Launch and configure Chef Server on an EC2 instance and leverage the AWS CLI to launch application servers and configure those instances using Che

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.html>

NEW QUESTION 16

- (Topic 1)

You are running a database on an EC2 instance, with the data stored on Elastic Block Store (EBS) for persistence At times throughout the day, you are seeing large variance in the response times of the database queries Looking into the instance with the isolate command you see a lot of wait time on the disk volume that the database's data is stored on.

What two ways can you improve the performance of the database's storage while maintaining the current persistence of the data?

Choose 2 answers

- A. Move to an SSD backed instance
- B. Move the database to an EBS-Optimized Instance
- C. T Use Provisioned IOPs EBS
- D. Use the ephemeral storage on an m2 4xlarge Instance Instead

Answer: AB

NEW QUESTION 19

- (Topic 1)

Which of the following requires a custom CloudWatch metric to monitor?

- A. Data transfer of an EC2 instance
- B. Disk usage activity of an EC2 instance
- C. Memory Utilization of an EC2 instance
- D. CPU Utilization of an EC2 instance

Answer: C

Explanation:

Reference:

<http://aws.amazon.com/cloudwatch/>

NEW QUESTION 22

- (Topic 1)

When an EC2 EBS-backed (EBS root) instance is stopped, what happens to the data on any ephemeral store volumes?

- A. Data will be deleted and win no longer be accessible
- B. Data is automatically saved in an EBS volum
- C. Data is automatically saved as an EBS snapshot
- D. Data is unavailable until the instance is restarted

Answer: D

NEW QUESTION 27

- (Topic 1)

Your application currently leverages AWS Auto Scaling to grow and shrink as load increases/ decreases and has been performing well. Your marketing team expects a steady ramp up in traffic to follow an upcoming campaign that will result in a 20x growth in traffic over 4 weeks. Your forecast for the approximate number of Amazon EC2 instances necessary to meet the peak demand is 175.

What should you do to avoid potential service disruptions during the ramp up in traffic?

- A. Ensure that you have pre-allocated 175 Elastic IP addresses so that each server will be able to obtain one as it launches
- B. Check the service limits in Trusted Advisor and adjust as necessary so the forecasted count remains within limit
- C. Change your Auto Scaling configuration to set a desired capacity of 175 prior to the launch of the marketing campaign
- D. Pre-warm your Elastic Load Balancer to match the requests per second anticipated during peak demand prior to the marketing campaign

Answer: D

NEW QUESTION 28

- (Topic 1)

If you want to launch Amazon Elastic Compute Cloud (EC2) Instances and assign each Instance a predetermined private IP address you should:

- A. Assign a group or sequential Elastic IP address to the instances
- B. Launch the instances in a Placement Group
- C. Launch the instances in the Amazon virtual Private Cloud (VPC).
- D. Use standard EC2 instances since each instance gets a private Domain Name Service (DNS) already
- E. Launch the Instance from a private Amazon Machine image (AMI)

Answer: C

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-ip-addressing.html>

NEW QUESTION 30

- (Topic 1)

You have an Auto Scaling group associated with an Elastic Load Balancer (ELB). You have noticed that instances launched via the Auto Scaling group are being marked unhealthy due to an ELB health check, but these unhealthy instances are not being terminated.

What do you need to do to ensure that instances marked unhealthy by the ELB will be terminated and replaced?

- A. Change the thresholds set on the Auto Scaling group health check
- B. Add an Elastic Load Balancing health check to your Auto Scaling group
- C. Increase the value for the Health check interval set on the Elastic Load Balancer
- D. Change the health check set on the Elastic Load Balancer to use TCP rather than HTTP checks

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-add-elb-healthcheck.html>

Add an Elastic Load Balancing Health Check to your Auto Scaling Group

By default, an Auto Scaling group periodically reviews the results of EC2 instance status to determine the health state of each instance. However, if you have associated your Auto Scaling group with an Elastic Load Balancing load balancer, you can choose to use the Elastic Load Balancing health check. In this case, Auto Scaling determines the health status of your instances by checking the results of both the EC2 instance status check and the Elastic Load Balancing instance health check.

For information about EC2 instance status checks, see *Monitor Instances With Status Checks* in the *Amazon EC2 User Guide for Linux Instances*. For information about Elastic Load Balancing health checks, see *Health Check* in the *Elastic Load Balancing Developer Guide*.

This topic shows you how to add an Elastic Load Balancing health check to your Auto Scaling group, assuming that you have created a load balancer and have registered the load balancer with your Auto Scaling group. If you have not registered the load balancer with your Auto Scaling group, see *Set Up a Scaled and Load-Balanced Application*.

Auto Scaling marks an instance unhealthy if the calls to the Amazon EC2 action `DescribeInstanceStatus` return any state other than `running`, the system status shows `impaired`, or the calls to Elastic Load Balancing action `DescribeInstanceHealth` returns `OutOfService` in the instance state field.

If there are multiple load balancers associated with your Auto Scaling group, Auto Scaling checks the health state of your EC2 instances by making health check calls to each load balancer. For each call, if the Elastic Load Balancing action returns any state other than `InService`, the instance is marked as unhealthy. After Auto Scaling marks an instance as unhealthy, it remains in that state, even if subsequent calls from other load balancers return an `InService` state for the same instance.

NEW QUESTION 32

- (Topic 1)

Your company is moving towards tracking web page users with a small tracking

image loaded on each page. Currently you are serving this image out of US-East, but are starting to get concerned about the time it takes to load the image for users on the west coast.

What are the two best ways to speed up serving this image?

Choose 2 answers

- A. Use Route 53's Latency Based Routing and serve the image out of US-West-2 as well as US-East-1
- B. Serve the image out through CloudFront
- C. Serve the image out of S3 so that it isn't being served out of your web application tier
- D. Use EBS PIOPs to serve the image faster out of your EC2 instances

Answer: AD

NEW QUESTION 35

- (Topic 1)

When attached to an Amazon VPC which two components provide connectivity with external networks? Choose 2 answers

- A. Elastic IPS (EIP)
- B. NAT Gateway (NAT)
- C. Internet Gateway (IGW)
- D. Virtual Private Gateway (VGW)

Answer: CD

NEW QUESTION 40

- (Topic 1)

You have been asked to automate many routine systems administrator backup and recovery activities. Your current plan is to leverage AWS-managed solutions as much as possible and automate the rest with the AWS CLI and scripts.

Which task would be best accomplished with a script?

- A. Creating daily EBS snapshots with a monthly rotation of snapshots
- B. Creating daily RDS snapshots with a monthly rotation of snapshots
- C. Automatically detect and stop unused or underutilized EC2 instances
- D. Automatically add Auto Scaled EC2 instances to an Amazon Elastic Load Balancer

Answer: A

NEW QUESTION 45

- (Topic 1)

What are characteristics of Amazon S3? Choose 2 answers

- A. Objects are directly accessible via a URL
- B. S3 should be used to host a relational database
- C. S3 allows you to store objects of virtually unlimited size
- D. S3 allows you to store virtually unlimited amounts of data
- E. S3 offers Provisioned IOPS

Answer: AD

NEW QUESTION 50

- (Topic 2)

A user is accessing RDS from an application. The user has enabled the Multi AZ feature with the MS SQL RDS DB. During a planned outage how will AWS ensure that a switch from DB to a standby replica will not affect access to the application?

- A. RDS will have an internal IP which will redirect all requests to the new DB
- B. RDS uses DNS to switch over to stand by replica for seamless transition
- C. The switch over changes Hardware so RDS does not need to worry about access
- D. RDS will have both the DBs running independently and the user has to manually switch over

Answer: B

Explanation:

In the event of a planned or unplanned outage of a DB instance, Amazon RDS automatically switches to a standby replica in another Availability Zone if the user has enabled Multi AZ. The automatic failover mechanism simply changes the DNS record of the DB instance to point to the standby DB instance. As a result, the user will need to re-establish any existing connections to the DB instance. However, as the DNS is the same, the application can access DB seamlessly.

NEW QUESTION 51

- (Topic 2)

You are managing the AWS account of a big organization. The organization has more than 1000+ employees and they want to provide access to the various services to most of the employees. Which of the below mentioned options is the best possible solution in this case?

- A. The user should create a separate IAM user for each employee and provide access to them as per the policy
- B. The user should create an IAM role and attach STS with the role
- C. The user should attach that role to the EC2 instance and setup AWS authentication on that server
- D. The user should create IAM groups as per the organization's departments and add each user to the group for better access control
- E. Attach an IAM role with the organization's authentication service to authorize each user for various AWS services

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user is managing an AWS account for an organization that already has an identity system, such as the login system for the corporate network (SSO). In this case, instead of creating individual IAM users or groups for each user who need AWS access, it may be more practical to use a proxy server to translate the user identities from the organization network into the temporary AWS security credentials. This proxy server will attach an IAM role to the user after authentication.

NEW QUESTION 54

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 with only a private subnet and VPN connection using the VPC wizard. The user wants to connect to the instance in a private subnet over SSH. How should the user define the security rule for SSH?

- A. Allow Inbound traffic on port 22 from the user's network
- B. The user has to create an instance in EC2 Classic with an elastic IP and configure the security group of a private subnet to allow SSH from that elastic IP
- C. The user can connect to a instance in a private subnet using the NAT instance
- D. Allow Inbound traffic on port 80 and 22 to allow the user to connect to a private subnet over the Internet

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, the user can setup a case with a VPN only subnet (private. which uses VPN access to connect with his data centre. When the user has configured this setup with Wizard, all network connections to the instances in the subnet will come from his data centre. The user has to configure the security group of the private subnet which allows the inbound traffic on SSH (port 22. from the data centre's network range.

NEW QUESTION 58

- (Topic 2)

A system admin is managing buckets, objects and folders with AWS S3. Which of the below mentioned statements is true and should be taken in consideration by the sysadmin?

- A. The folders support only ACL
- B. Both the object and bucket can have an Access Policy but folder cannot have policy
- C. Folders can have a policy
- D. Both the object and bucket can have ACL but folders cannot have ACL

Answer: A

Explanation:

A sysadmin can grant permission to the S3 objects or the buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice a versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level. The folders are similar to objects with no content. Thus, folders can have only ACL and cannot have a policy.

NEW QUESTION 60

- (Topic 2)

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- B. The organization should create each user in a separate region so that they have their own URL to login
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group
- E. The user can login with their own group ID

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

NEW QUESTION 64

- (Topic 2)

A user has created a photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Glacier
- B. AWS Elastic Transcoder
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

NEW QUESTION 66

- (Topic 2)

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day

D. AWS PIOPS volume of 10 GB size

Answer: D

Explanation:

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

NEW QUESTION 71

- (Topic 2)

A user is planning to use AWS Cloud formation for his automatic deployment requirements. Which of the below mentioned components are required as a part of the template?

- A. Parameters
- B. Outputs
- C. Template version
- D. Resources

Answer: D

Explanation:

AWS Cloud formation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. It can have option fields, such as Template Parameters, Output, Data tables, and Template file format version. The only mandatory value is Resource. The user can define the AWS services which will be used/ created by this template inside the Resource section

NEW QUESTION 74

- (Topic 2)

A user has created a queue named “myqueue” in US-East region with AWS SQS. The user’s AWS account ID is 123456789012. If the user wants to perform some action on this queue, which of the below Queue URL should he use?

- A. <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>
- B. <http://sqs.amazonaws.com/123456789012/myqueue>
- C. <http://sq>
- D. 123456789012.us-east-1.amazonaws.com/myqueue
- E. [http:// 123456789012.sq](http://123456789012.sq)
- F. us-east-1.amazonaws.com/myqueue

Answer: A

Explanation:

When creating a new queue in SQS, the user must provide a queue name that is unique within the scope of all queues of user’s account. If the user creates queues using both the latest WSDL and a previous version, he will have a single namespace for all his queues. Amazon SQS assigns each queue created by user an identifier called a queue URL, which includes the queue name and other components that Amazon SQS determines. Whenever the user wants to perform an action on a queue, he must provide its queue URL. The queue URL for the account id 123456789012 & queue name “myqueue” in US-East-1 region will be <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>.

NEW QUESTION 79

- (Topic 2)

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department’s employees

Answer: A

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

NEW QUESTION 80

- (Topic 2)

A root AWS account owner is trying to understand various options to set the permission to AWS S3. Which of the below mentioned options is not the right option to grant permission for S3?

- A. User Access Policy
- B. S3 Object Access Policy
- C. S3 Bucket Access Policy
- D. S3 ACL

Answer: B

Explanation:

Amazon S3 provides a set of operations to work with the Amazon S3 resources. Managing S3 resource access refers to granting others permissions to work with S3. There are three ways the root account owner can define access with S3: S3 ACL: The user can use ACLs to grant basic read/write permissions to other AWS accounts. S3 Bucket Policy: The policy is used to grant other AWS accounts or IAM users permissions for the bucket and the objects in it. User Access Policy: Define an IAM user and assign him the IAM policy which grants him access to S3.

NEW QUESTION 83

- (Topic 2)

A user is running one instance for only 3 hours every day. The user wants to save some cost with the instance. Which of the below mentioned Reserved Instance categories is advised in this case?

- A. The user should not use RI; instead only go with the on-demand pricing
- B. The user should use the AWS high utilized RI
- C. The user should use the AWS medium utilized RI
- D. The user should use the AWS low utilized RI

Answer: A

Explanation:

The AWS Reserved Instance provides the user with an option to save some money by paying a one-time fixed amount and then save on the hourly rate. It is advisable that if the user is having 30% or more usage of an instance per day, he should go for a RI. If the user is going to use an EC2 instance for more than 2200-2500 hours per year, RI will help the user save some cost. Here, the instance is not going to run for less than 1500 hours. Thus, it is advisable that the user should use the on-demand pricing.

NEW QUESTION 84

- (Topic 2)

An organization has setup consolidated billing with 3 different AWS accounts. Which of the below mentioned advantages will organization receive in terms of the AWS pricing?

- A. The consolidated billing does not bring any cost advantage for the organization
- B. All AWS accounts will be charged for S3 storage by combining the total storage of each account
- C. The EC2 instances of each account will receive a total of 750*3 micro instance hours free
- D. The free usage tier for all the 3 accounts will be 3 years and not a single year

Answer: B

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. For billing purposes, AWS treats all the accounts on the consolidated bill as one account. Some services, such as Amazon EC2 and Amazon S3 have volume pricing tiers across certain usage dimensions that give the user lower prices when he uses the service more.

NEW QUESTION 87

- (Topic 2)

A user has configured ELB with three instances. The user wants to achieve High Availability as well as redundancy with ELB. Which of the below mentioned AWS services helps the user achieve this for ELB?

- A. Route 53
- B. AWS Mechanical Turk
- C. Auto Scaling
- D. AWS EMR

Answer: A

Explanation:

The user can provide high availability and redundancy for applications running behind Elastic Load Balancer by enabling the Amazon Route 53 Domain Name System (DNS) failover for the load balancers. Amazon Route 53 is a DNS service that provides reliable routing to the user's infrastructure.

NEW QUESTION 88

- (Topic 2)

A user has enabled the Multi AZ feature with the MS SQL RDS database server. Which of the below mentioned statements will help the user understand the Multi AZ feature better?

- A. In a Multi AZ, AWS runs two DBs in parallel and copies the data asynchronously to the replica copy
- B. In a Multi AZ, AWS runs two DBs in parallel and copies the data synchronously to the replica copy
- C. In a Multi AZ, AWS runs just one DB but copies the data synchronously to the standby replica
- D. AWS MS SQL does not support the Multi AZ feature

Answer: C

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. In a Multi-AZ deployment, Amazon RDS automatically

provisions and maintains a synchronous standby replica in a different Availability Zone. The primary DB instance is synchronously replicated across Availability Zones to a standby replica to provide data redundancy, eliminate I/O freezes, and minimize latency spikes during system backups. Running a DB instance with high availability can enhance availability during planned system maintenance, and help protect your databases against DB instance failure and Availability Zone disruption. Note that the high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a read replica.

NEW QUESTION 91

- (Topic 2)

An organization is setting up programmatic billing access for their AWS account. Which of the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

Answer: C

Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3) APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value) file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

NEW QUESTION 94

- (Topic 2)

A user has stored data on an encrypted EBS volume. The user wants to share the data with his friend's AWS account. How can user achieve this?

- A. Create an AMI from the volume and share the AMI
- B. Copy the data to an unencrypted volume and then share
- C. Take a snapshot and share the snapshot with a friend
- D. If both the accounts are using the same encryption key then the user can share the volume directly

Answer: B

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. If the user is having data on an encrypted volume and is trying to share it with others, he has to copy the data from the encrypted volume to a new unencrypted volume. Only then can the user share it as an encrypted volume data. Otherwise the snapshot cannot be shared.

NEW QUESTION 95

- (Topic 2)

A user has launched an EC2 instance. The user is planning to setup the CloudWatch alarm. Which of the below mentioned actions is not supported by the CloudWatch alarm?

- A. Notify the Auto Scaling launch config to scale up
- B. Send an SMS using SNS
- C. Notify the Auto Scaling group to scale down
- D. Stop the EC2 instance

Answer: B

Explanation:

A user can create a CloudWatch alarm that takes various actions when the alarm changes state. An alarm watches a single metric over the time period that the user has specified, and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The actions could be sending a notification to an Amazon Simple Notification Service topic (SMS, Email, and HTTP end point), notifying the Auto Scaling policy or changing the state of the instance to Stop/Terminate.

NEW QUESTION 96

- (Topic 2)

A root account owner has created an S3 bucket testmycloud. The account owner wants to allow everyone to upload the objects as well as enforce that the person who uploaded the object should manage the permission of those objects. Which is the easiest way to achieve this?

- A. The root account owner should create a bucket policy which allows the IAM users to upload the object
- B. The root account owner should create the bucket policy which allows the other account owners to set the object policy of that bucket
- C. The root account should use ACL with the bucket to allow everyone to upload the object
- D. The root account should create the IAM users and provide them the permission to upload content to the bucket

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List) associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users in his account. ACLs are suitable for specific scenarios. For example, if a bucket owner allows other AWS accounts to upload objects,

permissions to these objects can only be managed using the object ACL by the AWS account that owns the object.

NEW QUESTION 101

- (Topic 2)

A user has configured ELB with two EBS backed EC2 instances. The user is trying to understand the DNS access and IP support for ELB. Which of the below mentioned statements may not help the user understand the IP mechanism supported by ELB?

- A. The client can connect over IPV4 or IPV6 using Dualstack
- B. ELB DNS supports both IPV4 and IPV6
- C. Communication between the load balancer and back-end instances is always through IPV4
- D. The ELB supports either IPV4 or IPV6 but not both

Answer: D

Explanation:

Elastic Load Balancing supports both Internet Protocol version 6 (IPv6) and Internet Protocol version 4 (IPv4). Clients can connect to the user's load balancer using either IPv4 or IPv6 (in EC2-Classic DNS). However, communication between the load balancer and its back-end instances uses only IPv4. The user can use the Dualstack-prefixed DNS name to enable IPv6 support for communications between the client and the load balancers. Thus, the clients are able to access the load balancer using either IPv4 or IPv6 as their individual connectivity needs dictate.

NEW QUESTION 106

- (Topic 2)

An organization has added 3 of his AWS accounts to consolidated billing. One of the AWS accounts has purchased a Reserved Instance (RI) of a small instance size in the US-East-1a zone. All other AWS accounts are running instances of a small size in the same zone. What will happen in this case for the RI pricing?

- A. Only the account that has purchased the RI will get the advantage of RI pricing
- B. One instance of a small size and running in the US-East-1a zone of each AWS account will get the benefit of RI pricing
- C. Any single instance from all the three accounts can get the benefit of AWS RI pricing if they are running in the same zone and are of the same size
- D. If there are more than one instances of a small size running across multiple accounts in the same zone no one will get the benefit of RI

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. For billing purposes, consolidated billing treats all the accounts on the consolidated bill as one account. This means that all accounts on a consolidated bill can receive the hourly cost benefit of the Amazon EC2 Reserved Instances purchased by any other account. In this case only one Reserved Instance has been purchased by one account. Thus, only a single instance from any of the accounts will get the advantage of RI. AWS will implement the blended rate for each instance if more than one instance is running concurrently.

NEW QUESTION 110

- (Topic 2)

A user has enabled detailed CloudWatch metric monitoring on an Auto Scaling group. Which of the below mentioned metrics will help the user identify the total number of instances in an Auto Scaling group including pending, terminating and running instances?

- A. GroupTotalInstances
- B. GroupSumInstances
- C. It is not possible to get a count of all the three metrics together
- D. The user has to find the individual number of running, terminating and pending instances and sum it
- E. GroupInstancesCount

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For Auto Scaling, CloudWatch provides various metrics to get the group information, such as the Number of Pending, Running or Terminating instances at any moment. If the user wants to get the total number of Running, Pending and Terminating instances at any moment, he can use the GroupTotalInstances metric.

NEW QUESTION 114

- (Topic 2)

A sys admin is trying to understand the Auto Scaling activities. Which of the below mentioned processes is not performed by Auto Scaling?

- A. Reboot Instance
- B. Schedule Actions
- C. Replace Unhealthy
- D. Availability Zone Balancing

Answer: A

Explanation:

There are two primary types of Auto Scaling processes: Launch and Terminate, which launch or terminate instances, respectively. Some other actions performed by Auto Scaling are: AddToLoadbalancer, AlarmNotification, HealthCheck, AZRebalance, ReplaceUnHealthy, and ScheduledActions.

NEW QUESTION 117

- (Topic 2)

A user is trying to setup a recurring Auto Scaling process. The user has setup one process to scale up every day at 8 am and scale down at 7 PM. The user is trying to setup another recurring process which scales up on the 1st of every month at 8 AM and scales down the same day at 7 PM. What will Auto Scaling do in this scenario?

- A. Auto Scaling will execute both processes but will add just one instance on the 1st
- B. Auto Scaling will add two instances on the 1st of the month
- C. Auto Scaling will schedule both the processes but execute only one process randomly
- D. Auto Scaling will throw an error since there is a conflict in the schedule of two separate Auto Scaling Processes

Answer: D

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. As per Auto Scaling, a scheduled action must have a unique time value. If the user attempts to schedule an activity at a time when another existing activity is already scheduled, the call will be rejected with an error message noting the conflict.

NEW QUESTION 122

- (Topic 2)

An organization (Account ID 123412341234. has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
  "Effect": "Allow",
  "Action": [
    "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}]
```

- A. 0
- B. 0
- C. 0
- D. 0

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage keys (access and secret access keys. of all IAM users, the organization should set the below mentioned policy which entitles the IAM user to modify keys of all IAM users with CLI, SDK or API.

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
  "Effect": "Allow",
  "Action": [
    "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}]
```

NEW QUESTION 125

- (Topic 2)

A user has launched an EBS backed instance. The user started the instance at 9 AM in the morning. Between 9 AM to 10 AM, the user is testing some script. Thus, he stopped the instance twice and restarted it. In the same hour the user rebooted the instance once. For how many instance hours will AWS charge the user?

- A. 3 hours
- B. 4 hours
- C. 2 hours
- D. 1 hour

Answer: A

Explanation:

A user can stop/start or reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. When the instance is rebooted AWS will not charge the user for the extra hours. In case the user stops the instance, AWS does not charge the running cost but charges only the EBS storage cost. If the user starts and stops the instance multiple times in a single hour, AWS will charge the user for every start and stop. In this case, since the instance was rebooted twice, it will cost the user for 3 instance hours.

NEW QUESTION 129

- (Topic 2)

An organization has created 50 IAM users. The organization has introduced a new policy which will change the access of an IAM user. How can the organization

implement this effectively so that there is no need to apply the policy at the individual user level?

- A. Use the IAM groups and add users as per their role to different groups and apply policy to group
- B. The user can create a policy and apply it to multiple users in a single go with the AWS CLI
- C. Add each user to the IAM role as per their organization role to achieve effective policy setup
- D. Use the IAM role and implement access at the role level

Answer: A

Explanation:

With AWS IAM, a group is a collection of IAM users. A group allows the user to specify permissions for a collection of users, which can make it easier to manage the permissions for those users. A group helps an organization manage access in a better way; instead of applying at the individual level, the organization can apply at the group level which is applicable to all the users who are a part of that group.

NEW QUESTION 133

- (Topic 2)

An organization is using AWS since a few months. The finance team wants to visualize the pattern of AWS spending. Which of the below AWS tool will help for this requirement?

- A. AWS Cost Manager
- B. AWS Cost Explorer
- C. AWS CloudWatch
- D. AWS Consolidated Billing

Answer: B

Explanation:

The AWS Billing and Cost Management console includes the Cost Explorer tool for viewing AWS cost data as a graph. It does not charge extra to user for this service. With Cost Explorer the user can filter graphs using resource tags or with services in AWS. If the organization is using Consolidated Billing it helps generate report based on linked accounts. This will help organization to identify areas that require further inquiry. The organization can view trends and use that to understand spend and to predict future costs.

NEW QUESTION 136

- (Topic 2)

A user has a refrigerator plant. The user is measuring the temperature of the plant every 15 minutes. If the user wants to send the data to CloudWatch to view the data visually, which of the below mentioned statements is true with respect to the information given above?

- A. The user needs to use AWS CLI or API to upload the data
- B. The user can use the AWS Import Export facility to import data to CloudWatch
- C. The user will upload data from the AWS console
- D. The user cannot upload data to CloudWatch since it is not an AWS service metric

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. While sending the data the user has to include the metric name, namespace and timezone as part of the request.

NEW QUESTION 140

- (Topic 2)

A user has recently started using EC2. The user launched one EC2 instance in the default subnet in EC2-VPC Which of the below mentioned options is not attached or available with the EC2 instance when it is launched?

- A. Public IP address
- B. Internet gateway
- C. Elastic IP
- D. Private IP address

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to a user's AWS account. A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC (default subnet). A default VPC has all the benefits of EC2-VPC and the ease of use of EC2-Classic. Each instance that the user launches into a default subnet has a private IP address and a public IP address. These instances can communicate with the internet through an internet gateway. An internet gateway enables the EC2 instances to connect to the internet through the Amazon EC2 network edge.

NEW QUESTION 143

- (Topic 2)

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP
- C. AWS SQS
- D. AWS SES

Answer: D

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", and "SMS".

NEW QUESTION 147

- (Topic 2)

A user has configured a VPC with a new subnet. The user has created a security group. The user wants to configure that instances of the same subnet communicate with each other. How can the user configure this with the security group?

- A. There is no need for a security group modification as all the instances can communicate with each other inside the same subnet
- B. Configure the subnet as the source in the security group and allow traffic on all the protocols and ports
- C. Configure the security group itself as the source and allow traffic on all the protocols and ports
- D. The user has to use VPC peering to configure this

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. If the user is using the default security group it will have a rule which allows the instances to communicate with other. For a new security group the user has to specify the rule, add it to define the source as the security group itself, and select all the protocols and ports for that source.

NEW QUESTION 152

- (Topic 2)

An organization is using cost allocation tags to find the cost distribution of different departments and projects. One of the instances has two separate tags with the key/ value as "InstanceName/HR", "CostCenter/HR". What will AWS do in this case?

- A. InstanceName is a reserved tag for AWS
- B. Thus, AWS will not allow this tag
- C. AWS will not allow the tags as the value is the same for different keys
- D. AWS will allow tags but will not show correctly in the cost allocation report due to the same value of the two separate keys
- E. AWS will allow both the tags and show properly in the cost distribution report

Answer: D

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV) file, with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. It is required that the key should be different for each tag. The value can be the same for different keys. In this case since the value is different, AWS will properly show the distribution report with the correct values.

NEW QUESTION 153

- (Topic 2)

A user has launched two EBS backed EC2 instances in the US-East-1a region. The user wants to change the zone of one of the instances. How can the user change it?

- A. Stop one of the instances and change the availability zone
- B. The zone can only be modified using the AWS CLI
- C. From the AWS EC2 console, select the Actions - > Change zones and specify new zone
- D. Create an AMI of the running instance and launch the instance in a separate AZ

Answer: D

Explanation:

With AWS EC2, when a user is launching an instance he can select the availability zone (AZ) at the time of launch. If the zone is not selected, AWS selects it on behalf of the user. Once the instance is launched, the user cannot change the zone of that instance unless he creates an AMI of that instance and launches a new instance from it.

NEW QUESTION 155

- (Topic 3)

A user has created a VPC with a public subnet. The user has terminated all the instances which are part of the subnet. Which of the below mentioned statements is true with respect to this scenario?

- A. The user cannot delete the VPC since the subnet is not deleted
- B. All network interface attached with the instances will be deleted
- C. When the user launches a new instance it cannot use the same subnet
- D. The subnet to which the instances were launched with will be deleted

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface. When the user terminates the instance all the network interfaces attached with it are also deleted.

NEW QUESTION 156

- (Topic 3)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB Instance is switched to the standby DB Instance
- B. A new DB instance is created in the standby availability zone
- C. The canonical name record (CNAME) is changed from primary to standby
- D. The RDS (Relational Database Service) DB instance reboots

Answer: D

Explanation:

Reference:

http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_RebootInstance.html

NEW QUESTION 159

- (Topic 3)

A user has launched an EC2 Windows instance from an instance store backed AMI. The user wants to convert the AMI to an EBS backed AMI. How can the user convert it?

- A. Attach an EBS volume to the instance and unbundle all the AMI bundled data inside the EBS
- B. A Windows based instance store backed AMI cannot be converted to an EBS backed AMI
- C. It is not possible to convert an instance store backed AMI to an EBS backed AMI
- D. Attach an EBS volume and use the copy command to copy all the ephemeral content to the EBS Volume

Answer: B

Explanation:

Generally when a user has launched an EC2 instance from an instance store backed AMI, it can be converted to an EBS backed AMI provided the user has attached the EBS volume to the instance and unbundles the AMI data to it. However, if the instance is a Windows instance, AWS does not allow this. In this case, since the instance is a Windows instance, the user cannot convert it to an EBS backed AMI.

NEW QUESTION 163

- (Topic 3)

An organization has created a Queue named "modularqueue" with SQS. The organization is not performing any operations such as SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission on the queue. What can happen in this scenario?

- A. AWS SQS sends notification after 15 days for inactivity on queue
- B. AWS SQS can delete queue after 30 days without notification
- C. AWS SQS marks queue inactive after 30 days
- D. AWS SQS notifies the user after 2 weeks and deletes the queue after 3 weeks

Answer: B

Explanation:

Amazon SQS can delete a queue without notification if one of the following actions hasn't been performed on it for 30 consecutive days: SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission.

NEW QUESTION 167

- (Topic 3)

A sys admin has enabled logging on ELB. Which of the below mentioned fields will not be a part of the log file name?

- A. Load Balancer IP
- B. EC2 instance IP
- C. S3 bucket name
- D. Random string

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Elastic Load Balancing publishes a log file from each load balancer node at the interval that the user has specified. The load balancer can deliver multiple logs for the same period. Elastic Load Balancing creates log file names in the following format: "{Bucket}/{Prefix}/AWSLogs/{AWS AccountID}/elasticloadbalancing/{Region}/{Year}/{Month}/{Day}/{AWS AccountID}_elasticloadbalancing_{Region}_{Load Balancer Name}_{End Time}_{Load Balancer IP}_{Random String}.log"

NEW QUESTION 170

- (Topic 3)

A user is trying to connect to a running EC2 instance using SSH. However, the user gets an Unprotected Private Key File error. Which of the below mentioned options can be a possible reason for rejection?

- A. The private key file has the wrong file permission
- B. The ppk file used for SSH is read only
- C. The public key file has the wrong permission
- D. The user has provided the wrong user name for the OS login

Answer: A

Explanation:

While doing SSH to an EC2 instance, if you get an Unprotected Private Key File error it means that the private key file's permissions on your computer are too open. Ideally the private key should have the Unix permission of 0400. To fix that, run the command: `chmod 0400 /path/to/private.key`

NEW QUESTION 174

- (Topic 3)

A user has launched 5 instances in EC2-CLASSIC and attached 5 elastic IPs to the five different instances in the US East region. The user is creating a VPC in the same region. The user wants to assign an elastic IP to the VPC instance. How can the user achieve this?

- A. The user has to request AWS to increase the number of elastic IPs associated with the account
- B. AWS allows 10 EC2 Classic IPs per region; so it will allow to allocate new Elastic IPs to the same region
- C. The AWS will not allow to create a new elastic IP in VPC; it will throw an error
- D. The user can allocate a new IP address in VPC as it has a different limit than EC2

Answer: D

Explanation:

Section: (none)

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. A user can have 5 IP addresses per region with EC2 Classic. The user can have 5 separate IPs with VPC in the same region as it has a separate limit than EC2 Classic.

NEW QUESTION 176

- (Topic 3)

A user has launched an EC2 instance store backed instance in the US-East-1a zone. The user created AMI #1 and copied it to the Europe region. After that, the user made a few updates to the application running in the US-East-1a zone. The user makes an AMI#2 after the changes. If the user launches a new instance in Europe from the AMI #1 copy, which of the below mentioned statements is true?

- A. The new instance will have the changes made after the AMI copy as AWS just copies the reference of the original AMI during the copyin
- B. Thus, the copied AMI will have all the updated data
- C. The new instance will have the changes made after the AMI copy since AWS keeps updating the AMI
- D. It is not possible to copy the instance store backed AMI from one region to another
- E. The new instance in the EU region will not have the changes made after the AMI copy

Answer: D

Explanation:

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source) AMI. The user can modify the source AMI without affecting the new AMI and vice versa. Therefore, in this case even if the source AMI is modified, the copied AMI of the EU region will not have the changes. Thus, after copy the user needs to copy the new source AMI to the destination region to get those changes.

NEW QUESTION 178

- (Topic 3)

A user has setup a VPC with CIDR 20.0.0.0/16. The VPC has a private subnet (20.0.1.0/24) and a public subnet (20.0.0.0/24). The user's data centre has CIDR of 20.0.54.0/24 and 20.1.0.0/24. If the private subnet wants to communicate with the data centre, what will happen?

- A. It will allow traffic communication on both the CIDRs of the data centre
- B. It will not allow traffic with data centre on CIDR 20.1.0.0/24 but allows traffic communication on 20.0.54.0/24
- C. It will not allow traffic communication on any of the data centre CIDRs
- D. It will allow traffic with data centre on CIDR 20.1.0.0/24 but does not allow on 20.0.54.0/24

Answer: D

Explanation:

VPC allows the user to set up a connection between his VPC and corporate or home network data centre. If the user has an IP address prefix in the VPC that overlaps with one of the networks' prefixes, any traffic to the network's prefix is dropped. In this case CIDR 20.0.54.0/24 falls in the VPC's CIDR range of 20.0.0.0/16. Thus, it will not allow traffic on that IP. In the case of 20.1.0.0/24, it does not fall in the VPC's CIDR range. Thus, traffic will be allowed on it.

NEW QUESTION 180

- (Topic 3)

A user is sending the data to CloudWatch using the CloudWatch API. The user is sending data 90 minutes in the future. What will CloudWatch do in this case?

- A. CloudWatch will accept the data
- B. It is not possible to send data of the future
- C. It is not possible to send the data manually to CloudWatch
- D. The user cannot send data for more than 60 minutes in the future

Answer: A

Explanation:

With Amazon CloudWatch, each metric data point must be marked with a time stamp. The user can send the data using CLI but the time has to be in the UTC format. If the user does not provide the time, CloudWatch will take the data received time in the UTC timezone. The time stamp sent by the user can be up to two weeks in the past and up to two hours into the future.

NEW QUESTION 183

- (Topic 3)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    },
    {
      "Sid": "DenyIP188",
      "Action": "s3:*",
      "Effect": "Deny",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    }
  ]
}
```

- A. Denies the server with the IP address 192.166 100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.166 100.188 full access to the "mybucket bucket
- C. Grants all the servers within the 192 168 100 0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192 168 100 188/32 subnet full access to the "mybucket" bucket

Answer: C

NEW QUESTION 186

- (Topic 3)

You have a business-to-business web application running in a VPC consisting of an Elastic Load Balancer (ELB), web servers, application servers and a database. Your web application should only accept traffic from pre-defined customer IP addresses.

Which two options meet this security requirement? Choose 2 answers A. Configure web server VPC security groups to allow traffic from your customers' IPs

- A. Configure your web servers to filter traffic based on the ELB's "X-forwarded-for" header
- B. Configure ELB security groups to allow traffic from your customers' IPs and deny all outbound traffic
- C. Configure a VPC NACL to allow web traffic from your customers' IPs and deny all outbound traffic

Answer: AB

NEW QUESTION 189

- (Topic 3)

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

Perform maintenance on standby
Promote standby to primary
Perform maintenance on original primary
Promote original master back as primary

- A. 1, 2, 3, 4
- B. 1, 2, 3
- C. 2, 3, 1, 4

Answer: B

Explanation:

Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order: Perform maintenance on standby Promote standby to primary Perform maintenance on original primary, which becomes the new standby.

NEW QUESTION 191

- (Topic 3)

Which method can be used to prevent an IP address block from accessing public objects in an S3 bucket?

- A. Create a bucket policy and apply it to the bucket
- B. Create a NACL and attach it to the VPC of the bucket
- C. Create an ACL and apply it to all objects in the bucket
- D. Modify the IAM policies of any users that would access the bucket

Answer: A

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

NEW QUESTION 196

- (Topic 3)

In AWS, which security aspects are the customer's responsibility? Choose 4 answers

- A. Controlling physical access to compute resources
- B. Patch management on the EC2 instance's operating system
- C. Encryption of EBS (Elastic Block Storage) volumes
- D. Life-cycle management of IAM credentials
- E. Decommissioning storage devices
- F. Security Group and ACL (Access Control List) settings

Answer: BCEF

NEW QUESTION 197

- (Topic 3)

A user is planning to scale up an application by 8 AM and scale down by 7 PM daily using Auto Scaling. What should the user do in this case?

- A. Setup the scaling policy to scale up and down based on the CloudWatch alarms
- B. The user should increase the desired capacity at 8 AM and decrease it by 7 PM manually
- C. The user should setup a batch process which launches the EC2 instance at a specific time
- D. Setup scheduled actions to scale up or down at a specific time

Answer: A

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. To configure the Auto Scaling group to scale based on a schedule, the user needs to create scheduled actions. A scheduled action tells Auto Scaling to perform a scaling action at a certain time in the future.

NEW QUESTION 198

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created one subnet with CIDR 20.0.0.0/16 in this VPC. The user is trying to create another subnet with the same VPC for CIDR 20.0.0.1/24. What will happen in this scenario?

- A. The VPC will modify the first subnet CIDR automatically to allow the second subnet IP range
- B. It is not possible to create a subnet with the same CIDR as VPC
- C. The second subnet will be created
- D. It will throw a CIDR overlaps error

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. The user can create a subnet with the same size of VPC. However, he cannot create any other subnet since the CIDR of the second subnet will conflict with the first subnet.

NEW QUESTION 202

- (Topic 3)

A user wants to find the particular error that occurred on a certain date in the AWS MySQL RDS DB. Which of the below mentioned activities may help the user to get the data easily?

- A. It is not possible to get the log files for MySQL RDS
- B. Find all the transaction logs and query on those records
- C. Direct the logs to the DB table and then query that table
- D. Download the log file to DynamoDB and search for the record

Answer: C

Explanation:

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI) or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow query log, and general logs. The user can also view the MySQL logs easily by directing the logs to a database table in the main database and querying that table.

NEW QUESTION 207

- (Topic 3)

A user is collecting 1000 records per second. The user wants to send the data to CloudWatch using the custom namespace. Which of the below mentioned options is recommended for this activity?

- A. Aggregate the data with statistics, such as Min, max, Average, Sum and Sample data and send the data to CloudWatch
- B. Send all the data values to CloudWatch in a single command by separating them with a comm
- C. CloudWatch will parse automatically
- D. Create one csv file of all the data and send a single file to CloudWatch
- E. It is not possible to send all the data in one cal
- F. Thus, it should be sent one by on
- G. CloudWatch will aggregate the data automatically

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. It is recommended that when the user is having multiple data points per minute, he should aggregate the data so that it will minimize the number of calls to put-metric-data. In this case it will be single call to CloudWatch instead of 1000 calls if the data is aggregated.

NEW QUESTION 212

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The user has not launched any instance manually and is trying to delete the VPC. What will happen in this scenario?

- A. It will not allow to delete the VPC as it has subnets with route tables
- B. It will not allow to delete the VPC since it has a running route instance
- C. It will terminate the VPC along with all the instances launched by the wizard
- D. It will not allow to delete the VPC since it has a running NAT instance

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. If the user is trying to delete the VPC it will not allow as the NAT instance is still running.

NEW QUESTION 216

- (Topic 3)

A user runs the command "dd if=/dev/zero of=/dev/xvdfbs=1M" on a fresh blank EBS volume attached to a Linux instance. Which of the below mentioned activities is the user performing with the command given above?

- A. Creating a file system on the EBS volume
- B. Mounting the device to the instance
- C. Pre warming the EBS volume
- D. Formatting the EBS volume

Answer: C

Explanation:

When the user creates a new EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a blank volume attached with a Linux OS, the "dd" command is used to write to all the blocks on the device. In the command "dd if=/dev/zero of=/dev/xvdfbs=1M" the parameter "if =import file" should be set to one of the Linux virtual devices, such as /dev/zero. The "of=output file" parameter should be set to the drive that the user wishes to warm. The "bs" parameter sets the block size of the write operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 221

- (Topic 3)

An organization (Account ID 123412341234) has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowUsersAllActionsForCredentials",
    "Effect": "Allow",
    "Action": [
      "iam:*LoginProfile",
      "iam:*AccessKey*",
      "iam:*SigningCertificate*"
    ],
    "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
  }]
}
```

- A. The policy allows the IAM user to modify all IAM user's credentials using the console, SDK, CLI or APIs
- B. The policy will give an invalid resource error

- C. The policy allows the IAM user to modify all credentials using only the console
D. The policy allows the user to modify all IAM user's password, sign in certificates and access keys using only CLI, SDK or APIs

Answer: D

Explanation:

WS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage credentials (access keys, password, and sing in certificates. of all IAM users, they should set an applicable policy to that user or group of users. The below mentioned policy allows the IAM user to modify the credentials of all IAM user's using only CLI, SDK or APIs. The user cannot use the AWS console for this activity since he does not have list permission for the IAM users.

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowUsersAllActionsForCredentials",
    "Effect": "Allow"
    "Action": [
      "iam:*LoginProfile",
      "iam:*AccessKey*",
      "iam:*SigningCertificate*"
    ],
    "Resource": ["arn:aws:iam::123412341234:user:${aws:username}"]
  }]
}
```

Amazon AWS-SysOps : Practice Test

NEW QUESTION 224

- (Topic 3)

The compliance department within your multi-national organization requires that all data for your customers that reside in the European Union (EU) must not leave the EU and also

data for customers that reside in the US must not leave the US without explicit authorization.

What must you do to comply with this requirement for a web based profile management application running on EC2?

- A. Run EC2 instances in multiple AWS Availability Zones in single Region and leverage an Elastic Load Balancer with session stickiness to route traffic to the appropriate zone to create their profile
B. Run EC2 instances in multiple Regions and leverage Route 53's Latency Based Routing capabilities to route traffic to the appropriate region to create their profile
C. Run EC2 instances in multiple Regions and leverage a third party data provider to determine if a user needs to be redirect to the appropriate region to create their profile
D. Run EC2 instances in multiple AWS Availability Zones in a single Region and leverage a third party data provider to determine if a user needs to be redirect to the appropriate zone to create their profile

Answer: C

NEW QUESTION 226

- (Topic 3)

A user has launched an EBS backed EC2 instance in the US-East-1a region. The user stopped the instance and started it back after 20 days. AWS throws up an 'InsufficientInstanceCapacity' error. What can be the possible reason for this?

- A. AWS does not have sufficient capacity in that availability zone
B. AWS zone mapping is changed for that user account
C. There is some issue with the host capacity on which the instance is launched
D. The user account has reached the maximum EC2 instance limit

Answer: A

Explanation:

When the user gets an 'InsufficientInstanceCapacity' error while launching or starting an EC2 instance, it means that AWS does not currently have enough available capacity to service the user request. If the user is requesting a large number of instances, there might not be enough server capacity to host them. The user can either try again later, by specifying a smaller number of instances or changing the availability zone if launching a fresh instance.

NEW QUESTION 227

- (Topic 3)

A sys admin has enabled a log on ELB. Which of the below mentioned activities are not captured by the log?

- A. Response processing time
B. Front end processing time
C. Backend processing time
D. Request processing time

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Each request will have details, such as client IP, request path, ELB IP, time, and latencies. The time will have information, such as Request Processing time, Backend Processing time and Response Processing time.

NEW QUESTION 231

- (Topic 3)

A user is using Cloudformation to launch an EC2 instance and then configure an application after the instance is launched. The user wants the stack creation of ELB and AutoScaling to wait until the EC2 instance is launched and configured properly. How can the user configure this?

- A. It is not possible that the stack creation will wait until one service is created and launched
- B. The user can use the HoldCondition resource to wait for the creation of the other dependent resources
- C. The user can use the DependentCondition resource to hold the creation of the other dependent resources
- D. The user can use the WaitCondition resource to hold the creation of the other dependent resources

Answer: D

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS CloudFormation provides a WaitCondition resource which acts as a barrier and blocks the creation of other resources until a completion signal is received from an external source, such as a user application or management system.

NEW QUESTION 233

- (Topic 3)

A user has created an EBS volume of 10 GB and attached it to a running instance. The user is trying to access EBS for first time. Which of the below mentioned options is the correct statement with respect to a first time EBS access?

- A. The volume will show a size of 8 GB
- B. The volume will show a loss of the IOPS performance the first time
- C. The volume will be blank
- D. If the EBS is mounted it will ask the user to create a file system

Answer: B

Explanation:

A user can create an EBS volume either from a snapshot or as a blank volume. If the volume is from a snapshot it will not be blank. The volume shows the right size only as long as it is mounted. This shows that the file system is created. When the user is accessing the volume the AWS EBS will wipe out the block storage or instantiate from the snapshot. Thus, the volume will show a loss of IOPS. It is recommended that the user should pre warm the EBS before use to achieve better IO.

NEW QUESTION 235

- (Topic 3)

A user is creating a Cloudformation stack. Which of the below mentioned limitations does not hold true for Cloudformation?

- A. One account by default is limited to 100 templates
- B. The user can use 60 parameters and 60 outputs in a single template
- C. The template, parameter, output, and resource description fields are limited to 4096 characters
- D. One account by default is limited to 20 stacks

Answer: A

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The limitations given below apply to the Cloudformation template and stack. There are no limits to the number of templates but each AWS CloudFormation account is limited to a maximum of 20 stacks by default. The Template, Parameter, Output, and Resource description fields are limited to 4096 characters. The user can include up to 60 parameters and 60 outputs in a template.

NEW QUESTION 236

- (Topic 3)

When you put objects in Amazon S3, what is the indication that an object was successfully stored?

- A. Each S3 account has a special bucket named _s3_log
- B. Success codes are written to this bucket with a timestamp and checksu
- C. A success code is inserted into the S3 object metadat
- D. A HTTP 200 result code and MD5 checksum, taken together, indicate that the operation was successfu
- E. Amazon S3 is engineered for 99.999999999% durabilit
- F. Therefore there is no need to confirm that data was inserte

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/API/RESTObjectPUT.html>

NEW QUESTION 240

- (Topic 3)

A user has created a VPC with the public subnet. The user has created a security group for that VPC. Which of the below mentioned statements is true when a security group is created?

- A. It can connect to the AWS services, such as S3 and RDS by default

- B. It will have all the inbound traffic by default
- C. It will have all the outbound traffic by default
- D. It will by default allow traffic to the internet gateway

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level while ACLs work at the subnet level. When a user creates a security group with AWS VPC, by default it will allow all the outbound traffic but block all inbound traffic.

NEW QUESTION 241

- (Topic 3)

Amazon EBS snapshots have which of the following two characteristics? (Choose 2.) Choose 2 answers

- A. EBS snapshots only save incremental changes from snapshot to snapshot
- B. EBS snapshots can be created in real-time without stopping an EC2 instance
- C. EBS snapshots can only be restored to an EBS volume of the same size or smaller
- D. EBS snapshots can only be restored and mounted to an instance in the same Availability Zone as the original EBS volume

Answer: AD

NEW QUESTION 246

- (Topic 3)

An organization has launched 5 instances: 2 for production and 3 for testing. The organization wants that one particular group of IAM users should only access the test instances and not the production ones. How can the organization set that as a part of the policy?

- A. Launch the test and production instances in separate regions and allow region wise access to the group
- B. Define the IAM policy which allows access based on the instance ID
- C. Create an IAM policy with a condition which allows access to only small instances
- D. Define the tags on the test and production servers and add a condition to the IAM policy which allows access to specific tags

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user can add conditions as a part of the IAM policies. The condition can be set on AWS Tags, Time, and Client IP as well as on various parameters. If the organization wants the user to access only specific instances he should define proper tags and add to the IAM policy condition.

The sample policy is shown below.

```
"Statement": [
{
  "Action": "ec2:*",
  "Effect": "Allow",
  "Resource": "*",
  "Condition": {
    "StringEquals": {
      "ec2:ResourceTag/InstanceType": "Production"
    }
  }
}
]
```

NEW QUESTION 249

- (Topic 3)

A user has created a mobile application which makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK and root account access/secret access key to connect to DynamoDB from mobile. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should create a separate IAM user for each mobile application and provide DynamoDB access with it
- B. The user should create an IAM role with DynamoDB and EC2 access
- C. Attach the role with EC2 and route all calls from the mobile through EC2
- D. The application should use an IAM role with web identity federation which validates calls to DynamoDB with identity providers, such as Google, Amazon, and Facebook
- E. Create an IAM Role with DynamoDB access and attach it with the mobile application

Answer: C

Explanation:

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. If the user is creating an app that runs on a mobile phone and makes requests to AWS, the user should not create an IAM user and distribute the user's access key with the app. Instead, he should use an identity provider, such as Login with Amazon, Facebook, or Google to authenticate the users, and then use that identity to get temporary security credentials.

NEW QUESTION 250

- (Topic 3)

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. The user has 3 elastic IPs and is trying to assign one of the Elastic IPs to the VPC instance from the console. The console does not show any instance in the IP assignment screen. What is a possible reason that the instance is unavailable in the assigned IP console?

- A. The IP address may be attached to one of the instances
- B. The IP address belongs to a different zone than the subnet zone
- C. The user has not created an internet gateway
- D. The IP addresses belong to EC2 Classic; so they cannot be assigned to VPC

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. If the user wants to connect to an instance from the internet he should create an elastic IP with VPC. If the elastic IP is a part of EC2 Classic it cannot be assigned to a VPC instance.

NEW QUESTION 254

- (Topic 3)

A sys admin is planning to subscribe to the RDS event notifications. For which of the below mentioned source categories the subscription cannot be configured?

- A. DB security group
- B. DB snapshot
- C. DB options group
- D. DB parameter group

Answer: C

Explanation:

Amazon RDS uses the Amazon Simple Notification Service (SNS) to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group.

NEW QUESTION 255

- (Topic 3)

A user has configured an HTTPS listener on an ELB. The user has not configured any security policy which can help to negotiate SSL between the client and ELB. What will ELB do in this scenario?

- A. By default ELB will select the first version of the security policy
- B. By default ELB will select the latest version of the policy
- C. ELB creation will fail without a security policy
- D. It is not required to have a security policy since SSL is already installed

Answer: B

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the user has created an HTTPS/SSL listener without associating any security policy, Elastic Load Balancing will, by default, associate the latest version of the ELBSecurityPolicy-YYYY-MM with the load balancer.

NEW QUESTION 258

- (Topic 3)

A user is receiving a notification from the RDS DB whenever there is a change in the DB security group. The user does not want to receive these notifications for only a month. Thus, he does not want to delete the notification. How can the user configure this?

- A. Change the Disable button for notification to "Yes" in the RDS console
- B. Set the send mail flag to false in the DB event notification console
- C. The only option is to delete the notification from the console
- D. Change the Enable button for notification to "No" in the RDS console

Answer: D

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. Event notifications are sent to the addresses that the user has provided while creating the subscription. The user can easily turn off the notification without deleting a subscription by setting the Enabled radio button to No in the Amazon RDS console or by setting the Enabled parameter to false using the CLI or Amazon RDS API.

NEW QUESTION 262

- (Topic 3)

A user runs the command "dd if=/dev/xvdf of=/dev/null bs=1M" on an EBS volume created from a snapshot and attached to a Linux instance. Which of the below mentioned activities is the user performing with the step given above?

- A. Pre warming the EBS volume
- B. Initiating the device to mount on the EBS volume
- C. Formatting the volume
- D. Copying the data from a snapshot to the device

Answer: A

Explanation:

When the user creates an EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a volume created from a snapshot and attached with a Linux OS, the “dd” command pre warms the existing data on EBS and any restored snapshots of volumes that have been previously fully pre warmed. This command maintains incremental snapshots; however, because this operation is read-only, it does not pre warm unused space that has never been written to on the original volume. In the command “dd if=/dev/xvdf of=/dev/null bs=1M” , the parameter “if=input file” should be set to the drive that the user wishes to warm. The “of=output file” parameter should be set to the Linux null virtual device, /dev/null. The “bs” parameter sets the block size of the read operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 266

- (Topic 3)

A user is measuring the CPU utilization of a private data centre machine every minute. The machine provides the aggregate of data every hour, such as Sum of data”, “Min value”, “Max value, and “Number of Data points”.

The user wants to send these values to CloudWatch. How can the user achieve this?

- A. Send the data using the put-metric-data command with the aggregate-values parameter
- B. Send the data using the put-metric-data command with the average-values parameter
- C. Send the data using the put-metric-data command with the statistic-values parameter
- D. Send the data using the put-metric-data command with the aggregate –data parameter

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish the data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. When sending the aggregate data, the user needs to send it with the parameter statistic-values: `awscloudwatch put-metric-data --metric-name <Name> --namespace <Custom namespace> --timestamp <UTC Format> --statistic-values Sum=XX,Minimum=YY,Maximum=AA,SampleCount=BB --unit Milliseconds`

NEW QUESTION 270

- (Topic 3)

An organization has configured Auto Scaling with ELB. There is a memory issue in the application which is causing CPU utilization to go above 90%. The higher CPU usage triggers an event for Auto Scaling as per the scaling policy. If the user wants to find the root cause inside the application without triggering a scaling activity, how can he achieve this?

- A. Stop the scaling process until research is completed
- B. It is not possible to find the root cause from that instance without triggering scaling
- C. Delete Auto Scaling until research is completed
- D. Suspend the scaling process until research is completed

Answer: D

Explanation:

Auto Scaling allows the user to suspend and then resume one or more of the Auto Scaling processes in the Auto Scaling group. This is very useful when the user wants to investigate a configuration problem or some other issue, such as a memory leak with the web application and then make changes to the application, without triggering the Auto Scaling process.

NEW QUESTION 273

- (Topic 3)

George has launched three EC2 instances inside the US-East-1a zone with his AWS account. Ray has launched two EC2 instances in the US-East-1a zone with his AWS account. Which of the below entioned statements will help George and Ray understand the availability zone (AZ. concept better?

- A. The instances of George and Ray will be running in the same data centre
- B. All the instances of George and Ray can communicate over a private IP with a minimal cost
- C. All the instances of George and Ray can communicate over a private IP without any cost
- D. The US-East-1a region of George and Ray can be different availability zones

Answer: D

Explanation:

Each AWS region has multiple, isolated locations known as Availability Zones. To ensure that the AWS resources are distributed across the Availability Zones for a region, AWS independently maps the Availability Zones to identifiers for each account. In this case the Availability Zone US-East-1a where George's EC2 instances are running might not be the same location as the US-East-1a zone of Ray's EC2 instances. There is no way for the user to coordinate the Availability Zones between accounts.

NEW QUESTION 278

- (Topic 3)

A sys admin is trying to understand the sticky session algorithm. Please select the correct sequence of steps, both when the cookie is present and when it is not, to help the admin understand the implementation of the sticky session:

ELB inserts the cookie in the response ELB chooses the instance based on the load balancing algorithm Check the cookie in the service request The cookie is found in the request The cookie is not found in the request

- A. 3,1,4,2 [Cookie is not Present] & 3,1,5,2 [Cookie is Present]

- B. 3,4,1,2 [Cookie is not Present] & 3,5,1,2 [Cookie is Present]
- C. 3,5,2,1 [Cookie is not Present] & 3,4,2,1 [Cookie is Present]
- D. 3,2,5,4 [Cookie is not Present] & 3,2,4,5 [Cookie is Present]

Answer: C

Explanation:

Generally AWS ELB routes each request to a zone with the minimum load. The Elastic Load Balancer provides a feature called sticky session which binds the user's session with a specific EC2 instance. The load balancer uses a special load-balancer-generated cookie to track the application instance for each request. When the load balancer receives a request, it first checks to see if this cookie is present in the request. If so, the request is sent to the application instance specified in the cookie. If there is no cookie, the load balancer chooses an application instance based on the existing load balancing algorithm. A cookie is inserted into the response for binding subsequent requests from the same user to that application instance.

NEW QUESTION 283

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AddToLoadBalancer (which adds instances to the load balancer. process for a while. What will happen to the instances launched during the suspension period?

- A. The instances will not be registered with ELB and the user has to manually register when the process is resumed
- B. The instances will be registered with ELB only once the process has resumed
- C. Auto Scaling will not launch the instance during this period due to process suspension
- D. It is not possible to suspend only the AddToLoadBalancer process

Answer: A

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate, add to Load Balancer etc. The user can also suspend the individual process. The AddToLoadBalancer process type adds instances to the load balancer when the instances are launched. If this process is suspended, Auto Scaling will launch the instances but will not add them to the load balancer. When the user resumes this process, Auto Scaling will resume adding new instances launched after resumption to the load balancer. However, it will not add running instances that were launched while the process was suspended; those instances must be added manually.

NEW QUESTION 285

- (Topic 3)

A user has configured an ELB to distribute the traffic among multiple instances. The user instances are facing some issues due to the back-end servers. Which of the below mentioned CloudWatch metrics helps the user understand the issue with the instances?

- A. HTTPCode_Backend_3XX
- B. HTTPCode_Backend_4XX
- C. HTTPCode_Backend_2XX
- D. HTTPCode_Backend_5XX

Answer: D

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For ELB, CloudWatch provides various metrics including error code by ELB as well as by back-end servers (instances.. It gives data for the count of the number of HTTP response codes generated by the back-end instances. This metric does not include any response codes generated by the load balancer. These metrics are: The 2XX class status codes represents successful actions The 3XX class status code indicates that the user agent requires action The 4XX class status code represents client errors The 5XX class status code represents back-end server errors

NEW QUESTION 288

- (Topic 3)

A user has created a VPC with two subnets: one public and one private. The user is planning to run the patch update for the instances in the private subnet. How can the instances in the private subnet connect to the internet?

- A. Use the internet gateway with a private IP
- B. Allow outbound traffic in the security group for port 80 to allow internet updates
- C. The private subnet can never connect to the internet
- D. Use NAT with an elastic IP

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created two subnets (one private and one public., he would need a Network Address Translation (NAT) instance with the elastic IP address. This enables the instances in the private subnet to send requests to the internet (for example, to perform software updates..

NEW QUESTION 289

- (Topic 3)

Which of the below mentioned AWS RDS logs cannot be viewed from the console for MySQL?

- A. Error Log
- B. Slow Query Log
- C. Transaction Log

D. General Log

Answer: C

Explanation:

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI), or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow querylog, and general logs. RDS does not support viewing the transaction logs.

NEW QUESTION 291

- (Topic 3)

An AWS account wants to be part of the consolidated billing of his organization's payee account. How can the owner of that account achieve this?

- A. The payee account has to request AWS support to link the other accounts with his account
- B. The owner of the linked account should add the payee account to his master account list from the billing console
- C. The payee account will send a request to the linked account to be a part of consolidated billing
- D. The owner of the linked account requests the payee account to add his account to consolidated billing

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. To add a particular account (linked to the master (payee) account, the payee account has to request the linked account to join consolidated billing. Once the linked account accepts the request henceforth all charges incurred by the linked account will be paid by the payee account.

NEW QUESTION 292

- (Topic 3)

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a Host key not found error. Which of the below mentioned options is a possible reason for rejection?

- A. The user has provided the wrong user name for the OS login
- B. The instance CPU is heavily loaded
- C. The security group is not configured properly
- D. The access key to connect to the instance is wrong

Answer: A

Explanation:

If the user is trying to connect to a Linux EC2 instance and receives the Host Key not found error the probable reasons are: The private key pair is not right The user name to login is wrong

NEW QUESTION 297

- (Topic 3)

How can software determine the public and private IP addresses of the Amazon EC2 instance that it is running on?

- A. Query the local instance metadat
- B. Query the appropriate Amazon CloudWatch metri
- C. Query the local instance userdat
- D. Use ipconfig or ifconfig comman

Answer: B

NEW QUESTION 300

- (Topic 3)

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. Which of the below mentioned SSL protocols is not supported by the security policy?

- A. TLS 1.3
- B. TLS 1.2
- C. SSL 2.0
- D. SSL 3.0

Answer: A

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. Elastic Load Balancing supports the following versions of the SSL protocol: TLS 1.2 TLS 1.1 TLS 1.0 SSL 3.0 SSL 2.0

NEW QUESTION 303

- (Topic 3)

A user has configured ELB with a TCP listener at ELB as well as on the back-end instances. The user wants to enable a proxy protocol to capture the source and destination IP information in the header. Which of the below mentioned statements helps the user understand a proxy protocol with TCP configuration?

- A. If the end user is requesting behind a proxy server then the user should not enable a proxy protocol on ELB
- B. ELB does not support a proxy protocol when it is listening on both the load balancer and the back-end instances
- C. Whether the end user is requesting from a proxy server or directly, it does not make a difference for the proxy protocol
- D. If the end user is requesting behind the proxy then the user should add the “isproxy” flag to the ELB Configuration

Answer: A

Explanation:

When the user has configured Transmission Control Protocol (TCP) or Secure Sockets Layer (SSL) for both front-end and back-end connections of the Elastic Load Balancer, the load balancer forwards the request to the back-end instances without modifying the request headers unless the proxy header is enabled. If the end user is requesting from a Proxy Protocol enabled proxy server, then the ELB admin should not enable the Proxy Protocol on the load balancer. If the Proxy Protocol is enabled on both the proxy server and the load balancer, the load balancer will add another header to the request which already has a header from the proxy server. This duplication may result in errors.

NEW QUESTION 308

- (Topic 3)

A storage admin wants to encrypt all the objects stored in S3 using server side encryption. The user does not want to use the AES 256 encryption key provided by S3. How can the user achieve this?

- A. The admin should upload his secret key to the AWS console and let S3 decrypt the objects
- B. The admin should use CLI or API to upload the encryption key to the S3 bucket
- C. When making a call to the S3 API mention the encryption key URL in each request
- D. S3 does not support client supplied encryption keys for server side encryption
- E. The admin should send the keys and encryption algorithm with each API call

Answer: D

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key. Amazon S3 never stores the user's encryption key. The user has to supply it for each encryption or decryption call.

NEW QUESTION 310

- (Topic 3)

A .NET application that you manage is running in Elastic Beanstalk. Your developers tell you they will need access to application log files to debug issues that arise. The infrastructure will scale up and down.

How can you ensure the developers will be able to access only the log files?

- A. Access the log files directly from Elastic Beanstalk
- B. Enable log file rotation to S3 within the Elastic Beanstalk configuration
- C. Ask your developers to enable log file rotation in the applications web.config file
- D. Connect to each Instance launched by Elastic Beanstalk and create a Windows Scheduled task to rotate the log files to S3.

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.loggingS3.title.html>

NEW QUESTION 315

- (Topic 3)

A user has enabled versioning on an S3 bucket. The user is using server side encryption for data at Rest. If the user is supplying his own keys for encryption (SSE-C), which of the below mentioned statements is true?

- A. The user should use the same encryption key for all versions of the same object
- B. It is possible to have different encryption keys for different versions of the same object
- C. AWS S3 does not allow the user to upload his own keys for server side encryption
- D. The SSE-C does not work when versioning is enabled

Answer: B

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C). If the bucket is versioning-enabled, each object version uploaded by the user using the SSE-C feature can have its own encryption key. The user is responsible for tracking which encryption key was used for which object's version

NEW QUESTION 319

- (Topic 3)

A user has created an application which will be hosted on EC2. The application makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK to connect with from the EC2 instance. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should attach an IAM role with DynamoDB access to the EC2 instance
- B. The user should create an IAM user with DynamoDB access and use its credentials within the application to connect with DynamoDB
- C. The user should create an IAM role, which has EC2 access so that it will allow deploying the application

- D. The user should create an IAM user with DynamoDB and EC2 access
- E. Attach the user with the application so that it does not use the root account credentials

Answer: A

Explanation:

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. Instead, the user should use roles for EC2 and give that role access to DynamoDB /S3. When the roles are attached to EC2, it will give temporary security credentials to the application hosted on that EC2, to connect with DynamoDB / S3.

NEW QUESTION 324

- (Topic 3)

A user has created a VPC with a subnet and a security group. The user has launched an instance in that subnet and attached a public IP. The user is still unable to connect to the instance. The internet gateway has also been created. What can be the reason for the error?

- A. The internet gateway is not configured with the route table
- B. The private IP is not present
- C. The outbound traffic on the security group is disabled
- D. The internet gateway is not configured with the security group

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. When a user launches an instance and wants to connect to an instance, he needs an internet gateway. The internet gateway should be configured with the route table to allow traffic from the internet.

NEW QUESTION 328

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24) and VPN only subnets CIDR (20.0.1.0/24) along with the VPN gateway (vgw-12345) to connect to the user's data centre. The user's data centre has CIDR 172.28.0.0/12. The user has also setup a NAT instance (i-123456) to allow traffic to the internet from the VPN subnet. Which of the below mentioned options is not a valid entry for the main route table in this scenario?

- A. Destination: 20.0.1.0/24 and Target: i-12345
- B. Destination: 0.0.0.0/0 and Target: i-12345
- C. Destination: 172.28.0.0/12 and Target: vgw-12345
- D. Destination: 20.0.0.0/16 and Target: local

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. If the user has setup a NAT instance to route all the internet requests then all requests to the internet should be routed to it. All requests to the organization's DC will be routed to the VPN gateway. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: i-12345 (To route all internet traffic to the NAT Instance. Destination: 172.28.0.0/12 & Target: vgw-12345 (To route all the organization's data centre traffic to the VPN gateway. Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC).

NEW QUESTION 329

- (Topic 3)

A user has enabled termination protection on an EC2 instance. The user has also set Instance initiated shutdown behaviour to terminate. When the user shuts down the instance from the OS, what will happen?

- A. The OS will shutdown but the instance will not be terminated due to protection
- B. It will terminate the instance
- C. It will not allow the user to shutdown the instance from the OS
- D. It is not possible to set the termination protection when an Instance initiated shutdown is set to Terminate

Answer: B

Explanation:

It is always possible that someone can terminate an EC2 instance using the Amazon EC2 console, command line interface or API by mistake. If the admin wants to prevent the instance from being accidentally terminated, he can enable termination protection for that instance. The user can also setup shutdown behaviour for an EBS backed instance to guide the instance on what should be done when he initiates shutdown from the OS using Instance initiated shutdown behaviour. If the instance initiated behaviour is set to terminate and the user shuts off the OS even though termination protection is enabled, it will still terminate the instance.

NEW QUESTION 334

- (Topic 3)

An organization is measuring the latency of an application every minute and storing data inside a file in the JSON format. The organization wants to send all latency data to AWS CloudWatch. How can the organization achieve this?

- A. The user has to parse the file before uploading data to CloudWatch

- B. It is not possible to upload the custom data to CloudWatch
- C. The user can supply the file as an input to the CloudWatch command
- D. The user can use the CloudWatch Import command to import data from the file to CloudWatch

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user has to always include the namespace as part of the request. If the user wants to upload the custom data from a Amazon AWS-SysOps : Practice Test file, he can supply file name along with the parameter -- metric-data to command put-metric-data.

NEW QUESTION 335

- (Topic 3)

A user has created an Auto Scaling group using CLI. The user wants to enable CloudWatch detailed monitoring for that group. How can the user configure this?

- A. When the user sets an alarm on the Auto Scaling group, it automatically enables detail monitoring
- B. By default detailed monitoring is enabled for Auto Scaling
- C. Auto Scaling does not support detailed monitoring
- D. Enable detail monitoring from the AWS console

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates an Auto Scaling launch config as the first step for creating an Auto Scaling group, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. Thus, the user does not need to set this flag if he wants detailed monitoring.

NEW QUESTION 338

- (Topic 3)

A user has granted read/write permission of his S3 bucket using ACL. Which of the below mentioned options is a valid ID to grant permission to other AWS accounts (grantee. using ACL?

- A. IAM User ID
- B. S3 Secure ID
- C. Access ID
- D. Canonical user ID

Answer: D

Explanation:

An S3 bucket ACL grantee can be an AWS account or one of the predefined Amazon S3 groups. The user can grant permission to an AWS account by the email address of that account or by the canonical user ID. If the user provides an email in the grant request, Amazon S3 finds the canonical user ID for that account and adds it to the ACL. The resulting ACL will always contain the canonical user ID for the AWS account, and not the AWS account's email address.

NEW QUESTION 343

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created one subnet with CIDR 20.0.0.0/16 by mistake. The user is trying to create another subnet of CIDR 20.0.0.1/24. How can the user create the second subnet?

- A. There is no need to update the subnet as VPC automatically adjusts the CIDR of the first subnet based on the second subnet's CIDR
- B. The user can modify the first subnet CIDR from the console
- C. It is not possible to create a second subnet as one subnet with the same CIDR as the VPC has been created
- D. The user can modify the first subnet CIDR with AWS CLI

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside the subnet. The user can create a subnet with the same size of VPC. However, he cannot create any other subnet since the CIDR of the second subnet will conflict with the first subnet. The user cannot modify the CIDR of a subnet once it is created. Thus, in this case if required, the user has to delete the subnet and create new subnets.

NEW QUESTION 347

- (Topic 3)

A user has launched a Windows based EC2 instance. However, the instance has some issues and the user wants to check the log. When the user checks the Instance console output from the AWS console, what will it display?

- A. All the event logs since instance boot
- B. The last 10 system event log error
- C. The Windows instance does not support the console output
- D. The last three system events' log errors

Answer: D

Explanation:

The AWS EC2 console provides a useful tool called Console output for problem diagnosis. It is useful to find out any kernel issues, termination reasons or service configuration issues. For a Windows instance it lists the last three system event log errors. For Linux it displays the exact console output.

NEW QUESTION 351

- (Topic 3)

Your organization is preparing for a security assessment of your use of AWS.

In preparation for this assessment, which two IAM best practices should you consider implementing? Choose 2 answers

- A. Create individual IAM users for everyone in your organization
- B. Configure MFA on the root account and for privileged IAM users
- C. Assign IAM users and groups configured with policies granting least privilege access
- D. Ensure all users have been assigned and are frequently rotating a password, access ID/secret key, and X.509 certificate

Answer: BC

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

NEW QUESTION 353

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using VPC Wizard. The user has created a public CIDR

(20.0.0.0/24. and a VPN only subnet CIDR (20.0.1.0/24. along with the hardware VPN access to connect to the user's data centre. Which of the below mentioned components is not present when the VPC is setup with the wizard?

- A. Main route table attached with a VPN only subnet
- B. A NAT instance configured to allow the VPN subnet instances to connect with the internet
- C. Custom route table attached with a public subnet
- D. An internet gateway for a public subnet

Answer: B

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. The wizard does not create a NAT instance by default. The user can create it manually and attach it with a VPN only subnet.

NEW QUESTION 358

.....

About ExamBible

[Your Partner of IT Exam](#)

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

- (Topic 1)

Your team is excited about the use of AWS because now they have access to programmable Infrastructure. You have been asked to manage your AWS infrastructure in a manner similar to the way you might manage application code. You want to be able to deploy exact copies of different versions of your infrastructure, stage changes into different environments, revert back to previous versions, and identify what versions are running at any particular time (development, test, QA, production).

Which approach addresses this requirement?

- A. Use cost allocation reports and AWS OpsWorks to deploy and manage your infrastructure
- B. Use AWS CloudWatch metrics and alerts along with resource tagging to deploy and manage your infrastructure
- C. Use AWS Beanstalk and a version control system like GIT to deploy and manage your infrastructure
- D. Use AWS CloudFormation and a version control system like GIT to deploy and manage your infrastructure

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/opsworks/faqs/>

NEW QUESTION 2

- (Topic 1)

A media company produces new video files on-premises every day with a total size of around 100GBs after compression. All files have a size of 1-2 GB and need to be uploaded to Amazon S3 every night in a fixed time window between 3am and 5am. Current upload takes almost 3 hours, although less than half of the available bandwidth is used.

What step(s) would ensure that the file uploads are able to complete in the allotted time window?

- A. Increase your network bandwidth to provide faster throughput to S3
- B. Upload the files in parallel to S3
- C. Pack all files into a single archive, upload it to S3, then extract the files in AWS
- D. Use AWS Import/Export to transfer the video files

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/importexport/faqs/>

NEW QUESTION 3

- (Topic 1)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB instance is switched to the standby DB instance
- B. The RDS (Relational Database Service) DB instance reboots
- C. A new DB instance is created in the standby availability zone
- D. The canonical name record (CNAME) is changed from primary to standby

Answer: D

NEW QUESTION 4

- (Topic 1)

How can the domain's zone apex for example "myzoneapexdomain.com" be pointed towards an Elastic Load Balancer?

- A. By using an AAAA record
- B. By using an A record
- C. By using an Amazon Route 53 CNAME record
- D. By using an Amazon Route 53 Alias record

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/resource-record-sets-choosing-alias-non-alias.html>

NEW QUESTION 5

- (Topic 1)

You are tasked with setting up a cluster of EC2 Instances for a NoSQL database. The database requires random read IO disk performance up to a 100,000 IOPS at 4KB block size per node.

Which of the following EC2 instances will perform the best for this workload?

- A. A High-Memory Quadruple Extra Large (m2.4xlarge) with EBS-Optimized set to true and a Provisioned IOPS EBS volume
- B. A Cluster Compute Eight Extra Large (cc2.8xlarge) using instance storage
- C. High I/O Quadruple Extra Large (hi1.4xlarge) using instance storage
- D. A Cluster GPU Quadruple Extra Large (cg1.4xlarge) using four separate 4000 PIOPS EBS volumes in a RAID 0 configuration

Answer: C

Explanation:

Explanation: Reference:
<http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 6

- (Topic 1)

You use S3 to store critical data for your company. Several users within your group currently have full permissions to your S3 buckets. You need to come up with a solution that does not impact your users and also protect against the accidental deletion of objects.

Which two options will address this issue? Choose 2 answers.

- A. Enable versioning on your S3 Buckets
- B. Configure your S3 Buckets with MFA delete
- C. Create a Bucket policy and only allow read-only permissions to all users at the bucket level
- D. Enable object life cycle policies and configure the data older than 3 months to be archived in Glacier

Answer: AB

NEW QUESTION 7

- (Topic 1)

You have been asked to leverage Amazon VPC, EC2, and SQS to implement an application that submits and receives millions of messages per second to a message queue. You want to ensure your application has sufficient bandwidth between your EC2 instances and SQS. Which option will provide the most scalable solution for communicating between the application and SQS?

- A. Ensure the application instances are properly configured with an Elastic Load Balancer
- B. Ensure the application instances are launched in private subnets with the EBS-optimized option enabled
- C. Ensure the application instances are launched in public subnets with the `associate-public-ip-address=true` option enabled
- D. Launch application instances in private subnets with an Auto Scaling group and Auto Scaling triggers configured to watch the SQS queue size

Answer: B

Explanation:

Reference:
<http://www.cardinalpath.com/autoscaling-your-website-with-amazon-web-services-part-2/>

NEW QUESTION 8

- (Topic 1)

You have a web-style application with a stateless but CPU and memory-intensive web tier running on a `cc2.8xlarge` EC2 instance inside of a VPC. The instance, when under load, is having problems returning requests within the SLA as defined by your business. The application maintains its state in a DynamoDB table, but the data tier is properly provisioned and responses are consistently fast.

How can you best resolve the issue of the application responses not meeting your SLA?

- A. Add another `cc2.8xlarge` application instance, and put both behind an Elastic Load Balancer
- B. Move the `cc2.8xlarge` to the same Availability Zone as the DynamoDB table
- C. Cache the database responses in ElastiCache for more rapid access
- D. Move the database from DynamoDB to RDS MySQL in scale-out read-replica configuration

Answer: B

Explanation:

Reference:
<http://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 9

- (Topic 1)

You have set up individual AWS accounts for each project. You have been asked to make sure your AWS Infrastructure costs do not exceed the budget set per project for each month.

Which of the following approaches can help ensure that you do not exceed the budget each month?

- A. Consolidate your accounts so you have a single bill for all accounts and projects
- B. Set up auto scaling with CloudWatch alarms using SNS to notify you when you are running too many instances in a given account
- C. Set up CloudWatch billing alerts for all AWS resources used by each project, with a notification occurring when the amount for each resource tagged to a particular project matches the budget allocated to the project
- D. Set up CloudWatch billing alerts for all AWS resources used by each account, with email notifications when it hits 50%, 80%, and 90% of its budgeted monthly spend

Answer: C

NEW QUESTION 10

- (Topic 1)

You run a web application where web servers on EC2 instances are in an Auto Scaling group. Monitoring over the last 6 months shows that 6 web servers are necessary to handle the minimum load. During the day, up to 12 servers are needed. Five to six days per year, the number of web servers required might go up to 15.

What would you recommend to minimize costs while being able to provide high availability?

- A. 6 Reserved instances (heavy utilization), 6 Reserved instances (medium utilization), rest covered by On-Demand instances
- B. 6 Reserved instances (heavy utilization), 6 On-Demand instances, rest covered by Spot instances
- C. 6 Reserved instances (heavy utilization), 6 Spot instances, rest covered by On-Demand instances
- D. 6 Reserved instances (heavy utilization), 6 Reserved instances (medium utilization), rest covered by Spot instances

Answer: B

NEW QUESTION 10

- (Topic 1)

You have a web application leveraging an Elastic Load Balancer (ELB) In front of the web servers deployed using an Auto Scaling Group Your database is running on Relational

Database Service (RDS) The application serves out technical articles and responses to them in general there are more views of an article than there are responses to the article. On occasion, an article on the site becomes extremely popular resulting in significant traffic Increases that causes the site to go down.

What could you do to help alleviate the pressure on the infrastructure while maintaining availability during these events?

Choose 3 answers

- A. Leverage CloudFront for the delivery of the article
- B. Add RDS read-replicas for the read traffic going to your relational database
- C. Leverage ElastiCache for caching the most frequently used dat
- D. Use SOS to queue up the requests for the technical posts and deliver them out of the queu
- E. Use Route53 health checks to fail over to an S3 bucket for an error pag

Answer: ACE

NEW QUESTION 14

- (Topic 1)

You are tasked with the migration of a highly trafficked Node JS application to AWS In order to comply with organizational standards Chef recipes must be used to configure the application servers that host this application and to support application lifecycle events.

Which deployment option meets these requirements while minimizing administrative burden?

- A. Create a new stack within Opsworks add the appropriate layers to the stack and deploy the application
- B. Create a new application within Elastic Beanstalk and deploy this application to a new environment
- C. Launch a Mode JS server from a community AMI and manually deploy the application to the launched EC2 instance
- D. Launch and configure Chef Server on an EC2 instance and leverage the AWS CLI to launch application servers and configure those instances using Che

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.html>

NEW QUESTION 16

- (Topic 1)

You are running a database on an EC2 instance, with the data stored on Elastic Block Store (EBS) for persistence At times throughout the day, you are seeing large variance in the response times of the database queries Looking into the instance with the isolate command you see a lot of wait time on the disk volume that the database's data is stored on.

What two ways can you improve the performance of the database's storage while maintaining the current persistence of the data?

Choose 2 answers

- A. Move to an SSD backed instance
- B. Move the database to an EBS-Optimized Instance
- C. T Use Provisioned IOPs EBS
- D. Use the ephemeral storage on an m2 4xlarge Instance Instead

Answer: AB

NEW QUESTION 19

- (Topic 1)

Which of the following requires a custom CloudWatch metric to monitor?

- A. Data transfer of an EC2 instance
- B. Disk usage activity of an EC2 instance
- C. Memory Utilization of an EC2 instance
- D. CPU Utilization of an EC2 instance

Answer: C

Explanation:

Reference:

<http://aws.amazon.com/cloudwatch/>

NEW QUESTION 22

- (Topic 1)

When an EC2 EBS-backed (EBS root) instance is stopped, what happens to the data on any ephemeral store volumes?

- A. Data will be deleted and win no longer be accessible
- B. Data is automatically saved in an EBS volum
- C. Data is automatically saved as an EBS snapshot
- D. Data is unavailable until the instance is restarted

Answer: D

NEW QUESTION 27

- (Topic 1)

Your application currently leverages AWS Auto Scaling to grow and shrink as load increases/ decreases and has been performing well. Your marketing team expects a steady ramp up in traffic to follow an upcoming campaign that will result in a 20x growth in traffic over 4 weeks. Your forecast for the approximate number of Amazon EC2 instances necessary to meet the peak demand is 175.

What should you do to avoid potential service disruptions during the ramp up in traffic?

- A. Ensure that you have pre-allocated 175 Elastic IP addresses so that each server will be able to obtain one as it launches
- B. Check the service limits in Trusted Advisor and adjust as necessary so the forecasted count remains within limit
- C. Change your Auto Scaling configuration to set a desired capacity of 175 prior to the launch of the marketing campaign
- D. Pre-warm your Elastic Load Balancer to match the requests per second anticipated during peak demand prior to the marketing campaign

Answer: D

NEW QUESTION 28

- (Topic 1)

If you want to launch Amazon Elastic Compute Cloud (EC2) Instances and assign each Instance a predetermined private IP address you should:

- A. Assign a group or sequential Elastic IP address to the instances
- B. Launch the instances in a Placement Group
- C. Launch the instances in the Amazon virtual Private Cloud (VPC).
- D. Use standard EC2 instances since each instance gets a private Domain Name Service (DNS) already
- E. Launch the Instance from a private Amazon Machine image (AMI)

Answer: C

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-ip-addressing.html>

NEW QUESTION 30

- (Topic 1)

You have an Auto Scaling group associated with an Elastic Load Balancer (ELB). You have noticed that instances launched via the Auto Scaling group are being marked unhealthy due to an ELB health check, but these unhealthy instances are not being terminated.

What do you need to do to ensure that instances marked unhealthy by the ELB will be terminated and replaced?

- A. Change the thresholds set on the Auto Scaling group health check
- B. Add an Elastic Load Balancing health check to your Auto Scaling group
- C. Increase the value for the Health check interval set on the Elastic Load Balancer
- D. Change the health check set on the Elastic Load Balancer to use TCP rather than HTTP checks

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-add-elb-healthcheck.html>

Add an Elastic Load Balancing Health Check to your Auto Scaling Group

By default, an Auto Scaling group periodically reviews the results of EC2 instance status to determine the health state of each instance. However, if you have associated your Auto Scaling group with an Elastic Load Balancing load balancer, you can choose to use the Elastic Load Balancing health check. In this case, Auto Scaling determines the health status of your instances by checking the results of both the EC2 instance status check and the Elastic Load Balancing instance health check.

For information about EC2 instance status checks, see *Monitor Instances With Status Checks* in the *Amazon EC2 User Guide for Linux Instances*. For information about Elastic Load Balancing health checks, see *Health Check* in the *Elastic Load Balancing Developer Guide*.

This topic shows you how to add an Elastic Load Balancing health check to your Auto Scaling group, assuming that you have created a load balancer and have registered the load balancer with your Auto Scaling group. If you have not registered the load balancer with your Auto Scaling group, see *Set Up a Scaled and Load-Balanced Application*.

Auto Scaling marks an instance unhealthy if the calls to the Amazon EC2 action `DescribeInstanceStatus` return any state other than `running`, the system status shows `impaired`, or the calls to Elastic Load Balancing action `DescribeInstanceHealth` returns `OutOfService` in the instance state field.

If there are multiple load balancers associated with your Auto Scaling group, Auto Scaling checks the health state of your EC2 instances by making health check calls to each load balancer. For each call, if the Elastic Load Balancing action returns any state other than `InService`, the instance is marked as unhealthy. After Auto Scaling marks an instance as unhealthy, it remains in that state, even if subsequent calls from other load balancers return an `InService` state for the same instance.

NEW QUESTION 32

- (Topic 1)

Your company is moving towards tracking web page users with a small tracking

image loaded on each page. Currently you are serving this image out of US-East, but are starting to get concerned about the time it takes to load the image for users on the west coast.

What are the two best ways to speed up serving this image?

Choose 2 answers

- A. Use Route 53's Latency Based Routing and serve the image out of US-West-2 as well as US-East-1
- B. Serve the image out through CloudFront
- C. Serve the image out of S3 so that it isn't being served out of your web application tier
- D. Use EBS PIOPs to serve the image faster out of your EC2 instances

Answer: AD

NEW QUESTION 35

- (Topic 1)

When attached to an Amazon VPC which two components provide connectivity with external networks? Choose 2 answers

- A. Elastic IPS (EIP)
- B. NAT Gateway (NAT)
- C. Internet Gateway (IGW)
- D. Virtual Private Gateway (VGW)

Answer: CD

NEW QUESTION 40

- (Topic 1)

You have been asked to automate many routine systems administrator backup and recovery activities. Your current plan is to leverage AWS-managed solutions as much as possible and automate the rest with the AWS CLI and scripts.

Which task would be best accomplished with a script?

- A. Creating daily EBS snapshots with a monthly rotation of snapshots
- B. Creating daily RDS snapshots with a monthly rotation of snapshots
- C. Automatically detect and stop unused or underutilized EC2 instances
- D. Automatically add Auto Scaled EC2 instances to an Amazon Elastic Load Balancer

Answer: A

NEW QUESTION 45

- (Topic 1)

What are characteristics of Amazon S3? Choose 2 answers

- A. Objects are directly accessible via a URL
- B. S3 should be used to host a relational database
- C. S3 allows you to store objects of virtually unlimited size
- D. S3 allows you to store virtually unlimited amounts of data
- E. S3 offers Provisioned IOPS

Answer: AD

NEW QUESTION 50

- (Topic 2)

A user is accessing RDS from an application. The user has enabled the Multi AZ feature with the MS SQL RDS DB. During a planned outage how will AWS ensure that a switch from DB to a standby replica will not affect access to the application?

- A. RDS will have an internal IP which will redirect all requests to the new DB
- B. RDS uses DNS to switch over to stand by replica for seamless transition
- C. The switch over changes Hardware so RDS does not need to worry about access
- D. RDS will have both the DBs running independently and the user has to manually switch over

Answer: B

Explanation:

In the event of a planned or unplanned outage of a DB instance, Amazon RDS automatically switches to a standby replica in another Availability Zone if the user has enabled Multi AZ. The automatic failover mechanism simply changes the DNS record of the DB instance to point to the standby DB instance. As a result, the user will need to re-establish any existing connections to the DB instance. However, as the DNS is the same, the application can access DB seamlessly.

NEW QUESTION 51

- (Topic 2)

You are managing the AWS account of a big organization. The organization has more than 1000+ employees and they want to provide access to the various services to most of the employees. Which of the below mentioned options is the best possible solution in this case?

- A. The user should create a separate IAM user for each employee and provide access to them as per the policy
- B. The user should create an IAM role and attach STS with the role
- C. The user should attach that role to the EC2 instance and setup AWS authentication on that server
- D. The user should create IAM groups as per the organization's departments and add each user to the group for better access control
- E. Attach an IAM role with the organization's authentication service to authorize each user for various AWS services

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user is managing an AWS account for an organization that already has an identity system, such as the login system for the corporate network (SSO). In this case, instead of creating individual IAM users or groups for each user who need AWS access, it may be more practical to use a proxy server to translate the user identities from the organization network into the temporary AWS security credentials. This proxy server will attach an IAM role to the user after authentication.

NEW QUESTION 54

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16 with only a private subnet and VPN connection using the VPC wizard. The user wants to connect to the instance in a private subnet over SSH. How should the user define the security rule for SSH?

- A. Allow Inbound traffic on port 22 from the user's network
- B. The user has to create an instance in EC2 Classic with an elastic IP and configure the security group of a private subnet to allow SSH from that elastic IP
- C. The user can connect to a instance in a private subnet using the NAT instance
- D. Allow Inbound traffic on port 80 and 22 to allow the user to connect to a private subnet over the Internet

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, the user can setup a case with a VPN only subnet (private. which uses VPN access to connect with his data centre. When the user has configured this setup with Wizard, all network connections to the instances in the subnet will come from his data centre. The user has to configure the security group of the private subnet which allows the inbound traffic on SSH (port 22. from the data centre's network range.

NEW QUESTION 58

- (Topic 2)

A system admin is managing buckets, objects and folders with AWS S3. Which of the below mentioned statements is true and should be taken in consideration by the sysadmin?

- A. The folders support only ACL
- B. Both the object and bucket can have an Access Policy but folder cannot have policy
- C. Folders can have a policy
- D. Both the object and bucket can have ACL but folders cannot have ACL

Answer: A

Explanation:

A sysadmin can grant permission to the S3 objects or the buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice a versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level. The folders are similar to objects with no content. Thus, folders can have only ACL and cannot have a policy.

NEW QUESTION 60

- (Topic 2)

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- B. The organization should create each user in a separate region so that they have their own URL to login
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group
- E. The user can login with their own group ID

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

NEW QUESTION 64

- (Topic 2)

A user has created a photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Glacier
- B. AWS Elastic Transcoder
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

NEW QUESTION 66

- (Topic 2)

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day

D. AWS PIOPS volume of 10 GB size

Answer: D

Explanation:

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

NEW QUESTION 71

- (Topic 2)

A user is planning to use AWS Cloud formation for his automatic deployment requirements. Which of the below mentioned components are required as a part of the template?

- A. Parameters
- B. Outputs
- C. Template version
- D. Resources

Answer: D

Explanation:

AWS Cloud formation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. It can have option fields, such as Template Parameters, Output, Data tables, and Template file format version. The only mandatory value is Resource. The user can define the AWS services which will be used/ created by this template inside the Resource section

NEW QUESTION 74

- (Topic 2)

A user has created a queue named “myqueue” in US-East region with AWS SQS. The user’s AWS account ID is 123456789012. If the user wants to perform some action on this queue, which of the below Queue URL should he use?

- A. <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>
- B. <http://sqs.amazonaws.com/123456789012/myqueue>
- C. <http://sq>
- D. 123456789012.us-east-1.amazonaws.com/myqueue
- E. [http:// 123456789012.sq](http://123456789012.sq)
- F. us-east-1.amazonaws.com/myqueue

Answer: A

Explanation:

When creating a new queue in SQS, the user must provide a queue name that is unique within the scope of all queues of user’s account. If the user creates queues using both the latest WSDL and a previous version, he will have a single namespace for all his queues. Amazon SQS assigns each queue created by user an identifier called a queue URL, which includes the queue name and other components that Amazon SQS determines. Whenever the user wants to perform an action on a queue, he must provide its queue URL. The queue URL for the account id 123456789012 & queue name “myqueue” in US-East-1 region will be <http://sqs.us-east-1.amazonaws.com/123456789012/myqueue>.

NEW QUESTION 79

- (Topic 2)

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department’s employees

Answer: A

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

NEW QUESTION 80

- (Topic 2)

A root AWS account owner is trying to understand various options to set the permission to AWS S3. Which of the below mentioned options is not the right option to grant permission for S3?

- A. User Access Policy
- B. S3 Object Access Policy
- C. S3 Bucket Access Policy
- D. S3 ACL

Answer: B

Explanation:

Amazon S3 provides a set of operations to work with the Amazon S3 resources. Managing S3 resource access refers to granting others permissions to work with S3. There are three ways the root account owner can define access with S3: S3 ACL: The user can use ACLs to grant basic read/write permissions to other AWS accounts. S3 Bucket Policy: The policy is used to grant other AWS accounts or IAM users permissions for the bucket and the objects in it. User Access Policy: Define an IAM user and assign him the IAM policy which grants him access to S3.

NEW QUESTION 83

- (Topic 2)

A user is running one instance for only 3 hours every day. The user wants to save some cost with the instance. Which of the below mentioned Reserved Instance categories is advised in this case?

- A. The user should not use RI; instead only go with the on-demand pricing
- B. The user should use the AWS high utilized RI
- C. The user should use the AWS medium utilized RI
- D. The user should use the AWS low utilized RI

Answer: A

Explanation:

The AWS Reserved Instance provides the user with an option to save some money by paying a one-time fixed amount and then save on the hourly rate. It is advisable that if the user is having 30% or more usage of an instance per day, he should go for a RI. If the user is going to use an EC2 instance for more than 2200-2500 hours per year, RI will help the user save some cost. Here, the instance is not going to run for less than 1500 hours. Thus, it is advisable that the user should use the on-demand pricing.

NEW QUESTION 84

- (Topic 2)

An organization has setup consolidated billing with 3 different AWS accounts. Which of the below mentioned advantages will organization receive in terms of the AWS pricing?

- A. The consolidated billing does not bring any cost advantage for the organization
- B. All AWS accounts will be charged for S3 storage by combining the total storage of each account
- C. The EC2 instances of each account will receive a total of 750*3 micro instance hours free
- D. The free usage tier for all the 3 accounts will be 3 years and not a single year

Answer: B

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. For billing purposes, AWS treats all the accounts on the consolidated bill as one account. Some services, such as Amazon EC2 and Amazon S3 have volume pricing tiers across certain usage dimensions that give the user lower prices when he uses the service more.

NEW QUESTION 87

- (Topic 2)

A user has configured ELB with three instances. The user wants to achieve High Availability as well as redundancy with ELB. Which of the below mentioned AWS services helps the user achieve this for ELB?

- A. Route 53
- B. AWS Mechanical Turk
- C. Auto Scaling
- D. AWS EMR

Answer: A

Explanation:

The user can provide high availability and redundancy for applications running behind Elastic Load Balancer by enabling the Amazon Route 53 Domain Name System (DNS) failover for the load balancers. Amazon Route 53 is a DNS service that provides reliable routing to the user's infrastructure.

NEW QUESTION 88

- (Topic 2)

A user has enabled the Multi AZ feature with the MS SQL RDS database server. Which of the below mentioned statements will help the user understand the Multi AZ feature better?

- A. In a Multi AZ, AWS runs two DBs in parallel and copies the data asynchronously to the replica copy
- B. In a Multi AZ, AWS runs two DBs in parallel and copies the data synchronously to the replica copy
- C. In a Multi AZ, AWS runs just one DB but copies the data synchronously to the standby replica
- D. AWS MS SQL does not support the Multi AZ feature

Answer: C

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. In a Multi-AZ deployment, Amazon RDS automatically

provisions and maintains a synchronous standby replica in a different Availability Zone. The primary DB instance is synchronously replicated across Availability Zones to a standby replica to provide data redundancy, eliminate I/O freezes, and minimize latency spikes during system backups. Running a DB instance with high availability can enhance availability during planned system maintenance, and help protect your databases against DB instance failure and Availability Zone disruption. Note that the high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a read replica.

NEW QUESTION 91

- (Topic 2)

An organization is setting up programmatic billing access for their AWS account. Which of the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

Answer: C

Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3) APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value) file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

NEW QUESTION 94

- (Topic 2)

A user has stored data on an encrypted EBS volume. The user wants to share the data with his friend's AWS account. How can user achieve this?

- A. Create an AMI from the volume and share the AMI
- B. Copy the data to an unencrypted volume and then share
- C. Take a snapshot and share the snapshot with a friend
- D. If both the accounts are using the same encryption key then the user can share the volume directly

Answer: B

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. If the user is having data on an encrypted volume and is trying to share it with others, he has to copy the data from the encrypted volume to a new unencrypted volume. Only then can the user share it as an encrypted volume data. Otherwise the snapshot cannot be shared.

NEW QUESTION 95

- (Topic 2)

A user has launched an EC2 instance. The user is planning to setup the CloudWatch alarm. Which of the below mentioned actions is not supported by the CloudWatch alarm?

- A. Notify the Auto Scaling launch config to scale up
- B. Send an SMS using SNS
- C. Notify the Auto Scaling group to scale down
- D. Stop the EC2 instance

Answer: B

Explanation:

A user can create a CloudWatch alarm that takes various actions when the alarm changes state. An alarm watches a single metric over the time period that the user has specified, and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The actions could be sending a notification to an Amazon Simple Notification Service topic (SMS, Email, and HTTP end point), notifying the Auto Scaling policy or changing the state of the instance to Stop/Terminate.

NEW QUESTION 96

- (Topic 2)

A root account owner has created an S3 bucket testmycloud. The account owner wants to allow everyone to upload the objects as well as enforce that the person who uploaded the object should manage the permission of those objects. Which is the easiest way to achieve this?

- A. The root account owner should create a bucket policy which allows the IAM users to upload the object
- B. The root account owner should create the bucket policy which allows the other account owners to set the object policy of that bucket
- C. The root account should use ACL with the bucket to allow everyone to upload the object
- D. The root account should create the IAM users and provide them the permission to upload content to the bucket

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List) associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users in his account. ACLs are suitable for specific scenarios. For example, if a bucket owner allows other AWS accounts to upload objects,

permissions to these objects can only be managed using the object ACL by the AWS account that owns the object.

NEW QUESTION 101

- (Topic 2)

A user has configured ELB with two EBS backed EC2 instances. The user is trying to understand the DNS access and IP support for ELB. Which of the below mentioned statements may not help the user understand the IP mechanism supported by ELB?

- A. The client can connect over IPV4 or IPV6 using Dualstack
- B. ELB DNS supports both IPV4 and IPV6
- C. Communication between the load balancer and back-end instances is always through IPV4
- D. The ELB supports either IPV4 or IPV6 but not both

Answer: D

Explanation:

Elastic Load Balancing supports both Internet Protocol version 6 (IPv6) and Internet Protocol version 4 (IPv4). Clients can connect to the user's load balancer using either IPv4 or IPv6 (in EC2-Classic DNS). However, communication between the load balancer and its back-end instances uses only IPv4. The user can use the Dualstack-prefixed DNS name to enable IPv6 support for communications between the client and the load balancers. Thus, the clients are able to access the load balancer using either IPv4 or IPv6 as their individual connectivity needs dictate.

NEW QUESTION 106

- (Topic 2)

An organization has added 3 of his AWS accounts to consolidated billing. One of the AWS accounts has purchased a Reserved Instance (RI) of a small instance size in the US-East-1a zone. All other AWS accounts are running instances of a small size in the same zone. What will happen in this case for the RI pricing?

- A. Only the account that has purchased the RI will get the advantage of RI pricing
- B. One instance of a small size and running in the US-East-1a zone of each AWS account will get the benefit of RI pricing
- C. Any single instance from all the three accounts can get the benefit of AWS RI pricing if they are running in the same zone and are of the same size
- D. If there are more than one instances of a small size running across multiple accounts in the same zone no one will get the benefit of RI

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. For billing purposes, consolidated billing treats all the accounts on the consolidated bill as one account. This means that all accounts on a consolidated bill can receive the hourly cost benefit of the Amazon EC2 Reserved Instances purchased by any other account. In this case only one Reserved Instance has been purchased by one account. Thus, only a single instance from any of the accounts will get the advantage of RI. AWS will implement the blended rate for each instance if more than one instance is running concurrently.

NEW QUESTION 110

- (Topic 2)

A user has enabled detailed CloudWatch metric monitoring on an Auto Scaling group. Which of the below mentioned metrics will help the user identify the total number of instances in an Auto Scaling group including pending, terminating and running instances?

- A. GroupTotalInstances
- B. GroupSumInstances
- C. It is not possible to get a count of all the three metrics together
- D. The user has to find the individual number of running, terminating and pending instances and sum it
- E. GroupInstancesCount

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For Auto Scaling, CloudWatch provides various metrics to get the group information, such as the Number of Pending, Running or Terminating instances at any moment. If the user wants to get the total number of Running, Pending and Terminating instances at any moment, he can use the GroupTotalInstances metric.

NEW QUESTION 114

- (Topic 2)

A sys admin is trying to understand the Auto Scaling activities. Which of the below mentioned processes is not performed by Auto Scaling?

- A. Reboot Instance
- B. Schedule Actions
- C. Replace Unhealthy
- D. Availability Zone Balancing

Answer: A

Explanation:

There are two primary types of Auto Scaling processes: Launch and Terminate, which launch or terminate instances, respectively. Some other actions performed by Auto Scaling are: AddToLoadbalancer, AlarmNotification, HealthCheck, AZRebalance, ReplaceUnHealthy, and ScheduledActions.

NEW QUESTION 117

- (Topic 2)

A user is trying to setup a recurring Auto Scaling process. The user has setup one process to scale up every day at 8 am and scale down at 7 PM. The user is trying to setup another recurring process which scales up on the 1st of every month at 8 AM and scales down the same day at 7 PM. What will Auto Scaling do in this scenario?

- A. Auto Scaling will execute both processes but will add just one instance on the 1st
- B. Auto Scaling will add two instances on the 1st of the month
- C. Auto Scaling will schedule both the processes but execute only one process randomly
- D. Auto Scaling will throw an error since there is a conflict in the schedule of two separate Auto Scaling Processes

Answer: D

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. As per Auto Scaling, a scheduled action must have a unique time value. If the user attempts to schedule an activity at a time when another existing activity is already scheduled, the call will be rejected with an error message noting the conflict.

NEW QUESTION 122

- (Topic 2)

An organization (Account ID 123412341234. has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
"Statement": [  
  {  
    "Sid": "AllowUsersAllActionsForCredentials",  
    "Effect": "Allow",  
    "Action": [  
      "iam:*AccessKey*",  
    ],  
    "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]  
  }  
]
```

- A. 0
- B. 0
- C. 0
- D. 0

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage keys (access and secret access keys. of all IAM users, the organization should set the below mentioned policy which entitles the IAM user to modify keys of all IAM users with CLI, SDK or API.

```
"Statement": [  
  {  
    "Sid": "AllowUsersAllActionsForCredentials",  
    "Effect": "Allow",  
    "Action": [  
      "iam:*AccessKey*",  
    ],  
    "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]  
  }  
]
```

NEW QUESTION 125

- (Topic 2)

A user has launched an EBS backed instance. The user started the instance at 9 AM in the morning. Between 9 AM to 10 AM, the user is testing some script. Thus, he stopped the instance twice and restarted it. In the same hour the user rebooted the instance once. For how many instance hours will AWS charge the user?

- A. 3 hours
- B. 4 hours
- C. 2 hours
- D. 1 hour

Answer: A

Explanation:

A user can stop/start or reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. When the instance is rebooted AWS will not charge the user for the extra hours. In case the user stops the instance, AWS does not charge the running cost but charges only the EBS storage cost. If the user starts and stops the instance multiple times in a single hour, AWS will charge the user for every start and stop. In this case, since the instance was rebooted twice, it will cost the user for 3 instance hours.

NEW QUESTION 129

- (Topic 2)

An organization has created 50 IAM users. The organization has introduced a new policy which will change the access of an IAM user. How can the organization

implement this effectively so that there is no need to apply the policy at the individual user level?

- A. Use the IAM groups and add users as per their role to different groups and apply policy to group
- B. The user can create a policy and apply it to multiple users in a single go with the AWS CLI
- C. Add each user to the IAM role as per their organization role to achieve effective policy setup
- D. Use the IAM role and implement access at the role level

Answer: A

Explanation:

With AWS IAM, a group is a collection of IAM users. A group allows the user to specify permissions for a collection of users, which can make it easier to manage the permissions for those users. A group helps an organization manage access in a better way; instead of applying at the individual level, the organization can apply at the group level which is applicable to all the users who are a part of that group.

NEW QUESTION 133

- (Topic 2)

An organization is using AWS since a few months. The finance team wants to visualize the pattern of AWS spending. Which of the below AWS tool will help for this requirement?

- A. AWS Cost Manager
- B. AWS Cost Explorer
- C. AWS CloudWatch
- D. AWS Consolidated Billing

Answer: B

Explanation:

The AWS Billing and Cost Management console includes the Cost Explorer tool for viewing AWS cost data as a graph. It does not charge extra to user for this service. With Cost Explorer the user can filter graphs using resource tags or with services in AWS. If the organization is using Consolidated Billing it helps generate report based on linked accounts. This will help organization to identify areas that require further inquiry. The organization can view trends and use that to understand spend and to predict future costs.

NEW QUESTION 136

- (Topic 2)

A user has a refrigerator plant. The user is measuring the temperature of the plant every 15 minutes. If the user wants to send the data to CloudWatch to view the data visually, which of the below mentioned statements is true with respect to the information given above?

- A. The user needs to use AWS CLI or API to upload the data
- B. The user can use the AWS Import Export facility to import data to CloudWatch
- C. The user will upload data from the AWS console
- D. The user cannot upload data to CloudWatch since it is not an AWS service metric

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. While sending the data the user has to include the metric name, namespace and timezone as part of the request.

NEW QUESTION 140

- (Topic 2)

A user has recently started using EC2. The user launched one EC2 instance in the default subnet in EC2-VPC Which of the below mentioned options is not attached or available with the EC2 instance when it is launched?

- A. Public IP address
- B. Internet gateway
- C. Elastic IP
- D. Private IP address

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to a user's AWS account. A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC (default subnet). A default VPC has all the benefits of EC2-VPC and the ease of use of EC2-Classic. Each instance that the user launches into a default subnet has a private IP address and a public IP address. These instances can communicate with the internet through an internet gateway. An internet gateway enables the EC2 instances to connect to the internet through the Amazon EC2 network edge.

NEW QUESTION 143

- (Topic 2)

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP
- C. AWS SQS
- D. AWS SES

Answer: D

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", and "SMS".

NEW QUESTION 147

- (Topic 2)

A user has configured a VPC with a new subnet. The user has created a security group. The user wants to configure that instances of the same subnet communicate with each other. How can the user configure this with the security group?

- A. There is no need for a security group modification as all the instances can communicate with each other inside the same subnet
- B. Configure the subnet as the source in the security group and allow traffic on all the protocols and ports
- C. Configure the security group itself as the source and allow traffic on all the protocols and ports
- D. The user has to use VPC peering to configure this

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. If the user is using the default security group it will have a rule which allows the instances to communicate with other. For a new security group the user has to specify the rule, add it to define the source as the security group itself, and select all the protocols and ports for that source.

NEW QUESTION 152

- (Topic 2)

An organization is using cost allocation tags to find the cost distribution of different departments and projects. One of the instances has two separate tags with the key/ value as "InstanceName/HR", "CostCenter/HR". What will AWS do in this case?

- A. InstanceName is a reserved tag for AWS
- B. Thus, AWS will not allow this tag
- C. AWS will not allow the tags as the value is the same for different keys
- D. AWS will allow tags but will not show correctly in the cost allocation report due to the same value of the two separate keys
- E. AWS will allow both the tags and show properly in the cost distribution report

Answer: D

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV) file, with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. It is required that the key should be different for each tag. The value can be the same for different keys. In this case since the value is different, AWS will properly show the distribution report with the correct values.

NEW QUESTION 153

- (Topic 2)

A user has launched two EBS backed EC2 instances in the US-East-1a region. The user wants to change the zone of one of the instances. How can the user change it?

- A. Stop one of the instances and change the availability zone
- B. The zone can only be modified using the AWS CLI
- C. From the AWS EC2 console, select the Actions - > Change zones and specify new zone
- D. Create an AMI of the running instance and launch the instance in a separate AZ

Answer: D

Explanation:

With AWS EC2, when a user is launching an instance he can select the availability zone (AZ) at the time of launch. If the zone is not selected, AWS selects it on behalf of the user. Once the instance is launched, the user cannot change the zone of that instance unless he creates an AMI of that instance and launches a new instance from it.

NEW QUESTION 155

- (Topic 3)

A user has created a VPC with a public subnet. The user has terminated all the instances which are part of the subnet. Which of the below mentioned statements is true with respect to this scenario?

- A. The user cannot delete the VPC since the subnet is not deleted
- B. All network interface attached with the instances will be deleted
- C. When the user launches a new instance it cannot use the same subnet
- D. The subnet to which the instances were launched with will be deleted

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface. When the user terminates the instance all the network interfaces attached with it are also deleted.

NEW QUESTION 156

- (Topic 3)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB Instance is switched to the standby DB Instance
- B. A new DB instance is created in the standby availability zone
- C. The canonical name record (CNAME) is changed from primary to standby
- D. The RDS (Relational Database Service) DB instance reboots

Answer: D

Explanation:

Reference:

http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_RebootInstance.html

NEW QUESTION 159

- (Topic 3)

A user has launched an EC2 Windows instance from an instance store backed AMI. The user wants to convert the AMI to an EBS backed AMI. How can the user convert it?

- A. Attach an EBS volume to the instance and unbundle all the AMI bundled data inside the EBS
- B. A Windows based instance store backed AMI cannot be converted to an EBS backed AMI
- C. It is not possible to convert an instance store backed AMI to an EBS backed AMI
- D. Attach an EBS volume and use the copy command to copy all the ephemeral content to the EBS Volume

Answer: B

Explanation:

Generally when a user has launched an EC2 instance from an instance store backed AMI, it can be converted to an EBS backed AMI provided the user has attached the EBS volume to the instance and unbundles the AMI data to it. However, if the instance is a Windows instance, AWS does not allow this. In this case, since the instance is a Windows instance, the user cannot convert it to an EBS backed AMI.

NEW QUESTION 163

- (Topic 3)

An organization has created a Queue named "modularqueue" with SQS. The organization is not performing any operations such as SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission on the queue. What can happen in this scenario?

- A. AWS SQS sends notification after 15 days for inactivity on queue
- B. AWS SQS can delete queue after 30 days without notification
- C. AWS SQS marks queue inactive after 30 days
- D. AWS SQS notifies the user after 2 weeks and deletes the queue after 3 weeks

Answer: B

Explanation:

Amazon SQS can delete a queue without notification if one of the following actions hasn't been performed on it for 30 consecutive days: SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission.

NEW QUESTION 167

- (Topic 3)

A sys admin has enabled logging on ELB. Which of the below mentioned fields will not be a part of the log file name?

- A. Load Balancer IP
- B. EC2 instance IP
- C. S3 bucket name
- D. Random string

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Elastic Load Balancing publishes a log file from each load balancer node at the interval that the user has specified. The load balancer can deliver multiple logs for the same period. Elastic Load Balancing creates log file names in the following format: "{Bucket}/{Prefix}/AWSLogs/{AWS AccountID}/elasticloadbalancing/{Region}/{Year}/{Month}/{Day}/{AWS Account ID}_elasticloadbalancing_{Region}_{Load Balancer Name}_{End Time}_{Load Balancer IP}_{Random String}.log"

NEW QUESTION 170

- (Topic 3)

A user is trying to connect to a running EC2 instance using SSH. However, the user gets an Unprotected Private Key File error. Which of the below mentioned options can be a possible reason for rejection?

- A. The private key file has the wrong file permission
- B. The ppk file used for SSH is read only
- C. The public key file has the wrong permission
- D. The user has provided the wrong user name for the OS login

Answer: A

Explanation:

While doing SSH to an EC2 instance, if you get an Unprotected Private Key File error it means that the private key file's permissions on your computer are too open. Ideally the private key should have the Unix permission of 0400. To fix that, run the command: `chmod 0400 /path/to/private.key`

NEW QUESTION 174

- (Topic 3)

A user has launched 5 instances in EC2-CLASSIC and attached 5 elastic IPs to the five different instances in the US East region. The user is creating a VPC in the same region. The user wants to assign an elastic IP to the VPC instance. How can the user achieve this?

- A. The user has to request AWS to increase the number of elastic IPs associated with the account
- B. AWS allows 10 EC2 Classic IPs per region; so it will allow to allocate new Elastic IPs to the same region
- C. The AWS will not allow to create a new elastic IP in VPC; it will throw an error
- D. The user can allocate a new IP address in VPC as it has a different limit than EC2

Answer: D

Explanation:

Section: (none)

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. A user can have 5 IP addresses per region with EC2 Classic. The user can have 5 separate IPs with VPC in the same region as it has a separate limit than EC2 Classic.

NEW QUESTION 176

- (Topic 3)

A user has launched an EC2 instance store backed instance in the US-East-1a zone. The user created AMI #1 and copied it to the Europe region. After that, the user made a few updates to the application running in the US-East-1a zone. The user makes an AMI#2 after the changes. If the user launches a new instance in Europe from the AMI #1 copy, which of the below mentioned statements is true?

- A. The new instance will have the changes made after the AMI copy as AWS just copies the reference of the original AMI during the copyin
- B. Thus, the copied AMI will have all the updated data
- C. The new instance will have the changes made after the AMI copy since AWS keeps updating the AMI
- D. It is not possible to copy the instance store backed AMI from one region to another
- E. The new instance in the EU region will not have the changes made after the AMI copy

Answer: D

Explanation:

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source) AMI. The user can modify the source AMI without affecting the new AMI and vice versa. Therefore, in this case even if the source AMI is modified, the copied AMI of the EU region will not have the changes. Thus, after copy the user needs to copy the new source AMI to the destination region to get those changes.

NEW QUESTION 178

- (Topic 3)

A user has setup a VPC with CIDR 20.0.0.0/16. The VPC has a private subnet (20.0.1.0/24) and a public subnet (20.0.0.0/24). The user's data centre has CIDR of 20.0.54.0/24 and 20.1.0.0/24. If the private subnet wants to communicate with the data centre, what will happen?

- A. It will allow traffic communication on both the CIDRs of the data centre
- B. It will not allow traffic with data centre on CIDR 20.1.0.0/24 but allows traffic communication on 20.0.54.0/24
- C. It will not allow traffic communication on any of the data centre CIDRs
- D. It will allow traffic with data centre on CIDR 20.1.0.0/24 but does not allow on 20.0.54.0/24

Answer: D

Explanation:

VPC allows the user to set up a connection between his VPC and corporate or home network data centre. If the user has an IP address prefix in the VPC that overlaps with one of the networks' prefixes, any traffic to the network's prefix is dropped. In this case CIDR 20.0.54.0/24 falls in the VPC's CIDR range of 20.0.0.0/16. Thus, it will not allow traffic on that IP. In the case of 20.1.0.0/24, it does not fall in the VPC's CIDR range. Thus, traffic will be allowed on it.

NEW QUESTION 180

- (Topic 3)

A user is sending the data to CloudWatch using the CloudWatch API. The user is sending data 90 minutes in the future. What will CloudWatch do in this case?

- A. CloudWatch will accept the data
- B. It is not possible to send data of the future
- C. It is not possible to send the data manually to CloudWatch
- D. The user cannot send data for more than 60 minutes in the future

Answer: A

Explanation:

With Amazon CloudWatch, each metric data point must be marked with a time stamp. The user can send the data using CLI but the time has to be in the UTC format. If the user does not provide the time, CloudWatch will take the data received time in the UTC timezone. The time stamp sent by the user can be up to two weeks in the past and up to two hours into the future.

NEW QUESTION 183

- (Topic 3)

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3:::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    },
    {
      "Principal": {
        "AWS": [
          "*"
        ]
      }
    }
  ]
}
```

- A. Denies the server with the IP address 192.166 100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.166 100.188 full access to the "mybucket bucket
- C. Grants all the servers within the 192 168 100 0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192 168 100 188/32 subnet full access to the "mybucket" bucket

Answer: C

NEW QUESTION 186

- (Topic 3)

You have a business-to-business web application running in a VPC consisting of an Elastic Load Balancer (ELB), web servers, application servers and a database. Your web application should only accept traffic from pre-defined customer IP addresses.

Which two options meet this security requirement? Choose 2 answers A. Configure web server VPC security groups to allow traffic from your customers' IPs

- A. Configure your web servers to filter traffic based on the ELB's "X-forwarded-for" header
- B. Configure ELB security groups to allow traffic from your customers' IPs and deny all outbound traffic
- C. Configure a VPC NACL to allow web traffic from your customers' IPs and deny all outbound traffic

Answer: AB

NEW QUESTION 189

- (Topic 3)

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

Perform maintenance on standby
Promote standby to primary
Perform maintenance on original primary
Promote original master back as primary

- A. 1, 2, 3, 4
- B. 1, 2, 3
- C. 2, 3, 1, 4

Answer: B

Explanation:

Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order: Perform maintenance on standby Promote standby to primary Perform maintenance on original primary, which becomes the new standby.

NEW QUESTION 191

- (Topic 3)

Which method can be used to prevent an IP address block from accessing public objects in an S3 bucket?

- A. Create a bucket policy and apply it to the bucket
- B. Create a NACL and attach it to the VPC of the bucket
- C. Create an ACL and apply it to all objects in the bucket
- D. Modify the IAM policies of any users that would access the bucket

Answer: A

Explanation:

Reference:
<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

NEW QUESTION 196

- (Topic 3)

In AWS, which security aspects are the customer's responsibility? Choose 4 answers

- A. Controlling physical access to compute resources
- B. Patch management on the EC2 instance's operating system
- C. Encryption of EBS (Elastic Block Storage) volumes
- D. Life-cycle management of IAM credentials
- E. Decommissioning storage devices
- F. Security Group and ACL (Access Control List) settings

Answer: BCEF

NEW QUESTION 197

- (Topic 3)

A user is planning to scale up an application by 8 AM and scale down by 7 PM daily using Auto Scaling. What should the user do in this case?

- A. Setup the scaling policy to scale up and down based on the CloudWatch alarms
- B. The user should increase the desired capacity at 8 AM and decrease it by 7 PM manually
- C. The user should setup a batch process which launches the EC2 instance at a specific time
- D. Setup scheduled actions to scale up or down at a specific time

Answer: A

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. To configure the Auto Scaling group to scale based on a schedule, the user needs to create scheduled actions. A scheduled action tells Auto Scaling to perform a scaling action at a certain time in the future.

NEW QUESTION 198

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created one subnet with CIDR 20.0.0.0/16 in this VPC. The user is trying to create another subnet with the same VPC for CIDR 20.0.0.1/24. What will happen in this scenario?

- A. The VPC will modify the first subnet CIDR automatically to allow the second subnet IP range
- B. It is not possible to create a subnet with the same CIDR as VPC
- C. The second subnet will be created
- D. It will throw a CIDR overlaps error

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. The user can create a subnet with the same size of VPC. However, he cannot create any other subnet since the CIDR of the second subnet will conflict with the first subnet.

NEW QUESTION 202

- (Topic 3)

A user wants to find the particular error that occurred on a certain date in the AWS MySQL RDS DB. Which of the below mentioned activities may help the user to get the data easily?

- A. It is not possible to get the log files for MySQL RDS
- B. Find all the transaction logs and query on those records
- C. Direct the logs to the DB table and then query that table
- D. Download the log file to DynamoDB and search for the record

Answer: C

Explanation:

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI) or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow query log, and general logs. The user can also view the MySQL logs easily by directing the logs to a database table in the main database and querying that table.

NEW QUESTION 207

- (Topic 3)

A user is collecting 1000 records per second. The user wants to send the data to CloudWatch using the custom namespace. Which of the below mentioned options is recommended for this activity?

- A. Aggregate the data with statistics, such as Min, max, Average, Sum and Sample data and send the data to CloudWatch
- B. Send all the data values to CloudWatch in a single command by separating them with a comm
- C. CloudWatch will parse automatically
- D. Create one csv file of all the data and send a single file to CloudWatch
- E. It is not possible to send all the data in one cal
- F. Thus, it should be sent one by on
- G. CloudWatch will aggregate the data automatically

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. It is recommended that when the user is having multiple data points per minute, he should aggregate the data so that it will minimize the number of calls to put-metric-data. In this case it will be single call to CloudWatch instead of 1000 calls if the data is aggregated.

NEW QUESTION 212

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The user has not launched any instance manually and is trying to delete the VPC. What will happen in this scenario?

- A. It will not allow to delete the VPC as it has subnets with route tables
- B. It will not allow to delete the VPC since it has a running route instance
- C. It will terminate the VPC along with all the instances launched by the wizard
- D. It will not allow to delete the VPC since it has a running NAT instance

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. If the user is trying to delete the VPC it will not allow as the NAT instance is still running.

NEW QUESTION 216

- (Topic 3)

A user runs the command "dd if=/dev/zero of=/dev/xvdfbs=1M" on a fresh blank EBS volume attached to a Linux instance. Which of the below mentioned activities is the user performing with the command given above?

- A. Creating a file system on the EBS volume
- B. Mounting the device to the instance
- C. Pre warming the EBS volume
- D. Formatting the EBS volume

Answer: C

Explanation:

When the user creates a new EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a blank volume attached with a Linux OS, the "dd" command is used to write to all the blocks on the device. In the command "dd if=/dev/zero of=/dev/xvdfbs=1M" the parameter "if =import file" should be set to one of the Linux virtual devices, such as /dev/zero. The "of=output file" parameter should be set to the drive that the user wishes to warm. The "bs" parameter sets the block size of the write operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 221

- (Topic 3)

An organization (Account ID 123412341234) has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowUsersAllActionsForCredentials",
    "Effect": "Allow",
    "Action": [
      "iam:*LoginProfile",
      "iam:*AccessKey*",
      "iam:*SigningCertificate*"
    ],
    "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
  }]
}
```

- A. The policy allows the IAM user to modify all IAM user's credentials using the console, SDK, CLI or APIs
- B. The policy will give an invalid resource error

- C. The policy allows the IAM user to modify all credentials using only the console
D. The policy allows the user to modify all IAM user's password, sign in certificates and access keys using only CLI, SDK or APIs

Answer: D

Explanation:

WS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage credentials (access keys, password, and sing in certificates. of all IAM users, they should set an applicable policy to that user or group of users. The below mentioned policy allows the IAM user to modify the credentials of all IAM user's using only CLI, SDK or APIs. The user cannot use the AWS console for this activity since he does not have list permission for the IAM users.

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AllowUsersAllActionsForCredentials",
    "Effect": "Allow"
    "Action": [
      "iam:*LoginProfile",
      "iam:*AccessKey*",
      "iam:*SigningCertificate*"
    ],
    "Resource": ["arn:aws:iam::123412341234:user:${aws:username}"]
  }]
}
```

Amazon AWS-SysOps : Practice Test

NEW QUESTION 224

- (Topic 3)

The compliance department within your multi-national organization requires that all data for your customers that reside in the European Union (EU) must not leave the EU and also

data for customers that reside in the US must not leave the US without explicit authorization.

What must you do to comply with this requirement for a web based profile management application running on EC2?

- A. Run EC2 instances in multiple AWS Availability Zones in single Region and leverage an Elastic Load Balancer with session stickiness to route traffic to the appropriate zone to create their profile
B. Run EC2 instances in multiple Regions and leverage Route 53's Latency Based Routing capabilities to route traffic to the appropriate region to create their profile
C. Run EC2 instances in multiple Regions and leverage a third party data provider to determine if a user needs to be redirect to the appropriate region to create their profile
D. Run EC2 instances in multiple AWS Availability Zones in a single Region and leverage a third party data provider to determine if a user needs to be redirect to the appropriate zone to create their profile

Answer: C

NEW QUESTION 226

- (Topic 3)

A user has launched an EBS backed EC2 instance in the US-East-1a region. The user stopped the instance and started it back after 20 days. AWS throws up an 'InsufficientInstanceCapacity' error. What can be the possible reason for this?

- A. AWS does not have sufficient capacity in that availability zone
B. AWS zone mapping is changed for that user account
C. There is some issue with the host capacity on which the instance is launched
D. The user account has reached the maximum EC2 instance limit

Answer: A

Explanation:

When the user gets an 'InsufficientInstanceCapacity' error while launching or starting an EC2 instance, it means that AWS does not currently have enough available capacity to service the user request. If the user is requesting a large number of instances, there might not be enough server capacity to host them. The user can either try again later, by specifying a smaller number of instances or changing the availability zone if launching a fresh instance.

NEW QUESTION 227

- (Topic 3)

A sys admin has enabled a log on ELB. Which of the below mentioned activities are not captured by the log?

- A. Response processing time
B. Front end processing time
C. Backend processing time
D. Request processing time

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Each request will have details, such as client IP, request path, ELB IP, time, and latencies. The time will have information, such as Request Processing time, Backend Processing time and Response Processing time.

NEW QUESTION 231

- (Topic 3)

A user is using Cloudformation to launch an EC2 instance and then configure an application after the instance is launched. The user wants the stack creation of ELB and AutoScaling to wait until the EC2 instance is launched and configured properly. How can the user configure this?

- A. It is not possible that the stack creation will wait until one service is created and launched
- B. The user can use the HoldCondition resource to wait for the creation of the other dependent resources
- C. The user can use the DependentCondition resource to hold the creation of the other dependent resources
- D. The user can use the WaitCondition resource to hold the creation of the other dependent resources

Answer: D

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS CloudFormation provides a WaitCondition resource which acts as a barrier and blocks the creation of other resources until a completion signal is received from an external source, such as a user application or management system.

NEW QUESTION 233

- (Topic 3)

A user has created an EBS volume of 10 GB and attached it to a running instance. The user is trying to access EBS for first time. Which of the below mentioned options is the correct statement with respect to a first time EBS access?

- A. The volume will show a size of 8 GB
- B. The volume will show a loss of the IOPS performance the first time
- C. The volume will be blank
- D. If the EBS is mounted it will ask the user to create a file system

Answer: B

Explanation:

A user can create an EBS volume either from a snapshot or as a blank volume. If the volume is from a snapshot it will not be blank. The volume shows the right size only as long as it is mounted. This shows that the file system is created. When the user is accessing the volume the AWS EBS will wipe out the block storage or instantiate from the snapshot. Thus, the volume will show a loss of IOPS. It is recommended that the user should pre warm the EBS before use to achieve better IO.

NEW QUESTION 235

- (Topic 3)

A user is creating a Cloudformation stack. Which of the below mentioned limitations does not hold true for Cloudformation?

- A. One account by default is limited to 100 templates
- B. The user can use 60 parameters and 60 outputs in a single template
- C. The template, parameter, output, and resource description fields are limited to 4096 characters
- D. One account by default is limited to 20 stacks

Answer: A

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The limitations given below apply to the Cloudformation template and stack. There are no limits to the number of templates but each AWS CloudFormation account is limited to a maximum of 20 stacks by default. The Template, Parameter, Output, and Resource description fields are limited to 4096 characters. The user can include up to 60 parameters and 60 outputs in a template.

NEW QUESTION 236

- (Topic 3)

When you put objects in Amazon S3, what is the indication that an object was successfully stored?

- A. Each S3 account has a special bucket named _s3_log
- B. Success codes are written to this bucket with a timestamp and checksu
- C. A success code is inserted into the S3 object metadat
- D. A HTTP 200 result code and MD5 checksum, taken together, indicate that the operation was successfu
- E. Amazon S3 is engineered for 99.999999999% durabilit
- F. Therefore there is no need to confirm that data was inserte

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/API/RESTObjectPUT.html>

NEW QUESTION 240

- (Topic 3)

A user has created a VPC with the public subnet. The user has created a security group for that VPC. Which of the below mentioned statements is true when a security group is created?

- A. It can connect to the AWS services, such as S3 and RDS by default

- B. It will have all the inbound traffic by default
- C. It will have all the outbound traffic by default
- D. It will by default allow traffic to the internet gateway

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level while ACLs work at the subnet level. When a user creates a security group with AWS VPC, by default it will allow all the outbound traffic but block all inbound traffic.

NEW QUESTION 241

- (Topic 3)

Amazon EBS snapshots have which of the following two characteristics? (Choose 2.) Choose 2 answers

- A. EBS snapshots only save incremental changes from snapshot to snapshot
- B. EBS snapshots can be created in real-time without stopping an EC2 instance
- C. EBS snapshots can only be restored to an EBS volume of the same size or smaller
- D. EBS snapshots can only be restored and mounted to an instance in the same Availability Zone as the original EBS volume

Answer: AD

NEW QUESTION 246

- (Topic 3)

An organization has launched 5 instances: 2 for production and 3 for testing. The organization wants that one particular group of IAM users should only access the test instances and not the production ones. How can the organization set that as a part of the policy?

- A. Launch the test and production instances in separate regions and allow region wise access to the group
- B. Define the IAM policy which allows access based on the instance ID
- C. Create an IAM policy with a condition which allows access to only small instances
- D. Define the tags on the test and production servers and add a condition to the IAM policy which allows access to specific tags

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user can add conditions as a part of the IAM policies. The condition can be set on AWS Tags, Time, and Client IP as well as on various parameters. If the organization wants the user to access only specific instances he should define proper tags and add to the IAM policy condition.

The sample policy is shown below.

```
"Statement": [  
  {  
    "Action": "ec2:*",  
    "Effect": "Allow",  
    "Resource": "*",  
    "Condition": {  
      "StringEquals": {  
        "ec2:ResourceTag/InstanceType": "Production"  
      }  
    }  
  }  
]
```

NEW QUESTION 249

- (Topic 3)

A user has created a mobile application which makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK and root account access/secret access key to connect to DynamoDB from mobile. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should create a separate IAM user for each mobile application and provide DynamoDB access with it
- B. The user should create an IAM role with DynamoDB and EC2 access
- C. Attach the role with EC2 and route all calls from the mobile through EC2
- D. The application should use an IAM role with web identity federation which validates calls to DynamoDB with identity providers, such as Google, Amazon, and Facebook
- E. Create an IAM Role with DynamoDB access and attach it with the mobile application

Answer: C

Explanation:

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. If the user is creating an app that runs on a mobile phone and makes requests to AWS, the user should not create an IAM user and distribute the user's access key with the app. Instead, he should use an identity provider, such as Login with Amazon, Facebook, or Google to authenticate the users, and then use that identity to get temporary security credentials.

NEW QUESTION 250

- (Topic 3)

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. The user has 3 elastic IPs and is trying to assign one of the Elastic IPs to the VPC instance from the console. The console does not show any instance in the IP assignment screen. What is a possible reason that the instance is unavailable in the assigned IP console?

- A. The IP address may be attached to one of the instances
- B. The IP address belongs to a different zone than the subnet zone
- C. The user has not created an internet gateway
- D. The IP addresses belong to EC2 Classic; so they cannot be assigned to VPC

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. If the user wants to connect to an instance from the internet he should create an elastic IP with VPC. If the elastic IP is a part of EC2 Classic it cannot be assigned to a VPC instance.

NEW QUESTION 254

- (Topic 3)

A sys admin is planning to subscribe to the RDS event notifications. For which of the below mentioned source categories the subscription cannot be configured?

- A. DB security group
- B. DB snapshot
- C. DB options group
- D. DB parameter group

Answer: C

Explanation:

Amazon RDS uses the Amazon Simple Notification Service (SNS) to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group.

NEW QUESTION 255

- (Topic 3)

A user has configured an HTTPS listener on an ELB. The user has not configured any security policy which can help to negotiate SSL between the client and ELB. What will ELB do in this scenario?

- A. By default ELB will select the first version of the security policy
- B. By default ELB will select the latest version of the policy
- C. ELB creation will fail without a security policy
- D. It is not required to have a security policy since SSL is already installed

Answer: B

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the user has created an HTTPS/SSL listener without associating any security policy, Elastic Load Balancing will, by default, associate the latest version of the ELBSecurityPolicy-YYYY-MM with the load balancer.

NEW QUESTION 258

- (Topic 3)

A user is receiving a notification from the RDS DB whenever there is a change in the DB security group. The user does not want to receive these notifications for only a month. Thus, he does not want to delete the notification. How can the user configure this?

- A. Change the Disable button for notification to "Yes" in the RDS console
- B. Set the send mail flag to false in the DB event notification console
- C. The only option is to delete the notification from the console
- D. Change the Enable button for notification to "No" in the RDS console

Answer: D

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. Event notifications are sent to the addresses that the user has provided while creating the subscription. The user can easily turn off the notification without deleting a subscription by setting the Enabled radio button to No in the Amazon RDS console or by setting the Enabled parameter to false using the CLI or Amazon RDS API.

NEW QUESTION 262

- (Topic 3)

A user runs the command "dd if=/dev/xvdf of=/dev/null bs=1M" on an EBS volume created from a snapshot and attached to a Linux instance. Which of the below mentioned activities is the user performing with the step given above?

- A. Pre warming the EBS volume
- B. Initiating the device to mount on the EBS volume
- C. Formatting the volume
- D. Copying the data from a snapshot to the device

Answer: A

Explanation:

When the user creates an EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a volume created from a snapshot and attached with a Linux OS, the “dd” command pre warms the existing data on EBS and any restored snapshots of volumes that have been previously fully pre warmed. This command maintains incremental snapshots; however, because this operation is read-only, it does not pre warm unused space that has never been written to on the original volume. In the command “dd if=/dev/xvdf of=/dev/null bs=1M” , the parameter “if=input file” should be set to the drive that the user wishes to warm. The “of=output file” parameter should be set to the Linux null virtual device, /dev/null. The “bs” parameter sets the block size of the read operation; for optimal performance, this should be set to 1 MB.

NEW QUESTION 266

- (Topic 3)

A user is measuring the CPU utilization of a private data centre machine every minute. The machine provides the aggregate of data every hour, such as Sum of data”, “Min value”, “Max value, and “Number of Data points”.

The user wants to send these values to CloudWatch. How can the user achieve this?

- A. Send the data using the put-metric-data command with the aggregate-values parameter
- B. Send the data using the put-metric-data command with the average-values parameter
- C. Send the data using the put-metric-data command with the statistic-values parameter
- D. Send the data using the put-metric-data command with the aggregate –data parameter

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish the data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. When sending the aggregate data, the user needs to send it with the parameter statistic-values: `awscloudwatch put-metric-data --metric-name <Name> --namespace <Custom namespace> --timestamp <UTC Format> --statistic-values Sum=XX,Minimum=YY,Maximum=AA,SampleCount=BB --unit Milliseconds`

NEW QUESTION 270

- (Topic 3)

An organization has configured Auto Scaling with ELB. There is a memory issue in the application which is causing CPU utilization to go above 90%. The higher CPU usage triggers an event for Auto Scaling as per the scaling policy. If the user wants to find the root cause inside the application without triggering a scaling activity, how can he achieve this?

- A. Stop the scaling process until research is completed
- B. It is not possible to find the root cause from that instance without triggering scaling
- C. Delete Auto Scaling until research is completed
- D. Suspend the scaling process until research is completed

Answer: D

Explanation:

Auto Scaling allows the user to suspend and then resume one or more of the Auto Scaling processes in the Auto Scaling group. This is very useful when the user wants to investigate a configuration problem or some other issue, such as a memory leak with the web application and then make changes to the application, without triggering the Auto Scaling process.

NEW QUESTION 273

- (Topic 3)

George has launched three EC2 instances inside the US-East-1a zone with his AWS account. Ray has launched two EC2 instances in the US-East-1a zone with his AWS account. Which of the below entioned statements will help George and Ray understand the availability zone (AZ. concept better?

- A. The instances of George and Ray will be running in the same data centre
- B. All the instances of George and Ray can communicate over a private IP with a minimal cost
- C. All the instances of George and Ray can communicate over a private IP without any cost
- D. The US-East-1a region of George and Ray can be different availability zones

Answer: D

Explanation:

Each AWS region has multiple, isolated locations known as Availability Zones. To ensure that the AWS resources are distributed across the Availability Zones for a region, AWS independently maps the Availability Zones to identifiers for each account. In this case the Availability Zone US-East-1a where George's EC2 instances are running might not be the same location as the US-East-1a zone of Ray's EC2 instances. There is no way for the user to coordinate the Availability Zones between accounts.

NEW QUESTION 278

- (Topic 3)

A sys admin is trying to understand the sticky session algorithm. Please select the correct sequence of steps, both when the cookie is present and when it is not, to help the admin understand the implementation of the sticky session:

ELB inserts the cookie in the response ELB chooses the instance based on the load balancing algorithm Check the cookie in the service request The cookie is found in the request The cookie is not found in the request

- A. 3,1,4,2 [Cookie is not Present] & 3,1,5,2 [Cookie is Present]

- B. 3,4,1,2 [Cookie is not Present] & 3,5,1,2 [Cookie is Present]
- C. 3,5,2,1 [Cookie is not Present] & 3,4,2,1 [Cookie is Present]
- D. 3,2,5,4 [Cookie is not Present] & 3,2,4,5 [Cookie is Present]

Answer: C

Explanation:

Generally AWS ELB routes each request to a zone with the minimum load. The Elastic Load Balancer provides a feature called sticky session which binds the user's session with a specific EC2 instance. The load balancer uses a special load-balancer-generated cookie to track the application instance for each request. When the load balancer receives a request, it first checks to see if this cookie is present in the request. If so, the request is sent to the application instance specified in the cookie. If there is no cookie, the load balancer chooses an application instance based on the existing load balancing algorithm. A cookie is inserted into the response for binding subsequent requests from the same user to that application instance.

NEW QUESTION 283

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AddToLoadBalancer (which adds instances to the load balancer. process for a while. What will happen to the instances launched during the suspension period?

- A. The instances will not be registered with ELB and the user has to manually register when the process is resumed
- B. The instances will be registered with ELB only once the process has resumed
- C. Auto Scaling will not launch the instance during this period due to process suspension
- D. It is not possible to suspend only the AddToLoadBalancer process

Answer: A

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate, add to Load Balancer etc. The user can also suspend the individual process. The AddToLoadBalancer process type adds instances to the load balancer when the instances are launched. If this process is suspended, Auto Scaling will launch the instances but will not add them to the load balancer. When the user resumes this process, Auto Scaling will resume adding new instances launched after resumption to the load balancer. However, it will not add running instances that were launched while the process was suspended; those instances must be added manually.

NEW QUESTION 285

- (Topic 3)

A user has configured an ELB to distribute the traffic among multiple instances. The user instances are facing some issues due to the back-end servers. Which of the below mentioned CloudWatch metrics helps the user understand the issue with the instances?

- A. HTTPCode_Backend_3XX
- B. HTTPCode_Backend_4XX
- C. HTTPCode_Backend_2XX
- D. HTTPCode_Backend_5XX

Answer: D

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For ELB, CloudWatch provides various metrics including error code by ELB as well as by back-end servers (instances.. It gives data for the count of the number of HTTP response codes generated by the back-end instances. This metric does not include any response codes generated by the load balancer. These metrics are: The 2XX class status codes represents successful actions The 3XX class status code indicates that the user agent requires action The 4XX class status code represents client errors The 5XX class status code represents back-end server errors

NEW QUESTION 288

- (Topic 3)

A user has created a VPC with two subnets: one public and one private. The user is planning to run the patch update for the instances in the private subnet. How can the instances in the private subnet connect to the internet?

- A. Use the internet gateway with a private IP
- B. Allow outbound traffic in the security group for port 80 to allow internet updates
- C. The private subnet can never connect to the internet
- D. Use NAT with an elastic IP

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created two subnets (one private and one public., he would need a Network Address Translation (NAT) instance with the elastic IP address. This enables the instances in the private subnet to send requests to the internet (for example, to perform software updates..

NEW QUESTION 289

- (Topic 3)

Which of the below mentioned AWS RDS logs cannot be viewed from the console for MySQL?

- A. Error Log
- B. Slow Query Log
- C. Transaction Log

D. General Log

Answer: C

Explanation:

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI), or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow querylog, and general logs. RDS does not support viewing the transaction logs.

NEW QUESTION 291

- (Topic 3)

An AWS account wants to be part of the consolidated billing of his organization's payee account. How can the owner of that account achieve this?

- A. The payee account has to request AWS support to link the other accounts with his account
- B. The owner of the linked account should add the payee account to his master account list from the billing console
- C. The payee account will send a request to the linked account to be a part of consolidated billing
- D. The owner of the linked account requests the payee account to add his account to consolidated billing

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. To add a particular account (linked to the master (payee) account, the payee account has to request the linked account to join consolidated billing. Once the linked account accepts the request henceforth all charges incurred by the linked account will be paid by the payee account.

NEW QUESTION 292

- (Topic 3)

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a Host key not found error. Which of the below mentioned options is a possible reason for rejection?

- A. The user has provided the wrong user name for the OS login
- B. The instance CPU is heavily loaded
- C. The security group is not configured properly
- D. The access key to connect to the instance is wrong

Answer: A

Explanation:

If the user is trying to connect to a Linux EC2 instance and receives the Host Key not found error the probable reasons are: The private key pair is not right The user name to login is wrong

NEW QUESTION 297

- (Topic 3)

How can software determine the public and private IP addresses of the Amazon EC2 instance that it is running on?

- A. Query the local instance metadat
- B. Query the appropriate Amazon CloudWatch metri
- C. Query the local instance userdat
- D. Use ipconfig or ifconfig comman

Answer: B

NEW QUESTION 300

- (Topic 3)

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. Which of the below mentioned SSL protocols is not supported by the security policy?

- A. TLS 1.3
- B. TLS 1.2
- C. SSL 2.0
- D. SSL 3.0

Answer: A

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. Elastic Load Balancing supports the following versions of the SSL protocol: TLS 1.2 TLS 1.1 TLS 1.0 SSL 3.0 SSL 2.0

NEW QUESTION 303

- (Topic 3)

A user has configured ELB with a TCP listener at ELB as well as on the back-end instances. The user wants to enable a proxy protocol to capture the source and destination IP information in the header. Which of the below mentioned statements helps the user understand a proxy protocol with TCP configuration?

- A. If the end user is requesting behind a proxy server then the user should not enable a proxy protocol on ELB
- B. ELB does not support a proxy protocol when it is listening on both the load balancer and the back-end instances
- C. Whether the end user is requesting from a proxy server or directly, it does not make a difference for the proxy protocol
- D. If the end user is requesting behind the proxy then the user should add the “isproxy” flag to the ELB Configuration

Answer: A

Explanation:

When the user has configured Transmission Control Protocol (TCP) or Secure Sockets Layer (SSL) for both front-end and back-end connections of the Elastic Load Balancer, the load balancer forwards the request to the back-end instances without modifying the request headers unless the proxy header is enabled. If the end user is requesting from a Proxy Protocol enabled proxy server, then the ELB admin should not enable the Proxy Protocol on the load balancer. If the Proxy Protocol is enabled on both the proxy server and the load balancer, the load balancer will add another header to the request which already has a header from the proxy server. This duplication may result in errors.

NEW QUESTION 308

- (Topic 3)

A storage admin wants to encrypt all the objects stored in S3 using server side encryption. The user does not want to use the AES 256 encryption key provided by S3. How can the user achieve this?

- A. The admin should upload his secret key to the AWS console and let S3 decrypt the objects
- B. The admin should use CLI or API to upload the encryption key to the S3 bucket
- C. When making a call to the S3 API mention the encryption key URL in each request
- D. S3 does not support client supplied encryption keys for server side encryption
- E. The admin should send the keys and encryption algorithm with each API call

Answer: D

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key. Amazon S3 never stores the user's encryption key. The user has to supply it for each encryption or decryption call.

NEW QUESTION 310

- (Topic 3)

A .NET application that you manage is running in Elastic Beanstalk. Your developers tell you they will need access to application log files to debug issues that arise. The infrastructure will scale up and down.

How can you ensure the developers will be able to access only the log files?

- A. Access the log files directly from Elastic Beanstalk
- B. Enable log file rotation to S3 within the Elastic Beanstalk configuration
- C. Ask your developers to enable log file rotation in the applications web.config file
- D. Connect to each Instance launched by Elastic Beanstalk and create a Windows Scheduled task to rotate the log files to S3.

Answer: D

Explanation:

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.loggingS3.title.html>

NEW QUESTION 315

- (Topic 3)

A user has enabled versioning on an S3 bucket. The user is using server side encryption for data at Rest. If the user is supplying his own keys for encryption (SSE-C), which of the below mentioned statements is true?

- A. The user should use the same encryption key for all versions of the same object
- B. It is possible to have different encryption keys for different versions of the same object
- C. AWS S3 does not allow the user to upload his own keys for server side encryption
- D. The SSE-C does not work when versioning is enabled

Answer: B

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C). If the bucket is versioning-enabled, each object version uploaded by the user using the SSE-C feature can have its own encryption key. The user is responsible for tracking which encryption key was used for which object's version

NEW QUESTION 319

- (Topic 3)

A user has created an application which will be hosted on EC2. The application makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK to connect with from the EC2 instance. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should attach an IAM role with DynamoDB access to the EC2 instance
- B. The user should create an IAM user with DynamoDB access and use its credentials within the application to connect with DynamoDB
- C. The user should create an IAM role, which has EC2 access so that it will allow deploying the application

- D. The user should create an IAM user with DynamoDB and EC2 access
- E. Attach the user with the application so that it does not use the root account credentials

Answer: A

Explanation:

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. Instead, the user should use roles for EC2 and give that role access to DynamoDB /S3. When the roles are attached to EC2, it will give temporary security credentials to the application hosted on that EC2, to connect with DynamoDB / S3.

NEW QUESTION 324

- (Topic 3)

A user has created a VPC with a subnet and a security group. The user has launched an instance in that subnet and attached a public IP. The user is still unable to connect to the instance. The internet gateway has also been created. What can be the reason for the error?

- A. The internet gateway is not configured with the route table
- B. The private IP is not present
- C. The outbound traffic on the security group is disabled
- D. The internet gateway is not configured with the security group

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. When a user launches an instance and wants to connect to an instance, he needs an internet gateway. The internet gateway should be configured with the route table to allow traffic from the internet.

NEW QUESTION 328

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24) and VPN only subnets CIDR (20.0.1.0/24) along with the VPN gateway (vgw-12345) to connect to the user's data centre. The user's data centre has CIDR 172.28.0.0/12. The user has also setup a NAT instance (i-123456) to allow traffic to the internet from the VPN subnet. Which of the below mentioned options is not a valid entry for the main route table in this scenario?

- A. Destination: 20.0.1.0/24 and Target: i-12345
- B. Destination: 0.0.0.0/0 and Target: i-12345
- C. Destination: 172.28.0.0/12 and Target: vgw-12345
- D. Destination: 20.0.0.0/16 and Target: local

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. If the user has setup a NAT instance to route all the internet requests then all requests to the internet should be routed to it. All requests to the organization's DC will be routed to the VPN gateway. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: i-12345 (To route all internet traffic to the NAT Instance. Destination: 172.28.0.0/12 & Target: vgw-12345 (To route all the organization's data centre traffic to the VPN gateway. Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC).

NEW QUESTION 329

- (Topic 3)

A user has enabled termination protection on an EC2 instance. The user has also set Instance initiated shutdown behaviour to terminate. When the user shuts down the instance from the OS, what will happen?

- A. The OS will shutdown but the instance will not be terminated due to protection
- B. It will terminate the instance
- C. It will not allow the user to shutdown the instance from the OS
- D. It is not possible to set the termination protection when an Instance initiated shutdown is set to Terminate

Answer: B

Explanation:

It is always possible that someone can terminate an EC2 instance using the Amazon EC2 console, command line interface or API by mistake. If the admin wants to prevent the instance from being accidentally terminated, he can enable termination protection for that instance. The user can also setup shutdown behaviour for an EBS backed instance to guide the instance on what should be done when he initiates shutdown from the OS using Instance initiated shutdown behaviour. If the instance initiated behaviour is set to terminate and the user shuts off the OS even though termination protection is enabled, it will still terminate the instance.

NEW QUESTION 334

- (Topic 3)

An organization is measuring the latency of an application every minute and storing data inside a file in the JSON format. The organization wants to send all latency data to AWS CloudWatch. How can the organization achieve this?

- A. The user has to parse the file before uploading data to CloudWatch

- B. It is not possible to upload the custom data to CloudWatch
- C. The user can supply the file as an input to the CloudWatch command
- D. The user can use the CloudWatch Import command to import data from the file to CloudWatch

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user has to always include the namespace as part of the request. If the user wants to upload the custom data from a Amazon AWS-SysOps : Practice Test file, he can supply file name along with the parameter -- metric-data to command put-metric-data.

NEW QUESTION 335

- (Topic 3)

A user has created an Auto Scaling group using CLI. The user wants to enable CloudWatch detailed monitoring for that group. How can the user configure this?

- A. When the user sets an alarm on the Auto Scaling group, it automatically enables detail monitoring
- B. By default detailed monitoring is enabled for Auto Scaling
- C. Auto Scaling does not support detailed monitoring
- D. Enable detail monitoring from the AWS console

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates an Auto Scaling launch config as the first step for creating an Auto Scaling group, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. Thus, the user does not need to set this flag if he wants detailed monitoring.

NEW QUESTION 338

- (Topic 3)

A user has granted read/write permission of his S3 bucket using ACL. Which of the below mentioned options is a valid ID to grant permission to other AWS accounts (grantee. using ACL?

- A. IAM User ID
- B. S3 Secure ID
- C. Access ID
- D. Canonical user ID

Answer: D

Explanation:

An S3 bucket ACL grantee can be an AWS account or one of the predefined Amazon S3 groups. The user can grant permission to an AWS account by the email address of that account or by the canonical user ID. If the user provides an email in the grant request, Amazon S3 finds the canonical user ID for that account and adds it to the ACL. The resulting ACL will always contain the canonical user ID for the AWS account, and not the AWS account's email address.

NEW QUESTION 343

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created one subnet with CIDR 20.0.0.0/16 by mistake. The user is trying to create another subnet of CIDR 20.0.0.1/24. How can the user create the second subnet?

- A. There is no need to update the subnet as VPC automatically adjusts the CIDR of the first subnet based on the second subnet's CIDR
- B. The user can modify the first subnet CIDR from the console
- C. It is not possible to create a second subnet as one subnet with the same CIDR as the VPC has been created
- D. The user can modify the first subnet CIDR with AWS CLI

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside the subnet. The user can create a subnet with the same size of VPC. However, he cannot create any other subnet since the CIDR of the second subnet will conflict with the first subnet. The user cannot modify the CIDR of a subnet once it is created. Thus, in this case if required, the user has to delete the subnet and create new subnets.

NEW QUESTION 347

- (Topic 3)

A user has launched a Windows based EC2 instance. However, the instance has some issues and the user wants to check the log. When the user checks the Instance console output from the AWS console, what will it display?

- A. All the event logs since instance boot
- B. The last 10 system event log error
- C. The Windows instance does not support the console output
- D. The last three system events' log errors

Answer: D

Explanation:

The AWS EC2 console provides a useful tool called Console output for problem diagnosis. It is useful to find out any kernel issues, termination reasons or service configuration issues. For a Windows instance it lists the last three system event log errors. For Linux it displays the exact console output.

NEW QUESTION 351

- (Topic 3)

Your organization is preparing for a security assessment of your use of AWS.

In preparation for this assessment, which two IAM best practices should you consider implementing? Choose 2 answers

- A. Create individual IAM users for everyone in your organization
- B. Configure MFA on the root account and for privileged IAM users
- C. Assign IAM users and groups configured with policies granting least privilege access
- D. Ensure all users have been assigned and are frequently rotating a password, access ID/secret key, and X.509 certificate

Answer: BC

Explanation:

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

NEW QUESTION 353

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using VPC Wizard. The user has created a public CIDR

(20.0.0.0/24. and a VPN only subnet CIDR (20.0.1.0/24. along with the hardware VPN access to connect to the user's data centre. Which of the below mentioned components is not present when the VPC is setup with the wizard?

- A. Main route table attached with a VPN only subnet
- B. A NAT instance configured to allow the VPN subnet instances to connect with the internet
- C. Custom route table attached with a public subnet
- D. An internet gateway for a public subnet

Answer: B

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. The wizard does not create a NAT instance by default. The user can create it manually and attach it with a VPN only subnet.

NEW QUESTION 358

.....

Relate Links

100% Pass Your AWS-SysOps Exam with Examible Prep Materials

<https://www.exambible.com/AWS-SysOps-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>