

Amazon

Exam Questions AWS-Certified-Solutions-Architect-Professional

Amazon AWS Certified Solutions Architect Professional



NEW QUESTION 1

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent notification to all devices associated with an identity to notify them that new data is available.

- A. get
- B. post
- C. pull
- D. push

Answer: D

Explanation:

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent push notification to all devices associated with an identity to notify them that new data is available.

Reference: <http://aws.amazon.com/cognito/faqs/>

NEW QUESTION 2

You want to use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC). What criterion must be met for this to be possible?

- A. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access only the public AWS CodeDeploy endpoint.
- B. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access only the public Amazon S3 service endpoint.
- C. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access the public AWS CodeDeploy and Amazon S3 service endpoints.
- D. It is not currently possible to use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC.)

Answer: C

Explanation:

You can use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC). However, the AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access the public AWS CodeDeploy and Amazon S3 service endpoints. Reference: <http://aws.amazon.com/codedeploy/faqs/>

NEW QUESTION 3

An IAM user is trying to perform an action on an object belonging to some other root account's bucket. Which of the below mentioned options will AWS S3 not verify?

- A. The object owner has provided access to the IAM user
- B. Permission provided by the parent of the IAM user on the bucket
- C. Permission provided by the bucket owner to the IAM user
- D. Permission provided by the parent of the IAM user

Answer: B

Explanation:

If the IAM user is trying to perform some action on the object belonging to another AWS user's bucket, S3 will verify whether the owner of the IAM user has given sufficient permission to him. It also verifies the policy for the bucket as well as the policy defined by the object owner.

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/access-control-auth-workflow-object-operation.html>

NEW QUESTION 4

An organization is planning to extend their data center by connecting their DC with the AWS VPC using the VPN gateway. The organization is setting up a dynamically routed VPN connection. Which of the below mentioned answers is not required to setup this configuration?

- A. The type of customer gateway, such as Cisco ASA, Juniper J-Series, Juniper SSG, Yamaha.
- B. Elastic IP ranges that the organization wants to advertise over the VPN connection to the VPC.
- C. Internet-routable IP address (static) of the customer gateway's external interface.
- D. Border Gateway Protocol (BGP) Autonomous System Number (ASN) of the customer gateway

Answer: B

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. The organization wants to extend their network into the cloud and also directly access the internet from their AWS VPC. Thus, the organization should setup a Virtual Private Cloud (VPC) with a public subnet and a private subnet, and a virtual private gateway to enable communication with their data center network over an IPsec VPN tunnel. To setup this configuration the organization needs to use the Amazon VPC with a VPN connection. The organization network administrator must designate a physical appliance as a customer gateway and configure it. The organization would need the below mentioned information to setup this configuration:

The type of customer gateway, such as Cisco ASA, Juniper J-Series, Juniper SSG, Yamaha Internet-routable IP address (static) of the customer gateway's external interface

Border Gateway Protocol (BGP) Autonomous System Number (ASN) of the customer gateway, if the organization is creating a dynamically routed VPN connection.

Internal network IP ranges that the user wants to advertise over the VPN connection to the VPC. Reference:

http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_VPN.html

NEW QUESTION 5

An organization is planning to host a Wordpress blog as well a Joomla CMS on a single instance launched with VPC. The organization wants to have separate domains for each application and assign them using Route 53. The organization may have about ten instances each with two applications as mentioned above. While launching the instance, the organization configured two separate network interfaces (primary + ENI) and wanted to have two elastic IPs for that instance. It was suggested to use a public IP from AWS instead of an elastic IP as the number of elastic IPs is restricted. What action will you recommend to the organization?

- A. I agree with the suggestion but will prefer that the organization should use separate subnets with each ENI for different public IPs.
- B. I do not agree as it is required to have only an elastic IP since an instance has more than one ENI and AWS does not assign a public IP to an instance with multiple ENIs.
- C. I do not agree as AWS VPC does not attach a public IP to an ENI; so the user has to use only an elastic IP only.
- D. I agree with the suggestion and it is recommended to use a public IP from AWS since the organization is going to use DNS with Route 53.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. An Elastic Network Interface (ENI) is a virtual network interface that the user can attach to an instance in a VPC.

The user can attach up to two ENIs with a single instance. However, AWS cannot assign a public IP when there are two ENIs attached to a single instance. It is recommended to assign an elastic IP in this scenario. If the organization wants more than 5 EIPs they can request AWS to increase the number.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

NEW QUESTION 6

What is the default maximum number of VPCs allowed per region?

- A. 5
- B. 10
- C. 100
- D. 15

Answer: A

Explanation:

The maximum number of VPCs allowed per region is 5.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Appendix_Limits.html

NEW QUESTION 7

A customer has a website which shows all the deals available across the market. The site experiences a load of 5 large EC2 instances generally. However, a week before Thanksgiving vacation they encounter a load of almost 20 large instances. The load during that period varies over the day based on the office timings. Which of the below mentioned solutions is cost effective as well as help the website achieve better performance?

- A. Setup to run 10 instances during the pre-vacation period and only scale up during the office time by launching 10 more instances using the AutoScaling schedule.
- B. Keep only 10 instances running and manually launch 10 instances every day during office hours.
- C. During the pre-vacation period setup 20 instances to run continuously.
- D. During the pre-vacation period setup a scenario where the organization has 15 instances running and 5 instances to scale up and down using Auto Scaling based on the network I/O policy.

Answer: D

Explanation:

AWS provides an on demand, scalable infrastructure. AWS EC2 allows the user to launch On-Demand instances and the organization should create an AMI of the running instance. When the organization is experiencing varying loads and the time of the load is not known but it is higher than the routine traffic it is recommended that the organization launches a few instances before hand and then setups AutoScaling with policies which scale up and down as per the EC2 metrics, such as Network I/O or CPU utilization.

If the organization keeps all 10 additional instances as a part of the AutoScaling policy sometimes during a sudden higher load it may take time to launch instances and may not give an optimal performance. This is the reason it is recommended that the organization keeps an additional 5 instances running and the next 5 instances scheduled as per the AutoScaling policy for cost effectiveness.

Reference: http://media.amazonwebservices.com/AWS_Web_Hosting_Best_Practices.pdf

NEW QUESTION 8

An organization is setting a website on the AWS VPC. The organization has blocked a few IPs to avoid a D-DOS attack. How can the organization configure that a request from the above mentioned IPs does not access the application instances?

- A. Create an IAM policy for VPC which has a condition to disallow traffic from that IP address.
- B. Configure a security group at the subnet level which denies traffic from the selected IP.
- C. Configure the security group with the EC2 instance which denies access from that IP address.
- D. Configure an ACL at the subnet which denies the traffic from that IP address

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. Security group works at the instance level while ACL works at the subnet level. ACL allows both allow and deny rules.

Thus, when the user wants to reject traffic from the selected IPs it is recommended to use ACL with subnets.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_ACLs.html

NEW QUESTION 9

An organization has 4 people in the IT operations team who are responsible to manage the AWS infrastructure. The organization wants to setup that each user will

have access to launch and manage an instance in a zone which the other user cannot modify. Which of the below mentioned options is the best solution to set this up?

- A. Create four AWS accounts and give each user access to a separate account.
- B. Create an IAM user and allow them permission to launch an instance of a different sizes only.
- C. Create four IAM users and four VPCs and allow each IAM user to have access to separate VPCs.
- D. Create a VPC with four subnets and allow access to each subnet for the individual IAM user

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC also work with IAM and the organization can create IAM users who have access to various VPC services. The organization can setup access for the IAM user who can modify the security groups of the VPC. The sample policy is given below:

```
{
"Version": "2012-10-17",
"Statement":
[
  {
    "Effect": "Allow",
    "Action": "ec2:RunInstances",
    "Resource":
    [
      "arn:aws:ec2:region::image/ami-*",
      "arn:aws:ec2:region:account:subnet/subnet-1a2b3c4d",
      "arn:aws:ec2:region:account:network-interface/*",
      "arn:aws:ec2:region:account:volume/*",
      "arn:aws:ec2:region:account:key-pair/*",
      "arn:aws:ec2:region:account:security-group/sg-123abc123"
    ]
  }
]
```

With this policy the user can create four subnets in separate zones and provide IAM user access to each subnet

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_IAM.html

NEW QUESTION 10

An organization is planning to host an application on the AWS VPC. The organization wants dedicated instances. However, an AWS consultant advised the organization not to use dedicated instances with VPC as the design has a few limitations. Which of the below mentioned statements is not a limitation of dedicated instances with VPC?

- A. All instances launched with this VPC will always be dedicated instances and the user cannot use a default tenancy model for them.
- B. It does not support the AWS RDS with a dedicated tenancy VPC.
- C. The user cannot use Reserved Instances with a dedicated tenancy model.
- D. The EBS volume will not be on the same tenant hardware as the EC2 instance though the user has configured dedicated tenancy.

Answer: C

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Dedicated instances are Amazon EC2 instances that run in a Virtual Private Cloud (VPC) on hardware that is dedicated to a single customer. The client's dedicated instances are physically isolated at the host hardware level from instances that are not dedicated instances as well as from instances that belong to other AWS accounts.

All instances launched with the dedicated tenancy model of VPC will always be dedicated instances. Dedicated tenancy has a limitation that it may not support a few services, such as RDS. Even the EBS will not be on dedicated hardware. However the user can save some cost as well as reserve some capacity by using a Reserved Instance model with dedicated tenancy.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/dedicated-instance.html>

NEW QUESTION 10

In which step of using AWS Direct Connect should the user determine the required port speed?

- A. Complete the Cross Connect
- B. Verify Your Virtual Interface
- C. Download Router Configuration
- D. Submit AWS Direct Connect Connection Request

Answer: D

Explanation:

To submit an AWS Direct Connect connection request, you need to provide the following information: Your contact information.

The AWS Direct Connect Location to connect to.

Details of AWS Direct Connect partner if you use the AWS Partner Network (APN) service. The port speed you require, either 1 Gbps or 10 Gbps.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/getstarted.html#ConnectionRequest>

NEW QUESTION 14

In Amazon IAM, what is the maximum length for a role name?

- A. 128 characters
- B. 512 characters
- C. 64 characters
- D. 256 characters

Answer: C

Explanation:

In Amazon IAM, the maximum length for a role name is 64 characters.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 16

While implementing the policy keys in AWS Direct Connect, if you use and the request comes from an Amazon EC2 instance, the instance's public IP address is evaluated to determine if access is allowed.

- A. aws:SecureTransport
- B. aws:EpochIP
- C. aws:SourceIp
- D. aws:CurrentTime

Answer: C

Explanation:

While implementing the policy keys in Amazon RDS, if you use aws:SourceIp and the request comes from an Amazon EC2 instance, the instance's public IP address is evaluated to determine if access is allowed. Reference: http://docs.aws.amazon.com/directconnect/latest/UserGuide/using_iam.html

NEW QUESTION 21

How many g2.2xlarge on-demand instances can a user run in one region without taking any limit increase approval from AWS?

- A. 20
- B. 2
- C. 5
- D. 10

Answer: C

Explanation:

Generally AWS EC2 allows running 20 on-demand instances and 100 spot instances at a time. This limit can be increased by requesting at <https://aws.amazon.com/contact-us/ec2-request>. Excluding certain types of instances, the limit is lower than mentioned above. For g2.2xlarge, the user can run only 5 on-demand instance at a time.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2

NEW QUESTION 22

A user has created a MySQL RDS instance with PIOPS. Which of the below mentioned statements will help user understand the advantage of PIOPS?

- A. The user can achieve additional dedicated capacity for the EBS I/O with an enhanced RDS option
- B. It uses a standard EBS volume with optimized configuration the stacks
- C. It uses optimized EBS volumes and optimized configuration stacks
- D. It provides a dedicated network bandwidth between EBS and RDS

Answer: C

Explanation:

RDS DB instance storage comes in two types: standard and provisioned IOPS. Standard storage is allocated on the Amazon EBS volumes and connected to the user's DB instance. Provisioned IOPS uses optimized EBS volumes and an optimized configuration stack. It provides additional, dedicated capacity for the EBS I/O.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 26

A user authenticating with Amazon Cognito will go through a multi-step process to bootstrap their credentials. Amazon Cognito has two different flows for authentication with public providers. Which of the following are the two flows?

- A. Authenticated and non-authenticated
- B. Public and private
- C. Enhanced and basic
- D. Single step and multistep

Answer: C

Explanation:

A user authenticating with Amazon Cognito will go through a multi-step process to bootstrap their credentials. Amazon Cognito has two different flows for authentication with public providers: enhanced and basic.

Reference: <http://docs.aws.amazon.com/cognito/devguide/identity/concepts/authentication-flow/>

NEW QUESTION 27

Which of the following is the Amazon Resource Name (ARN) condition operator that can be used within an Identity and Access Management (IAM) policy to check the case-insensitive matching of the ARN?

- A. ArnCheck
- B. ArnMatch
- C. ArnCase
- D. ArnLike

Answer: D

Explanation:

Amazon Resource Name (ARN) condition operators let you construct Condition elements that restrict access based on comparing a key to an ARN. ArnLike, for instance, is a case-insensitive matching of the ARN. Each of the six colon-delimited components of the ARN is checked separately and each can include a multi-character match wildcard (*) or a single-character match wildcard (?).

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 31

An organization is creating a VPC for their application hosting. The organization has created two private subnets in the same AZ and created one subnet in a separate zone. The organization wants to make a HA system with the internal ELB. Which of these statements is true with respect to an internal ELB in this scenario?

- A. ELB can support only one subnet in each availability zone.
- B. ELB does not allow subnet selection; instead it will automatically select all the available subnets of the VPC.
- C. If the user is creating an internal ELB, he should use only private subnets.
- D. ELB can support all the subnets irrespective of their zone

Answer: A

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances.

There are two ELBs available with VPC: internet facing and internal (private) ELB. For internal servers, such as App servers the organization can create an internal load balancer in their VPC and then place back-end application instances behind the internal load balancer. The internal load balancer will route requests to the back-end application instances, which are also using private IP addresses and only accept requests from the internal load balancer.

The Internal ELB supports only one subnet in each AZ and asks the user to select a subnet while configuring internal ELB.

Reference: http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/USVPC_creating_basic_lb.html

NEW QUESTION 34

IV|apMySite is setting up a web application in the AWS VPC. The organization has decided to use an AWS RDS instead of using its own DB instance for HA and DR requirements.

The organization also wants to secure RDS access. How should the web application be setup with RDS?

- A. Create a VPC with one public and one private subne
- B. Launch an application instance in the public subnet while RDS is launched in the private subnet.
- C. Setup a public and two private subnets in different AZs within a VPC and create a subnet grou
- D. Launch RDS with that subnet group.
- E. Create a network interface and attach two subnets to i
- F. Attach that network interface with RDS while launching a DB instance.
- G. Create two separate VPCs and launch a Web app in one VPC and RDS in a separate VPC and connect them with VPC peering.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on the security and operational needs.

A DB subnet group is a collection of subnets (generally private) that a user can create in a VPC and assign to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating the DB instances. Each DB subnet group should have subnets in at least two Availability Zones in a given region.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html

NEW QUESTION 38

An organization (account ID 123412341234) has configured the IAM policy to allow the user to modify his credentials. What will the below mentioned statement allow the user to perform?

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow", "Action": [ "iam:AddUserToGroup",
    "iam:RemoveUserFromGroup", "iam:GetGroup"
    ]!
    "Resource": "arn:aws:iam:: 123412341234:group/TestingGroup"
  ]!
}
```

- A. Allow the IAM user to update the membership of the group called TestingGroup
- B. The IAM policy will throw an error due to an invalid resource name
- C. The IAM policy will allow the user to subscribe to any IAM group
- D. Allow the IAM user to delete the TestingGroup

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (account ID 123412341234) wants their users to manage their subscription to the groups, they should create a relevant policy for that. The below mentioned policy allows the respective IAM user to update the membership of the group called MarketingGroup.

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow", "Action": [ "iam:AddUserToGroup",
    "iam:RemoveUserFromGroup", "iam:GetGroup"
    ]!
    "Resource": "arn:aws:iam:: 123412341234:group/ TestingGroup "
  ]!
}
```

Reference:

<http://docs.aws.amazon.com/IAM/latest/UserGuide/Credentials-Permissions-examples.htm#creds-polici es-credentials>

NEW QUESTION 40

How can multiple compute resources be used on the same pipeline in AWS Data Pipeline?

- A. You can use multiple compute resources on the same pipeline by defining multiple cluster objects in your definition file and associating the cluster to use for each actMty via its runsOn field.
- B. You can use multiple compute resources on the same pipeline by defining multiple cluster definition files.
- C. You can use multiple compute resources on the same pipeline by defining multiple clusters for your actMty.
- D. You cannot use multiple compute resources on the same pipelin

Answer: A

Explanation:

Multiple compute resources can be used on the same pipeline in AWS Data Pipeline by defining multiple cluster objects in your definition file and associating the cluster to use for each actMty via its runsOn field, which allows pipelines to combine AWS and on-premise resources, or to use a mix of instance types for their actMties.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 42

The two policies that you attach to an IAM role are the access policy and the trust policy. The trust policy identifies who can assume the role and grants the permission in the AWS Lambda account principal by adding the action.

- A. aws:AssumeAdmin
- B. lambda:InvokeAsync
- C. sts:InvokeAsync
- D. sts:AssumeRole

Answer: D

Explanation:

The two policies that you attach to an IAM role are the access policy and the trust policy.

Remember that adding an account to the trust policy of a role is only half of establishing the trust relationship. By default, no users in the trusted accounts can assume the role until the administrator for that account grants the users the permission to assume the role by adding the Amazon Resource Name (ARN) of the role to an Allow element for the sts:AssumeRole action.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_manage_modify.html

NEW QUESTION 47

The MySecureData company has five branches across the globe. They want to expand their data centers such that their web server will be in the AWS and each branch would have their own database in the local data center. Based on the user login, the company wants to connect to the data center. How can MySecureData company implement this scenario with the AWS VPC?

- A. Create five VPCs with the public subnet for the app server and setup the VPN gateway for each VPN to connect them indMdually.
- B. Use the AWS VPN CloudHub to communicate with multiple VPN connections.
- C. Use the AWS CloudGateway to communicate with multiple VPN connections.
- D. It is not possible to connect different data centers from a single VPC.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. If the organization has multiple VPN connections, he can provide secure communication between sites using the AWS VPN CloudHub.

The VPN CloudHub operates on a simple hub-and-spoke model that the user can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing internet connections who would like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectMty between remote offices.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html

NEW QUESTION 50

True or False: In Amazon ElastiCache replication groups of Redis, for performance tuning reasons, you can change the roles of the cache nodes within the replication group, with the primary and one of the replicas exchanging roles.

- A. True, however, you get lower performance.
- B. FALSE
- C. TRUE
- D. False, you must recreate the replication group to improve performance tunin

Answer: C

Explanation:

In Amazon ElastiCache, a replication group is a collection of Redis Cache Clusters, with one primary read-write cluster and up to five secondary, read-only clusters, which are called read replicas. You can change the roles of the cache clusters within the replication group, with the primary cluster and one of the replicas exchanging roles. You might decide to do this for performance tuning reasons.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/Replication.Redis.Groups.html>

NEW QUESTION 52

Regarding Amazon SNS, you can send notification messages to mobile devices through any of the following supported push notification services, EXCEPT:

- A. Microsoft Windows Mobile Messaging (MWMM)
- B. Google Cloud Messaging for Android (GCM)
- C. Amazon Device Messaging (ADM)

D. Apple Push Notification Service (APNS)

Answer: A

Explanation:

In Amazon SNS, you have the ability to send notification messages directly to apps on mobile devices. Notification messages sent to a mobile endpoint can appear in the mobile app as message alerts, badge updates, or even sound alerts. Microsoft Windows Mobile Messaging (MWMM) doesn't exist and is not supported by Amazon SNS.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

NEW QUESTION 56

IAM Secure And Scalable is an organization which provides scalable and secure SAAS to its clients. They are planning to host a web server and App server on AWS VPC as separate tiers. The organization wants to implement the scalability by configuring Auto Scaling and load balancer with their app servers (middle tier) too. Which of the below mentioned options suits their requirements?

- A. Since ELB is internet facing, it is recommended to setup HAProxy as the Load balancer within the VPC.
- B. Create an Internet facing ELB with VPC and configure all the App servers with it.
- C. The user should make ELB with EC2-CLASSIC and enable SSH with it for security.
- D. Create an Internal Load balancer with VPC and register all the App servers with it.

Answer: D

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances.

There are two ELBs available with VPC: internet facing and internal (private) ELB. For internal servers, such as App servers the organization can create an internal load balancer in their VPC and then place back-end application instances behind the internal load balancer. The internal load balancer will route requests to the back-end application instances, which are also using private IP addresses and only accept requests from the internal load balancer.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/vpc-loadbalancer-types.html>

NEW QUESTION 58

Which of the following is NOT an advantage of using AWS Direct Connect?

- A. AWS Direct Connect provides users access to public and private resources by using two different connections while maintaining network separation between the public and private environments.
- B. AWS Direct Connect provides a more consistent network experience than Internet-based connections.
- C. AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS.
- D. AWS Direct Connect reduces your network cost

Answer: A

Explanation:

AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS. Using AWS Direct Connect, you can establish private connectivity between AWS and your datacenter, office, or colocation environment, which in many cases can reduce your network costs, increase bandwidth throughput, and provide a more consistent network experience than Internet-based connections.

By using industry standard 802.1q VLANs, this dedicated connection can be partitioned into multiple virtual interfaces. This allows you to use the same connection to access public resources such as objects stored in Amazon S3 using public IP address space, and private resources such as Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC) using private IP space, while maintaining network separation between the public and private environments.

Reference: <http://aws.amazon.com/directconnect/#details>

NEW QUESTION 60

An organization is setting up an application on AWS to have both High Availability (HA) and Disaster Recovery (DR). The organization wants to have both Recovery point objective (RPO) and Recovery time objective (RTO) of 10 minutes. Which of the below mentioned service configurations does not help the organization achieve the said RPO and RTO?

- A. Take a snapshot of the data every 10 minutes and copy it to the other region.
- B. Use an elastic IP to assign to a running instance and use Route 53 to map the user's domain with that IP.
- C. Create ELB with multi-region routing to allow automated failover when required.
- D. Use an AMI copy to keep the AMI available in other region

Answer: C

Explanation:

AWS provides an on demand, scalable infrastructure. AWS EC2 allows the user to launch On-Demand instances and the organization should create an AMI of the running instance. Copy the AMI to another region to enable Disaster Recovery (DR) in case of region failure. The organization should also use EBS for persistent storage and take a snapshot every 10 minutes to meet Recovery time objective (RTO). They should also setup an elastic IP and use it with Route 53 to route requests to the same IP.

When one of the instances fails the organization can launch new instances and assign the same EIP to a new instance to achieve High Availability (HA). The ELB works only for a particular region and does not route requests across regions.

Reference: http://d36cz9buwru1tt.ccloudfront.net/AWS_Disaster_Recovery.pdf

NEW QUESTION 64

By default, what is the maximum number of Cache Nodes you can run in Amazon ElastiCache?

- A. 20
- B. 50

- C. 100
- D. 200

Answer: A

Explanation:

In Amazon ElastiCache, you can run a maximum of 20 Cache Nodes. Reference: <http://aws.amazon.com/elasticache/faqs/>

NEW QUESTION 65

Does an AWS Direct Connect location provide access to Amazon Web Services in the region it is associated with as well as access to other US regions?

- A. No, it provides access only to the region it is associated with.
- B. No, it provides access only to the US regions other than the region it is associated with.
- C. Yes, it provides access.
- D. Yes, it provides access but only when there's just one Availability Zone in the regio

Answer: C

Explanation:

An AWS Direct Connect location provides access to Amazon Web Services in the region it is associated with, as well as access to other US regions. For example, you can provision a single connection to any AWS Direct Connect location in the US and use it to access public AWS services in all US Regions and AWS GovCloud (US).

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

NEW QUESTION 67

In IAM, which of the following is true of temporary security credentials?

- A. Once you issue temporary security credentials, they cannot be revoked.
- B. None of these are correct.
- C. Once you issue temporary security credentials, they can be revoked only when the virtual MFA device is used.
- D. Once you issue temporary security credentials, they can be revoke

Answer: A

Explanation:

Temporary credentials in IAM are valid throughout their defined duration of time and hence can't be revoked. However, because permissions are evaluated each time an AWS request is made using the credentials, you can achieve the effect of revoking the credentials by changing the permissions for the credentials even after they have been issued. Reference:

[http://docs.aws.amazon.com/IAM/latest/UserGuide/id_credentials_temp_control-access_disable-perms.h tml](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_credentials_temp_control-access_disable-perms.html)

NEW QUESTION 71

In Amazon VPC, what is the default maximum number of BGP advertised routes allowed per route table?

- A. 15
- B. 100
- C. 5
- D. 10

Answer: B

Explanation:

The maximum number of BGP advertised routes allowed per route table is 100.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Appendix_Limits.html

NEW QUESTION 72

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create each user in a separate region so that they have their own URL to login
- B. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group
- E. The user can login with their own group ID

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_SettingUpUser.html

NEW QUESTION 76

The user has provisioned the PIOPS volume with an EBS optimized instance. Generally speaking, in which I/O chunk should the bandwidth experienced by the user be measured by AWS?

- A. 128 KB

- B. 256 KB
- C. 64 KB
- D. 32 KB

Answer: B

Explanation:

IOPS are input/output operations per second. Amazon EBS measures each I/O operation per second (that is 256 KB or smaller) as one IOPS.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-io-characteristics.html>

NEW QUESTION 78

ExamKiller has three separate departments and each department has their own AWS accounts. The HR department has created a file sharing site where all the on roll employees' data is uploaded. The Admin department uploads data about the employee presence in the office to their DB hosted in the VPC. The Finance department needs to access data from the HR department to know the on roll employees to calculate the salary based on the number of days that an employee is present in the office.
How can ExamKiller setup this scenario?

- A. It is not possible to configure VPC peering since each department has a separate AWS account.
- B. Setup VPC peering for the VPCs of Admin and Finance.
- C. Setup VPC peering for the VPCs of Finance and HR as well as between the VPCs of Finance and Admin.
- D. Setup VPC peering for the VPCs of Admin and HR

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. A VPC peering connection allows the user to route traffic between the peer VPCs using private IP addresses as if they are a part of the same network. This is helpful when one VPC from the same or different AWS account wants to connect with resources of the other VPC.

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/PeeringGuide/peering-configurations-full-access.html#three-vpcs-full-access>

NEW QUESTION 79

An organization is undergoing a security audit. The auditor wants to view the AWS VPC configurations as the organization has hosted all the applications in the AWS VPC. The auditor is from a remote place and wants to have access to AWS to view all the VPC records.
How can the organization meet the expectations of the auditor without compromising on the security of their AWS infrastructure?

- A. The organization should not accept the request as sharing the credentials means compromising on security.
- B. Create an IAM role which will have read only access to all EC2 services including VPC and assign that role to the auditor.
- C. Create an IAM user who will have read only access to the AWS VPC and share those credentials with the auditor.
- D. The organization should create an IAM user with VPC full access but set a condition that will not allow to modify anything if the request is from any IP other than the organization's data center.

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC also works with IAM and the organization can create IAM users who have access to various VPC services.

If an auditor wants to have access to the AWS VPC to verify the rules, the organization should be careful before sharing any data which can allow making updates to the AWS infrastructure. In this scenario it is recommended that the organization creates an IAM user who will have read only access to the VPC. Share the above mentioned credentials with the auditor as it cannot harm the organization. The sample policy is given below:

```
{
  "Effect": "Allow",
  "Action": [
    "ec2:DescribeVpcs",
    "ec2:DescribeSubnets",
    "ec2:DescribeInternetGateways",
    "ec2:DescribeCustomerGateways",
    "ec2:DescribeVpnGateways",
    "ec2:DescribeVpnConnections",
    "ec2:DescribeRouteTables",
    "ec2:DescribeAddresses",
    "ec2:DescribeSecurityGroups",
    "ec2:DescribeNetworkAcls",
    "ec2:DescribeDhcpOptions",
    "ec2:DescribeTags",
    "ec2:DescribeInstances"
  ],
  "Resource": "*"
}
```

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_IAM.html

NEW QUESTION 82

A user has configured EBS volume with PIOPS. The user is not experiencing the optimal throughput. Which of the following could not be factor affecting I/O performance of that EBS volume?

- A. EBS bandwidth of dedicated instance exceeding the PIOPS
- B. EC2 bandwidth
- C. EBS volume size
- D. Instance type is not EBS optimized

Answer: C

Explanation:

If the user is not experiencing the expected IOPS or throughput that is provisioned, ensure that the EC2 bandwidth is not the limiting factor, the instance is EBS-optimized (or include 10 Gigabit network connectMty) and the instance type EBS dedicated bandwidth exceeds the IOPS more than he has provisioned.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-io-characteristics.html>

NEW QUESTION 83

If a single condition within an IAM policy includes multiple values for one key, it will be evaluated using a logical .

- A. OR
- B. NAND
- C. NOR
- D. AND

Answer: A

Explanation:

If a single condition within an IAM policy includes multiple values for one key, it will be evaluated using a logical OR.
Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements.html

NEW QUESTION 84

In a VPC, can you modify a set of DHCP options after you create them?

- A. Yes, you can modify a set of DHCP options within 48 hours after creation and there are no VPCs associated with them.
- B. Yes, you can modify a set of DHCP options any time after you create them.
- C. No, you can't modify a set of DHCP options after you create them.
- D. Yes, you can modify a set of DHCP options within 24 hours after creation.

Answer: C

Explanation:

After you create a set of DHCP options, you can't modify them. If you want your VPC to use a different set of DHCP options, you must create a new set and associate them with your VPC. You can also set up your VPC to use no DHCP options at all.
Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_DHCP_Options.html

NEW QUESTION 85

A bucket owner has allowed another account's IAM users to upload or access objects in his bucket. The IAM user of Account A is trying to access an object created by the IAM user of account B. What will happen in this scenario?

- A. It is not possible to give permission to multiple IAM users
- B. AWS S3 will verify proper rights given by the owner of Account A, the bucket owner as well as by the IAM user B to the object
- C. The bucket policy may not be created as S3 will give error due to conflict of Access Rights
- D. It is not possible that the IAM user of one account accesses objects of the other IAM user

Answer: B

Explanation:

If a IAM user is trying to perform some action on an object belonging to another AWS user's bucket, S3 will verify whether the owner of the IAM user has given sufficient permission to him. It also verifies the policy for the bucket as well as the policy defined by the object owner.
Reference:
<http://docs.aws.amazon.com/AmazonS3/latest/dev/access-control-auth-workflow-object-operation.html>

NEW QUESTION 88

An organization has hosted an application on the EC2 instances. There will be multiple users connecting to the instance for setup and configuration of application. The organization is planning to implement certain security best practices. Which of the below mentioned pointers will not help the organization achieve better security arrangement?

- A. Allow only IAM users to connect with the EC2 instances with their own secret access key.
- B. Create a procedure to revoke the access rights of the individual user when they are not required to connect to EC2 instance anymore for the purpose of application configuration.
- C. Apply the latest patch of OS and always keep it updated.
- D. Disable the password based login for all the user
- E. All the users should use their own keys to connect with the instance securely.

Answer: A

Explanation:

Since AWS is a public cloud any application hosted on EC2 is prone to hacker attacks. It becomes extremely important for a user to setup a proper security mechanism on the EC2 instances. A few of the security measures are listed below:

Always keep the OS updated with the latest patch

Always create separate users within OS if they need to connect with the EC2 instances, create their keys and disable their password

Create a procedure using which the admin can revoke the access of the user when the business work on the EC2 instance is completed

Lock down unnecessary ports

Audit any proprietary applications that the user may be running on the EC2 instance

Provide temporary escalated privileges, such as sudo for users who need to perform occasional privileged tasks

The IAM is useful when users are required to work with AWS resources and actions, such as launching an instance. It is not useful to connect (RDP / SSH) with an instance.

Reference: <http://aws.amazon.com/articles/1233/>

NEW QUESTION 90

With Amazon Elastic MapReduce (Amazon EMR) you can analyze and process vast amounts of data. The cluster is managed using an open-source framework called Hadoop.

You have set up an application to run Hadoop jobs. The application reads data from DynamoDB and generates a temporary file of 100 TBs.

The whole process runs for 30 minutes and the output of the job is stored to S3. Which of the below mentioned options is the most cost effective solution in this case?

- A. Use Spot Instances to run Hadoop jobs and configure them with EBS volumes for persistent data storage.
- B. Use Spot Instances to run Hadoop jobs and configure them with ephemeral storage for output file storage.

- C. Use an on demand instance to run Hadoop jobs and configure them with EBS volumes for persistent storage.
- D. Use an on demand instance to run Hadoop jobs and configure them with ephemeral storage for output file storage.

Answer: B

Explanation:

AWS EC2 Spot Instances allow the user to quote his own price for the EC2 computing capacity. The user can simply bid on the spare Amazon EC2 instances and run them whenever his bid exceeds the current Spot Price. The Spot Instance pricing model complements the On-Demand and Reserved Instance pricing models, providing potentially the most cost-effective option for obtaining compute capacity, depending on the application. The only challenge with a Spot Instance is data persistence as the instance can be terminated whenever the spot price exceeds the bid price.

In the current scenario a Hadoop job is a temporary job and does not run for a longer period. It fetches data from a persistent DynamoDB. Thus, even if the instance gets terminated there will be no data loss and the job can be re-run. As the output files are large temporary files, it will be useful to store data on ephemeral storage for cost savings.

Reference: <http://aws.amazon.com/ec2/purchasing-options/spot-instances/>

NEW QUESTION 92

True or False : "In the context of Amazon ElastiCache, from the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an individual cache node."

- A. True, from the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an individual cache node since, each has a unique node identifier.
- B. True, from the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an individual cache node.
- C. False, you can connect to a cache node, but not to a cluster configuration endpoint.
- D. False, you can connect to a cluster configuration endpoint, but not to a cache node

Answer: B

Explanation:

This is true. From the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an individual cache node. In the process of connecting to cache nodes, the application resolves the configuration endpoint's DNS name. Because the configuration endpoint maintains CNAME entries for all of the cache nodes, the DNS name resolves to one of the nodes; the client can then connect to that node.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/AutoDiscovery.HowAutoDiscoveryWorks.html>

NEW QUESTION 96

An EC2 instance that performs source/destination checks by default is launched in a private VPC subnet. All security, NACL, and routing definitions are configured as expected. A custom NAT instance is launched.

Which of the following must be done for the custom NAT instance to work?

- A. The source/destination checks should be disabled on the NAT instance.
- B. The NAT instance should be launched in public subnet.
- C. The NAT instance should be configured with a public IP address.
- D. The NAT instance should be configured with an elastic IP address

Answer: A

Explanation:

Each EC2 instance performs source/destination checks by default. This means that the instance must be the source or destination of any traffic it sends or receives. However, a NAT instance must be able to send and receive traffic when the source or destination is not itself. Therefore, you must disable source/destination checks on the NAT instance.

Reference:

http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_NAT_Instance.html#EIP_Disable_SrcDestCheck

NEW QUESTION 97

How does in-memory caching improve the performance of applications in ElastiCache?

- A. It improves application performance by deleting the requests that do not contain frequently accessed data.
- B. It improves application performance by implementing good database indexing strategies.
- C. It improves application performance by using a part of instance RAM for caching important data.
- D. It improves application performance by storing critical pieces of data in memory for low-latency access

Answer: D

Explanation:

In Amazon ElastiCache, in-memory caching improves application performance by storing critical pieces of data in memory for low-latency access. Cached information may include the results of I/O-intensive database queries or the results of computationally intensive calculations.

Reference: <http://aws.amazon.com/elasticache/faqs/#g4>

NEW QUESTION 98

A user is thinking to use EBS PIOPS volume. Which of the below mentioned options is a right use case for the PIOPS EBS volume?

- A. Analytics
- B. System boot volume
- C. MongoDB
- D. Log processing

Answer: C

Explanation:

Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads that are sensitive to storage performance and consistency in random access I/O throughput. Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads, that are sensitive to storage performance and consistency in random access I/O throughput business applications, database workloads, such as NoSQL DB, RDBMS, etc. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 103

Which of the following is true of an instance profile when an IAM role is created using the console?

- A. The instance profile uses a different name.
- B. The console gives the instance profile the same name as the role it corresponds to.
- C. The instance profile should be created manually by a user.
- D. The console creates the role and instance profile as separate actions.

Answer: B

Explanation:

Amazon EC2 uses an instance profile as a container for an IAM role. When you create an IAM role using the console, the console creates an instance profile automatically and gives it the same name as the role it corresponds to. If you use the AWS CLI, API, or an AWS SDK to create a role, you create the role and instance profile as separate actions, and you might give them different names.

Reference:

http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_use_switch-role-ec2_instance-profiles.html

NEW QUESTION 107

Which of the following is true while using an IAM role to grant permissions to applications running on Amazon EC2 instances?

- A. All applications on the instance share the same role, but different permissions.
- B. All applications on the instance share multiple roles and permissions.
- C. Multiple roles are assigned to an EC2 instance at a time.
- D. Only one role can be assigned to an EC2 instance at a time

Answer: D

Explanation:

Only one role can be assigned to an EC2 instance at a time, and all applications on the instance share the same role and permissions.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/role-usecase-ec2app.html>

NEW QUESTION 110

When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose ones. streqi is the short version of the string condition.

- A. StringEqualsIgnoreCase
- B. StringNotEqualsIgnoreCase
- C. StringLikeStringEquals
- D. StringNotEquals

Answer: A

Explanation:

When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. For instance, streqi is the short version of StringEqualsIgnoreCase that checks for the exact match between two strings ignoring their case.

Reference: <http://awsdocs.s3.amazonaws.com/SNS/20100331/sns-gsg-2010-03-31.pdf>

NEW QUESTION 111

Attempts, one of the three types of items associated with the schedule pipeline in the AWS Data Pipeline, provides robust data management.

Which of the following statements is NOT true about Attempts?

- A. Attempts provide robust data management.
- B. AWS Data Pipeline retries a failed operation until the count of retries reaches the maximum number of allowed retry attempts.
- C. An AWS Data Pipeline Attempt object compiles the pipeline components to create a set of actionable instances.
- D. AWS Data Pipeline Attempt objects track the various attempts, results, and failure reasons if applicable.

Answer: C

Explanation:

Attempts, one of the three types of items associated with a schedule pipeline in AWS Data Pipeline, provides robust data management. AWS Data Pipeline retries a failed operation. It continues to do so until the task reaches the maximum number of allowed retry attempts. Attempt objects track the various attempts, results, and failure reasons if applicable. Essentially, it is the instance with a counter. AWS Data Pipeline performs retries using the same resources from the previous attempts, such as Amazon EMR clusters and EC2 instances.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-tasks-scheduled.html>

NEW QUESTION 116

Select the correct statement about Amazon ElastiCache.

- A. It makes it easy to set up, manage, and scale a distributed in-memory cache environment in the cloud.
- B. It allows you to quickly deploy your cache environment only if you install software.
- C. It does not integrate with other Amazon Web Services.
- D. It cannot run in the Amazon Virtual Private Cloud (Amazon VPC) environment

Answer: A

Explanation:

ElastiCache is a web service that makes it easy to set up, manage, and scale a distributed in-memory cache environment in the cloud. It provides a high-performance, scalable, and cost-effective caching solution, while removing the complexity associated with deploying and managing a distributed cache environment. With ElastiCache, you can quickly deploy your cache environment, without having to provision hardware or install software.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/WhatIs.html>

NEW QUESTION 120

In Amazon RDS for PostgreSQL, you can provision up to 3TB storage and 30,000 IOPS per database instance. For a workload with 50% writes and 50% reads running on a cr1.8xlarge instance, you can realize over 25,000 IOPS for PostgreSQL. However, by provisioning more than this limit, you may be able to achieve:

- A. higher latency and lower throughput.
- B. lower latency and higher throughput.
- C. higher throughput only.
- D. higher latency onl

Answer: B

Explanation:

You can provision up to 3TB storage and 30,000 IOPS per database instance. For a workload with 50% writes and 50% reads running on a cr1.8xlarge instance, you can realize over 25,000 IOPS for PostgreSQL. However, by provisioning more than this limit, you may be able to achieve lower latency and higher throughput. Your actual realized IOPS may vary from the amount you provisioned based on your database workload, instance type, and database engine choice.

Reference: <https://aws.amazon.com/rds/postgresql/>

NEW QUESTION 123

AWS Direct Connect itself has NO specific resources for you to control access to. Therefore, there are no AWS Direct Connect Amazon Resource Names (ARNs) for you to use in an Identity and Access Nmanagement (IAM) policy. With that in mind, how is it possible to write a policy to control access to AWS Direct Connect actions?

- A. You can leave the resource name field blank.
- B. You can choose the name of the AWS Direct Connection as the resource.
- C. You can use an asterisk (*) as the resource.
- D. You can create a name for the resourc

Answer: C

Explanation:

AWS Direct Connect itself has no specific resources for you to control access to. Therefore, there are no AWS Direct Connect ARNs for you to use in an IAM policy. You use an asterisk (*) as the resource when writing a policy to control access to AWS Direct Connect actions.

Reference: http://docs.aws.amazon.com/directconnect/latest/UserGuide/using_iam.html

NEW QUESTION 124

An organization is planning to use NoSQL DB for its scalable data needs. The organization wants to host an application securely in AWS VPC. What action can be recommended to the organization?

- A. The organization should setup their own NoSQL cluster on the AWS instance and configure route tables and subnets.
- B. The organization should only use a DynamoDB because by default it is always a part of the default subnet provided by AWS.
- C. The organization should use a DynamoDB while creating a table within the public subnet.
- D. The organization should use a DynamoDB while creating a table within a private subne

Answer: A

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Currently VPC does not support DynamoDB. Thus, if the user wants to implement VPC, he has to setup his own NoSQL DB within the VPC. Reference:

http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Introduction.htm

NEW QUESTION 129

An organization is setting up RDS for their applications. The organization wants to secure RDS access with VPC. Which of the following options is not required while designing the RDS with VPC?

- A. The organization must create a subnet group with public and private subnet
- B. Both the subnets can be in the same or separate AZ.
- C. The organization should keep minimum of one IP address in each subnet reserved for RDS failover.
- D. If the organization is connecting RDS from the internet it must enable the VPC attributes DNS hostnames and DNS resolution.
- E. The organization must create a subnet group with VPC using more than one subnet which are a part of separate AZs.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on security and operational needs. A DB subnet group is a collection of subnets (generally private) that the user can create in a VPC and assign to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating the DB instances.

Each DB subnet group should have subnets in at least two Availability Zones in a given region. If the RDS instance is required to be accessible from the internet the organization must enable the VPC attributes, DNS hostnames and DNS resolution. For each RDS DB instance that the user runs in a VPC, he should reserve

at least one address in each subnet in the DB subnet group for use by Amazon RDS for recovery actions.
Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html

NEW QUESTION 133

You create a VPN connection, and your VPN device supports Border Gateway Protocol (BGP). Which of the following should be specified to configure the VPN connection?

- A. Classless routing
- B. Classfull routing
- C. Dynamic routing
- D. Static routing

Answer: C

Explanation:

If you create a VPN connection, you must specify the type of routing that you plan to use, which will depend upon on the make and model of your VPN devices. If your VPN device supports Border Gateway Protocol (BGP), you need to specify dynamic routing when you configure your VPN connection. If your device does not support BGP, you should specify static routing.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_VPN.html

NEW QUESTION 135

An organization is having a VPC for the HR department, and another VPC for the Admin department. The HR department requires access to all the instances running in the Admin VPC while the Admin department requires access to all the resources in the HR department. How can the organization setup this scenario?

- A. Setup VPC peering between the VPCs of Admin and HR.
- B. Setup ACL with both VPCs which will allow traffic from the CIDR of the other VPC.
- C. Setup the security group with each VPC which allows traffic from the CIDR of another VPC.
- D. It is not possible to connect resources of one VPC from another VPC.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. A VPC peering connection allows the user to route traffic between the peer VPCs using private IP addresses as if they are a part of the same network.

This is helpful when one VPC from the same or different AWS account wants to connect with resources of the other VPC.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-peering.html>

NEW QUESTION 140

ExamKiller has created a multi-tenant Learning Management System (LMS). The application is hosted for five different tenants (clients) in the VPCs of the respective AWS accounts of the tenant. ExamKiller wants to setup a centralized server which can connect with the LMS of each tenant upgrade if required. ExamKiller also wants to ensure that one tenant VPC should not be able to connect to the other tenant VPC for security reasons. How can ExamKiller setup this scenario?

- A. ExamKiller has to setup one centralized VPC which will peer in to all the other VPCs of the tenants.
- B. ExamKiller should setup VPC peering with all the VPCs peering each other but block the IPs from CIDR of the tenant VPCs to deny them.
- C. ExamKiller should setup all the VPCs with the same CIDR but have a centralized VP
- D. This way only the centralized VPC can talk to the other VPCs using VPC peering.
- E. ExamKiller should setup all the VPCs meshed together with VPC peering for all VPC

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. A VPC peering connection allows the user to route traffic between the peer VPCs using private IP addresses as if they are a part of the same network.

This is helpful when one VPC from the same or different AWS account wants to connect with resources of the other VPC. The organization wants to setup that one VPC can connect with all the other VPCs but all other VPCs cannot connect among each other. This can be achieved by configuring VPC peering where one VPC is peered with all the other VPCs, but the other VPCs are not peered to each other. The VPCs are in the same or a separate AWS account and should not have overlapping CIDR blocks.

Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/PeeringGuide/peering-configurations-full-access.html#many-vpcs-full-access>

NEW QUESTION 141

True or False: The Amazon ElastiCache clusters are not available for use in VPC at this time.

- A. TRUE
- B. True, but they are available only in the GovCloud.
- C. True, but they are available only on request.
- D. FALSE

Answer: D

Explanation:

Amazon ElastiCache clusters can be run in an Amazon VPC. With Amazon VPC, you can define a virtual network topology and customize the network configuration to closely resemble a traditional network that you might operate in your own datacenter. You can now take advantage of the manageability, availability and scalability benefits of Amazon ElastiCache Clusters in your own isolated network. The same functionality of Amazon ElastiCache, including automatic failure detection, recovery, scaling, auto discovery, Amazon CloudWatch metrics, and software patching, are now available in Amazon VPC. Reference:

<http://aws.amazon.com/about-aws/whats-new/2012/12/20/amazon-elasticache-announces-support-for-a-mazon-vpc/>

NEW QUESTION 145

Identify a true statement about using an IAM role to grant permissions to applications running on Amazon EC2 instances.

- A. When AWS credentials are rotated, developers have to update only the root Amazon EC2 instance that uses their credentials.
- B. When AWS credentials are rotated, developers have to update only the Amazon EC2 instance on which the password policy was applied and which uses their credentials.
- C. When AWS credentials are rotated, you don't have to manage credentials and you don't have to worry about long-term security risks.
- D. When AWS credentials are rotated, you must manage credentials and you should consider precautions for long-term security risks.

Answer: C

Explanation:

Using IAM roles to grant permissions to applications that run on EC2 instances requires a bit of extra configuration. Because role credentials are temporary and rotated automatically, you don't have to manage credentials, and you don't have to worry about long-term security risks.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/role-usecase-ec2app.html>

NEW QUESTION 148

In the context of Amazon ElastiCache CLI, which of the following commands can you use to view all ElastiCache instance events for the past 24 hours?

- A. `elasticache-events --duration 24`
- B. `elasticache-events --duration 1440`
- C. `elasticache-describe-events --duration 24`
- D. `elasticache describe-events --source-type cache-cluster --duration 1440`

Answer: D

Explanation:

In Amazon ElastiCache, the code `"aws elasticache describe-events --source-type cache-cluster --duration 1440"` is used to list the cache-cluster events for the past 24 hours (1440 minutes). Reference:

<http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/ECEvents.Viewing.html>

NEW QUESTION 153

In Amazon Cognito what is a silent push notification?

- A. It is a push message that is received by your application on a user's device that will not be seen by the user.
- B. It is a push message that is received by your application on a user's device that will return the user's geolocation.
- C. It is a push message that is received by your application on a user's device that will not be heard by the user.
- D. It is a push message that is received by your application on a user's device that will return the user's authentication credentials.

Answer: A

Explanation:

Amazon Cognito uses the Amazon Simple Notification Service (SNS) to send silent push notifications to devices. A silent push notification is a push message that is received by your application on a user's device that will not be seen by the user.

Reference: <http://aws.amazon.com/cognito/faqs/>

NEW QUESTION 158

Which of the following IAM policy elements lets you specify an exception to a list of actions?

- A. `NotException`
- B. `ExceptionAction`
- C. `Exception`
- D. `NotAction`

Answer: D

Explanation:

The `NotAction` element lets you specify an exception to a list of actions. Reference:

http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 159

In AWS IAM, which of the following predefined policy condition keys checks how long ago (in seconds) the MFA-validated security credentials making the request were issued using multi-factor authentication (MFA)?

- A. `aws:MultiFactorAuthAge`
- B. `aws:MultiFactorAuthLast`
- C. `aws:MFAAge`
- D. `aws:MultiFactorAuthPrevious`

Answer: A

Explanation:

`aws:MultiFactorAuthAge` is one of the predefined keys provided by AWS that can be included within a Condition element of an IAM policy. The key allows to check how long ago (in seconds) the

MFA-validated security credentials making the request were issued using Multi-Factor Authentication (MFA).
Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 162

A user is configuring MySQL RDS with PIOPS. What should be the minimum PIOPS that the user should provision?

- A. 1000
- B. 200
- C. 2000
- D. 500

Answer: A

Explanation:

If a user is trying to enable PIOPS with MySQL RDS, the minimum size of storage should be 100 GB and the minimum PIOPS should be 1000.
Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_PIOPS.html

NEW QUESTION 166

You are setting up some EBS volumes for a customer who has requested a setup which includes a RAID (redundant array of inexpensive disks). AWS has some recommendations for RAID setups. Which RAID setup is not recommended for Amazon EBS?

- A. RAID 1 only
- B. RAID 5 only
- C. RAID 5 and RAID 6
- D. RAID 0 only

Answer: C

Explanation:

With Amazon EBS, you can use any of the standard RAID configurations that you can use with a traditional bare metal server, as long as that particular RAID configuration is supported by the operating system for your instance. This is because all RAID is accomplished at the software level. For greater I/O performance than you can achieve with a single volume, RAID 0 can stripe multiple volumes together; for on-instance redundancy, RAID 1 can mirror two volumes together. RAID 5 and RAID 6 are not recommended for Amazon EBS because the parity write operations of these RAID modes consume some of the IOPS available to your volumes.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

NEW QUESTION 169

Once the user has set ElastiCache for an application and it is up and running, which services, does Amazon not provide for the user:

- A. The ability for client programs to automatically identify all of the nodes in a cache cluster, and to initiate and maintain connections to all of these nodes
- B. Automating common administrative tasks such as failure detection and recovery, and software patching
- C. Providing default Time To Live (TTL) in the AWS ElastiCache Redis Implementation for different type of data.
- D. Providing detailed monitoring metrics associated with your Cache Nodes, enabling you to diagnose and react to issues very quickly

Answer: C

Explanation:

Amazon provides failure detection and recovery, and software patching and monitoring tools which is called CloudWatch. In addition it provides also Auto Discovery to automatically identify and initialize all nodes of cache cluster for Amazon ElastiCache.
Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/WhatIs.html>

NEW QUESTION 171

What is the average queue length recommended by AWS to achieve a lower latency for the 200 PIOPS EBS volume?

- A. 5
- B. 1
- C. 2
- D. 4

Answer: B

Explanation:

The queue length is the number of pending I/O requests for a device. The optimal average queue length will vary for every customer workload, and this value depends on a particular application's sensitivity to IOPS and latency. If the workload is not delivering enough I/O requests to maintain the optimal average queue length, then the EBS volume might not consistently deliver the IOPS that have been provisioned. However, if the workload maintains an average queue length that is higher than the optimal value, then the per-request I/O latency will increase; in this case, the user should provision more IOPS for his volume. AWS recommends that the user should target an optimal average queue length of 1 for every 200 provisioned IOPS and tune that value based on his application requirements.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-workload-demand.html>

NEW QUESTION 172

A user is trying to create a PIOPS EBS volume with 4000 IOPS and 100 GB size. AWS does not allow the user to create this volume. What is the possible root cause for this?

- A. PIOPS is supported for EBS higher than 500 GB size
- B. The maximum IOPS supported by EBS is 3000
- C. The ratio between IOPS and the EBS volume is higher than 30
- D. The ratio between IOPS and the EBS volume is lower than 50

Answer: C

Explanation:

A Provisioned IOPS (SSD) volume can range in size from 4 GiB to 16 TiB and you can provision up to 20,000 IOPS per volume. The ratio of IOPS provisioned to the volume size requested should be a maximum of 30; for example, a volume with 3000 IOPS must be at least 100 GB.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html#EBSVolumeTypes_provisioned_iops

NEW QUESTION 176

A user is planning to host a Highly Available system on the AWS VPC. Which of the below mentioned statements is helpful in this scenario?

- A. Create VPC subnets in two separate availability zones and launch instances in different subnets.
- B. Create VPC with only one public subnet and launch instances in different AZs using that subnet.
- C. Create two VPCs in two separate zones and setup failover with ELB such that if one VPC fails it will divert traffic to another VPC.
- D. Create VPC with only one private subnet and launch instances in different AZs using that subnet.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. Each subnet must reside entirely within one Availability Zone and cannot span across zones.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 177

A user is creating a PIOPS volume. What is the maximum ratio the user should configure between PIOPS and the volume size?

- A. 5
- B. 10
- C. 20
- D. 30

Answer: D

Explanation:

Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads that are sensitive to storage performance and consistency in random access I/O throughput. A provisioned IOPS volume can range in size from 10 GB to 1 TB and the user can provision up to 4000 IOPS per volume.

The ratio of IOPS provisioned to the volume size requested can be a maximum of 30; for example, a volume with 3000 IOPS must be at least 100 GB.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 178

What is a possible reason you would need to edit claims issued in a SAML token?

- A. The NameIdentifier claim cannot be the same as the username stored in AD.
- B. Authentication fails consistently.
- C. The NameIdentifier claim cannot be the same as the claim URI.
- D. The NameIdentifier claim must be the same as the username stored in AD.

Answer: A

Explanation:

The two reasons you would need to edit claims issued in a SAML token are: The NameIdentifier claim cannot be the same as the username stored in AD, and The app requires a different set of claim URIs.

Reference:

<https://azure.microsoft.com/en-us/documentation/articles/active-directory-saml-claims-customization/>

NEW QUESTION 183

You're trying to delete an SSL certificate from the IAM certificate store, and you're getting the message "Certificate: <certificate-id> is being used by CloudFront."

Which of the following statements is probably the reason why you are getting this error?

- A. Before you can delete an SSL certificate you need to set up https on your server.
- B. Before you can delete an SSL certificate, you need to set up the appropriate access level in IAM.
- C. Before you can delete an SSL certificate, you need to either rotate SSL certificates or revert from using a custom SSL certificate to using the default CloudFront certificate.
- D. You can't delete SSL certificates. You need to request it from AWS.

Answer: C

Explanation:

CloudFront is a web service that speeds up distribution of your static and dynamic web content, for example, .html, .css, .php, and image files, to end users.

Every CloudFront web distribution must be associated either with the default CloudFront certificate or with a custom SSL certificate. Before you can delete an SSL certificate, you need to either rotate SSL certificates (replace the current custom SSL certificate with another custom SSL certificate) or revert from using a custom SSL certificate to using the default CloudFront certificate.

Reference: <http://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/Troubleshooting.html>

NEW QUESTION 188

Do you need to use Amazon Cognito to use the Amazon Mobile Analytics service?

- A. N
- B. However, it is recommend by AWS to use Amazon Cognito for security best practices.
- C. Ye
- D. You need to use it only if you have IAM root access.
- E. N
- F. You cannot use it at all, and you need to use AWS IAM accounts.
- G. Ye
- H. It is recommended by AWS to use Amazon Cognito to use Amazon Mobile Analytics servic

Answer: A

Explanation:

You can initialize Amazon Mobile Analytics using AWS IAM accounts. AWS recommend using Amazon Cognito for security best practices.

Reference: <http://aws.amazon.com/mobileanalytics/faqs/>

NEW QUESTION 190

Which of the following AWS services can be used to define alarms to trigger on a certain actMty, such as actMty success, failure, or delay in AWS Data Pipeline?

- A. Amazon SES
- B. Amazon CodeDeploy
- C. Amazon SNS
- D. Amazon SQS

Answer: C

Explanation:

In AWS Data Pipeline, you can define Amazon SNS alarms to trigger on actMties such as success, failure, or delay by creating an alarm object and referencing it in the onFail, onSuccess, or onLate slots of the actMty object.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 195

You want to use Amazon Redshift and you are planning to deploy dw1.8xlarge nodes. What is the minimum amount of nodes that you need to deploy with this kind of configuration?

- A. 1
- B. 4
- C. 3
- D. 2

Answer: D

Explanation:

For a single-node configuration in Amazon Redshift, the only option available is the smallest of the two options. The 8XL extra-large nodes are only available in a multi-node configuration

Reference: <http://docs.aws.amazon.com/redshift/latest/mgmt/working-with-clusters.html>

NEW QUESTION 196

Can Provisioned IOPS be used on RDS instances launched in a VPC?

- A. Yes, they can be used only with Oracle based instances.
- B. Yes, they can be used for all RDS instances.
- C. No
- D. Yes, they can be used only with MySQL based instance

Answer: B

Explanation:

The basic building block of Amazon RDS is the DB instance. DB instance storage comes in three types: Magnetic, General Purpose (SSD), and Provisioned IOPS (SSD). When you buy a server, you get CPU, memory, storage, and IOPS, all bundled together. With Amazon RDS, these are split apart so that you can scale them independently. So, for example, if you need more CPU, less IOPS, or more storage, you can easily allocate them.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/RDSFAQ.PIOPS.html>

NEW QUESTION 200

A user is hosting a public website on AWS. The user wants to have the database and the app server on the AWS VPC. The user wants to setup a database that can connect to the Internet for any patch upgrade but cannot receive any request from the internet. How can the user set this up?

- A. Setup DB in a private subnet with the security group allowing only outbound traffic.
- B. Setup DB in a public subnet with the security group allowing only inbound data.
- C. Setup DB in a local data center and use a private gateway to connect the application with DB.
- D. Setup DB in a private subnet which is connected to the internet via NAT for outbound.

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. When the user wants to setup both the DB and App on VPC, the user should make one public and one private subnet. The DB should be hosted in a private subnet and instances in that subnet

cannot reach the internet. The user can allow an instance in his VPC to initiate outbound connections to the internet but prevent unsolicited inbound connections from the internet by using a Network Address Translation (NAT) instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html

NEW QUESTION 202

In Amazon ElastiCache, the default cache port is:

- A. for Memcached 11210 and for Redis 6380.
- B. for Memcached 11211 and for Redis 6380.
- C. for Memcached 11210 and for Redis 6379.
- D. for Memcached 11211 and for Redis 6379.

Answer: D

Explanation:

In Amazon ElastiCache, you can specify a new port number for your cache cluster, which by default is 11211 for Memcached and 6379 for Redis.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/GettingStarted.AuthorizeAccess.html>

NEW QUESTION 205

An organization is hosting a scalable web application using AWS. The organization has configured internet facing ELB and Auto Scaling to make the application scalable. Which of the below mentioned statements is required to be followed when the application is planning to host a web application on VPC?

- A. The ELB can be in a public or a private subnet but should have the ENI which is attached to an elastic IP.
- B. The ELB must not be in any subnet; instead it should face the internet directly.
- C. The ELB must be in a public subnet of the VPC to face the internet traffic.
- D. The ELB can be in a public or a private subnet but must have routing tables attached to divert the internet traffic to it.

Answer: C

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances. There are two ELBs available with VPC: internet facing and internal (private) ELB. For internet facing ELB it is required that ELB should be in a public subnet.

After the user creates the public subnet, he should ensure to associate the route table of the public subnet with the internet gateway to enable the load balancer in the subnet to connect with the internet. Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/CreateVPCForELB.html>

NEW QUESTION 207

Is there any way to own a direct connection to Amazon Web Services?

- A. No, AWS only allows access from the public Internet.
- B. No, you can create an encrypted tunnel to VPC, but you cannot own the connection.
- C. Yes, you can via Amazon Dedicated Connection.
- D. Yes, you can via AWS Direct Connect

Answer: D

Explanation:

AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. One end of the cable is connected to your router, the other to an AWS Direct Connect router. With this connection in place, you can create virtual interfaces directly to the AWS cloud (for example, to Amazon Elastic Compute Cloud (Amazon EC2) and Amazon Simple Storage Service (Amazon S3)) and to Amazon Virtual Private Cloud (Amazon VPC), bypassing Internet service providers in your network path.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

NEW QUESTION 210

In Amazon ElastiCache, which of the following statements is correct?

- A. When you launch an ElastiCache cluster into an Amazon VPC private subnet, every cache node is assigned a public IP address within that subnet.
- B. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.
- C. If your AWS account supports only the EC2-VPC platform, ElastiCache will never launch your cluster in a VPC.
- D. ElastiCache is not fully integrated with Amazon Virtual Private Cloud (VPC).

Answer: B

Explanation:

The VPC must allow non-dedicated EC2 instances. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/AmazonVPC.EC.html>

NEW QUESTION 214

You are looking to migrate your Development (Dev) and Test environments to AWS. You have decided to use separate AWS accounts to host each environment. You plan to link each accounts bill to a Master AWS account using Consolidated Billing. To make sure you Keep within budget you would like to implement a way for administrators in the Master account to have access to stop, delete and/or terminate resources in both the Dev and Test accounts. Identify which option will allow you to achieve this goal.

- A. Create IAM users in the Master account with full Admin permission
- B. Create cross-account roles in the Dev and Test accounts that grant the Master account access to the resources in the account by inheriting permissions from the Master account.

- C. Create IAM users and a cross-account role in the Master account that grants full Admin permissions to the Dev and Test accounts.
- D. Create IAM users in the Master account Create cross-account roles in the Dev and Test accounts that have full Admin permissions and grant the Master account access.
- E. Link the accounts using Consolidated Billin
- F. This will give IAM users in the Master account access to resources in the Dev and Test accounts

Answer: C

NEW QUESTION 218

To serve Web traffic for a popular product your chief financial officer and IT director have purchased 10 ml large heavy utilization Reserved Instances (RIs) evenly spread across two availability zones: Route 53 is used to deliver the traffic to an Elastic Load Balancer (ELB). After several months, the product grows even more popular and you need additional capacity As a result, your company purchases two C3.2xlarge medium utilization Ris You register the two c3 2xlarge instances with your ELB and quickly find that the ml large instances are at 100% of capacity and the c3 2xlarge instances have significant capacity that's unused Which option is the most cost effective and uses EC2 capacity most effectively?

- A. Configure Autoscaling group and Launch Configuration with ELB to add up to 10 more on-demand m1 .large instances when triggered by Cloudwatc
- B. Shut off c3.2xlarge instances.
- C. Configure ELB with two c3.2xlarge instances and use on-demand Autoscaling group for up to two additional c3.2xlarge instance
- D. Shut off m1 .large instances.
- E. Route traffic to EC2 m1 .large and c3.2xlarge instances directly using Route 53 latency based routing and health check
- F. Shut off ELB.
- G. Use a separate ELB for each instance type and distribute load to ELBs with Route 53 weighted round robin.

Answer: B

NEW QUESTION 222

A read only news reporting site with a combined web and application tier and a database tier that receives large and unpredictable traffic demands must be able to respond to these traffic fluctuations automatically. What AWS services should be used meet these requirements?

- A. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaimg group monitored with CloudWatch and RDS with read replicas.
- B. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatch and RDS with read replicas.
- C. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatc
- D. And multi-AZ RDS.
- E. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaling group monitored with CloudWatch and multi-AZ RDS.

Answer: A

NEW QUESTION 226

You are designing a photo-sharing mobile app. The application will store all pictures in a single Amazon S3 bucket. Users will upload pictures from their mobile device directly to Amazon S3 and will be able to view and download their own pictures directly from Amazon S3. You want to configure security to handle potentially millions of users in the most secure manner possible. What should your server-side application do when a new user registers on the photo-sharing mobile application?

- A. Create an IAM use
- B. Update the bucket policy with appropriate permissions for the IAM use
- C. Generate an access key and secret key for the IAM user, store them in the mobile app and use these credentials to access Amazon S3.
- D. Create an IAM use
- E. Assign appropriate permissions to the IAM use
- F. Generate an access key and secret key for the IAM user, store them in the mobile app and use these credentials to access Amazon S3.
- G. Create a set of long-term credentials using AWS Security Token Service with appropriate permission
- H. Store these credentials in the mobile app and use them to access Amazon S3.
- I. Record the user's information in Amazon RDS and create a role in IAM with appropriate permission
- J. When the user uses their mobile app, create temporary credentials using the AWS Security Token Service "AssumeRole" functio
- K. Store these credentials in the mobile app's memory and use them to access Amazon S3. Generate new credentials the next time the user runs the mobile app.
- L. Record the user's information in Amazon DynamoD
- M. When the user uses their mobile app, create temporary credentials using AWS Security Token Service with appropriate permission
- N. Store these credentials in the mobile app's memory and use them to access Amazon S3. Generate new credentials the next time the user runs the mobile app.

Answer: D

NEW QUESTION 229

You have a periodic Image analysis application that gets some files In Input analyzes them and tor each file writes some data in output to a ten file the number of files in input per day is high and concentrated in a few hours of the day.

Currently you have a server on EC2 with a large EBS volume that hosts the input data and the results it takes almost 20 hours per day to complete the process What services could be used to reduce the elaboration time and improve the availability of the solution?

- A. S3 to store I/O file
- B. SQS to distribute elaboration commands to a group of hosts working in paralle
- C. Auto scaling to dynamically size the group of hosts depending on the length of the SQS queue
- D. EBS with Provisioned IOPS (PIOPS) to store I/O file
- E. SNS to distribute elaboration commands to a group of hosts working in parallel Auto Scaling to dynamically size the group of hosts depending on the number of SNS notifications
- F. S3 to store I/O files, SNS to distribute evaporation commands to a group of hosts working in paralle
- G. Auto scaling to dynamically size the group of hosts depending on the number of SNS notifications
- H. EBS with Provisioned IOPS (PIOPS) to store I/O files SQS to distribute elaboration commands to a group of hosts working in parallel Auto Scaling to dynamically size the group ot hosts depending on the length of the SQS queue.

Answer: D

NEW QUESTION 234

You have been asked to design the storage layer for an application. The application requires disk performance of at least 100,000 IOPS. In addition, the storage layer must be able to survive the loss of an individual disk, EC2 instance, or Availability Zone without any data loss. The volume you provide must have a capacity of at least 3 TB. Which of the following designs will meet these objectives?

- A. Instantiate a c3.8xlarge instance in us-east-1. Provision 4x1TB EBS volumes, attach them to the instance, and configure them as a single RAID 5 volume.
- B. Ensure that EBS snapshots are performed every 15 minutes.
- C. Instantiate a c3.8xlarge instance in us-east-1. Provision 3x1TB EBS volumes, attach them to the instance, and configure them as a single RAID 0 volume.
- D. Ensure that EBS snapshots are performed every 15 minutes.
- E. Instantiate an i2.8xlarge instance in us-east-1.
- F. Create a RAID 0 volume using the four 800GB SSD ephemeral disks provided with the instance.
- G. Provision 3x1TB EBS volumes, attach them to the instance, and configure them as a second RAID 0 volume.
- H. Configure synchronous, block-level replication from the ephemeral-backed volume to the EBS-backed volume.
- I. Instantiate a c3.8xlarge instance in us-east-1. Provision an AWS Storage Gateway and configure it for 3 TB of storage and 100,000 IOP.
- J. Attach the volume to the instance.
- K. Instantiate an i2.8xlarge instance in us-east-1.
- L. Create a RAID 0 volume using the four 800GB SSD ephemeral disks provided with the instance.
- M. Configure synchronous, block-level replication to an identically configured instance in us-east-1b.

Answer: C

NEW QUESTION 239

A large real-estate brokerage is exploring the option of adding a cost-effective location-based alert to their existing mobile application. The application backend infrastructure currently runs on AWS. Users who opt in to this service will receive alerts on their mobile device regarding real-estate offers in proximity to their location. For the alerts to be relevant, delivery time needs to be in the low minute count. The existing mobile app has 5 million users across the US. Which one of the following architectural suggestions would you make to the customer?

- A. The mobile application will submit its location to a web service endpoint utilizing Elastic Load Balancing and EC2 instances. DynamoDB will be used to store and retrieve relevant offers. EC2 instances will communicate with mobile carriers/device providers to push alerts back to the mobile application.
- B. Use AWS DirectConnect or VPN to establish connectivity with mobile carriers. EC2 instances will receive the mobile applications' location through carrier connection. RDS will be used to store and retrieve relevant offers. EC2 instances will communicate with mobile carriers to push alerts back to the mobile application.
- C. The mobile application will send device location using SQS.
- D. EC2 instances will retrieve the relevant offers from DynamoDB. AWS Mobile Push will be used to send offers to the mobile application.
- E. The mobile application will send device location using AWS Mobile Push. EC2 instances will retrieve the relevant offers from DynamoDB. EC2 instances will communicate with mobile carriers/device providers to push alerts back to the mobile application.

Answer: A

NEW QUESTION 240

You require the ability to analyze a large amount of data, which is stored on Amazon S3 using Amazon Elastic MapReduce. You are using the cc2.8xlarge instance type, whose CPUs are mostly idle during processing. Which of the below would be the most cost-efficient way to reduce the runtime of the job?

- A. Create more smaller files on Amazon S3.
- B. Add additional cc2.8xlarge instances by introducing a task group.
- C. Use smaller instances that have higher aggregate I/O performance.
- D. Create fewer, larger files on Amazon S3.

Answer: C

NEW QUESTION 242

An AWS customer is deploying an application that is composed of an AutoScaling group of EC2 instances.

The customer's security policy requires that every outbound connection from these instances to any other service within the customer's Virtual Private Cloud must be authenticated using a unique X.509 certificate that contains the specific instance-ID.

In addition, X.509 certificates must be designed by the customer's Key Management Service in order to be trusted for authentication.

Which of the following configurations will support these requirements?

- A. Configure an IAM Role that grants access to an Amazon S3 object containing a signed certificate and configure the Auto Scaling group to launch instances with this role. Have the instances bootstrap and get the certificate from Amazon S3 upon first boot.
- B. Embed a certificate into the Amazon Machine Image that is used by the Auto Scaling group. Have the launched instances generate a certificate signature request with the instance's assigned instance-ID to the Key Management Service for signature.
- C. Configure the Auto Scaling group to send an SNS notification of the launch of a new instance to the trusted Key Management Service.
- D. Have the Key Management Service generate a signed certificate and send it directly to the newly launched instance.
- E. Configure the launched instances to generate a new certificate upon first boot. Have the Key Management Service poll the Auto Scaling group for associated instances and send new instances a certificate signature (that contains the specific instance-ID).

Answer: A

NEW QUESTION 244

Your company runs a customer-facing event registration site. This site is built with a 3-tier architecture with web and application tier servers and a MySQL database. The application requires 6 web tier servers and 6 application tier servers for normal operation, but can run on a minimum of 65% server capacity and a single MySQL database. When deploying this application in a region with three availability zones (AZs), which architecture provides high availability?

- A. A web tier deployed across 2 AZs with 3 EC2 (Elastic Compute Cloud) instances in each AZ inside an Auto Scaling Group behind an ELB (elastic load balancer), and an application tier deployed across 2 AZs with 3 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and one RDS (Relational Database Service) instance deployed with read replicas in the other AZ.
- B. A web tier deployed across 3 AZs with 2 EC2 (Elastic Compute Cloud) instances in each AZ inside an Auto Scaling Group behind an ELB (elastic load balancer).

and an application tier deployed across 3 AZs with 2 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and one RDS (Relational Database Service) Instance deployed with read replicas in the two other AZs.

C. A web tier deployed across 2 AZs with 3 EC2 (Elastic Compute Cloud) instances in each AZ inside an Auto Scaling Group behind an ELB (elastic load balancer) and an application tier deployed across 2 AZs with 3 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and a Multi-AZ RDS (Relational Database Service) deployment.

D. A web tier deployed across 3 AZs with 2 EC2 (Elastic Compute Cloud) instances in each AZ Inside an Auto Scaling Group behind an ELB (elastic load balancer). And an application tier deployed across 3 AZs with 2 EC2 instances in each AZ inside an Auto Scaling Group behind an ELB and a Multi-AZ RDS (Relational Database services) deployment.

Answer: D

NEW QUESTION 245

Your customer wishes to deploy an enterprise application to AWS which will consist of several web servers, several application servers and a small (50GB) Oracle database information is stored, both in the database and the file systems of the various servers. The backup system must support database recovery whole server and whole disk restores, and individual file restores with a recovery time of no more than two hours. They have chosen to use RDS Oracle as the database Which backup architecture will meet these requirements?

- A. Backup RDS using automated daily DB backups Backup the EC2 instances using AMIs and supplement with file-level backup to S3 using traditional enterprise backup software to provide file level restore
- B. Backup RDS using a Multi-AZ Deployment Backup the EC2 instances using Amis, and supplement by copying file system data to S3 to provide file level restore.
- C. Backup RDS using automated daily DB backups Backup the EC2 instances using EBS snapshots and supplement with file-level backups to Amazon Glacier using traditional enterprise backup software to provide file level restore
- D. Backup RDS database to S3 using Oracle RMAN Backup the EC2 instances using Amis, and supplement with EBS snapshots for individual volume restore.

Answer: A

NEW QUESTION 247

Your company has HQ in Tokyo and branch offices all over the world and is using a logistics software with a multi-regional deployment on AWS in Japan, Europe and US

- A. The logistic software has a 3-tier architecture and currently uses MySQL 5.6 for data persistence
- B. Each region has deployed its own database In the HQ region you run an hourly batch process reading data from every region to compute cross-regional reports that are sent by email to all offices this batch process must be completed as fast as possible to quickly optimize logistics how do you build the database architecture in order to meet the requirements'?
- C. For each regional deployment, use RDS MySQL with a master in the region and a read replica in the HQ region
- D. For each regional deployment, use MySQL on EC2 with a master in the region and send hourly EBS snapshots to the HQ region
- E. For each regional deployment, use RDS MySQL with a master in the region and send hourly RDS snapshots to the HQ region
- F. For each regional deployment, use MySQL on EC2 with a master in the region and use S3 to copy data files hourly to the HQ region
- G. Use Direct Connect to connect all regional MySQL deployments to the HQ region and reduce network latency for the batch process

Answer: A

NEW QUESTION 248

You would like to create a mirror image of your production environment in another region for disaster recovery purposes. Which of the following AWS resources do not need to be recreated in the second region? (Choose 2 answers)

- A. Route 53 Record Sets
- B. IAM Roles
- C. Elastic IP Addresses (EIP)
- D. EC2 Key Pairs
- E. Launch configurations
- F. Security Groups

Answer: AC

NEW QUESTION 249

Your company currently has a 2-tier web application running in an on-premises data center. You have experienced several infrastructure failures in the past two months resulting in significant financial losses. Your CIO is strongly agreeing to move the application to AWS. While working on achieving buy-in from the other company executives, he asks you to develop a disaster recovery plan to help improve Business continuity in the short term. He specifies a target Recovery Time Objective (RTO) of 4 hours and a Recovery Point Objective (RPO) of 1 hour or less. He also asks you to implement the solution within 2 weeks. Your database is 200GB in size and you have a 20Mbps Internet connection. How would you do this while minimizing costs?

- A. Create an EBS backed private AMI which includes a fresh install of your application
- B. Develop a Cloud Formation template which includes your AMI and the required EC2, AutoScaling, and ELB resources to support deploying the application across Multiple- Availability-Zone
- C. Asynchronously replicate transactions from your on-premises database to a database instance in AWS across a secure VPN connection.
- D. Deploy your application on EC2 instances within an Auto Scaling group across multiple availability zone
- E. Asynchronously replicate transactions from your on-premises database to a database instance in AWS across a secure VPN connection.
- F. Create an EBS backed private AMI which includes a fresh install of your application
- G. Setup a script in your data center to backup the local database every 1 hour and to encrypt and copy the resulting file to an S3 bucket using multi-part upload.
- H. Install your application on a compute-optimized EC2 instance capable of supporting the application's average load
- I. Synchronously replicate transactions from your on-premises database to a database instance in AWS across a secure Direct Connect connection.

Answer: A

NEW QUESTION 252

An enterprise wants to use a third-party SaaS application. The SaaS application needs to have access to issue several API commands to discover Amazon EC2 resources running within the enterprise's account The enterprise has internal security policies that require any outside access to their environment must conform to

the principles of least privilege and there must be controls in place to ensure that the credentials used by the SaaS vendor cannot be used by any other third party. Which of the following would meet all of these conditions?

- A. From the AWS Management Console, navigate to the Security Credentials page and retrieve the access and secret key for your account.
- B. Create an IAM user within the enterprise account assign a user policy to the IAM user that allows only the actions required by the SaaS application create a new access and secret key for the user and provide these credentials to the SaaS provider.
- C. Create an IAM role for cross-account access allows the SaaS provider's account to assume the role and assign it a policy that allows only the actions required by the SaaS application.
- D. Create an IAM role for EC2 instances, assign it a policy that allows only the actions required for the SaaS application to work, provide the role ARN to the SaaS provider to use when launching their application instances.

Answer: C

NEW QUESTION 254

A customer has a 10 GB AWS Direct Connect connection to an AWS region where they have a web application hosted on Amazon Elastic Computer Cloud (EC2). The application has dependencies on an on-premises mainframe database that uses a BASE (Basic Available. Sort stale Eventual consistency) rather than an ACID (Atomicity. Consistency isolation. Durability) consistency model. The application is exhibiting undesirable behavior because the database is not able to handle the volume of writes. How can you reduce the load on your on-premises database resources in the most cost-effective way?

- A. Use an Amazon Elastic Map Reduce (EMR) S3DistCp as a synchronization mechanism between the on-premises database and a Hadoop cluster on AWS.
- B. Modify the application to write to an Amazon SQS queue and develop a worker process to flush the queue to the on-premises database.
- C. Modify the application to use DynamoDB to feed an EMR cluster which uses a map function to write to the on-premises database.
- D. Provision an RDS read-replica database on AWS to handle the writes and synchronize the two databases using Data Pipeline.

Answer: A

NEW QUESTION 257

You are responsible for a legacy web application whose server environment is approaching end of life You would like to migrate this application to AWS as quickly as possible, since the application environment currently has the following limitations:

The VM's single 10GB VNIDK is almost full; The virtual network interface still uses the 10Gbps driver, which leaves your 100Mbps WAN connection completely underutilized;

It is currently running on a highly customized. Windows VM within a VMware environment; You do not have installation media;

This is a mission critical application with an RTO (Recovery Time Objective) of 8 hours. RPO (Recovery Point Objective) of 1 hour. How could you best migrate this application to AWS while meeting your business continuity requirements?

- A. Use the EC2 VM Import Connector for vCenter to import the VNI into EC2.
- B. Use Import/Export to import the VNI as an ESS snapshot and attach to EC2.
- C. Use S3 to create a backup of the VM and restore the data into EC2.
- D. Use the ec2-bundle-instance API to Import an Image of the VNI into EC2

Answer: A

NEW QUESTION 258

You are implementing a URL whitelisting system for a company that wants to restrict outbound HTTP'S connections to specific domains from their EC2-hosted applications you deploy a single EC2 instance running proxy software and configure it to accept traffic from all subnets and EC2 instances in the VPC. You configure the proxy to only pass through traffic to domains that you define in its whitelist configuration You have a nightly maintenance window of 10 minutes where all instances fetch new software updates. Each update is about 200MB in size and there are 500 instances in the VPC that routinely fetch updates After a few days you notice that some machines are failing to successfully download some, but not all of their updates within the maintenance window. The download URLs used for these updates are correctly listed in the proxy's whitelist configuration and you are able to access them manually using a web browser on the instances. What might be happening? (Choose 2 answers)

- A. You are running the proxy on an undersized EC2 instance type so network throughput is not sufficient for all instances to download their updates in time.
- B. You are running the proxy on a sufficiently-sized EC2 instance in a private subnet and its network throughput is being throttled by a NAT running on an undersized EC2 instance.
- C. The route table for the subnets containing the affected EC2 instances is not configured to direct network traffic for the software update locations to the proxy.
- D. You have not allocated enough storage to the EC2 instance running the proxy so the network buffer is filling up, causing some requests to fail.
- E. You are running the proxy in a public subnet but have not allocated enough EIPs to support the needed network throughput through the Internet Gateway (IGW).

Answer: AB

NEW QUESTION 261

Refer to the architecture diagram above of a batch processing solution using Simple Queue Service (SQS) to set up a message queue between EC2 instances which are used as batch processors Cloud Watch monitors the number of Job requests (queued messages) and an Auto Scaling group adds or deletes batch servers automatically based on parameters set in Cloud Watch alarms. You can use this architecture to implement which of the following features in a cost effective and efficient manner?

- A. Reduce the overall time for executing jobs through parallel processing by allowing a busy EC2 instance that receives a message to pass it to the next instance in a daisy-chain setup.
- B. Implement fault tolerance against EC2 instance failure since messages would remain in SQS and work can continue with recovery of EC2 instances implement fault tolerance against SQS failure by backing up messages to S3.
- C. Implement message passing between EC2 instances within a batch by exchanging messages through SQS.
- D. Coordinate number of EC2 instances with number of job requests automatically thus Improving cost effectiveness.
- E. Handle high priority jobs before lower priority jobs by assigning a priority metadata field to SQS messages.

Answer: D

NEW QUESTION 263

Your website is serving on-demand training videos to your workforce. Videos are uploaded monthly in high resolution MP4 format. Your workforce is distributed globally often on the move and using company-provided tablets that require the HTTP Live Streaming (HLS) protocol to watch a video. Your company has no video transcoding expertise and it required you may need to pay for a consultant.

How do you implement the most cost-efficient architecture without compromising high availability and quality of video delivery'?

- A. A video transcoding pipeline running on EC2 using SQS to distribute tasks and Auto Scaling to adjust the number of nodes depending on the length of the queue
- B. EBS volumes to host videos and EBS snapshots to incrementally backup original files after a few day
- C. CloudFront to serve HLS transcoded videos from EC2.
- D. Elastic Transcoder to transcode original high-resolution MP4 videos to HL
- E. EBS volumes to host videos and EBS snapshots to incrementally backup original files after a few day
- F. CloudFront to serve HLS transcoded videos from EC2.
- G. Elastic Transcoder to transcode original high-resolution MP4 videos to HL
- H. S3 to host videos with Lifecycle Management to archive original files to Glacier after a few day
- I. CloudFront to serve HLS transcoded videos from S3.
- J. A video transcoding pipeline running on EC2 using SQS to distribute tasks and Auto Scaling to adjust the number of nodes depending on the length of the queue
- K. S3 to host videos with Lifecycle Management to archive all files to Glacier after a few day
- L. CloudFront to serve HLS transcoded videos from Glacier.

Answer: C

NEW QUESTION 266

Your website is serving on-demand training videos to your workforce. Videos are uploaded monthly in high resolution MP4 format. Your workforce is distributed globally often on the move and using company-provided tablets that require the HTTP Live Streaming (HLS) protocol to watch a video. Your company has no video transcoding expertise and it required you may need to pay for a consultant.

How do you implement the most cost-efficient architecture without compromising high availability and quality of video delivery'?

- A. A video transcoding pipeline running on EC2 using SQS to distribute tasks and Auto Scaling to adjust the number of nodes depending on the length of the queue
- B. EBS volumes to host videos and EBS snapshots to incrementally backup original files after a few day
- C. CloudFront to serve HLS transcoded videos from EC2.
- D. Elastic Transcoder to transcode original high-resolution MP4 videos to HL
- E. EBS volumes to host videos and EBS snapshots to incrementally backup original files after a few day
- F. CloudFront to serve HLS transcoded videos from EC2.
- G. Elastic Transcoder to transcode original high-resolution MP4 videos to HL
- H. S3 to host videos with Lifecycle Management to archive original files to Glacier after a few day
- I. CloudFront to serve HLS transcoded videos from S3.
- J. A video transcoding pipeline running on EC2 using SQS to distribute tasks and Auto Scaling to adjust the number of nodes depending on the length of the queue
- K. S3 to host videos with Lifecycle Management to archive all files to Glacier after a few day
- L. CloudFront to serve HLS transcoded videos from Glacier.

Answer: C

NEW QUESTION 269

A customer has established an AWS Direct Connect connection to AWS. The link is up and routes are being advertised from the customer's end, however the customer is unable to connect from EC2 instances inside its VPC to servers residing in its datacenter.

Which of the following options provide a viable solution to remedy this situation? (Choose 2 answers)

- A. Add a route to the route table with an IPsec VPN connection as the target.
- B. Enable route propagation to the virtual pinnate gateway (VGW).
- C. Enable route propagation to the customer gateway (CGW).
- D. Modify the route table of all Instances using the 'route' command.
- E. Modify the Instances VPC subnet route table by adding a route back to the customer's on-premises environment.

Answer: AC

NEW QUESTION 270

You are running a news website in the eu-west-1 region that updates every 15 minutes. The website has a world-wide audience it uses an Auto Scaling group behind an Elastic Load Balancer and an Amazon

RDS database Static content resides on Amazon S3, and is distributed through Amazon CloudFront. Your Auto Scaling group is set to trigger a scale up event at 60% CPU utilization, you use an Amazon RDSextra large DB instance with 10.000 Provisioned IOPS its CPU utilization is around 80%. While freeable memory is in the 2 GB range.

Web analytics reports show that the average load time of your web pages is around 1.5 to 2 seconds, but your SEO consultant wants to bring down the average load time to under 0.5 seconds.

How would you improve page load times for your users? (Choose 3 answers)

- A. Lower the scale up trigger of your Auto Scaling group to 30% so it scales more aggressively.
- B. Add an Amazon ElastiCache caching layer to your application for storing sessions and frequent DB queries
- C. Configure Amazon CloudFront dynamic content support to enable caching of re-usable content from your site
- D. Switch the Amazon RDS database to the high memory extra large Instance type
- E. Set up a second installation in another region, and use the Amazon Route 53 latency-based routing feature to select the right region.

Answer: ABD

NEW QUESTION 275

Your company produces customer commissioned one-of-a-kind skiing helmets combining nigh fashion with custom technical enhancements Customers can show off their Individuality on the ski slopes and have access to head-up-displays. GPS rear-view cams and any other technical innovation they wish to embed in the helmet.

The current manufacturing process is data rich and complex including assessments to ensure that the custom electronics and materials used to assemble the helmets are to the highest standards Assessments are a mixture of human and automated assessments you need to add a new set of assessment to model the

failure modes of the custom electronics using GPUs with CUDA, across a cluster of servers with low latency networking.

What architecture would allow you to automate the existing process using a hybrid approach and ensure that the architecture can support the evolution of processes over time?

- A. Use AWS Data Pipeline to manage movement of data & meta-data and assessments Use an auto-scaling group of G2 instances in a placement group.
- B. Use Amazon Simple Workflow (SWF) to manages assessments, movement of data & meta-data Use an auto-scaling group of G2 instances in a placement group.
- C. Use Amazon Simple Workflow (SWF) to manages assessments movement of data & meta-data Use an auto-scaling group of C3 instances with SR-IOV (Single Root I/O Virtualization).
- D. Use AWS data Pipeline to manage movement of data & meta-data and assessments use auto-scaling group of C3 with SR-IOV (Single Root I/O virtualization).

Answer: B

NEW QUESTION 276

You are designing an SSUTLS solution that requires HTTPS clients to be authenticated by the Webserver using client certificate authentication. The solution must be resilient.

Which of the following options would you consider for configuring the web server infrastructure? (Choose 2 answers)

- A. Configure ELB with TCP listeners on TCP/443. And place the Web servers behind it.
- B. Configure your Web servers with EIP
- C. Place the Web servers in a Route53 Record Set and configure health checks against all Web servers.
- D. Configure ELB with HTTPS listeners, and place the Web sewers behind it.
- E. Configure your web sewers as the origins for a CloudFront distributio
- F. Use custom SSL certificates on your CloudFront distribution.

Answer: AB

NEW QUESTION 277

You are designing a personal document-archMng solution for your global enterprise with thousands of employee. Each employee has potentially gigabytes of data to be backed up in this archMng solution. The solution will be exposed to the employees as an application, where they can just drag and drop their files to the archMng system. Employees can retrieve their archives through a web interface. The corporate network has high bandwidth AWS Direct Connect connectMty to AWS.

You have a regulatory requirement that all data needs to be encrypted before being uploaded to the cloud.

How do you implement this in a highly available and cost-efficient way?

- A. Manage encryption keys on-premises in an encrypted relational databas
- B. Set up an on-premises server with sufficient storage to temporarily store files, and then upload them to Amazon S3, providing a client-side master key.
- C. Mange encryption keys in a Hardware Security Module (HSM) appliance on-premises serve r with sufficient storage to temporarily store, encrypt, and upload files directly into Amazon Glacier.
- D. Nlanage encryption keys in Amazon Key Management Service (KMS), upload to Amazon Simple Storage Service (S3) with client-side encryption using a KMS customer master key ID, and configure Amazon S3 lifecycle policies to store each object using the Amazon Glacier storage tier.
- E. Manage encryption keys in an AWS CloudHSNI applananc
- F. Encrypt files prior to uploading on the employee desktop, and then upload directly into Amazon Glacier.

Answer: C

NEW QUESTION 279

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-Solutions-Architect-Professional Practice Exam Features:

- * AWS-Certified-Solutions-Architect-Professional Questions and Answers Updated Frequently
- * AWS-Certified-Solutions-Architect-Professional Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Solutions-Architect-Professional Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Solutions-Architect-Professional Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-Solutions-Architect-Professional Practice Test Here](#)